

# STIC Search Report

# STIC Database Tracking Number: 121980

TO: Andrea Ragonese Location: pk1 11e50

Art Unit: 3743

Monday, May 17, 2004

Case Serial Number: 10/660366

From: Emory Damron Location: EIC 3700

CP2-2C08

Phone: 305-8587

Emory.Damron@uspto.gov

### Search Notes

Dear Andrea,

Please find below an inventor search in the bibliographic and full-text foreign patent files, as well as keyword searches in the patent and non-patent literature files, both

References of potential pertinence have been tagged, but please review all the bibliographic and full text.

packets in case you like something I didn't. In addition to searching on Dialog, I also searched Google.com, EPO/JPO/Derwent,

I searched the major concepts you provided, and focused on the "venous return", the possibility of a wireless communication feature, and the fact that this was a "method" per se; as expected, most of the better art was related to one or all of the inventors in some way, but please review all the material nonetheless.

Please contact me if I can refocus or expand any aspect of this case, and please take a moment to provide any feedback (on the form provided) so EIC 3700 may better serve your needs.

Sincerely,

**Emory Damron** 

Technical Information Specialist

EIC 3700, US Patent & Trademark Office

Phone: (703) 305-8587/ Fax: (703) 306-5915

Emory.damron@uspto.gov



# STIC Search Results Feedback Form

EIC 3700

Questions about the scope or the results of the search? Contact the EIC searcher or contact:

John Sims, EIC 3700 Team Leader 308-4836, CP2-2C08

Voluntary Results Feedback Form
> I am an examiner in Workgroup: 3743 Example: 3730
<ul> <li>➤ Relevant prior art found, search results used as follows:</li> <li>□ 102 rejection</li> <li>□ 103 rejection</li> <li>□ Cited as being of interest.</li> <li>□ Helped examiner better understand the invention.</li> <li>□ Helped examiner better understand the state of the art in their technology.</li> </ul>
Types of relevant prior art found:  [ Foreign Patent(s)  [ Non-Patent Literature
<ul> <li>Relevant prior art not found:</li> <li>Results verified the lack of relevant prior art (helped determine patentability).</li> <li>Results were not useful in determining patentability or understanding the invention.</li> </ul>
Comments:

Drop off or send completed forms to STIC/EIC3700 CP2 2C08



## SEARCH REQUEST FORM

## Scientific and Technical Information Center

	77465 note 5/13/04
ANDREA KAGUNEST	Examiner #:
Requester's Full Name.  Phone Number 30 6 - 5	Examiner #: 77465 Date: 5/13/04  1055 Serial Number: 10/660366  Results Format Preferred (circle): PAPER DISK E-MAIL
Art Unit: S11/2 India Port India PK1 11	Results Format Preferred (chees).
Mail Box and Blug Room Both Both E 50	wire corches in order of need.
and is submitted, please pri	oritize searches in order of
******* and de	scribe as specifically as possible and beautiful with the concept or
Please provide a detailed statement of the search topic, and det	scribe as specifically as possible the subject matter to be searched. scribe as specifically as possible the subject matter to be searched. scribe as specifically as possible the subject matter to be searched. scribe as specifically as possible the subject matter to be searched. Scribe as specifically as possible the subject matter to be searched. Scribe as specifically as possible the subject matter to be searched. Scribe as specifically as possible the subject matter to be searched. Scribe as specifically as possible the subject matter to be searched. Scribe as specifically as possible the subject matter to be searched. Scribe as specifically as possible the subject matter to be searched.
Include the elected species of state any terms that may have a spe	cial meaning. Give examples
utility of the invention. Define any terms that may have a spe known. Please attach a copy of the cover sheet, pertinent clair	ns, and abstract.
a large continued	and waster to the take of the state of the s
Title of Invention:	VERN. ZIELINSKI, TODD;
- 11 LAZIONE 12 Page 1 1 1	
BIONDI JAMES.	
Earliest Priority Filing Date: 9/11/2003	·
Earliest Priority Filing Date:	energion (parent, child, divisional, or issued patent numbers) along with the
** *For Sequence Searches Only* Please include all pertinent inju-	rmation (parent, child, divisional, or issued patent numbers) along with the
appropriate serial number.	-ACHED
appropriate serial number.  5 \( \xi \) \( \text{A} \) \( \tau \)	
,	
*************	**************************************
STAFF USE ONLY Searcher: En any Damker NA Sequence (#	- 7
Souther Emony DAMRON NA Sequence (#	) STN
Searcher Phone #: 30 5 8 5 8 7  AA Sequence (#	) Dialog _ X
Searcher Phone #: CP7. 2 C8 Structure (#)	Questel/Orbit
	Dr.Link
Date Searcher Picked Up: 3/0 9/ Bibliographic	Lexis/Nexis
Date Completed: Litigation	
Searcher Prep & Review Time:Fulltext	Sequence Systems X SCINUS / SCI 5~C5 DIREC,
Searcher Free Remity	WWW/Internet 43 (11W)
Clerical Prep Time:	Other (specify)
Online Time:Other	

PTO-1590 (8-01)

AU=(LURIE K? OR LURIE, K? OR MENK V? OR MENK, V? OR ZIELIN-SKI T? OR ZIELINSKI, T? OR BIONDI J? OR BIONDI, J?) Items Set 0 KEITH(2W)LURIE OR VERN(2W)MENK OR TODD(2W)ZIELINSKI OR JAM-70 S1 RESUSC? OR RESPIRAT? OR BREATH? OR VENTILAT? OR CPR OR PEEP S2 ES(2W)BIONDI OR (POSITIVE OR NEGATIVE) (2N) PRESSUR? 182939 s3IC=(A62B? OR A61G? OR A61M?) 145640 IDPAT (sorted in duplicate/non-duplicate order) S1:S2 AND S3:S4 S4 43 S5 43 S6 File 347: JAPIO Nov 1976-2003/Dec(Updated 040402) (c) 2004 JPO & JAPIO File 350: Derwent WPIX 1963-2004/UD, UM &UP=200429 (c) 2004 Thomson Derwent

(Item 1 from file: 350) 6/3, K/1DIALOG(R)File 350:Derwent WPIX (c) 2004 Thomson Derwent. All rts. reserv. \*\*Image available\*\* Related WPI Acc No: 1995-193914; 1996-433571; 2000-421466; 2002-139260; 2002-641994; 2002-681034; 2003-030322; 2003-310772; 2003-371349 Facial mask for patients, has metronome coupled to body to produce XRPX Acc No: N03-614219 repeating chest compression signal to facilitate performance of regular chest compressions when performing cardiopulmonary resuscitation Patent Assignee: CPRX LLC (CPRX-N) Inventor: LURIE K G ; SCHARENBROICH G; ZIELINSKI T Number of Countries: 001 Number of Patents: 001 Week Date Kind Patent Family: Applicat No 200372 B 19931109 Date Kind 20031016 US 93149203 Α Patent No US 20030192547 A1 19950310 Α US 95403009 19971015 Α US 97950702 20000322 Α US 2000532601 20000410 Α US 2000546252 20010511 Α US 2001854238 20020408 Α US 2002119203 20021105 Α US 2002224263 20030324 Α US 2003396007 Priority Applications (No Type Date): US 2003396007 A 20030324; US 93149203 A 19931109; US 95403009 A 19950310; US 97950702 A 19971015; US 2000532601 A 20000322; US 2000546252 A 20000410; US 2001854238 A 20010511; US 2002119203 A 20020408; US 2002224263 A 20021105 Filing Notes Patent Details: CIP of application US 93149203 Main IPC Patent No Kind Lan Pg CIP of application US 95403009 16 A62B-018/10. US 20030192547 A1 Cont of application US 97950702 Cont of application US 2000532601 CIP of application US 2000546252 CIP of application US 2001854238 CIP of application US 2002119203 CIP of application US 2002224263 CIP of patent US 5441658 CIP of patent US 5692498 Cont of patent US 6062219 CIP of patent US 6526973

CIP of patent US 6604523 produce repeating chest compression signal to facilitate performance of regular chest compressions when performing cardiopulmonary resuscitation

Inventor: LURIE K G ...

#### ... ZIELINSKI T

a patient's face, and a valve system (24) permitting the inflow and outflow of respiratory gases to and from the body, respectively. Abstract (Basic): A metronome is coupled to the body to...

...repeating chest compression signal to facilitate the performance of regular chest compressions when performing cardiopulmonary

An INDEPENDENT CLAIM is also included for a method of performing resuscitation . cardio pulmonary resuscitation .

... Used for assisting a rescuer in performing appropriately timed chest compressions and in ventilating patients...

...mask body provides a rescuer with the ability to facilitate the proper performance of cardiopulmonary resuscitation without requiring extra peripheral equipment

... Title Terms: RESUSCITATION

Æ.,

International Patent Class (Main): A62B-018/10

(Item 2 from file: 350) 6/3, K/2

DIALOG(R) File 350: Derwent WPIX (c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 015469481

WPI Acc No: 2003-531627/200350

XRAM Acc No: C03-143545

Method for administering drugs for e.g. assisting cardiac treatment, XRPX Acc No: N03-421782 involves lowering intrathoracic pressure using valve system after introducing drug into patient, to cause blood flow into thorax

Patent Assignee: CPRX LLC (CPRX-N)

Inventor: KEITH L; WOLFGANG V; LURIE K G; VOELCKEL W

Number of Countries: 100 Number of Patents: 002

Date Patent Family: Kind Applicat No 20010928 Date Kind 20030403 US 2001967029 Α Patent No 20020730 US 20030062041 Al Al 20030410 WO 2002US24325 A WO 200328793

Priority Applications (No Type Date): US 2001967029 A 20010928

Patent Details:

Filing Notes Main IPC Patent No Kind Lan Pg

9 A61M-016/00 US 20030062041 A1

WO 200328793 A1 E

Designated States (National): AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO RU SD SE SG SI SK SL TJ TM TN TR TT TZ UA UG UZ VN YU ZA Designated States (Regional): AT BE BG CH CY CZ DE DK EA EE ES FI FR GB

GH GM GR IE IT KE LS LU MC MW MZ NL OA PT SD SE SK SL SZ TR TZ UG ZM ZW ...Inventor: LURIE K G

A valve system (200) connected to the patient's airway prevents Abstract (Basic): or impedes respiratory gases from flowing into lungs for a period of time to allow the intrathoracic pressure... International Patent Class (Main): A61M-016/00

(Item 3 from file: 350) 6/3, K/3

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 015441604

WPI Acc No: 2003-503746/200347

XRPX Acc No: N03-399911

Medical rescue system for cardio pulmonary resuscitation , has pressure responsive valve system to prevent flow of respiratory gases into patient's lungs until threshold negative intrathoracic pressure is

Patent Assignee: GISCH T M (GISC-I); HARDER S E (HARD-I); LEYDEN M V (LEYD-I); LURIE K G (LURI-I); WAFFENSMITH J (WAFF-I); ZIELINSKI T M

(ZIEL-I); CPRX LLC (CPRX-N) Inventor: GISCH T M; HARDER S E; LEYDEN M V; LURIE K G; WAFFENSMITH J; ZIELINSKI T M

Number of Countries: 101 Number of Patents: 002

Patent Family:

Week Date Kind Applicat No Date Kind Patent No 20010928 20030403 US 2001966945 Α US 20030062040 A1 20020905 A2 20030410 WO 2002US28568 A WO 200328613

Priority Applications (No Type Date): US 2001966945 A 20010928

Patent Details:

Filing Notes Patent No Kind Lan Pg Main IPC

21 A61M-016/00 US 20030062040 A1

A61H-000/00 WO 200328613 A2 E

Designated States (National): AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO RU SD SE SG SI SK SL TJ TM TN TR TT TZ UA UG UZ VC VN YU

Designated States (Regional): AT BE BG CH CY CZ DE DK EA EE ES FI FR GB GH GM GR IE IT KE LS LU MC MW MZ NL OA PT SD SE SK SL SZ TR TZ UG ZM ZW Medical rescue system for cardio pulmonary resuscitation , has pressure responsive valve system to prevent flow of respiratory gases into patient's lungs until threshold negative intrathoracic pressure is exceeded

...Inventor: LURIE K G ...

#### ... ZIELINSKI T M

Abstract (Basic):

A pressure responsive valve system (18) prevents the flow of respiratory gases into the patient's lungs during decompression of the chest, until a threshold negative intrathoracic pressure is exceeded. A ventilation tube (20) is pivotally coupled to a swivel mount of the valve system.

sudden cardiac arrest, loss of breadth, heart attack and heart rhythm abnormality during cardio pulmonary resuscitation ( CPR ),

ventilation and defibrillation...

... The valve system augments the extent and duration of the negative intrathoracic pressure, thereby enhancing the amount of blood flow to the patient's chest...

... Ventilation tube (20

... Title Terms: RESUSCITATION ;

...International Patent Class (Main): A61M-016/00

(Item 4 from file: 350) 6/3, K/4DIALOG(R)File 350:Derwent WPIX (c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 015378270

WPI Acc No: 2003-439208/200341

Related WPI Acc No: 1997-319553; 1999-561889; 2001-407473

XRPX Acc No: N03-350420

Patient ventilation system for automatically weaning patient from ventilator, has pressure source, spontaneous breathing rate monitor,

minute volume flow meter and data processor

Patent Assignee: CARDIOPULMONARY CORP (CARD-N) Inventor: BIONDI J W ; LOCKHORN N; REYNOLDS R Number of Countries: 001 Number of Patents: 002

Week Patent Family: Kind Date Applicat No Date Kind 200341 B 19951208 Patent No US 20030037786 A1 20030227 US 95569919 Α 19980320 US 9845461 Α 20000913 Α US 2000660820 20010122 Α US 2001767173 Α 20020930 US 2002260796 200402 , A 19951208 US 95569919 · B2 20031230 US 6668829 19980320 A US 9845461 20000913 Α US 2000660820 20010122 Α US 2001767173 Α 20020930 US 2002260796

Priority Applications (No Type Date): US 2001767173 A 20010122; US 95569919 A 19951208; US 9845461 A 19980320; US 2000660820 A 20000913; US 2002260796 A 20020930

Patent Details:

Main IPC Patent No Kind Lan Pg 30 A61M-016/00 US 20030037786 A1

Filing Notes

CIP of application US 95569919 Cont of application US 9845461 CIP of application US 2000660820 Cont of application US 2001767173 CIP of patent US 5931160

Cont of patent US 6158432 Cont of patent US 6463930

A61M-016/00 В2 US 6668829

CIP of application US 95569919 Cont of application US 9845461 CIP of application US 2000660820 Cont of application US 2001767173 CIP of patent US 5931160 Cont of patent US 6158432 Cont of patent US 6463930

Patient ventilation system for automatically weaning patient from ventilator, has pressure source, spontaneous breathing rate monitor, minute volume flow meter and data processor

Inventor: BIONDI J W ....

Abstract (Basic):

patient weaning system (10) includes a pressure source to provide support to patient, a spontaneous breathing rate monitor, a device to input predetermined breath rate range and tidal volume, a minute flow meter and data processor connected to all the above devices, compares patient's breath rate with predetermined rate and minute volume.

INDEPENDENT CLAIM is also included for the method for automatically weaning a patient from a ventilator .

. . . ... Used for automatically weaning a patient from a medical ventilator .

... The ventilator control system provides a clinician with complete control of patient's airway flow and pressure throughout the respiratory cycle, enabling to determine the optimal therapy for the patient. To decrease the work of exhalation by the patient, negative pressure can be applied to the exhalation circuit of patient's ventilator to reduce the resistance of airflow...

... The drawing shows the block diagram of the ventilator system...

... Ventilator control system (10...

... Ventilator (17

... Title Terms: VENTILATION ;

International Patent Class (Main): A61M-016/00

(Item 5 from file: 350) 6/3, K/5

DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

015330113

WPI Acc No: 2003-391048/200337

XRAM Acc No: C03-103809

Method for resuscitating a patient from cardiac arrest comprises administrating cardiopulmonary resuscitation and combination of vasopressor agent(s) or vasopressinergic agonist(s), and L-arginine, nitric oxide or direct nitric oxide donor

Patent Assignee: CPRX INC (CPRX-N)

Inventor: LURIE K G

Number of Countries: 001 Number of Patents: 001

Patent Family:

Date Kind Applicat No Date Kind Patent No 19970929 200337 B Ρ B1 20021126 US 9788362 US 6486206 19980929 WO 98US20461 Α US 2000538432 · A 20000329

Priority Applications (No Type Date): US 9788362 P 19970929; WO 98US20461 A 19980929; US 2000538432 A 20000329

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes Provisional application US 9788362 B1 12 A61K-031/195 US 6486206 Cont of application WO 98US20461

Method for resuscitating a patient from cardiac arrest comprises administrating cardiopulmonary resuscitation and combination of vasopressor agent(s) or vasopressinergic agonist(s), and L-arginine, nitric oxide...

Inventor: LURIE K G

Abstract (Basic):

Method for resuscitating a patient from cardiac arrest comprises administrating...

...1) cardiopulmonary resuscitation ( CPR ); and...

the compounds described in (A1) and (A2) are to be administered to a patient undergoing CPR; and...

...in the dorsal recumbent position and intubated using standard endotracheal intubation technique. The pigs were ventilated during the preparatory phase, and after return of spontaneous circulation at the end of the experiment with a mechanical respirator . The tidal volume was set at 450 cc and delivered between 11-15 breaths per minute with supplemental oxygen at 2 l/minute. Normal saline solution was administered intravenously...

- ...B) (40 microg/kg) combination, in a porcine model of ventricular fibrillation using standard cardiopulmonary resuscitation ( CPR ). Radiolabeled microspheres were used to measure myocardial blood flows during ventricular fibrillation prior to drug...
- ... For resuscitating a patient from cardiac arrest (claimed); for treating ventricular fibrillation involving rapid contractions and twitching...
- ...patient's blood pressure. The vasopressor epinephrine leads to superior vital organ blood flow during CPR , as compared with the conventional epinephrine therapy...

Technology Focus:

Preferred Method: The resuscitation method additionally involves administration of mannitol.

Extension Abstract:

or (e) are administered within 0-60 (preferably 0-10) minutes, after the initiation of CPR, for more than 10 minutes, repeated every 3-10 minutes.

... Title Terms: RESUSCITATION ;

(Item 6 from file: 350) 6/3,K/6

DIALOG(R) File 350: Derwent WPIX (c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 015310415

WPI Acc No: 2003-371349/200335

Related WPI Acc No: 1995-193914; 1996-433571; 2000-421466; 2002-139260;

2002-641994; 2002-681034; 2003-030322; 2003-310772; 2003-766762

XRAM Acc No: C03-098421 XRPX Acc No: N03-296207

Increasing blood circulation in breathing person, involves interfacing valve system to airway to decrease respiratory gas flow to lungs and permitting person to inhale and exhale through system

Patent Assignee: CPRX LLC (CPRX-N)

Inventor: LURIE K G

Number of Countries: 001 Number of Patents: 002

Patent Family:

Week Kind Date Applicat No Kind Date 19931109 200335 B Patent No US 20030037784 A1 20030227 US 93149203 Α 19950310 Α US 95403009 19971015 Α US 97950702 20000410 US 2000546252 Α 20010511 US 2001854238 Α 20020408 Α US 2002119203 Α 20021105 US 2002224263 A 19931109 200413 US 20040016428 A9 20040129 US 93149203 A 19950310 US 95403009 A 19971015 US 97950702 US 2000546252 A 20000410 US 2001854238 A 20010511 US 2002119203 A 20020408 US 2002224263 A 20021105

Priority Applications (No Type Date): US 2002224263 A 20021105; US 93149203 A 19931109; US 95403009 A 19950310; US 97950702 A 19971015; US 2000546252 A 20000410; US 2001854238 A 20010511; US 2002119203 A 20020408 Patent Details: Filing Notes Main IPC Patent No Kind Lan Pg CIP of application US 93149203 54 A61M-016/00 US 20030037784 A1 CIP of application US 95403009 CIP of application US 97950702 CIP of application US 2000546252 CIP of application US 2001854238 CIP of application US 2002119203 CIP of patent US 5441658 CIP of patent US 5692498 CIP of patent US 6062219 CIP of application US 93149203 A61M-016/00 US 20040016428 A9 CIP of application US 95403009 CIP of application US 97950702 CIP of application US 2000546252 CIP of application US 2001854238 CIP of application US 2002119203 CIP of patent US 5441658

CIP of patent US 6604523 Increasing blood circulation in breathing person, involves interfacing valve system to airway to decrease respiratory gas flow to lungs and permitting person to inhale and exhale through system

CIP of patent US 5692498 CIP of patent US 6062219 CIP of patent US 6526973

Inventor: LURIE K G

Abstract (Basic):

Increasing blood circulation in a breathing person comprises interfacing a valve system (VS) to the persons airway. The VS is configured to decrease or prevent respiratory gas flow to lungs during an inhalation event. The person is permitted to inhale and ...

The method spontaneously increases the blood circulation in a breathing person and increases the magnitude and prolongs the duration of negative intrathoracic pressure in the chest. The valve system provides a safety ventilation passage. The method prevents foreign (outside) air from flowing to lungs during attempted inhalations to improve and sustain the duration of negative intrathoracic pressure and improve blood oxygenation and cardiopulmonary circulation...

... Title Terms: BREATH ;

International Patent Class (Main): A61M-016/00

(Item 7 from file: 350) DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 015249846 WPI Acc No: 2003-310772/200330

Related WPI Acc No: 1995-193914; 1996-433571; 2000-421466; 2002-139260; 2002-641994; 2002-681034; 2003-030322; 2003-371349; 2003-766762

XRPX Acc No: N03-247313

Increasing method for blood flow to the thorax by manipulating patient body where inflow valve prevents respiratory gases from entering lungs until negative intrathoracic pressure level range is exceeded

Patent Assignee: CPRX LLC (CPRX-N)

Inventor: GOLD B; LURIE K G ; SWEENEY M

٦ {

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week
US 6526973 B1 20030304 US 93149204 A 19931109 200330 B
US 95403009 A 19950310

US 97950702 A 19971015
US 2000546252 A 20000410

Priority Applications (No Type Date): US 97950702 A 19971015; US 93149204 A 19931109; US 95403009 A 19950310; US 2000546252 A 20000410

Patent Details:

Patent No Kind Lan Pg Main IPC US 6526973 B1 24 A62B-009/02

Filing Notes

CIP of application US 93149204 CIP of application US 95403009 Cont of application US 97950702

CIP of patent US 5551420 CIP of patent US 5692498 Cont of patent US 6062219

... method for blood flow to the thorax by manipulating patient body where inflow valve prevents respiratory gases from entering lungs until negative intrathoracic pressure level range is exceeded ... Inventor: LURIE K G

Abstract (Basic):

The patient body is manipulated to increase magnitude and duration of patient's negative intrathoracic pressure. During manipulation, the inflow valve prevents respiratory gases from entering the lungs until a negative intrathoracic pressure level ranging from 0 to -30 cm of water is exceeded. One inflow valve assists in increasing magnitude and duration of negative pressure to enhance blood flow amount.

For increasing cardiopulmonary circulation induced by chest compression and decompression when performing cardiopulmonary

resuscitation .

...Amplifies the total intrathoracic pressure swing by augmentation of both negative and **positive** intrathoracic **pressure**.

... Title Terms: RESPIRATION ;

International Patent Class (Main): A62B-009/02

6/3,K/8 (Item 8 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

015058548 \*\*Image available\*\*
WPI Acc No: 2003-119064/200311

XRPX Acc No: N03-094745

Remote medical treatment system e.g. for treating heart attack, has remote device which controls treatment device by transmitting treatment control signal received from central controller in response to monitoring

Patent Assignee: CPRX LLC (CPRX-N)
Inventor: LURIE K G ; ZIELINSKI T M

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week
US 6459933 B1 20021001 US 2000186088 P 20000309 200311 B

Priority Applications (No Type Date): US 2000186088 P 20000309; US 2000564889 A 20000504

Patent Details:

1

Patent No Kind Lan Pg Main IPC Filing Notes

US 6459933 B1 10 A61N-001/39 Provisional application US 2000186088

Inventor: LURIE K G ...

#### ... ZIELINSKI T M

Abstract (Basic):

... patients remote from medical facility during emergency situations such as sudden cardiac arrest, loss of **breath**, heart attack, arrhythmias, ventricular fibrillation, ventricular tachycardia, end tidal CO2, O2 saturation, inspiratory and expiratory...

6/3,K/9 (Item 9 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

014986562 \*\*Image available\*\*

WPI Acc No: 2003-047077/200304

XRPX Acc No: N03-037043

CPR assistance device for patient under sudden cardiac arrest, has stethoscope system connected to applicator body to detect patient's heart beat and to disseminate heart beat information to rescuer

Patent Assignee: CPRX LLC (CPRX-N)

Inventor: LURIE K G ; ZIELINSKI T M

Number of Countries: 099 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week WO 200291905 A2 20021121 WO 2002US14038 A 20020501 200304 B

Priority Applications (No Type Date): US 2001854404 A 20010511 Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes WO 200291905 A2 E 37 A61B-000/00

Designated States (National): AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO RU SD SE SG SI SK SL TJ TM TN TR TT TZ UA UG UZ VN YU ZA ZM ZW

Designated States (Regional): AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW MZ NL OA PT SD SE SL SZ TR TZ UG ZM ZW

CPR assistance device for patient under sudden cardiac arrest, has stethoscope system connected to applicator body...

Inventor: LURIE K G ...

#### ... ZIELINSKI T M

Abstract (Basic):

... The CPR assistance device (10) has an applicator body (12) for arrangement on the chest of a...

... a) a CPR performing method...

...b) and a CPR performing system...

- ...For use in performing cardio pulmonary resuscitation to patient under sudden cardiac arrest...
- ...determination of heart beat of patient under cardiac arrest, before, during and after performance of CPR to patient. Enables disseminating patient's heart beat information to rescuer so that rescuer can determined whether CPR should continue. Enables rapid evaluation of heart beat of patient to determine return of spontaneous circulation without requiring removal of CPR assistance device from patient...
- $\dots$  The figure shows the side view of  $\ensuremath{\mathsf{CPR}}$  assistance device with internal stethoscope...

 $\dots$  CPR assistance device (10 Title Terms: CPR;

6/3,K/10 (Item 10 from file: 350)

DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

014969808 \*\*Image available\*\*
WPI Acc No: 2003-030322/200302

Related WPI Acc No: 1995-193914; 1996-433571; 2000-421466; 2002-139260; 2002-641994; 2002-681034; 2003-310772; 2003-371349; 2003-766762

XRPX Acc No: N03-023968

Blood pressure increasing device for spontaneously breathing patient, has inflow valve to vary respiratory gas flow through housing due to patient inhalation

Patent Assignee: ADVANCED CIRCULATORY SYSTEMS INC (ADCI-N); CPRX LLC (CPRX-N)

Inventor: LURIE K G ; ZIELINSKI T M

Number of Countries: 101 Number of Patents: 004

Patent Family:

Patent No Kind Date Applicat No Kind Date Week A1 20021121 WO 2002US14039 A WO 200292169 20020501 200302 B US 20020170562 A1 20021121 US 93149204 Α 19931109 US 95403009 Α 19950310 US 97950702 Α 19971015 US 2000546252 Α 20000410 US 2001854238 Α 20010511 US 2002119203 Α 20020408 US 6604523 B2 20030812 US 93149204 Α 19931109 200355 US 95403009 Α 19950310 US 97950702 Α 19971015 US 2000546252 Α 20000410 US 2001854238 Α 20010511 EP 1387714 20040211 Α1 EP 2002769675 Α 20020501 200411 WO 2002US14039 A 20020501

Priority Applications (No Type Date): US 2002119203 A 20020408; US 2001854238 A 20010511; US 93149204 A 19931109; US 95403009 A 19950310; US 97950702 A 19971015; US 2000546252 A 20000410 Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

WO 200292169 A1 E 98 A62B-009/02

Designated States (National): AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA
CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN
IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ
OM PH PL PT RO RU SD SE SG SI SK SL TJ TM TN TR TT TZ UA UG UZ VN YU ZA

.

1

B.4 B

ZM ZW

Designated States (Regional): AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW MZ NL OA PT SD SE SL SZ TR TZ UG ZM ZW

US 20020170562 A1 56 A62B-009/02 CIP of application US 93149204

CIP of application US 95403009 CIP of application US 97950702

CIP of application US 2000546252

CIP of application US 2001854238

CIP of patent US 5551420 CIP of patent US 5692498

CIP of patent US 6062219

US 6604523 B2 A62B-009/02 CIP of application US 93149204

CIP of application US 95403009 Cont of application US 97950702 CIP of application US 2000546252

CIP of patent US 5551420 CIP of patent US 5692498 Cont of patent US 6062219 CIP of patent US 6526973

EP 1387714 A1 E A62B-009/02 Based on patent WO 200292169
Designated States (Regional): AL AT BE CH CY DE DK ES FI FR GB GR IE IT
LI LT LU LV MC MK NL PT RO SE SI TR

Blood pressure increasing device for spontaneously breathing patient, has inflow valve to vary respiratory gas flow through housing due to patient inhalation

Inventor: LURIE K G ...

... ZIELINSKI T M

Abstract (Basic):

... interfaced with a patient's airway. An inflow valve (24) operated by a mechanism, varies **respiratory** gas flow through the housing due to patient inhalation and assists in manipulating intrathoracic pressures...

... 1) Method for increasing blood pressure in spontaneously breathing person...

...For increasing cardiopulmonary circulation in spontaneously breathing patient with severe low blood pressure or cardiac arrest...

... By varying respiratory gas flow through housing, the negative intrathoracic pressure is increased when the patient inhales and more blood is returned to the right heart...

... Title Terms: BREATH ;

International Patent Class (Main): A62B-009/02

International Patent Class (Additional): A61M-016/00 ...

... A62B-007/04

6/3,K/11 (Item 11 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

014968203 \*\*Image available\*\*
WPI Acc No: 2003-028717/200302

XRPX Acc No: N03-022569

Ventilator monitoring system for use in hospitals, has server comprising dedicated ventilator application program for each type of heterogeneous ventilator

Patent Assignee: CARDIOPULMONARY CORP (CARD-N); BIONDI J W (BION-I); FAND A

(FAND-I)

Inventor: BIONDI J W ; FAND A

Number of Countries: 101 Number of Patents: 003

Patent Family:

Patent No Kind Date Applicat No Kind Date Week US 20020120676 A1 20020829 US 2001791334 Α 20010223 200302 B 20020906 WO 2002US4515 WO 200269181 A2 Α 20020219 200302 EP 1399786 A2 20040324 EP 2002713602 Α 20020219 200421 WO 2002US4515 20020219

Priority Applications (No Type Date): US 2001791334 A 20010223

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

US 20020120676 A1 21 G06F-015/16

WO 200269181 A2 E G06F-017/00

Designated States (National): AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO RU SD SE SG SI SK SL TJ TM TN TR TT TZ UA UG UZ VN YU ZA ZM ZW

Designated States (Regional): AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW MZ NL OA PT SD SE SL SZ TR TZ UG ZM ZW

EP 1399786 A2 E G05B-019/05 Based on patent WO 200269181
Designated States (Regional): AL AT BE CH CY DE DK ES FI FR GB GR IE IT
LI LT LU LV MC MK NL PT RO SE SI TR

Ventilator monitoring system for use in hospitals, has server comprising dedicated ventilator application program for each type of heterogeneous ventilator

Inventor: BIONDI J W ...

#### Abstract (Basic):

- A server (36) comprises a dedicated **ventilator** application program (50) for each type of heterogeneous **ventilators** (20), and a database (44) storing data from the **ventilators**. A listener/pollster transmits requests to and receives data from the **ventilators**, through a data access point, and passes requests to and data from the program. A...
- ... Ventilator monitoring system for use in hospitals and other health-care institutions...
- ... Enables monitoring and collection of data such as **ventilator** settings, measured patient values, alarm conditions, etc., from heterogeneous **ventilators**, for display at a central monitoring station...
- $\dots$  The figure shows the block diagram of the  $\ensuremath{\mathbf{ventilator}}$  monitoring system

... Ventilator (20

Title Terms: VENTILATION;

6/3,K/12 (Item 12 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

014860328 \*\*Image available\*\*
WPI Acc No: 2002-681034/200273

Related WPI Acc No: 1995-193914; 1996-433571; 2000-421466; 2002-139260; 2002-641994; 2003-030322; 2003-310772; 2003-371349; 2003-766762

XRPX Acc No: NO2-537515

Person's ventilation altering method for providing positive expiratory pressure involves controlling valve opening depending upon the specific actuating pressure which is varied over time

Patent Assignee: CPRX LLC (CPRX-N)

Inventor: LURIE K G ; VOELCKEL W; ZIELINSKI T Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week US 6425393 B1 20020730 US 93149240 Α 19931109 200273 B US 95403009 Α 19950310 US 97950702 A 19971015 US 99386868 19990831 Α

Priority Applications (No Type Date): US 99386868 A 19990831; US 93149240 A 19931109; US 95403009 A 19950310; US 97950702 A 19971015

Patent Details:

Patent No Kind Lan Pg Main IPC US 6425393 18 A62B-007/00 В1

Filing Notes CIP of application US 93149240 CIP of application US 95403009

CIP of application US 97950702

CIP of patent US 5551420 CIP of patent US 5692498

CIP of patent US 6062219

Person's ventilation altering method for providing positive expiratory pressure involves controlling valve opening depending upon the specific actuating pressure which is varied over time Inventor: LURIE K G ...

#### ... ZIELINSKI T

Abstract (Basic):

An exit valve is opened or closed to block/permit respiratory gases from/to patient's lungs. The valve is opened when specific actuating pressure is...

An INDEPENDENT CLAIM is included for method for performing cardiopulmonary resuscitation .

...For providing positive expiratory pressure (PEP...

...oxygenation while maintaining and/or increasing coronary perfusion pressure, thereby increasing the procedure of cardiopulmonary resuscitation ( CPR ) procedure...

... The figure shows the flow chart illustrating method for performing CPR using an exit valve to alter the person's PEP over time

... Title Terms: VENTILATION ;

International Patent Class (Main): A62B-007/00

6/3, K/13(Item 13 from file: 350)

DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

014821288 \*\*Image available\*\* WPI Acc No: 2002-641994/200269

Related WPI Acc No: 1995-193914; 1996-433571; 2000-421466; 2002-139260;

2002-681034; 2003-030322; 2003-310772; 2003-371349; 2003-766762

XRAM Acc No: C04-014016

XRPX Acc No: N04-029046

Increasing cardiopulmonary circulation during cardiopulmonary resuscitation involves using pressure-responsive inflow valve which prevents respiratory gas from entering patient's lungs during chest decompression

Patent Assignee: CPRX LLC (CPRX-N)
Inventor: LURIE K G ; ZIELINSKI T M

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date US 20020069878 A1 20020613 US 93149204 Α 19931109 200269 B US 95403009 Α 19950310 US 97950702 Α 19971015 US 2000546252 Α 20000410

US 2001854238 A 20010511
Priority Applications (No Type Date): US 2001854238 A 20010511; US 93149204
A 19931109; US 95403009 A 19950310; US 97950702 A 19971015; US 2000546252

Patent Details:

Patent No Kind Lan Pg Main IPC US 20020069878 A1 45 A62B-007/00

Filing Notes
CIP of application US 93149204
CIP of application US 95403009
Cont of application US 97950702
CIP of application US 2000546252

Increasing cardiopulmonary circulation during cardiopulmonary resuscitation involves using pressure-responsive inflow valve which prevents respiratory gas from entering patient's lungs during chest decompression

Inventor: LURIE K G ...

#### ... ZIELINSKI T M

Abstract (Basic):

cardiopulmonary circulation during cardiopulmonary resuscitation is increased by interfacing valving system having pressure-responsive inflow valve to a patient's airway, performing chest compression and decompression, and supplying pressurized respiratory gas via the inflow valve. The inflow valve prevents respiratory gas from entering the lungs during chest decompression.

Increasing cardiopulmonary circulation during cardiopulmonary resuscitation includes interfacing a valving system with a patient's airway, performing chest compression and decompression, and supplying pressurized respiratory gas to the patient. The valving system comprises a housing having upstream and downstream regions, and a pressure-responsive valve to prevent respiratory gas from flowing from the upstream region to the downstream region until the pressure in the downstream region falls below a threshold level. During chest decompression, the inflow valve prevents respiratory gas from entering the lungs until a predetermined negative intra-thoracic pressure level is exceeded at which time the inflow valve opens. The inflow valve assists in increasing the magnitude and duration of negative intra-thoracic pressure during decompression and enhances the amount of blood flow into the heart and lungs. The pressurized respiratory gas is supplied via the inflow valve when the valve opens to ventilate the patient. An INDEPENDENT CLAIM is included for a device for carrying out the method...

...is used in increasing cardiopulmonary circulation induced by chest compression and decompression when performing cardiopulmonary resuscitation . It is useful in increasing blood pressure in

spontaneously breathing person having low blood pressure secondary to vasovagal syncope or due to blood loss, administration... Technology Focus:

- valve to the patient's airway to prevent air from leaving the lungs until a positive intra-thoracic pressure of 2-20 cm H2O is exceeded at which time the exhalation valve opens. The...
- ...Preferred Parameters: The negative intra-thoracic pressure is -3 to -30 cm H2O. The respiratory gas has a pressure that is less than the opening pressure of inflow valve...
- ...than the actuating pressure of the inflow valve, and a safety mechanism for maintaining safety ventilation passageway open to permit respiratory gas to freely flow to the patient's lungs until actuated by a rescuer. The...
- ...of the shaft. The safety mechanism comprises a sensor to detect when the rescuer injects respiratory gas into the housing, and a control system to move the inflow valve from open...

... Title Terms: RESUSCITATION ;

International Patent Class (Main): A62B-007/00

International Patent Class (Additional): A62B-009/00

#### 6/3, K/14(Item 14 from file: 350) DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

014447044 \*\*Image available\*\* WPI Acc No: 2002-267747/200231

Related WPI Acc No: 1995-223538; 1996-401428; 1998-178372; 2000-012719;

2000-104863; 2001-513528; 2003-066281

XRPX Acc No: N02-208214

Precurved coronary sinus guiding introducer, has lumen extending through elongated member, from the straight proximal section to the distal section which curves through an arc of about 50 to 150 degrees

Patent Assignee: DAIG CORP (DAIG-N); ST JUDE MEDICAL INC (SJUD-N)

Inventor: BENDITT D G; BLANC J J; LURIE K G ; STARKS D J

Number of Countries: 001 Number of Patents: 002

Patent Family:

Patent No Kind Date Applicat No Kind Date Week US 20020029030 A1 20020307 US 97853631 A 19970509 200231 B US 2001930315 A 20010815 US 6656166 B2 20031202 US 93106383 Α 19930813 200379 US 95371849 Α 19950112 US 96625908 A 19960401 US 97853631 Α 19970509 US 2001930315

Α 20010815 Priority Applications (No Type Date): US 97853631 A 19970509; US 2001930315 A 20010815; US 93106383 A 19930813; US 95371849 A 19950112; US 96625908 A 19960401

Patent Details:

Patent No Kind Lan Pg Main IPC

Filing Notes

Div ex patent US 6277107 Cont of application US 93106383 Cont of application US 95371849 CIP of application US 96625908

A61M-005/00

Div ex application US 97853631

Cont of patent US 5423772

US 6656166 B2

Cont of patent US 5549581 CIP of patent US 5722963 Div ex patent US 6277107

... Inventor: LURIE K G

International Patent Class (Main): A61M-005/00 ...

... A61M-005/178

6/3, K/15(Item 15 from file: 350) DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

014396229 \*\*Image available\*\* WPI Acc No: 2002-216932/200227 Related WPI Acc No: 2001-431720

XRPX Acc No: N02-166293

Cardiopulmonary resuscitation training apparatus for use to train individuals to do resuscitation has inflatable bladder beneath flexible compression platform included in compression compartment

Patent Assignee: CPRX LLC (CPRX-N) Inventor: LURIE K G ; ZIELINSKI T M

Number of Countries: 095 Number of Patents: 002

Patent Family:

Applicat No Kind Kind Date Patent No A2 20020117 WO 2001US22180 A 20010710 200227 B WO 200203905 20010710 200234 20020121 AU 200182889 Α AU 200182889 Α

Priority Applications (No Type Date): US 2000614064 A 20000711

Patent Details:

Filing Notes Patent No Kind Lan Pg Main IPC

WO 200203905 A2 E 30 A61H-000/00

Designated States (National): AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT TZ UA UG UZ VN YU ZA ZW Designated States (Regional): AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW MZ NL OA PT SD SE SL SZ TR TZ UG ZW Based on patent WO 200203905 A61H-000/00 AU 200182889 A

Cardiopulmonary resuscitation training apparatus for use to train individuals to do resuscitation has inflatable bladder beneath flexible compression platform included in compression compartment

Inventor: LURIE K G ...

... ZIELINSKI T M

Abstract (Basic):

To train individuals to do CPR (Cardiopulmonary Resuscitation

... The drawing shows a CPR training device Title Terms: RESUSCITATION ;

6/3,K/16 (Item 16 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 014393541

WPI Acc No: 2002-214244/200227

Related WPI Acc No: 2000-105799; 2001-569813; 2002-139267

XRPX Acc No: N02-163874

Cardiopulmonary circulation increasing method for cardiopulmonary resuscitation, involves simulating diaphragm to contract, to suddenly increase negative intrathoracic pressure during recovery phase

Patent Assignee: CPRX LLC (CPRX-N) Inventor: BENDITT D G; LURIE K G

Number of Countries: 001 Number of Patents: 001

Patent Family:

Applicat No Kind Date Date Patent No Kind 200227 B 19980611 B1 20010522 US 9895916 Α US 6234985

Priority Applications (No Type Date): US 9895916 A 19980611

Patent Details:

Filing Notes Patent No Kind Lan Pg Main IPC

18 A61H-031/00 US 6234985 В1

Cardiopulmonary circulation increasing method for cardiopulmonary resuscitation , involves simulating diaphragm to contract, to suddenly increase negative intrathoracic pressure during recovery phase ...Inventor: LURIE K G

#### Abstract (Basic):

A patient's chest is actively compressed during a compression phase of the cardiopulmonary resuscitation ( CPR ). The diaphragm is simulated to contract to cause a sudden rise in the magnitude and duration of negative intrathoracic pressure during a recovery phase so as to enhance the amount of venous blood flow into... a) Cardiopulmonary resuscitation method...

...b) Cardiopulmonary resuscitation assistance device...

... For increasing cardiopulmonary circulation during cardiopulmonary resuscitation ( CPR ) such as standard, manual, closed chest CPR , interposed abdominal counter pulsation CPR , ACD- CPR , Lifestick' CPR , etc...

... The figure illustrate a cardiopulmonary resuscitation assistance device when used to treat a patient...

... Title Terms: RESUSCITATION ;

(Item 17 from file: 350) 6/3, K/17

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 014318565 WPI Acc No: 2002-139267/200218

Related WPI Acc No: 2000-105799; 2001-569813; 2002-214244

XRPX Acc No: N02-105012

Increasing method for blood flow to thorax of patient periodically stimulating phrenic nerve and periodically occluding airflow to lungs

Patent Assignee: CPRX LLC (CPRX-N)

Inventor: LINDNER K; LURIE K G; MCKNITE S; PATTERSON R; SAMNIAH N;

VOELCKEL W; ZIELINSKI T M

Number of Countries: 094 Number of Patents: 005

Patent Family:

Date Week Kind Applicat No Date Kind Patent No

```
200218
                                             Α.
                                                 20010316
                             WO 2001US8687
                   20010927
               Α2
WO 200170332
                                                           200218
                                                 20010316
                   20011003 AU 200145852
                                             Α
AU 200145852
               Α
                                                           200269
                                                 19980611
                                             Α
                             US 9895916
               В1
                   20021008
US 6463327
                                                 19981120
                                             Α
                             US 98197286
                                                  19990520
                                             Α
                             US 99315396
                                             Α
                                                 20000322
                             US 2000533880
                                                   19980611 200301
                    20021212 US 9895916
                                             Α
US 20020188332 A1
                                                  19981120
                                             Α
                             US 98197286
                                                  19990520
                                             Α
                             US 99315396
                                             Α
                                                  20000322
                             US 2000533880
                                             Α
                                                  20020529
                             US 2002158528
                                                            200345
                                             Α
                                                  19980611
                   20030701
                             US 9895916
US 6587726
                                                  19981120
                                              Α
                              US 98197286
                                                  19990520
                                              Α
                              US 99315396
                                                  20000322
                              US 2000533880
                                              Α
                                                  20020529
                                              Α
                              US 2002158528
Priority Applications (No Type Date): US 2000533880 A 20000322; US 9895916
  A 20020529
Patent Details:
                                      Filing Notes
                          Main IPC
 Patent No Kind Lan Pg
```

A 19980611; US 98197286 A 19981120; US 99315396 A 19990520; US 2002158528

WO 200170332 A2 E 80 A61N-000/00

Designated States (National): AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CR CU CZ DE DK DM DZ EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT TZ UA UG UZ VN YU ZA ŹW Designated States (Regional): AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IŤ KE LS LU MC MW MZ NL OA PT SD SE SL SZ TR TZ UG ZW

Based on patent WO 200170332 A61N-000/00 AU 200145852 A CIP of application US 9895916 A61N-001/36 US 6463327 В1 CIP of application US 98197286 CIP of application US 99315396 CIP of patent US 6224562 CIP of patent US 6234985

CIP of application US 9895916 A61N-001/18 US 20020188332 A1 CIP of application US 98197286 CIP of application US 99315396

Cont of application US 2000533880 CIP of patent US 6224562

CIP of patent US 6234985 CIP of patent US 6312399

CIP of application US 9895916 A61N-001/18 B2 US 6587726 CIP of application US 98197286 CIP of application US 99315396

Cont of application US 2000533880

CIP of patent US 6224562 CIP of patent US 6234985 CIP of patent US 6312399 Cont of patent US 6463327

...Inventor: LURIE K G ... ... ZIELINSKI T M

- ... Abstract (Basic): cause the diaphragm to contract and cause an increase in the magnitude and duration of negative intrathoracic pressure . The airflow to the lungs is periodically occluded during contraction of the diaphragm with a...
- ...control airflow into the patient's airway to further increase the magnitude and duration of negative intrathoracic pressure . This

forces more blood into the thorax...

...DETAILED DESCRIPTION - INDEPENDENT CLAIMS are included for a method for ventilating a patient, for a method of increasing blood flow to the thorax, for a medical...

... USE - For cardiopulmonary resuscitation .

...ADVANTAGE - Improved patient **ventilation**, especially if intubation is undesirable or where **ventilation** can result in bursting of pulmonary alveoli and bronchioles...

...DESCRIPTION OF DRAWING(S) - The figure shows a respiratory muscle stimulation device

```
(Item 18 from file: 350)
6/3,K/18
DIALOG(R)File 350:Derwent WPIX
(c) 2004 Thomson Derwent. All rts. reserv.
             **Image available**
014318558
WPI Acc No: 2002-139260/200218
Related WPI Acc No: 1995-193914; 1996-433571; 2000-421466; 2002-641994;
  2002-681034; 2003-030322; 2003-310772; 2003-371349; 2003-766762
XRPX Acc No: N02-105005
  Facial resuscitation mask has metronome with power supply in
  replaceable module
Patent Assignee: CPRX LLC (CPRX-N); ADVANCED CIRCULATORY SYSTEMS INC
  (ADCI-N)
Inventor: LURIE K G ; SCHARENBROICH G; ZIELINSKI T M
Number of Countries: 094 Number of Patents: 004
Patent Family:
                                                            Week
                                                   Date
                             Applicat No
                                            Kind
                     Date
Patent No
              Kind
                                                           200218
                                                 20010316
                             WO 2001US8505
                                            Α
               A2 20010927
WO 200170092
                                                           200218
                                                 20010316
                                             Α
                   20011003
                             AU 200149233
               Α
AU 200149233
                                                           200357
                                                 20010316
                             EP 2001922429
               A2 20030827
EP 1337292
                                                 20010316
                             WO 2001US8505
                                             Α
                                                           200424
                                                 20010316
                            JP 2001568295
                                             Α
JP 2004509654 W
                   20040402
                                                 20010316
                             WO 2001US8505
Priority Applications (No Type Date): US 2000532601 A 20000322
Patent Details:
                                     Filing Notes
                         Main IPC
Patent No Kind Lan Pg
WO 200170092 A2 E 26 A61B-000/00
```

Patent No Kind Lan Pg Main IPC FIIIII Notes

WO 200170092 A2 E 26 A61B-000/00

Designated States (National): AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA

CH CN CR CU CZ DE DK DM DZ EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP

KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ PL PT

RO RU SD SE SG SI SK SL TJ TM TR TT TZ UA UG UZ VN YU ZA ZW

Designated States (Regional): AT BE CH CY DE DK EA ES FI FR GB GH GM GR

IE IT KE LS LU MC MW MZ NL OA PT SD SE SL SZ TR TZ UG ZW

Based on patent WO 200170092

AU 200149233 A

ED 1337292 A2 E A61M-015/00 Based on patent WO 200170092

EP 1337292 A2 E A61M-015/00 Based on patent WO 2001/0092
Designated States (Regional): AT BE CH CY DE DK ES FI FR GB GR IE IT LI
LU MC NL PT SE TR

JP 2004509654 W 46 A61M-016/06 Based on patent WO 200170092

Facial resuscitation mask has metronome with power supply in replaceable module
Inventor: LURIE K G ...

į

#### ... ZIELINSKI T M

- ... Abstract (Basic): NOVELTY Mask comprises a valve (24) enabling respiratory gases to flow into and out of the mask body (12) and a metronome (26...
- ... chest compression signal at 50-100 signals per minute facilitating regular chest compressions when performing CPR . The metronome has a light (36) and speaker (34), the bottom end of the mask...
- ...DETAILED DESCRIPTION There are INDEPENDENT CLAIMS for (1) a CPR method, (2) a CPR kit...
- ... USE Mask is for use in cardiopulmonary resuscitation .
- ... Title Terms: RESUSCITATION ;
- ....International Patent Class (Main): A61M-015/00 ...
- ... A61M-016/06
- ...International Patent Class (Additional): A61M-016/20

(Item 19 from file: 350) 6/3,K/19

DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 014085599

WPI Acc No: 2001-569813/200164

Related WPI Acc No: 2000-105799; 2002-139267; 2002-214244

XRPX Acc No: N01-424612

Cardiopulmonary circulation enhancement in cardiopulmonary resuscitation , involves increasing amount of venous blood flow to heart and lungs by increasing magnitude and duration of negative intrathoracic pressure

Patent Assignee: CPRX LLC (CPRX-N)

Inventor: BENDITT D G; LURIE K G

Number of Countries: 001 Number of Patents: 001

Patent Family:

Week Date Applicat No Kind Date Patent No Kind 19980611 200164 B Α B1 20010501 US 9895916 US 6224562 19981120 Α US 98197286

Priority Applications (No Type Date): US 9895916 A 19980611; US 98197286 A 19981120

Patent Details:

Filing Notes Main IPC Patent No Kind Lan Pg

Cont of application US 9895916 B1 18 A61H-031/00 US 6224562 Cardiopulmonary circulation enhancement in cardiopulmonary resuscitation , involves increasing amount of venous blood flow to heart and lungs by increasing magnitude and duration of negative intrathoracic pressure

...Inventor: LURIE K G

Abstract (Basic):

The patient's chest is actively compressed during the compression phase. Some of the respiratory muscles are stimulated to contract, to increase the magnitude and duration of negative intrathoracic pressure during decompression phase. The increase in the magnitude and duration of negative intrathoracic pressure enhances the amount of venous blood flow into the heart and lungs. The respiratory muscles are stimulated to contract at a

frequency range of 30-120 times per minute, by applying electric

current to phrenic nerve. An INDEPENDENT CLAIM is also included for cardiopulmonary resuscitation device...

- ... For increasing cardiopulmonary circulation during cardiopulmonary resuscitation procedures...
- ... Cardiopulmonary circulation is increased during cardiopulmonary resuscitation procedures by enhancing the amount of venous blood flow to heart and lungs. The amount of negative intrathoracic pressure generated by contraction of respiratory muscles are used to adjust energy needed for subsequent contractions, hence respiratory muscles stimulating system can be located in emergency vehicle or health care facility...
- ... The figure shows the schematic view of respiratory muscle stimulation device...
- ... Title Terms: RESUSCITATION ;

(Item 20 from file: 350) 6/3, K/20

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 014029314

WPI Acc No: 2001-513528/200156

Related WPI Acc No: 1995-223538; 1996-401428; 1998-178372; 2000-012719;

2000-104863; 2002-267747; 2003-066281

XRPX Acc No: N01-380345

Introducer for guiding devices into the coronary sinus has a distal section whose straight proximal part is joined by a curved intermediate part to a terminal part curved in a plane at an acute angle to that of the intermediate part

Patent Assignee: DAIG CORP (DAIG-N)

Inventor: BENDITT D G; BLANC J J; LURIE K G ; STARKS D J

Number of Countries: 001 Number of Patents: 001

Patent Family:

Date Week Applicat No Kind Date Patent No Kind 200156 B 19930813 Α US 6277107 B1 20010821 US 93106383 US 95371849 Α 19950112 Α 19960401 US 96625908 US 97853631 19970509 Α

Priority Applications (No Type Date): US 97853631 A 19970509; US 93106383 A 19930813; US 95371849 A 19950112; US 96625908 A 19960401

Filing Notes

Patent Details:

Main IPC Patent No Kind Lan Pg 17 A61M-025/01 B1US 6277107

Cont of application US 93106383 Cont of application US 95371849 CIP of application US 96625908 Cont of patent US 5423772

Cont of patent US 5549581 CIP of patent US 5722963

...Inventor: LURIE K G

International Patent Class (Main): A61M-025/01

(Item 21 from file: 350) 6/3, K/21

DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 013923260 WPI Acc No: 2001-407473/200143 Related WPI Acc No: 1999-561889; 2003-439208 XRPX Acc No: N01-301437 Automatic weaning of patient from medical ventilator, involves adjusting patient support level according to comparison results of patient spontaneous breathing rate and minute volume with preset range Patent Assignee: CARDIOPULMONARY CORP (CARD-N); BIONDI J W (BION-I); LOCKHORN N (LOCK-I); REYNOLDS R (REYN-I) Inventor: BIONDI J W ; LOCKHORN N; REYNOLDS R Number of Countries: 101 Number of Patents: 005 Patent Family: Week Date Applicat No Kind Date Patent No Kind 19951208 200143 B Α 20010628 US 95569919 US 20010004893 A1 19980320 Α US 9845461 20000913 Α US 2000660820 20010123 US 2001767173 Α 200260 20020122 Α WO 2002US1716 20020801 Α2 WO 200258619 200271 19951208 Α 20021015 US 95569919 В2 US 6463930 19980320 Α US 9845461 20000913 US 2000660820 Α 20010123 US 2001767173 Α 200379 20020122 Α EP 2002704199 20031029 A2 EP 1355690 20020122 Α WO 2002US1716 200427 20020122 AU 2002237895 Α AU 2002237895 A1 20020806 Priority Applications (No Type Date): US 2001767173 A 20010123; US 95569919 A 19951208; US 9845461 A 19980320; US 2000660820 A 20000913 Patent Details: Filing Notes Main IPC Patent No Kind Lan Pg CIP of application US 95569919 30 A62B-007/00 US 20010004893 A1 Cont of application US 9845461 CIP of application US 2000660820 CIP of patent US 5931160 Cont of patent US 6158432 WO 200258619 A2 E A61H-031/00 Designated States (National): AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO RU SD SE SG SI SK SL TJ TM TN TR TT TZ UA UG UZ VN YU ZA Designated States (Regional): AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW MZ NL OA PT SD SE SL SZ TR TZ UG ZM ZW CIP of application US 95569919 A61M-016/00 В2 US 6463930 Cont of application US 9845461 CIP of application US 2000660820 CIP of patent US 5931160 Cont of patent US 6158432 Based on patent WO 200258619 A61M-016/00 EP 1355690 A2 E Designated States (Regional): AL AT BE CH CY DE DK ES FI FR GB GR IE IT LI LT LU LV MC MK NL PT RO SE SI TR Based on patent WO 200258619 A61H-031/00 AU 2002237895 A1 Automatic weaning of patient from medical ventilator , involves adjusting patient support level according to comparison results of patient spontaneous breathing rate and minute volume with preset range Inventor: BIONDI J W ...

Abstract (Basic):

system (41) with pressurized gas source (45). A data processor (30) detects and measures spontaneous breathing rate of patient. A

flow meter (11) measures patient's minute volume. The detected breathing rate and measured minute volume are compared with preset range of breathing rates and preset tidal volume respectively, based on which the processor adjusts patient's support...

An INDEPENDENT CLAIM is also included for ventilator system

for automatically weaning patient from ventilator .

... For control of ventilator pneumatic system in medical ventilator .

... Automatically weans a patient from ventilator and reduces air-way resistance in the breathing circuit during exhalation and enables the clinician to determine the optimal therapy for the patient...

... The figure shows the block diagram of ventilator .

... Title Terms: VENTILATION ;

...International Patent Class (Main): A61M-016/00 ...

... A62B-007/00

(Item 22 from file: 350) 6/3, K/22

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 013249583

WPI Acc No: 2000-421466/200036

Related WPI Acc No: 1995-193914; 1996-433571; 2002-139260; 2002-641994;

2002-681034; 2003-030322; 2003-310772; 2003-371349; 2003-766762

XRPX Acc No: N00-314350

Apparatus and methods for assisting cardiopulmonary resuscitation that incorporates a transition tube, which connects the endotracheal tube to the ventilation bag, the ventilation valve serves to introduce air into the device

Patent Assignee: CPRX LLC (CPRX-N)

Inventor: GOLD B; LURIE K G ; SWEENEY M

Number of Countries: 001 Number of Patents: 001

Patent Family:

Date Week Kind Applicat No Kind Date Patent No 200036 B 19931109 20000516 US 93149204 Α Α US 6062219 19950310 Α US 95403009 19971015 US 97950702 Α

Priority Applications (No Type Date): US 97950702 A 19971015; US 93149204 A 19931109; US 95403009 A 19950310

Patent Details:

Filing Notes Patent No Kind Lan Pg Main IPC

CIP of application US 93149204 23 A62B-009/02 US 6062219 Α

CIP of application US 95403009

CIP of patent US 5551420

CIP of patent US 5692498

Apparatus and methods for assisting cardiopulmonary resuscitation that incorporates a transition tube, which connects the endotracheal tube to the ventilation bag, the ventilation valve serves to introduce air into the device

...Inventor: LURIE K G

Abstract (Basic):

consists an endotracheal tube (36), which is placed into the patients trachea and provides a ventilation passageway. Connected is a transition tube (38), which connects the endotracheal tube to the ventilation bag (28). The ventilation valve (26) serves to introduce air into the device. Attached or connected to the transition... ...airflow responsive valve (24). The inflow valve is biased so that it opens when the negative intrathoracic pressure in the patients chest reaches a threshold amount. External chest compression and decompression as part of the

... Properly ventilate the patient with air, in a controlled manner...

... Ventilation valve (26...

... Ventilation tube (28

... Title Terms: RESUSCITATION ;

International Patent Class (Main): A62B-009/02

International Patent Class (Additional): A61M-016/00 ...

cardiopulmonary resuscitation procedures...

... A62B-007/10

(Item 23 from file: 350) 6/3, K/23

DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 013145782 WPI Acc No: 2000-317654/200027

XRPX Acc No: N00-238437

Cardiopulmonary resuscitation ventilator for ventilating patient uses ventilator to periodically supply respiratory gases to patient's lungs using sensor to detect chest compressions by sensing intrathoracic pressure changes

Patent Assignee: CPRX LLC (CPRX-N) Inventor: LURIE K G ; ZIELINSKI T M

Number of Countries: 090 Number of Patents: 004

Patent Family:

Week Date Kind Applicat No Date Kind Patent No 19991005 200027 20000413 WO 99US23233 Α A1 WO 200020061 19991005 Α 20000426 AU 9964164 AU 9964164 Α 200066 19981007 Α US 98168049 20001205 US 6155257 Α 200144 19991005 Α A1 20010801 EP 99951803 EP 1119385 19991005 Α WO 99US23233

Priority Applications (No Type Date): US 98168049 A 19981007

Patent Details:

Filing Notes Main IPC Patent No Kind Lan Pg

WO 200020061 A1 E 55 A61M-016/00

Designated States (National): AE AL AM AT AU AZ BA BB BG BR BY CA CH CN CR CÚ CZ DE DK DM EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT TZ UA UG UZ VN YU ZA ZW Designated States (Regional): AT BE CH CY DE DK EA ES FI FR GB GH GM GR

IE IT KE LS LU MC MW NL OA PT SD SE SL SZ TZ UG ZW

Based on patent WO 200020061 A61M-016/00 Α AU 9964164

A61M-016/00 US 6155257 Α Based on patent WO 200020061 A61M-016/00 A1 E EP 1119385 Designated States (Regional): AL AT BE CH CY DE DK ES FI FR GB GR IE IT LI LT LU LV MC MK NL PT RO SE SI Cardiopulmonary resuscitation ventilator for ventilating patient uses ventilator to periodically supply respiratory gases to patient's lungs using sensor to detect chest compressions by sensing intrathoracic pressure...

Inventor: LURIE K G ...

#### ... ZIELINSKI T M

Abstract (Basic):

The cardiopulmonary resuscitation ventilator ventilates a patient using a ventilator (12) to periodically supply respiratory gases to patient's lungs and uses a sensor (14) to detect chest compressions by...

...pressure changes. A controller is coupled to the sensor to control the action of the **ventilator** after a predetermined number of chest compressions are detected by the sensor.

. As a cardiopulmonary resuscitation ventilator for ventilating a patient...

... Easily and conveniently co-ordinates the timing of chest compressions with the **ventilation**, and precisely controls the volume of **respiratory** gases delivered to the patient...

... The drawing shows a schematic view of the **ventilator** coupled to a valve with a sensor to detect chest compressions by sensing changes in

... ventilator (12

Title Terms: RESUSCITATION ;

International Patent Class (Main): A61M-016/00

6/3,K/24 (Item 24 from file: 350)

DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

013065040 \*\*Image available\*\*
WPI Acc No: 2000-236912/200020

XRPX Acc No: N00-177652

Heart failure mask and methods for increasing negative intrathoracic pressures that incorporates an airflow controller

Patent Assignee: CPRX LLC (CPRX-N)

Inventor: LURIE K G

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week
US 6029667 A 20000229 US 96747371 A 19961112 200020 B
US 9819843 A 19980206

Priority Applications (No Type Date): US 9819843 A 19980206; US 96747371 A 19961112

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

US 6029667 A 9 A61M-016/00 CIP of application US 96747371

CIP of patent US 5730122

Heart failure mask and methods for increasing negative intrathoracic pressures that incorporates an airflow controller

Inventor: LURIE K G

Ç

Abstract (Basic):

includes an inflow hole (36) and a pair of outflow holes (38). The holes allow respiratory gasses to flow into and out from mask (12), when valves (22) and (24) are...

... The treatment proceeds by preventing respiratory gasses from entering the patients lungs during inhalation until a negative intrathoracic pressure within a desired range is developed within the patient...

International Patent Class (Main): A61M-016/00

International Patent Class (Additional): A62B-018/02 ...

#### ... A62B-018/10

(Item 25 from file: 350) 6/3, K/25DIALOG(R) File 350: Derwent WPIX (c) 2004 Thomson Derwent. All rts. reserv. \*\*Image available\*\* 012933952 WPI Acc No: 2000-105799/200009 Related WPI Acc No: 2001-569813; 2002-139267; 2002-214244 XRPX Acc No: N00-081272 Method for increasing cardiopulmonary circulation when performing cardiopulmonary resuscitation Patent Assignee: CPRX LLP (CPRX-N); CPRX LLC (CPRX-N); ADVANCED CIRCULATORY SYSTEMS INC (ADCI-N) Inventor: BENDITT D G; LURIE K G ; PATTERSON R; VOECKEL W; ZIELINSKI T M Number of Countries: 086 Number of Patents: 006 Patent Family: Week Applicat No Kind Date Kind Date Patent No 200009 19990610 WO 99US13161 Α 19991216 Α2 WO 9963926 200022 19990610 AU 9944352 Α 19991230 Α AU 9944352 19990610 200114 BR 9911093 Α 20010220 BR 9911093 Α WO 99US13161 Α 19990610 200128 20010516 EP 99927453 Α 19990610 **A2** EP 1098622 19990610 WO 99US13161 Α 200170 Α 19980611 US 9895916 US 6312399 В1 20011106 Α 19981120 US 98197286 Α 19990520 US 99315396 200242 19990610 20020618 WO 99US13161 Α JP 2002517283 W 19990610 JP 2000553001 Α Priority Applications (No Type Date): US 99315396 A 19990520; US 9895916 A 19980611; US 98197286 A 19981120 Patent Details: Patent No Kind Lan Pg Main IPC Filing Notes A2 E 51 A61H-000/00 WO 9963926 Designated States (National): AE AL AM AT AU AZ BA BB BG BR BY CA CH CN CU CZ DE DK EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT UA UG UZ VN YU ZA ZW Designated States (Regional): AT BE CH CY DE DK EA ES FI FR GB GH GM GR IE IT KE LS LU MC MW NL OA PT SD SE SL SZ UG ZW Based on patent WO 9963926 AU 9944352 Α Based on patent WO 9963926 A61N-001/36 BR 9911093 Α Based on patent WO 9963926 EP 1098622 A2 E A61H-001/00 Designated States (Regional): DE FR GB CIP of application US 9895916 A61H-031/00 US 6312399 В1 CIP of application US 98197286

CIP of patent US 6224562 CIP of patent US 6234985 Based on patent WO 9963926

JP 2002517283 W

48 A61M-016/04

Method for increasing cardiopulmonary circulation when performing cardiopulmonary resuscitation

...Inventor: LURIE K G ...

#### ... ZIELINSKI T M

Abstract (Basic):

... Respiratory muscles are stimulated during a decompression phase by applying electric or magnetic energy to the...

...cause the patient to gasp. The energy is applied such that magnitude and duration of **negative** intrathoracic **pressure** is increased, to enhance flow of blood in heart and lungs.

During stimulation, the respiratory muscles contract at a specific frequency between 30-120 times per minute. Respiratory gases may be supplied to the lung...

- ...INDEPENDENT CLAIMS are also included for a device to assist in cardiopulmonary resuscitation, a stimulation system, a system for producing a cough and a kit for cardiopulmonary resuscitation including the device...
- ...For cardiopulmonary resuscitation for treatment of sudden cardiac arrests...
- ... Enhances cardiopulmonary resuscitation , as electric or magnetic pulses are applied for muscle stimulation...
- ... The figure shows a top plan view of a respiratory muscle stimulation device...
- ... Title Terms: RESUSCITATION
- ...International Patent Class (Main): A61M-016/04

6/3,K/26 (Item 26 from file: 350)

DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

012933016 \*\*Image available\*\* WPI Acc No: 2000-104863/200009

Related WPI Acc No: 1995-223538; 1996-401428; 1998-178372; 2000-012719;

2001-513528; 2002-267747; 2003-066281

XRPX Acc No: N00-080524

Cardiac catheter for use in coronary sinus of human heart

Patent Assignee: DAIG CORP (DAIG-N)

Inventor: BENDITT D G; FLEISCHHACKER J J; LURIE K G; OCKULY J D; SHULTZ J

J

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week
US 6001085 A 19991214 US 93106383 A 19930813 200009 B
US 95371849 A 19950112
US 96625908 A 19960401

US 97996887 A 19971223

Priority Applications (No Type Date): US 93106383 A 19930813; US 95371849 A

19950112; US 96625908 A 19960401; US 97996887 A 19971223

Patent Details:

Patent No Kind Lan Pg Main IPC

US 6001085 A 9 A61M-025/00

Filing Notes

Cont of application US 93106383

Cont of application US 95371849

Cont of application US 96625908 Cont of patent US 5423772

Cont of patent US 5549581

Cont of patent US 5722963

... Inventor: LURIE K G

International Patent Class (Main): A61M-025/00

6/3,K/27 (Item 27 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

012840887 \*\*Image available\*\*

WPI Acc No: 2000-012719/200001 Related WPI Acc No: 1995-223538; 1996-401428; 1998-178372; 2000-104863;

2001-513528; 2002-267747; 2003-066281

XRPX Acc No: N00-009891 Coronary sinus catheter

Patent Assignee: DAIG CORP (DAIG-N)

Inventor: BENDITT D G; FLEISCHHACKER J J; LURIE K G; OCKULY J D; SHULTZ J

J

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week

US 5984909 A 19991116 US 93106383 A 19930813 US 95371849 A 19950112

US 97996887 A 19971223

US 98146857 A 19980903

Priority Applications (No Type Date): US 93106383 A 19930813; US 95371849 A 19950112; US 97996887 A 19971223; US 98146857 A 19980903

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

US 5984909 A 10 A61M-025/00 Cont of application

Cont of application US 93106383

Cont of application US 95371849

Cont of application US 97996887

Cont of patent US 5423772 Cont of patent US 5549581

... Inventor: LURIE K G

International Patent Class (Main): A61M-025/00

6/3,K/28 (Item 28 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

012755772 \*\*Image available\*\*

WPI Acc No: 1999-561889/199947

Related WPI Acc No: 1997-319553; 2001-407473; 2003-439208

XRPX Acc No: N99-415169

Compensating gas flow resistance in ventilation apparatus for

controlling ventilator pneumatic system

Patent Assignee: BIONDI J W (BION-I); GILMORE D D (GILM-I); JOHNSTON D M (JOHN-I); REYNOLDS R (REYN-I); SCHROEDER G P (SCHR-I); CARDIOPULMONARY

CORP (CARD-N)

Inventor: BIONDI J W ; GILMORE D D; JOHNSTON D M; REYNOLDS R; SCHROEDER G P; JOHNSON D M Number of Countries: 020 Number of Patents: 004 Patent Family: Date Week Applicat No Kind Patent No Kind Date 19990923 WO 99US6056 A 19990319 199947 WO 9947200 Α1 20001212 US 95569919 Α 19951208 US 6158432 Α US 9845461 Α 19980320 Α 19951208 200221 US 95569919 US 20020026941 A1 20020307 US 9845461 Ά 19980320 US 2000660820 Α 20000913 US 2001931572 Α 20010814 US 95569919 Α 19951208 200345 US 6584973 20030701 Α 19980320 US 9845461 US 2000660820 Α 20000913 Priority Applications (No Type Date): US 9845461 A 19980320; US 95569919 A 19951208; US 2000660820 A 20000913; US 2001931572 A 20010814 Patent Details: Filing Notes Main IPC Patent No Kind Lan Pg A1 E 55 A61M-016/00 WO 9947200 Designated States (National): IL Designated States (Regional): AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE CIP of application US 95569919 A61M-016/00 US 6158432 Α CIP of patent US 5931160 CIP of application US 95569919 A62B-007/00 US 20020026941 A1 Cont of application US 9845461 Cont of application US 2000660820 CIP of patent US 5931160 Cont of patent US 6158432 CIP of application US 95569919 A61M-016/00 В1 US 6584973 Cont of application US 9845461 CIP of patent US 5931160 Cont of patent US 6158432 Compensating gas flow resistance in ventilation apparatus for controlling ventilator pneumatic system Inventor: BIONDI J W ... Abstract (Basic): peak exhalation flow rate an airway resistance. An effective airway pressure is calculated and a negative airway pressure is applied to an exhalation circuit such that the effective circuit pressure is greater than zero and less than positive end-expiratory pressure ( PEEP ). alarm and mandatory patient support upon detection of apnea (i.e., the detected absence of breathing ), During operation, both systems perform background tests to detect system faults. INDEPENDENT CLAIMS are included for: a ventilator assist device controlling processor and user interface... ... For controlling a ventilator pneumatic system... ... Reduces patient work of breathing without compromising patient ventilation requirements... ... ventilator control system (10 ... Title Terms: VENTILATION ;

International Patent Class (Main): A61M-016/00 ...

... A62B-007/00

(Item 29 from file: 350) 6/3, K/29DIALOG(R)File 350:Derwent WPIX (c) 2004 Thomson Derwent. All rts. reserv. \*\*Image available\*\* 012140348 WPI Acc No: 1998-557260/199847 XRPX Acc No: N98-434385 Implanted device for detection and treatment of syncope - in which pharmaceutical composition for treating syncope is infused into heart upon detection of physiological activity associated with onset of syncope Patent Assignee: PHARMATARGET INC (PHAR-N) Inventor: BENDITT D; BUSCEMI P J; LURIE K G ; OBINO S F Number of Countries: 021 Number of Patents: 003 Patent Family: Applicat No Date Week Kind Date Patent No 199847 19980408 19981015 WO 98US7364 Α A1 WO 9844986 19970410 199933 Α US 97831608 19990706 US 5919210 Α 200035 Α 19970410 US 97831608 20000620 US 6078834 Α 19990225 US 99257566 Α Priority Applications (No Type Date): US 97831608 A 19970410; US 99257566 A 19990225 Patent Details: Main IPC Filing Notes Patent No Kind Lan Pg A1 E 28 A61N-001/368 WO 9844986 Designated States (National): CA JP Designated States (Regional): AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE A61M-005/142 US 5919210 Α A61M-005/142 Cont of application US 97831608 US 6078834 Α Cont of patent US 5919210 ...Inventor: LURIE K G International Patent Class (Main): A61M-005/142 ...

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

(Item 30 from file: 350)

\*\*Image available\*\* 011799163 WPI Acc No: 1998-216073/199819

XRPX Acc No: N98-170832

Heart failure mask for increasing negative intrathoracic pressures has mask placed on patients face and includes one-way expiration valve with inspiratory threshold valve

Patent Assignee: CPRX INC (CPRX-N)

Inventor: LURIE K G

Number of Countries: 079 Number of Patents: 004

Patent Family:

6/3.K/30

Date Kind Applicat No Patent No Kind Date A 19961112 US 96747371 Α 19980324 US 5730122 A 19971112 WO 97US20378 A1 19980522 WO 9820938 A 19971112 199842 19980603 AU 9851734 Α AU 9851734 19971112 199948 EP 97946595 Α EP 949941 Α1 19991020 19971112 Α WO 97US20378

Priority Applications (No Type Date): US 96747371 A 19961112

Patent Details:

Filing Notes Patent No Kind Lan Pg Main IPC

8 A62B-018/10 A US 5730122

A1 E A62B-018/10 WO 9820938

Designated States (National): AL AM AT AU AZ BA BB BG BR BY CA CH CN CU CZ DE DK EE ES FI GB GE GH HU ID IL IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT UA UG UZ VN YU ZW

Designated States (Regional): AT BE CH DE DK EA ES FI FR GB GH GR IE IT KE LS LU MC MW NL OA PT SD SE SZ UG ZW

Based on patent WO 9820938 A62B-018/10 AU 9851734 Based on patent WO 9820938 A62B-018/10 EP 949941 A1 E

Designated States (Regional): DE FR GB

Heart failure mask for increasing negative intrathoracic pressures -Inventor: LURIE K G

- ... Abstract (Basic): range from about -3 cm H2O to about -25 cm H2O. The patient is kept breathing while the mask is sealed to the face...
- ... Respiratory gases are substantially completely prevented from entering the patient's lungs during inhalation until such...
- $\dots$ 3 cm H2O to about -25 cm H2O, whereupon the inspiratory valve opens to allow respiratory gases into the lungs International Patent Class (Main): A62B-018/10

International Patent Class (Additional): A62B-018/02

(Item 31 from file: 350) 6/3,K/31

DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 011761462

WPI Acc No: 1998-178372/199816

Related WPI Acc No: 1995-223538; 1996-401428; 2000-012719; 2000-104863; 2001-513528; 2002-267747; 2003-066281

XRPX Acc No: N98-141189

Catheter for coronary sinus of heart - has two sections each curved with respective arcs such that sum of arcs is between about 75 to about 100 degrees

Patent Assignee: DAIG CORP (DAIG-N)

Inventor: BENDITT D G; FLEISCHHACKER J J; LURIE K G; OCKULY J D; SHULTZ J

Number of Countries: 001 Number of Patents: 001

Patent Family:

Applicat No Week Kind Date Date Kind Patent No 199816 B 19930813 A 19980303 US 93106383 Α US 5722963 19950112 US 95371849 Α

19960401 Α US 96625908

Priority Applications (No Type Date): US 93106383 A 19930813; US 95371849 A 19950112; US 96625908 A 19960401

Patent Details:

Filing Notes Patent No Kind Lan Pg Main IPC

Cont of application US 93106383 8 A61M-025/00 US 5722963 Cont of application US 95371849

Cont of patent US 5423772 Cont of patent US 5549581

...Inventor: LURIE K G

International Patent Class (Main): A61M-025/00

(Item 32 from file: 350) 6/3,K/32 DIALOG(R) File 350: Derwent WPIX Thomson Derwent. All rts. reserv. 011591259 WPI Acc No: 1998-008388/199801 XRAM Acc No: C98-002868 Use of vasopressin in medicaments to treat cardiac arrest - in conjunction with adrenergic and/or bradycardic agent(s), for administration to patients undergoing cardio-pulmonary resuscitation Patent Assignee: LINDNER K (LIND-I); LURIE K G (LURI-I) Inventor: LINDNER K; LURIE K G Number of Patents: 010 Number of Countries: 022 Patent Family: Kind Date Week Applicat No Date Kind Patent No 199801 19970327 WO 97US5056 Ά 19971009 WO 9736609 Α2 19970327 199808 AU 9725527 Α Α 19971022 AU 9725527 19960329 199850 .US 96625733 Α 19981027 US 5827893 Α EP 97917089 Α 19970327 199917 19990331 EP 904097 A2 19970327 WO 97US5056 Α 200028 19970327 Α AU 9725527 AU 718520 20000413 200036 19970327 Α JP 97535438 20000627 JP 2000507954 19970327 Α WO 97US5056 200309 Α 19970327 CA 2250420 20021217 CA 2250420 С 19970327 WO 97US5056 200336 19970327 EP 97917089 20030528 EP 904097 В1 WO 97US5056 19970327 200351 19970327 20030703 DE 622401 DE 69722401 EP 97917089 19970327 19970327 WO 97US5056 200426 19970327 20040301 EP 97917089 ES 2200171 Т3 Priority Applications (No Type Date): US 96625733 A 19960329 Patent Details: Main IPC Filing Notes Patent No Kind Lan Pg A2 E 36 A61K-038/11 WO 9736609 Designated States (National): AU CA JP Designated States (Regional): AT BE CH DE DK ES FI FR GB GR IE IT LU MC NL PT SE Based on patent WO 9736609 A61K-038/11 AU 9725527 Α A61K-025/00 US 5827893 Α Based on patent WO 9736609 A2 E A61K-038/11 EP 904097 Designated States (Regional): AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE Previous Publ. patent AU 9725527 A61K-038/11 AU 718520 Based on patent WO 9736609 Based on patent WO 9736609 35 A61K-038/11 JP 2000507954 W Based on patent WO 9736609 A61K-038/11 CA 2250420 C Ε Based on patent WO 9736609 A61K-038/11 B1 E EP 904097 Designated States (Regional): AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE Based on patent EP 904097 DE 69722401 A61K-038/11 Based on patent WO 9736609 Based on patent EP 904097 A61K-038/11 ES 2200171 Т3

<sup>...</sup> conjunction with adrenergic and/or bradycardic agent(s), for administration to patients undergoing cardio-pulmonary resuscitation ...Inventor: LURIE K G

- ... Abstract (Basic): in conjunction with one or more adrenergic agents; when administered to a patient undergoing cardiopulmonary resuscitation; are new. Also claimed are: (a) a kit for the treatment of cardiac arrest comprising...
- ...instructions indicating that the active agents are to be administered to a patient undergoing cardiopulmonary resuscitation .
- ... The kits are useful in treatment of cardiac arrest when administered to patients undergoing cardiopulmonary resuscitation .

... Title Terms: RESUSCITATION (Item 33 from file: 350) 6/3, K/33DIALOG(R)File 350:Derwent WPIX (c) 2004 Thomson Derwent. All rts. reserv. 011035578 \*\*Image available\*\* WPI Acc No: 1997-013502/199702 Related WPI Acc No: 1995-223538; 1996-401428; 1998-178372; 2000-012719; 2000-104863 XRPX Acc No: N97-011775 Catheter for use in the coronary sinus - has main reinforced portion, intermediate zone portion and tip portion, where portion of the catheter is curved in compound curve formed by first and second curve Patent Assignee: DAIG CORP (DAIG-N); UNIV MINNESOTA (MINU ) Inventor: BENDITT D G; FLEISCHHACKER J J; 1LURIE K G; OCKULY J D; SHULTZ J ıΤ Number of Countries: 013 Number of Patents: 008 Patent Family: Week Kind Date Applicat No Date Patent No Kind 199702 EP 96102200 Ά 19960214 A2 19961204 EP 745406 199708 19960408 19961210 JP 9685364 Α Α JP 8322939 19951228 199714 Α 19961202 CA 2166260 Α CA 2166260 19960214 199715 Α EP 96102200 EP 745406 A3 19970205 . A 19930813 US 93106383 19970701 Α US 5643231 19950112 US 95371849 Α 19950601 US 95457675 Α 19951228 .199936 Ά CA 2166260 CA 2166260 С 19990504 EP 96102200 19960214 200355 Α EP 745406 20030813 B1DE 629418 Α 19960214 200369 20030918 DE 69629418 Ε 19960214 EP 96102200 Α Priority Applications (No Type Date): US 95457675 A 19950601; US 93106383 A 19930813; US 95371849 A 19950112 Patent Details: Filing Notes Patent No Kind Lan Pg Main IPC A2 E 9 A61M-025/00 EP 745406 Designated States (Regional): AT CH DE ES FR GB IT LI NL SE 7 A61M-025/00 JP 8322939 Α A61M-025/00 CA 2166260 Α A61M-025/00 EP 745406 A3 CIP of application US 93106383 8 A61M-025/00 US 5643231 Α CIP of application US 95371849

A61M-025/00

A61M-025/00

Designated States (Regional): AT CH DE ES FR GB IT LI NL SE

CA 2166260

EP 745406

C E B1 E CIP of patent US 5423772 CIP of patent US 5549581

Based on patent EP 745406 A61M-025/00 Ė DE 69629418 ...Inventor: LURIE K G International Patent Class (Main): A61M-025/00 International Patent Class (Additional): A61M-025/01 ... (Item 34 from file: 350) 6/3,K/34 DIALOG(R)File 350:Derwent WPIX (c) 2004 Thomson Derwent. All rts. reserv. \*\*Image available\*\* 010936621 WPI Acc No: 1996-433571/199643 Related WPI Acc No: 1995-193914; 2000-421466; 2002-139260; 2002-641994; 2002-681034; 2003-030322; 2003-310772; 2003-371349; 2003-766762 XRPX Acc No: N96-365340 Cardio-pulmonary resuscitation device - has airflow impeding structure in form of restrictive orifice or pressure responsive valve placed within or in series with mask or breathing tube Patent Assignee: CPRX CORP (CPRX-N); CPRX LLC (CPRX-N); CPRX INC (CPRX-N); GOLD B (GOLD-I); LURIE K G (LURI-I); SWEENEY M (SWEE-I) Inventor: GOLD B; LURIE K G ; SWEENEY M Number of Countries: 070 Number of Patents: 007 Patent Family: Date Week Kind Applicat No Date Patent No Kind 199643 Α 19960216 WO 96US2097 19960919 Α1 WO 9628215 AU 9649257 199703 19960216 Α 19961002 Α AU 9649257 199803 19931109 Α 19971202 US 93149204 US 5692498 Α 19950310 Α US 95403009 199913 19960216 Α 19990303 EP 96905523 EP 898485 Α1 Α 19960216 WO 96US2097 200242 Α 19960216 CN 96193712 19980603 CN 1183731 Α 200330 19960216 EP 96905523 Α 20030502 EP 898485  $_{\rm B1}$ 19960216 WO 96US2097 Α Α 19960216 200345 DE 627898 20030605 DE 69627898 Ε EP 96905523 Α 19960216 19960216 WO 96US2097 Α Priority Applications (No Type Date): US 95403009 A 19950310; US 93149204 A 19931109 Patent Details: Main IPC Filing Notes Patent No Kind Lan Pg A1 E 48 A62B-007/00 Designated States (National): AL AM AT AU AZ BB BG BR BY CA CH CN CZ DE DK EE ES FI GB GE HU IS JP KE KG KP KR KZ LK LR LS LT LU LV MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK TJ TM TR TT UA UG US UZ VN Designated States (Regional): AT BE CH DE DK EA ES FR GB GR IE IT KE LS LU MC MW NL OA PT SD SE SZ UG Based on patent WO 9628215 AU 9649257 Α CIP of application US 93149204 23 A62B-009/02 US 5692498 A CIP of patent US 5551420 Based on patent WO 9628215 A1 E A62B-007/00 EP 898485 Designated States (Regional): DE FR GB IT SE A62B-007/00 A CN 1183731 Based on patent WO 9628215 A62B-007/00 B1 E EP 898485 Designated States (Regional): DE FR GB IT SE Based on patent EP 898485 A62B-007/00 E DE 69627898 Based on patent WO 9628215 Cardio-pulmonary resuscitation device...

... of restrictive orifice or pressure responsive valve placed within or in

series with mask or breathing tube ... Inventor: LURIE K G

- ... Abstract (Basic): The cardio-pulmonary resuscitation device has an airflow impeding structure in the form of a restrictive orifice or a pressure responsive valve (24) placed within or in series with a mask or breathing tube (36...
- ... ADVANTAGE Enhances extent and duration of negative intra-thoracic pressure during decompression of the patient's chest to enhance venous blood flow into the heart and lungs from the peripheral venous vasculature when performing cardio-pulmonary resuscitation .
- ... Abstract (Equivalent): The cardio-pulmonary resuscitation device has an airflow impeding structure in the form of a restrictive orifice or a pressure responsive valve (24) placed within or in series with a mask or breathing tube (36...
- ...ADVANTAGE Enhances extent and duration of negative intra-thoracic pressure during decompression of the patient's chest to enhance venous blood flow into the heart and lungs from the peripheral venous vasculature when performing cardio-pulmonary resuscitation .

... Title Terms: RESUSCITATION; International Patent Class (Main): A62B-007/00 ...

... A62B-009/02 International Patent Class (Additional): A61M-016/04 ...

... A61M-016/20

(Item 35 from file: 350) 6/3, K/35DIALOG(R) File 350: Derwent WPIX (c) 2004 Thomson Derwent. All rts. reserv.

010904477 \*\*Image available\*\* WPI Acc No: 1996-401428/199640

Related WPI Acc No: 1995-223538; 1998-178372; 2000-012719; 2000-104863; 2001-513528; 2002-267747; 2003-066281

XRPX Acc No: N96-338248

Catheter for insertion in ostium of coronary sinus in right atrium - has main reinforcing portion, intermediate zone portion and soft tip portion, with portion of catheter is curved in double curve, with first and second curve being longitudinal curves

Patent Assignee: DAIG CORP (DAIG-N)

Inventor: BENDITT D G; FLEISCHHACKER J J; LURIE K G; OCKULY J D; SHULTZ J

Number of Countries: 001 Number of Patents: 001

Patent Family:

Date Week Applicat No Kind Kind Date Patent No 199640 B 19930813 · A 19960827 US 93106383 Α US 5549581 19950112 US 95371849 A.

Priority Applications (No Type Date): US 93106383 A 19930813; US 95371849 A 19950112

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes Cont of application US 93106383 US 5549581 A 8 A61M-025/00 Cont of patent US 5423772

...Inventor: LURIE K G

International Patent Class (Main): A61M-025/00

```
(Item 36 from file: 350)
 6/3, K/36
DIALOG(R)File 350:Derwent WPIX
(c) 2004 Thomson Derwent. All rts. reserv.
             **Image available**
010789985
WPI Acc No: 1996-286938/199629
XRPX Acc No: N96-240896.
  Pneumatic system for ventilator to control inspired and expired gas
  flow during respiratory therapy - has pneumatic system including
  circuit for controlling supply of one or more selected gases to patient
  breathing circuit
Patent Assignee: CARDIOPULMONARY CORP (CARD-N)
Inventor: BIONDI J W ; JOHNSTON D M; SCHROEDER G
Number of Countries: 023 Number of Patents: 009
Patent Family:
                                                    Date
                             Applicat No
                                             Kind
              Kind
                     Date
Patent No
                                                 19951204
                                                            199629
                                             Α
                   19960613
                             WO 95US15706
               A1
WO 9617641
                                                 19951204
                                                            199641
                                             Α
                             AU 9646391
               Α
                   19960626
AU 9646391
                                                 19941209
                                                            199742
                                             Α
                             US 94352658
               Α
                   19970909
US 5664563
                                                 19951204
                                                            199743
                             EP 95944311
                                             Α
                  19970924
EP 796119
               Α1
                                                 19951204
                             WO 95US15706
                                              Α
                                              Α
                                                 19951204
                                                            199826
                             AU 9646391
                   19980326
AU 689371
               В
                                                 19951204
                                                            199850
                             WO 95US15706
                                              Α
                   19981006
               W
JP 10510182
                                                 19951204
                                              A
                              JP 96517683
                                                            199950
                             EP 95944311
                                              Α
                                                 19951204
                   19991027
EP 796119
               В1
                                                  19951204
                             WO 95US15706
                                              Α
                                                  19951204
                                                            200003
                             DE 613042
                   19991202
DE 69513042
                              EP 95944311
                                                  19951204
                              WO 95US15706
                                                  19951204
                                                            200049
                             IL 116236
                                                  19951203
               Α
                   20000716
IL 116236
Priority Applications (No Type Date): US 94352658 A 19941209
Patent Details:
                                      Filing Notes
Patent No Kind Lan Pg
                         Main IPC
              A1 E 25 A61M-016/00
WO 9617641
   Designated States (National): AU CA JP KR NZ
   Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT LU MC NL
   PT SE
                                      Based on patent WO 9617641
                       A61M-016/00
AU 9646391
                     14 A61M-016/00
US 5664563
               Α
                                      Based on patent WO 9617641
                        A61M-016/00
EP 796119
              A1 E
    Designated States (Regional): DE FR GB SE
                                      Previous Publ. patent AU 9646391
                        A61M-016/00
AU 689371
               В
                                      Based on patent WO 9617641
                                      Based on patent WO 9617641
                     33 A61M-016/12
              W
JP 10510182
                                      Based on patent WO 9617641
                        A61M-016/00
              B1 E
EP 796119
    Designated States (Regional): DE FR GB SE
                                      Based on patent EP 796119
                        A61M-016/00
 DE 69513042
               Ε
                                      Based on patent WO 9617641
                        A61M-016/00
 IL 116236
               Α
   Pneumatic system for ventilator to control inspired and expired gas
   flow during respiratory therapy...
 ...pneumatic system including circuit for controlling supply of one or more
```

selected gases to patient breathing circuit

Inventor: BIONDI J W ...

- ... Abstract (Basic): A patient breathing circuit includes a first port for introducing the gas into the patient breathing circuit with a humidifier downstream from the inlet for humidifying the gas, and a flexible...
- ...a heating device for heating the sterilisation chamber, and is located upstream from the patient breathing circuit...
- ... ADVANTAGE Allows a patient to spontaneously breathe from the bag reservoir at any time and allows the pneumatic circuit to deliver a control breath through the bag by pressurizing the canister that the bag resides in. The patient breathing circuit provides significant advantages when compared to other ventilator circuits namely, ease of spontaneously rebreathing. Therefor the external gas mixing is allowed as well...
- ...Abstract (Equivalent): A pneumatic system for a ventilator in fluid communication with a source of gas comprising...
- ...a patient breathing circuit including a first port for introducing said gas into said patient breathing circuit, a humidifier downstream from said source of gas for humidifying said gas, a flexible...

... Title Terms: VENTILATION ;

International Patent Class (Main): A61M-016/00 ...

... A61M-016/12

(Item 37 from file: 350) 6/3,K/37

DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 010322265

WPI Acc No: 1995-223538/199529

Related WPI Acc No: 1996-401428; 1998-178372; 2000-012719; 2000-104863;

2001-513528; 2002-267747; 2003-066281

XRPX Acc No: N95-175252

Catheter for use in coronary sinks - has intermediate zone portion and pliable tip, with first and second curved portions

Patent Assignee: DAIG CORP (DAIG-N)

Inventor: BENDITT D G; FLEISCHHACKER J J; LURIE K G; OCKULY J D; SHULTZ J

Number of Countries: 001 Number of Patents: 001

Patent Family:

Applicat No Kind Date Date Patent No Kind 19930813 199529 B 19950613 US 93106383 Α US 5423772 Α

Priority Applications (No Type Date): US 93106383 A 19930813

Patent Details:

Main IPC Filing Notes Patent No Kind Lan Pg

6 A61M-025/00 US 5423772 Α

...Inventor: LURIE K G

A61M-025/00 International Patent Class (Main):

(Item 38 from file: 350) 6/3, K/38

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 010292655

WPI Acc No: 1995-193914/199525 Related WPI Acc No: 1996-433571; 2000-421466; 2002-139260; 2002-641994; 2002-681034; 2003-030322; 2003-310772; 2003-371349; 2003-766762 XRPX Acc No: N95-152234 Method for increasing cardiopulmonary circulation - involves impeding airflow into patient's lungs by placing ventilation tube in patient's Patent Assignee: CPRX INC (CPRX-N); CPRX LLC (CPRX-N); GOLD B (GOLD-I); LURIE K G (LURI-I); SWEENEY M (SWEE-I) Inventor: GOLD B; LURIE K G ; SWEENEY M Number of Countries: 060 Number of Patents: 010 Patent Family: Kind Date Applicat No Kind Date Patent No 19941107 199525 Α A1 19950518 WO 94US12870 WO 9513108 19941107 199537 Α 19950529 AU 9510918 AU 9510918 Α Α 19941107 199639 WO 94US12870 19960828 Α1 EP 728028 19941107 EP 95901822 Α 19931109 199641 Α 19960903 US 93149204 US 5551420 -Α 199746 EP 95901822 Α Α4 19970604 EP 728028 19941107 199746 WO 94US12870 Α 19970909 JP 9508811 Α 19941107 JP 95513953 199820 19941107 AU 9510918 Α 19980305 AU 687942 В 200341 19941107 WO 94US12870 Α EP 728028 B120030521 19941107 EP 95901822 19941107 200350 Α DE 632708 20030626 DE 69432708 WO 94US12870 Α 19941107 EP 95901822 19941107 Α 200426 EP 95901822 19941107 20040301 ES 2199976 Т3 Priority Applications (No Type Date): US 93149204 A 19931109 Patent Details: Main IPC Filing Notes Patent No Kind Lan Pg 31 A61M-015/00 Α1 WO 9513108 Designated States (National): AM AT AU BB BG BR BY CA CH CN CZ DE DK EE ES FÍ GB GE HU JP KE KG KP KR KZ LK LR LT LU LV MD MG MN MW NL NO NZ PL PT RO RU SD SE SI SK TJ TT UA UZ VN Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT KE LU MC MW NL OA PT SD SE SZ Based on patent WO 9513108 AU 9510918 Based on patent WO 9513108 A1 E 31 A61M-015/00 EP 728028 Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE 13 A62B-009/02 US 5551420 Α Based on patent WO 9513108 31 A61M-016/00 JP 9508811 W Previous Publ. patent AU 9510918 AU 687942 В Based on patent WO 9513108 Based on patent WO 9513108 A61M-015/00 B1 E EP 728028 Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE Based on patent EP 728028 A61M-015/00 DE 69432708 Based on patent WO 9513108 Based on patent EP 728028 A61M-015/00 ES 2199976 involves impeding airflow into patient's lungs by placing ventilation tube in patient's airway

- ... Abstract (Basic): impeding air flow into the patient's lungs to enhance the extent and duration of **negative** intrathoracic **pressure** during decompression of the patient's chest...
- ... USE For increasing cardiopulmonary circulation when performing

... Inventor: LURIE K G

cardiopulmonary resuscitation .

- ...Abstract (Equivalent): method for increasing cardiopulmonary circulation induced by chest compression and decompression when performing cardio pulmonary resuscitation, by augmenting at least the negative intrathoracic pressure, said method comprising the steps of...
- ...providing a **ventilatory** tube having a length which extends at least between a patient's mouth and throat, a source of **respiratory** gases, and at least one inflow valve...
- ...compression and chest decompression, wherein during chest decompression, said at least one inflow valve prevents respiratory gases from entering the lungs until a negative intrathoracic pressure level is exceeded at which time said at least one inflow valve opens, said at least one inflow valve assisting in increasing the magnitude and duration of negative intrathoracic pressure during decompression and thereby enhancing the amount of venous blood flow into the heart and...
- ...periodically, every 2-10 chest compressions, supplying the patient with gas from the **respiratory** gas source so as to properly **ventilate** the patient...
- ... Title Terms: VENTILATION ;

International Patent Class (Main): A61M-015/00 ...

... A61M-016/00 ...

... A62B-009/02

...International Patent Class (Additional): A62B-007/00 ...

... A62B-009/06 ...

... A62B-018/02

6/3,K/39 (Item 39 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

010149536 \*\*Image available\*\*
WPI Acc No: 1995-050788/199507

XRPX Acc No: N95-039918

Circulatory and respiratory assistance method - reducing intra-thoracic pressure in patient by extracting, under sub-ambient respiratory gas pressure portion of respiratory gas volume from lungs beginning during diastolic period of same cardiac cycle

Patent Assignee: CARDIOPULMONARY CORP (CARD-N)
Inventor: BIONDI J W ; HERMAN S J; JOHNSTON D M
Number of Countries: 001 Number of Patents: 001

Patent Family:

Kind Week Patent No Applicat No Date Kind Date US 5377671 19950103 US 91692153 Д 19910426 199507 B Α US 91760409 19910916

Priority Applications (No Type Date): US 91760409 A 19910916; US 91692153 A 19910426

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

US 5377671 A 10 A61H-031/00 CIP of application US 91692153

Circulatory and respiratory assistance method...

- ...reducing intra-thoracic pressure in patient by extracting, under sub-ambient respiratory gas pressure portion of respiratory gas volume from lungs beginning during diastolic period of same cardiac cycle Inventor: BIONDI J W ...
- ... Abstract (Basic): The method of providing circulatory and respiratory assistance in a patient having a cardiac cycle including a ventricular systolic portion and a ventricular diastolic portion, involves beginning the introduction of the respiratory gas upon the start of an inhalation by the patient, determining the onset and duration...
- ...increasing the intra-thoracic pressure of the patient by introducing a volume of a **respiratory** gas into the lungs of the patient during the ventricular systolic portion of the cardiac...
- ...intra-thoracic pressure of the patient is reduced by beginning extracting the volume of the **respiratory** gas from the lungs of the patient during the diastolic portion of the same cardiac...
- ... USE/ADVANTAGE Providing circulatory and respiratory assistance.

  Provides improved cardiac output while employing normal physiological breath rate and tidal volume...
- ... Title Terms: RESPIRATION;

6/3,K/40 (Item 40 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

010075354 \*\*Image available\*\*
WPI Acc No: 1994-343067/199443
Related WPI Acc No: 1992-351402

XRPX Acc No: N94-269211

Cardiopulmonary resuscitation device - has vacuum cup with connecting stem attached with handle having pair of spaced-apart gripping surfaces

Patent Assignee: UNIV CALIFORNIA (REGC ); AMBU INT AS (AMBU-N)

Inventor: COHEN T J; KOHNKE O B; LURIE K G

Number of Countries: 022 Number of Patents: 011

Patent Family:

Pal	ent ramily:	;	•						
Pat	ent No	Kind	Date	App	olicat No	Kind	Date	Week	
ΕP	623334	A1	19941109	ΕP	94106492	A	19940426	199443	В
AU	9460539	A	19941110	ΑU	9460539	Α	19940418	199445	
CA	2117275	A	19941105	CA	2117275	A	19940414	199505	
BR	9401638	А	19941220	BR	941638	A	19940428	199507	
US	5645522	A	19970708	US	91686542	Α	19910417	199733	
				US	9358195	A	19930504		
AU	687379	В	19980226	ΑU	9460539	A	19940418	199821	
ΕP	623334	В1	19990609				٠	199927	
DE	69418937	E	19990715	DE	618937	A	19940426	199934	
				EΡ	94106492	A	19940426		
ES	2132274	Т3	19990816	ΕP	94106492	Α	19940426	199939	
JР	3072318	B2	20000731	JР	9494478	A	19940506	200041	
CA	2117275	С	20011216	CA	2117275	A	19940414	200163	

Priority Applications (No Type Date): US 9358195 A 19930504; US 91686542 A 19910417

Patent Details:

Patent No Kind Lan Pq Main IPC Filing Notes

```
A1 E 19 A61H-031/00
EP 623334
   Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT LI LU MC
   NL PT SE
                       A61H-031/00
AU 9460539
              А
BR 9401638
              Α
                       A61B-019/00
                    17
                                     CIP of application US 91686542
US 5645522
              А
                                     Previous Publ. patent AU 9460539
AU 687379
                       A61H-031/00
              B
EP 623334
              B1 E
  Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT LI LU MC
  NL PT SE
                                     Based on patent EP 623334
DE 69418937
                                     Based on patent EP 623334
              Т3
ES 2132274
                                     Previous Publ. patent JP 6343701
                    14 A61H-031/00
JP 3072318
              B2
                       A61H-031/00
CA 2117275
              C E
  Cardiopulmonary resuscitation device...
... Inventor: LURIE K G
... Abstract (Basic): ADVANTAGE - Provides an alternatively compressing and
    expanding of patient's chest to induce both ventilation and blood
    circulation...
... Abstract (Equivalent): A device for performing cardiopulmonary
    resuscitation of a patient, said device comprising...
Title Terms: RESUSCITATION ;
 6/3, K/41
              (Item 41 from file: 350)
DIALOG(R) File 350: Derwent WPIX
(c) 2004 Thomson Derwent. All rts. reserv.
009915468
             **Image available**
WPI Acc No: 1994-183178/199422
XRAM Acc No: C94-082996
XRPX Acc No: N94-144660
  Method for enhanced cardiopulmonary resuscitation - useful in patients
  suffering from cardiac arrest
Patent Assignee: UNIV MINNESOTA (MINU )
Inventor: GOLD B S; LURIE K G
Number of Countries: 021 Number of Patents: 003
Patent Family:
Patent No
                             Applicat No
                                            Kind
                                                   Date
                                                            Week
              Kind
                     Date
                                                           199422 B
                                                 19931115
WO 9411045
               A1
                   19940526
                             WO 93US11034
                                             Α
                                                           199435
                             AU 9456064
                                             Α
                                                 19931115
                   19940608
AU 9456064
               Α
                                                 19921117 199707
                   19961231 US 92977498
                                             Α
US 5588422
              Α
Priority Applications (No Type Date): US 92977498 A 19921117
Patent Details:
                        Main IPC
                                     Filing Notes
Patent No Kind Lan Pg
              A1 E 25 A61M-015/00
WO 9411045
   Designated States (National): AU CA JP KR
   Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT LU MC NL
   PT SE
                                     Based on patent WO 9411045
AU 9456064
                       A61M-015/00
                     7 A61M-015/00
US 5588422
  Method for enhanced cardiopulmonary resuscitation -
... Inventor: LURIE K G
... Abstract (Basic): Resuscitating a patient suffering from cardiac
    arrest comprises actively inducing venous blood transport into the
    heart and arterial blood transport from the heart, ventilating the
```

patient's lungs, admin. to the patient concurrently with the inducing

and **ventilating** steps of an amt. of an arterial constrictor sufficient to increase the patient arterial blood pressure, and admin. to the patient concurrently with the inducing and **ventilating** steps of an amt. of a venodilator sufficient to enhance arterial blood flow to the...

... USE/ADVANTAGE - The method and compsns. are useful for resuscitating patients suffering from cardiac arrest. The method enhances patient survival and reduces heart and brain-

... Abstract (Equivalent): A method for resuscitating a patient suffering from cardiac arrest, said method comprising...

...b) ventilating the patient's lungs...

...c) administering to the patient concurrently with said inducing and ventilating steps, a bolus of medicament comprising epinephrine and nitroglycerin in amounts of from 1 mg...

... Title Terms: RESUSCITATION ;

AU 651189

US 5454779

EP 509773

В

Α

A61H-031/00

13 A61H-031/02

B1 E 12 A61H-031/00

International Patent Class (Main): A61M-015/00

```
6/3, K/42
              (Item 42 from file: 350)
DIALOG(R) File 350: Derwent WPIX
(c) 2004 Thomson Derwent. All rts. reserv.
009223981
             **Image available**
WPI Acc No: 1992-351402/199243
Related WPI Acc No: 1994-343067
XRPX Acc No: N92-267925
  External chest compression for resuscitation - using body with stiff
  upper surface which withstand force, lower soft surface which spreads on
  application of force and handle
Patent Assignee: UNIV CALIFORNIA (REGC )
Inventor: COHEN T J; LURIE K G
Number of Countries: 019 Number of Patents: 009
Patent Family:
Patent No
              Kind
                     Date
                             Applicat No
                                            Kind
                                                   Date
                                                             Week
EP 509773
               Al 19921021
                             EP 92303367
                                             Α
                                                 19920415
                                                            199243
AU 9214877
                             AU 9214877
                   19921022
               Α
                                             Α
                                                 19920413
CA 2066297
                             CA 2066297
               Α
                   19921018
                                             Α
                                                 19920416
AU 651189
                             AU 9214877
               В
                   19940714
                                             Α
                                                 19920413
                                                            199432
US 5454779
                             US 91686542
                   19951003
               Α
                                             Α
                                                 19910417
                                                            199545
                             US 94226431
                                             Α
                                                 19940412
EP 509773
                             EP 92303367
               В1
                   19980107
                                             Α
                                                 19920415
                                                            199806
DE 69223840
               Ε
                   19980212
                             DE 623840
                                             Α
                                                 19920415
                                                            199812
                             EP 92303367
                                             Α
                                                 19920415
                             EP 92303367
ES 2112298
               Т3
                   19980401
                                             Α
                                                 19920415
                                                            199819
CA 2066297
                             CA 2066297
               С
                   20000905
                                             Α
                                                 19920416
                                                            200053
Priority Applications (No Type Date): US 91686542 A 19910417; US 94226431 A
  19940412
Patent Details:
Patent No Kind Lan Pg
                         Main IPC
                                     Filing Notes
EP 509773
              A1 E 13 A61H-031/00
   Designated States (Regional): AT BE CH DE DK ES FR GB GR IT LI LU MC NL
   PT SE
AU 9214877
              Α
                       A61H-031/00
CA 2066297
              Α
                       A61H-031/00
```

Previous Publ. patent AU 9214877

Cont of application US 91686542

Designated States (Regional): DE ES FR GB IT

Based on patent EP 509773 A61H-031/00 DE 69223840 F. Based on patent EP 509773 ES 2112298 Т3 A61H-031/00 C E A61H-031/00

CA 2066297

External chest compression for resuscitation -

... Inventor: LURIE K G

... Abstract (Basic): USE/ADVANTAGE - Cardiopulmonary resuscitation device. Actively expands halienty chest to improve respiration and blood flow...

... Abstract (Equivalent): USE/ADVANTAGE - Cardiopulmonary resuscitation device. Actively expands halienty chest to improve respiration and blood flow...

... Title Terms: RESUSCITATION ;

6/3, K/43(Item 43 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

\*\*Image available\*\* 008044251 WPI Acc No: 1989-309363/198942

XRPX Acc No: N89-235729

Computerised control system for cardiocirculatory assistance - detects particular phase of cardiac cycle and controls increase in intrathoracic pressure in relative phase with this event

Patent Assignee: CARDIOPULMONARY CORP (CARD-N); CARDIOPULMONARY COR (CARD-N)

Inventor: BIONDI J W ; MENTELOS R A

Number of Countries: 018 Number of Patents: 012

Datont Family

Pat	ent ramily	:							
Pat	ent No	Kind	Date	App	olicat No	Kind	Date	Week	
WO	8909041	A	19891005	WO	89US1356	Α	19890331	198942	В
ΑU	8935477	Α	19891016					199008	
ΕP	407463	A	19910116	EΡ	89905326	A	19890331	199103	
FI	9004784	Α	19900928					199105	
DK.	9002354	A	19900928					199106	
JP	2504596	W	19901227	JP	89504999	A	19890331	199107	
NO	9004250	A	19901128					199108	
US	5020516	A	19910604	US	88175810	A	19880331	199125	
ΑU	9215167	A	19920625	ΑU	9215167	A	19920427	199233	
				AU	8935477	A			
ΕP	407463	A4	19910605	ΕP	89905326	A		199516	
FΙ	103376	ВÌ	19990630	WO	89US1356	A	19890331	199932	
				FI	904784	A	19900928		
DK	173598	В	20010423	WO	89US1356	A	19890331	200131	
				DK	902354	A	19900928		

Priority Applications (No Type Date): US 88175810 A 19880331

Patent Details:

Filing Notes Patent No Kind Lan Pg Main IPC

A E 27 WO 8909041

Designated States (National): AU DK FI JP KR NO

Designated States (Regional): AT BE CH DE FR GB IT LU NL SE

EP 407463

Designated States (Regional): AT BE CH DE FR GB IT LI LU NL SE A61H-031/00 Div ex application AU 8935477 AU 9215167 Α FI 103376 Previous Publ. patent FI 9004784 A61H-031/00 В1 DK 173598 В A61H-031/00 Previous Publ. patent DK 9002354 Inventor: BIONDI J W ...

...Abstract (Basic): system (10) to the patient. The patient interface may include equipment for supplying high frequency respiration pulses in synchronising with the cardiac cycle, for example, by inflating a bladder in contact...

...Abstract (Equivalent): N is a positive integer. The patient interface may include apparatus for supplying high frequency respiration pulses in synchronism with the cardiac cycle. Alternately, or in addition, the pulses may be...

International Patent Class (Additional): A61M-016/00

set S1		Description AU=(LURIE K? OR LURIE, K? OR MENK V? OR MENK, V? OR ZIELIN- KI T? OR ZIELINSKI, T? OR BIONDI J? OR BIONDI, J?) KEITH(2W)LURIE OR VERN(2W)MENK OR TODD(2W)ZIELINSKI OR JAM-
S2	0 E.S	KEITH(2W)LURIE OR VERN(2W)MENK ON 1991 G(2W)BIONDI OR PREPERS OR VENTUAT? OR CPR OR PEEP
s3	115081	RESUSC? OR RESPIRAT? OR BREATH! OR VENTILIES
S4	39663	IC=(A62B? OR A61G? OR A61M?)
S5	39	S1:S2 AND S3:S4 IDPAT (sorted in duplicate/non-duplicate order)
S6		IDPAT (sorted in duplicate, non dar
File	(c) 21	EAN PATENTS 1978-2004/May W01 004 European Patent Office ULLTEXT 1979-2002/UB=20040506,UT=20040429 004 WIPO/Univentio

6/3,AU/1 (Item 1 from file: 348)
DIALOG(R)File 348:EUROPEAN PATENTS
(c) 2004 European Patent Office. All rts. reserv.
01588505

FACE MASK VENTILATION /PERFUSION SYSTEMS AND METHOD SYSTEMES DE VENTILATION /PERFUSION A MASQUE FACIAL ET PROCEDE ASSOCIE PATENT ASSIGNEE:

- CPRX LLC, (3001041), 4330 Upton Avenue South, Minneapolis, MN 55410, (US), (Applicant designated States: all)
INVENTOR:

LURIE, Keith, G., 4751 Girard Avenue South, Minneapolis, MN 55409, (US) ZIELINSKI, Todd, M., 3549 43rd Ave. South, Minneapolis, MN 55406, (US) HARDER, Scott, Edward, 4601 Emerson Avenue South, Minneapolis, MN 55409, (US)

GISCH, Teresa, Marie, 4605 Bower Path, Inver Grove Heights, MN 55076, (US)

WAFFENSMITH, Jeff, 4337 Beard Avenue North, Robinsdale, MN 55422, (US) LEYDEN, Matt, V., 1024 Laurel Avenue, St. Paul, MN 55104, (US PATENT (CC, No, Kind, Date):

WO 2003028613 030410

APPLICATION (CC, No, Date): EP 2002768824 020905; WO 2002US28568 020905

PRIORITY (CC, No, Date): US 966945 010928

DESIGNATED STATES: AT; BE; BG; CH; CY; CZ; DE; DK; EE; ES; FI; FR; GB; GR;

IE; IT; LI; LU; MC; NL; PT

EXTENDED DESIGNATED STATES: AL; LT; LV; MK; RO; SI

INTERNATIONAL PATENT CLASS: A61H-001/00

LANGUAGE (Publication, Procedural, Application): English; English; English

6/3,AU/2 (Item 2 from file: 349)
DIALOG(R)File 349:PCT FULLTEXT
(c) 2004 WIPO/Univentio. All rts. reserv.

00999003

FACE MASK VENTILATION /PERFUSION SYSTEMS AND METHOD
SYSTEMES DE VENTILATION /PERFUSION A MASQUE FACIAL ET PROCEDE ASSOCIE
Patent Applicant/Assignee:

ADVANCED CIRCULATORY SYSTEMS INC, 7615 Golden Triangle Drive, Suite A, Technology Park #5, Eden Prairie, MN 55344, US, US (Residence), US (Nationality)

Inventor(s):

LURIE Keith G , 4751 Girard Avenue South, Minneapolis, MN 55409, US, ZIELINSKI Todd M , 3549 43rd Ave. South, Minneapolis, MN 55406, US, HARDER Scott Edward, 4601 Emerson Avenue South, Minneapolis, MN 55409, US

GISCH Teresa Marie, 4605 Bower Path, Inver Grove Heights, MN 55076, US, WAFFENSMITH Jeff, 4337 Beard Avenue North, Robinsdale, MN 55422, US, LEYDEN Matt V, 1024 Laurel Avenue, St. Paul, MN 55104, US

Legal Representative:
GIBBY Darin J (et al) (agent), Townsend and Townsend and Crew LLP, Two
Embarcadero Center, Eighth Floor, San Francisco, CA 94111-3834, US,

Patent and Priority Information (Country, Number, Date):

Patent: WO 200328613 A2-A3 20030410 (WO 0328613)
Application: WO 2002US28568 20020905 (PCT/WO US0228568)

Priority Application: US 2001966945 20010928

Designated States: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO RU SD SE SG SI SK SL TJ TM TN TR TT TZ UA UG UZ VC VN YU ZA ZM ZW

(EP) AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LU MC NL PT SE SK TR

(OA) BF BJ CF CG CI CM GA GN GQ GW ML MR NE SN TD TG (AP) GH GM KE LS MW MZ SD SL SZ TZ UG ZM ZW

(EA) AM AZ BY KG KZ MD RU TJ TM

Publication Language: English Filing Language: English Fulltext Word Count: 8782

(Item 3 from file: 348) 6/3,AU/3

DIALOG(R)File 348:EUROPEAN PATENTS

(c) 2004 European Patent Office. All rts. reserv.

SYSTEMS AND METHODS TO FACILITATE THE DELIVERY OF DRUGS SYSTEMES ET PROCEDES FACILITANT L'ADMINISTRATION DE MEDICAMENTS

PATENT ASSIGNEE:

CPRX LLC, (3001041), 4330 Upton Avenue South, Minneapolis, MN 55410, (US) (Applicant designated States: all)

INVENTOR:

LURIE, Keith, G., 4751 Girard Avenue South, Minneapolis, MN 55409, (US) VOELCKEL, Wolfgang, Krehbachgasse 13C, A-6410 Telfs, (AT

PATENT (CC, No, Kind, Date):

WO 2003028793 030410

WO 2002US24325 020730 EP 2002756853 020730; APPLICATION (CC, No, Date):

PRIORITY (CC, No, Date): US 967029 010928

DESIGNATED STATES: AT; BE; BG; CH; CY; CZ; DE; DK; EE; ES; FI; FR; GB; GR;

IE; IT; LI; LU; MC; NL; PT

EXTENDED DESIGNATED STATES: AL; LT; LV; MK; RO; SI

INTERNATIONAL PATENT CLASS: A61M-016/00

LANGUAGE (Publication, Procedural, Application): English; English; English

(Item 4 from file: 349) 6/3, AU/4

DIALOG(R)File 349:PCT FULLTEXT

(c) 2004 WIPO/Univentio. All rts. reserv.

00999082

SYSTEMS AND METHODS TO FACILITATE THE DELIVERY OF DRUGS SYSTEMES ET PROCEDES FACILITANT L'ADMINISTRATION DE MEDICAMENTS

Patent Applicant/Assignee:

CPRX LLC, 4330 Upton Avenue South, Minneapolis, MN 55410, US, US (Residence), US (Nationality)

LURIE Keith G , 4751 Girard Avenue South, Minneapolis, MN 55409, US, Inventor(s): VOELCKEL Wolfgang, Krehbachgasse 13C, A-6410 Telfs, AT

Legal Representative:

GIBBY Darin J (et al) (agent), Townsend and Townsend and Crew LLP, Two Embarcadero Center, Eighth Floor, San Francisco, CA 94111-3834, US,

Patent and Priority Information (Country, Number, Date):

Patent:

WO 200328793 A1 20030410 (WO 0328793) WO 2002US24325 20020730 (PCT/WO US0224325)

Application: Priority Application: US 2001967029 20010928

Designated States: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO RU SD SE SG SI SK SL TJ TM TN TR TT TZ UA UG UZ VN YU ZA ZM ZW (EP) AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LU MC NL PT SE SK TR

(OA) BF BJ CF CG CI CM GA GN GQ GW ML MR NE SN TD TG

(AP) GH GM KE LS MW MZ SD SL SZ TZ UG ZM ZW

(EA) AM AZ BY KG KZ MD RU TJ TM

Publication Language: English

Filing Language: English Fulltext Word Count: 3408

6/3, AU/5 (Item 5 from file: 348)

DIALOG(R) File 348: EUROPEAN PATENTS

(c) 2004 European Patent Office. All rts. reserv.

01531563

SHOCK TREATMENT SYSTEMS AND METHODS

SYSTEM UND VERFAHREN ZUR SCHOCKBEHANDLUNG

SYSTEMES ET PROCEDES DE TRAITEMENT DE L'ETAT DE CHOC

PATENT ASSIGNEE:

Advanced Circulatory Systems, Inc., (4475370), 7615 Golden Triangel Drive, Suite A,, Eden Prairie, Minnesota 55344, (US), (Applicant designated States: all)

INVENTOR:

LURIE, Keith, G., 4751 Girard Avenue South, Minneapolis, MN 55409, (US) ZIELINSKI, Todd, M., 3549 43rd Ave. South, Minneapolis, MN 55406, (US LEGAL REPRESENTATIVE:

Evens, Paul Jonathan et al (83931), Maguire Boss, 5 Crown Street, St. Ives, Cambridge PE27 5EB, (GB)

PATENT (CC, No, Kind, Date): EP 1387714 A1 040211 (Basic)
WO 2002092169 021121

APPLICATION (CC, No, Date): EP 2002769675 020501; WO 2002US14039 020501 PRIORITY (CC, No, Date): US 854238 010511; US 119203 020408

DESIGNATED STATES: AT; BE; CH; CY; DE; DK; ES; FI; FR; GB; GR; IE; IT; LI; LU; MC; NL; PT; SE; TR

EXTENDED DESIGNATED STATES: AL; LT; LV; MK; RO; SI

INTERNATIONAL PATENT CLASS: A62B-009/02; A62B-007/04; A61M-016/00; F16K-031/26

NOTE:

No A-document published by EPO

LANGUAGE (Publication, Procedural, Application): English; English; English

6/3,AU/6 (Item 6 from file: 349)

DIALOG(R) File 349:PCT FULLTEXT

(c) 2004 WIPO/Univentio. All rts. reserv.

00958376

SHOCK TREATMENT SYSTEMS AND METHODS

SYSTEMES ET PROCEDES DE TRAITEMENT DE L'ETAT DE CHOC

Patent Applicant/Assignee:

ADVANCED CIRCULATORY SYSTEMS INC, 7615 Golden Triangle Drive, Suite A, Technology Park #5, Eden Prairie, MN 55344, US, US (Residence), US (Nationality)

Inventor(s):

LURIE Keith G , 4751 Girard Avenue South, Minneapolis, MN 55409, US, ZIELINSKI Todd M , 3549 43rd Ave. South, Minneapolis, MN 55406, US Legal Representative:

GIBBY Darin J (et al) (agent), Townsend and Townsend and Crew LLP, Two Embarcadero Center, Eighth Floor, San Francisco, CA 94111-3834, US,

Patent and Priority Information (Country, Number, Date):

Patent: WO 200292169 A1 20021121 (WO 0292169)
Application: WO 2002US14039 20020501 (PCT/WO US020

Application: WO 2002US14039 20020501 (PCT/WO US02014039)
Priority Application: US 2001854238 20010511; US 2002119203 20020408
Designated States: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU

CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO

RU SD SE SG SI SK SL TJ TM TN TR TT TZ UA UG UZ VN YU ZA ZM ZW

(EP) AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE TR (OA) BF BJ CF CG CI CM GA GN GQ GW ML MR NE SN TD TG

(AP) GH GM KE LS MW MZ SD SL SZ TZ UG ZM ZW

(EA) AM AZ BY KG KZ MD RU TJ TM

Publication Language: English

Filing Language: English Fulltext Word Count: 25183

(Item 7 from file: 348) 6/3,AU/7

DIALOG(R) File 348: EUROPEAN PATENTS

(c) 2004 European Patent Office. All rts. reserv.

01530028

CARDIOPULMONARY RESUSCITATION CHEST COMPRESSION/DECOMPRESSION DEVICE WITH ELECTRONIC STETHOSCOPE

APPAREIL DE REANIMATION CARDIO-PULMONAIRE PAR COMPRESSION/DECOMPRESSION DU THORAX EQUIPE D'UN STETHOSCOPE ELECTRONIQUE ET DE BIOCAPTEURS

PATENT ASSIGNEE:

CPRX LLC, (3001041), 4330 Upton Avenue South, Minneapolis, MN 55410, (US) , (Applicant designated States: all)

INVENTOR:

LURIE, Keith, G., 4751 Girard Avenue South, Minneapolis, MN 55409, (US) ZIELINSKI, Todd, M., 3549 43rd Ave. South, Minneapolis, MN 55406, (US PATENT (CC, No, Kind, Date):

WO 2002091905 021121

EP 2002725913 020501; WO 2002US14038 020501 APPLICATION (CC, No, Date): PRIORITY (CC, No, Date): US 854404 010511

DESIGNATED STATES: AT; BE; CH; CY; DE; DK; ES; FI; FR; GB; GR; IE; IT; LI; LU; MC; NL; PT; SE; TR

EXTENDED DESIGNATED STATES: AL; LT; LV; MK; RO; SI

INTERNATIONAL PATENT CLASS: A61B-001/00

LANGUAGE (Publication, Procedural, Application): English; English; English

6/3,AU/8 (Item 8 from file: 349)

DIALOG(R) File 349: PCT FULLTEXT

(c) 2004 WIPO/Univentio. All rts. reserv.

00958230

CARDIOPULMONARY RESUSCITATION CHEST COMPRESSION/DECOMPRESSION DEVICE WITH ELECTRONIC STETHOSCOPE

APPAREIL DE REANIMATION CARDIO-PULMONAIRE PAR COMPRESSION/DECOMPRESSION DU THORAX EQUIPE D'UN STETHOSCOPE ELECTRONIQUE ET DE BIOCAPTEURS

Patent Applicant/Assignee:

ADVANCED CIRCULATORY SYSTEMS INC, 7615 Golden Triangle Drive, Suite A, Technology Park #5, Eden Prairie, MN 55344, US, US (Residence), US (Nationality)

Inventor(s):

LURIE Keith G , 4751 Girard Avenue South, Minneapolis, MN 55409, US, ZIELINSKI Todd M , 3549 43rd Ave. South, Minneapolis, MN 55406, US Legal Representative:

GIBBY Darin J (et al) (agent), Townsend and Townsend and Crew LLP, Two Embarcadero Center, Eighth Floor, San Francisco, CA 94111-3834, US, Patent and Priority Information (Country, Number, Date):

WO 200291905 A2-A3 20021121 (WO 0291905) WO 2002US14038 20020501 (PCT/WO US0214038)

Application:

Priority Application: US 2001854404 20010511

Designated States: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO RU SD SE SG SI SK SL TJ TM TN TR TT TZ UA UG UZ VN YU ZA ZM ZW (EP) AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE TR (OA) BF BJ CF CG CI CM GA GN GQ GW ML MR NE SN TD TG (AP) GH GM KE LS MW MZ SD SL SZ TZ UG ZM ZW (EA) AM AZ BY KG KZ MD RU TJ TM

Publication Language: English Filing Language: English Fulltext Word Count: 9294

6/3,AU/9 (Item 9 from file: 348)
DIALOG(R)File 348:EUROPEAN PATENTS

(c) 2004 European Patent Office. All rts. reserv.

01454168

VENTILATOR CONTROL SYSTEM AND METHOD

STEUERUNG EINES BEATMUNGSGERATES UND VERFAHREN

SYSTEME DE VENTILATEUR PERMETTANT DE SEVRER AUTOMATIQUEMENT UN PATIENT DE SA VENTILATION MECANIQUE ET TECHNIQUE A CET EFFET PATENT ASSIGNEE:

CARDIOPULMONARY CORPORATION, (1156111), 200 Cascade Boulevard, Milford, CT 06460, (US), (Applicant designated States: all) INVENTOR:

BIONDI, James, W., 1601 Ridge Road, North Haven, CT 06473, (US) LOCKHORN, Nancy, Apt. 1C, 275 Circular Avenue, Hamden, CT 06514, (US REYNOLDS, Robert, 299 Townsend Street, New Haven, CT 06512, (US LEGAL REPRESENTATIVE:

McKechnie, Neil et al (81374), Kennedys Patent Agency Limited, Floor 5, Queens House, 29 St. Vincent Place, Glasgow G1 2DT, (GB) PATENT (CC, No, Kind, Date): EP 1355690 A2 031029 (Basic)

PATENT (CC, No, Kind, Date): EP 1355690 A2 031029 (Basic)
WO 2002058619 020801

APPLICATION (CC, No, Date): EP 2002704199 020122; WO 2002US1716 020122 PRIORITY (CC, No, Date): US 767173 010122

DESIGNATED STATES: AT; BE; CH; CY; DE; DK; ES; FI; FR; GB; GR; IE; IT; LI; LU; MC; NL; PT; SE; TR

EXTENDED DESIGNATED STATES: AL; LT; LV; MK; RO; SI

INTERNATIONAL PATENT CLASS: A61M-016/00

NOTE:

No A-document published by EPO LANGUAGE (Publication, Procedural, Application): English; English; English

6/3,AU/10 (Item 10 from file: 349)
DIALOG(R)File 349:PCT FULLTEXT
(c) 2004 WIPO/Univentio. All rts. reserv.

00926148

VENTILATOR CONTROL SYSTEM AND METHOD

SYSTEME DE VENTILATEUR PERMETTANT DE SEVRER AUTOMATIQUEMENT UN PATIENT DE SA VENTILATION MECANIQUE ET TECHNIQUE A CET EFFET
Patent Applicant/Assignee:

CARDIOPULMONARY CORPORATION, 200 Cascade Boulevard, Milford, CT 06460, US , US (Residence), US (Nationality)

Inventor(s):

BIONDI James W , 1601 Ridge Road, North Haven, CT 06473, US, LOCKHORN Nancy, Apartment 1C, 275 Circular Avenue, Hamden, CT 06514, US,

REYNOLDS Robert, 299 Townsend Street, New Haven, CT 06512, US Legal Representative: MOORE Ronda P (agent), Testa, Hurwitz & Thibeault, LLP, High Street Tower, 125 High Street, Boston, MA 02110, US, Patent and Priority Information (Country, Number, Date): WO 200258619 A2-A3 20020801 (WO 0258619) Patent: (PCT/WO US0201716) WO 2002US1716 20020122 Application: Priority Application: US 2001767173 20010122 Designated States: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO RU SD SE SG SI SK SL TJ TM TN TR TT TZ UA UG UZ VN YU ZA ZM ZW (EP) AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE TR (OA) BF BJ CF CG CI CM GA GN GQ GW ML MR NE SN TD TG (AP) GH GM KE LS MW MZ SD SL SZ TZ UG ZM ZW (EA) AM AZ BY KG KZ MD RU TJ TM Publication Language: English Filing Language: English Fulltext Word Count: 13638 6/3,AU/11 (Item 11 from file: 348) DIALOG(R) File 348: EUROPEAN PATENTS

(c) 2004 European Patent Office. All rts. reserv.

01405027

CPR TRAINING APPARATUS AND METHODS DISPOSITIF ET PROCEDES D'ENTRAINEMENT A LA REANIMATION CARDIO- RESPIRATOIRE

PATENT ASSIGNEE:

CPRX LLC, (3001041), 4330 Upton Avenue South, Minneapolis, MN 55410, (US) , (Applicant designated States: all)

INVENTOR:

LURIE, Keith, G., 4751 girard Avenue South, Minneapolis, MN 55409, (US) ZIELINSKI, Todd, M., 48 27th Avenue S.E. 203, Minneapolis, MN 55414, (US

PATENT (CC, No, Kind, Date):

WO 2002003905 020117

EP 2001961640 010710; WO 2001US22180 010710 APPLICATION (CC, No, Date): PRIORITY (CC, No, Date): US 614064 000711 DESIGNATED STATES: AT; BE; CH; CY; DE; DK; ES; FI; FR; GB; GR; IE; IT; LI; LU; MC; NL; PT; SE; TR

EXTENDED DESIGNATED STATES: AL; LT; LV; MK; RO; SI

INTERNATIONAL PATENT CLASS: A61H-001/00

LANGUAGE (Publication, Procedural, Application): English; English; English

6/3, AU/12(Item 12 from file: 349) DIALOG(R) File 349: PCT FULLTEXT (c) 2004 WIPO/Univentio. All rts. reserv.

00870227

CPR TRAINING APPARATUS AND METHODS DISPOSITIF ET PROCEDES D'ENTRAINEMENT A LA REANIMATION CARDIO- RESPIRATOIRE

Patent Applicant/Assignee: CPRX LLC, 4330 Upton Avenue South, Minneapolis, MN 55410, US, US (Residence), US (Nationality) Inventor(s):

LURIE Keith G , 4751 girard Avenue South, Minneapolis, MN 55409, US,

ZIELINSKI Todd M , 48 27th Avenue S.E. #203, Minneapolis, MN 55414, US Legal Representative: GIBBY Darin J (et al) (agent), Townsend and Townsend and Crew LLP, Two Embarcadero Center, 8th floor, San Francisco, CA 94111-3834, US, Patent and Priority Information (Country, Number, Date): WO 200203905 A2 20020117 (WO 0203905) Patent:

WO 2001US22180 20010710 (PCT/WO US0122180) Application:

Priority Application: US 2000614064 20000711 Designated States: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ PL PT RO RU SD

SE SG SI SK SL TJ TM TR TT TZ UA UG UZ VN YU ZA ZW

(EP) AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE TR

(OA) BF BJ CF CG CI CM GA GN GW ML MR NE SN TD TG

(AP) GH GM KE LS MW MZ SD SL SZ TZ UG ZW

(EA) AM AZ BY KG KZ MD RU TJ TM

Publication Language: English Filing Language: English Fulltext Word Count: 7376

(Item 13 from file: 348) 6/3,AU/13 DIALOG(R) File 348: EUROPEAN PATENTS

(c) 2004 European Patent Office. All rts. reserv.

01357151

CPR MASK WITH COMPRESSION TIMING METRONOME AND METHODS

KARDIOPULMONARE MASKE MIT METRONOM ZUR ZEITGEBUNG VON KOMPRESSIONEN UND VERFAHREN

CARDIOPULMONAIRE COMPORTANT UN METRONOME DE REANIMATION MASOUE DE SYNCHRONISATION DE COMPRESSION ET PROCEDES

PATENT ASSIGNEE:

Advanced Circulatory Systems, Inc., (4475370), 7615 Golden Triangel Drive, Suite A,, Eden Prairie, Minnesota 55344, (US), (Applicant designated States: all)

INVENTOR:

LURIE, Keith, G., 4751 Girard Avenue South, Minneapolis, MN 55409, (US) ZIELINSKI, Todd, M., 48 27th Avenue S.E. 203, Minneapolis, MN 55414,

SCHARENBROICH, Gene, 1660 Wild Ridge Court S., Newport, MN 55055, (US

LEGAL REPRESENTATIVE: Evens, Paul Jonathan et al (83933), Maguire Boss, 5 Crown Street, St.

Ives, Cambridgeshire PE27 5EB, (GB) A2 030827 (Basic) PATENT (CC, No, Kind, Date): EP 1337292

010927 WO 2001070092

EP 2001922429 010316; WO 2001US8505 010316 APPLICATION (CC, No, Date):

PRIORITY (CC, No, Date): US 532601 000322 DESIGNATED STATES: AT; BE; CH; CY; DE; DK; ES; FI; FR; GB; GR; IE; IT; LI; LU; MC; NL; PT; SE; TR

EXTENDED DESIGNATED STATES: AL; LT; LV; MK; RO; SI

INTERNATIONAL PATENT CLASS: A61M-015/00

NOTE:

No A-document published by EPO LANGUAGE (Publication, Procedural, Application): English; English; English

(Item 14 from file: 349) 6/3, AU/14

DIALOG(R) File 349: PCT FULLTEXT

<sup>(</sup>c) 2004 WIPO/Univentio. All rts. reserv.

00836931

CPR MASK WITH COMPRESSION TIMING METRONOME AND METHODS

CARDIOPULMONAIRE COMPORTANT UN METRONOME DE REANIMATION MASQUE DE SYNCHRONISATION DE COMPRESSION ET PROCEDES

Patent Applicant/Assignee:

CPRX LLC, 4330 Upton Avenue South, Minneapolis, MN 55410, US, US (Residence), US (Nationality)

Inventor(s):

LURIE Keith G., 4751 Girard Avenue South, Minneapolis, MN 55409, US, ZIELINSKI Todd M , 48 27th Avenue S.E. #203, Minneapolis, MN 55414, US, SCHARENBROICH Gene, 1660 Wild Ridge Court S., Newport, MN 55055, US

Legal Representative: GIBBY Darin J (et al) (agent), Townsend and Townsend and Crew LLP, 1200 Seventeenth Street, Suite 2700, Denver, CO 8022, US,

Patent and Priority Information (Country, Number, Date):

WO 200170092 A2-A3 20010927 (WO 0170092) Patent: WO 2001US8505 20010316 (PCT/WO US0108505)

Application: Priority Application: US 2000532601 20000322

Designated States: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CR CU CZ DE DK DM DZ EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT TZ UA UG UZ VN YU ZA ZW

(EP) AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE TR

(OA) BF BJ CF CG CI CM GA GN GW ML MR NE SN TD TG

(AP) GH GM KE LS MW MZ SD SL SZ TZ UG ZW

(EA) AM AZ BY KG KZ MD RU TJ TM

Publication Language: English Filing Language: English Fulltext Word Count: 7129

(Item 15 from file: 348) 6/3, AU/15

DIALOG(R) File 348: EUROPEAN PATENTS

(c) 2004 European Patent Office. All rts. reserv.

01156759

VENTILATOR AND METHODS CARDIOPULMONARY RESUSCITATION KARDIOPULMONALES BEATMUNGSGERAT ZUR REANIMATION UND ZUGEHORIGE METHODEN VENTILATEUR ET PROCEDES DE REANIMATION CARDIO-PULMONAIRE PATENT ASSIGNEE:

CPRX LLC, (3001040), 4751 Girard Avenue South; Minneapolis, MN 55409, (US), (Applicant designated States: all)

LURIE, Keith, G., 4751 Girard Avenue South, Minneapolis, MN 55409, (US) ZIELINSKI, Todd, M., 48 27th Avenue S.E. No.203, Minneapolis, MN 55414, (US

LEGAL REPRESENTATIVE:

Evens, Paul Jonathan et al (83931), Maguire Boss, 5 Crown Street, St. Ives, Cambridge PE27 5EB, (GB)

PATENT (CC, No, Kind, Date): EP 1119385 Al 010801 (Basic)

WO 200020061 000413

EP 99951803 991005; WO 99US23233 991005 APPLICATION (CC, No, Date):

PRIORITY (CC, No, Date): US 168049 981007

DESIGNATED STATES: AT; BE; CH; CY; DE; DK; ES; FI; FR; GB; GR; IE; IT; LI;

LU; MC; NL; PT; SE

EXTENDED DESIGNATED STATES: AL; LT; LV; MK; RO; SI

INTERNATIONAL PATENT CLASS: A61M-016/00

NOTE:

No A-document published by EPO

LANGUAGE (Publication, Procedural, Application): English; English; English

(Item 16 from file: 349) 6/3,AU/16 DIALOG(R) File 349: PCT FULLTEXT (c) 2004 WIPO/Univentio. All rts. reserv. 00556688 VENTILATOR AND METHODS CARDIOPULMONARY RESUSCITATION VENTILATEUR ET PROCEDES DE REANIMATION CARDIO-PULMONAIRE Patent Applicant/Assignee: CPRX LLC, Inventor(s): LURIE Keith G , ZIELINSKI Todd M Patent and Priority Information (Country, Number, Date): WO 200020061 A1 20000413 (WO 0020061) Patent: WO 99US23233 19991005 (PCT/WO US9923233) Application: Priority Application: US 98168049 19981007 Designated States: AE AL AM AT AU AZ BA BB BG BR BY CA CH CN CR CU CZ DE DK DM EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT TZ UA UG UZ VN YU ZA ZW GH GM KE LS MW SD SL SZ TZ UG ZW AM AZ BY KG KZ MD RU TJ TM AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE BF BJ CF CG CI CM GA GN GW ML MR NE SN TD TG Publication Language: English Fulltext Word Count: 11470 (Item 17 from file: 348) 6/3,AU/17 DIALOG(R)File 348:EUROPEAN PATENTS (c) 2004 European Patent Office. All rts. reserv. 01118682 TO ENHANCE VENOUS BLOOD RETURN DURING STIMULATORY DEVICE AND METHODS CARDIOPULMONARY RESUSCITATION VERFAHREN ZUM VERBESSERN DES VENOSEN SOWIE STIMULIERUNGSVORRICHTUNG BLUTRUCKLAUFS WAHREND EINER KARDIOPULMONAREN REANIMATION DISPOSITIFS ET PROCEDES DE STIMULATION PERMETTANT D'AMELIORER LE RETOUR VEINEUX EN COURS DE REANIMATION CARDIORESPIRATOIRE PATENT ASSIGNEE: CPRX LLC, (3001040), 4751 Girard Avenue South, Minneapolis, MN 55409, (US), (Applicant designated States: all) INVENTOR: LURIE, Keith, G., 4751 Girard Avenue South, Minneapolis, MN 55409, (US) BENDITT, David, G., 2 Circle West, Edina, MN 55436, (US) ZIELINSKI, Todd, M., 48 27th Avenue S.E. 203, Minneapolis, MN 55414, VOECKEL, Wolfgang, Krehbachgasse 13C, A-6410 Telfs, (AT) PATTERSON, Robert, 3761 Foss Road, Minneapolis, MN 55421, (US LEGAL REPRESENTATIVE: Harrison, David Christopher et al (31532), MEWBURN ELLIS York House 23 Kingsway, London WC2B 6HP, (GB) EP 1098622 A2 010516 (Basic) PATENT (CC, No, Kind, Date): WO 9963926 991216 EP 99927453 990610; WO 99US13161 990610 APPLICATION (CC, No, Date): PRIORITY (CC, No, Date): US 95916 980611; US 197286 981120; US 315396 990520 DESIGNATED STATES: DE; FR; GB

INTERNATIONAL PATENT CLASS: A61H-001/00

NOTE:

No A-document published by EPO LANGUAGE (Publication, Procedural, Application): English; English; English

(Item 18 from file: 349) 6/3,AU/18 DIALOG(R) File 349: PCT FULLTEXT (c) 2004 WIPO/Univentio. All rts. reserv. STIMULATORY DEVICE AND METHODS TO ENHANCE VENOUS BLOOD RETURN DURING CARDIOPULMONARY RESUSCITATION DISPOSITIFS ET PROCEDES DE STIMULATION PERMETTANT D'AMELIORER LE RETOUR VEINEUX EN COURS DE REANIMATION CARDIORESPIRATOIRE Patent Applicant/Assignee: CPRx LLP, Inventor(s): LURIE Keith G , BENDITT David G, ZIELINSKI Todd M , VOECKEL Wolfgang, PATTERSON Robert Patent and Priority Information (Country, Number, Date): WO 9963926 A2 19991216 Patent: WO 99US13161 19990610 (PCT/WO US9913161) Application: Priority Application: US 9895916 19980611; US 98197286 19981120; US 99315396 19990520 Designated States: AE AL AM AT AU AZ BA BB BG BR BY CA CH CN CU CZ DE DK EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT UA UG UZ VN YU ZA ZW GH GM KE LS MW SD SL SZ UG ZW AM AZ BY KG KZ MD RU TJ TM AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE BF BJ CF CG CI CM GA GN GW ML MR NE SN TD TG Publication Language: English Fulltext Word Count: 13343 (Item 19 from file: 348) 6/3, AU/19DIALOG(R) File 348: EUROPEAN PATENTS (c) 2004 European Patent Office. All rts. reserv. 01092788 VENTILATOR CONTROL SYSTEM AND METHOD STEUERVORRICHTUNG FUR BEATMUNGSGERAT SOWIE VERFAHREN SYSTEME ET PROCEDE DE COMMANDE D'UN VENTILATEUR PATENT ASSIGNEE: CARDIOPULMONARY CORPORATION, (1156111), 200 Cascade Boulevard, Milford, CT 06460, (US), (Applicant designated States: all) INVENTOR:

VENTILATOR CONTROL SYSTEM AND METHOD
STEUERVORRICHTUNG FUR BEATMUNGSGERAT SOWIE VERFAHREN
SYSTEME ET PROCEDE DE COMMANDE D'UN VENTILATEUR
PATENT ASSIGNEE:
CARDIOPULMONARY CORPORATION, (1156111), 200 Cascade Boulevard, Milford,
CT 06460, (US), (Applicant designated States: all)
INVENTOR:
BIONDI, James, W., 1601 Ridge Road, North Haven, CT 06473, (US)
JOHNSTON, Douglas, M., 48 Winthrop Street, Winchester, MA 01890, (US)
SCHROEDER, Gerhardt, P., 24 Seasons Lane, Londonderry, NH 03053, (US)
GILMORE, Donald, D., 1083 Kupulau Drive, Kiehi, HI 96753, (US)
REYNOLDS, Robert, 299 Townsend Street, New Haven, CT 06512, (US)
PATENT (CC, No, Kind, Date):
WO 9947200 990923
APPLICATION (CC, No, Date): WO 99913981 990319; WO 99US6056 990319
PRIORITY (CC, No, Date): US 45461 980320
DESIGNATED STATES: AT; BE; CH; CY; DE; DK; ES; FI; FR; GB; GR; IE; IT; LI;
LU; MC; NL; PT; SE
INTERNATIONAL PATENT CLASS: A61M-016/00

(Item 20 from file: 349) 6/3,AU/20 DIALOG(R) File 349: PCT FULLTEXT (c) 2004 WIPO/Univentio. All rts. reserv. 00515848 -VENTILATOR -- CONTROL SYSTEM AND METHOD SYSTEME ET PROCEDE DE COMMANDE D'UN VENTILATEUR Patent Applicant/Assignee: CARDIOPULMONARY CORPORATION, Inventor(s): BIONDI James W , JOHNSTON Douglas M, SCHROEDER Gerhardt P, GILMORE Donald D, REYNOLDS Robert Patent and Priority Information (Country, Number, Date): WO 9947200 A1 19990923 Patent: WO 99US6056 19990319 (PCT/WO US9906056) Application: Priority Application: US 9845461 19980320 Designated States: IL AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE Publication Language: English Fulltext Word Count: 12115 (Item 21 from file: 348) 6/3,AU/21 DIALOG(R) File 348: EUROPEAN PATENTS (c) 2004 European Patent Office. All rts. reserv. 00958085 HEART FAILURE TREATMENT METHOD REQUIRING SET NEGATIVE INTRATHORACIC PRESSURE EINEN DEFINIERTEN NEGATIVEN INNEREN THORAXDRUCK ERFORDERNDES VERFAHREN ZUM BEHANDELN VON HERZVERSAGEN PROCEDE DE TRAITEMENT DES INSUFFISANCES CARDIAQUES NECESSITANT UNE PRESSION INTRATHORACIQUE NEGATIVE DEFINIE PATENT ASSIGNEE: CPRX, INC., (2305590), 4751 Girard Avenue South, Minneapolis, MN 55409, (US), (Applicant designated States: all) LURIE, Keith, G., 4751 Girard Avenue South, Minneapolis, MN 55409, (US INVENTOR: LEGAL REPRESENTATIVE: Sanderson, Michael John et al (35592), MEWBURN ELLIS York House 23 Kingsway, London WC2B 6HP, (GB) PATENT (CC, No, Kind, Date): EP 949941 Al 991020 (Basic) WO 9820938 980522 EP 97946595 971112; WO 97US20378 971112 APPLICATION (CC, No, Date): PRIORITY (CC, No, Date): US 747371 961112 DESIGNATED STATES: DE; FR; GB INTERNATIONAL PATENT CLASS: A62B-018/10; A62B-018/02 NOTE: No A-document published by EPO LANGUAGE (Publication, Procedural, Application): English; English; English

6/3,AU/22 (Item 22 from file: 349)
DIALOG(R)File 349:PCT FULLTEXT
(c) 2004 WIPO/Univentio. All rts. reserv.

00430474 NEGATIVE INTRATHORACIC HEART FAILURE TREATMENT METHOD REQUIRING SET PRESSURE PROCEDE DE TRAITEMENT DES INSUFFISANCES CARDIAQUES NECESSITANT UNE PRESSION INTRATHORACIQUE NEGATIVE DEFINIE Patent Applicant/Assignee: CPRx INC, Inventor(s): LURIE Keith G Patent and Priority Information (Country, Number, Date): WO 9820938 A1 19980522 Patent: (PCT/WO US9720378) WO 97US20378 19971112 Application: Priority Application: US 96747371 19961112 Designated States: AL AM AT AU AZ BA BB BG BR BY CA CH CN CU CZ DE DK EE ES FI GB GE GH HU ID IL IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT UA UG UZ VN YU ZW GH KE LS MW SD SZ UG ZW AM AZ BY KG KZ MD RU TJ TM AT BE CH DE DK ES FI FR GB GR IE IT LU MC NL PT SE BF BJ CF CG CI CM GA GN ML MR NE SN TD Publication Language: English Fulltext Word Count: 4340 (Item 23 from file: 348) 6/3, AU/23DIALOG(R) File 348: EUROPEAN PATENTS (c) 2004 European Patent Office. All rts. reserv. 00895107 COMBINATIONS OF VASOPRESSIN AND ADRENERGIC AGENTS FOR THE TREATMENT OF CARDIAC ARREST KOMBINATIONEN VON VASOPRESSIN UND ADRENERGISCHEN WIRKSTOFFEN ZUR BEHANDLUNG DES PLOTZLICHEN HERZTODS ASSOCIATIONS DE VASOPRESSINE ET D'AGENTS ADRENERGIQUES POUR LE TRAITEMENT DES ARRETS CARDIAQUES PATENT ASSIGNEE: Lurie, Keith G., (1986760), 4751 Girard Avenue South, Minneapolis, MN 55409, (US), (Proprietor designated states: all) Lindner, Karl, (2403880), Steinhovelstrasse 9, 89075 Ulm, (DE), (Proprietor designated states: all) INVENTOR: Lurie, Keith G., 4751 Girard Avenue South, Minneapolis, MN 55409, (US) Lindner, Karl, Steinhovelstrasse 9, 89075 Ulm, (DE LEGAL REPRESENTATIVE: Hay, Martin Alexander (59434), Martin A. Hay & Co. 13 Queen Victoria Street, Macclesfield Cheshire SK11 6LP, (GB) PATENT (CC, No, Kind, Date): EP 904097 A2 990331 (Basic) EP 904097 B1 030528 WO 97036609 971009 EP 97917089 970327; WO 97US5056 970327 APPLICATION (CC, No, Date): PRIORITY (CC, No, Date): US 625733 960329 DESIGNATED STATES: AT; BE; CH; DE; DK; ES; FI; FR; GB; GR; IE; IT; LI; LU; MC; NL; PT; SE INTERNATIONAL PATENT CLASS: A61K-038/11; A61K-031/55; A61P-009/04 NOTE: No A-document published by EPO LANGUAGE (Publication, Procedural, Application): English; English; English

Word Count

672

Update

FULLTEXT AVAILABILITY:

Available Text Language

CLAIMS B (English) 200322

```
681
                           200322
     CLAIMS B
                 (German)
                                       750
                           200322
     CLAIMS B
                 (French)
                                      6372
                (English) 200322
     SPEC B
                                         0
Total word count - document A
                                      8475
Total word count - document B
                                      8475
Total word count - documents A + B
               (Item 24 from file: 349)
 6/3, AU/24
DIALOG(R) File 349: PCT FULLTEXT
(c) 2004 WIPO/Univentio. All rts. reserv.
00395866
COMBINATIONS OF VASOPRESSIN AND ADRENERGIC AGENTS FOR THE TREATMENT OF
    CARDIAC ARREST
ASSOCIATIONS DE VASOPRESSINE ET D'AGENTS ADRENERGIQUES POUR LE TRAITEMENT
    DES ARRETS CARDIAQUES
Patent Applicant/Assignee:
  LURIE Keith G,
  LINDNER Karl,
Inventor(s):
   LURIE Keith G ,
  LINDNER Karl
Patent and Priority Information (Country, Number, Date):
                        WO 9736609 A2 19971009
  Patent:
                        WO 97US5056 19970327 (PCT/WO US9705056)
  Application:
  Priority Application: US 96625733 19960329
Designated States: AU CA JP AT BE CH DE DK ES FI FR GB GR IE IT LU MC NL PT
Publication Language: English
Fulltext Word Count: 8350
                (Item 25 from file: 348)
 6/3,AU/25
DIALOG(R) File 348: EUROPEAN PATENTS
(c) 2004 European Patent Office. All rts. reserv.
00804856
       DEVICE HAVING STRUCTURE FOR INCREASING THE DURATION AND MAGNITUDE OF
     NEGATIVE INTRA-THORACIC PRESSURE
HERZ-LUNGEN-WIEDERBELEBUNGSEINRICHTUNG MIT DER MOGLICHKEIT ZUM ERHOHEN DER
    DAUER UND DES BETRAGES DES NEGATIVEN INNEREN THORAXDRUCKS
DISPOSITIF DE REANIMATION CARDIO-PULMONAIRE A STRUCTURE AUGMENTANT LA DUREE
     ET L'INTENSITE D'UNE PRESSION INTRA-THORACIQUE NEGATIVE.
 PATENT ASSIGNEE:
  CPRX, LLC., (4268230), 7615 Golden Triangle Drive, Suite A, Technology
     Park #5, Eden Prairie, MN 55344, (US), (Proprietor designated states:
     all)
 INVENTOR:
```

LURIE, Keith, G., 4751 Girard Avenue South, Minneapolis, MN 55409, (US) SWEENEY, Michael, 1525 Goodrich Avenue, St. Paul, MN 55105, (US) GOLD, Barbara, 4751 Girard Avenue South, Minneapolis, MN 55409, (US LEGAL REPRESENTATIVE: Sanderson, Michael John et al (35592), MEWBURN ELLIS York House 23 Kingsway, London WC2B 6HP, (GB)
PATENT (CC, No, Kind, Date): EP 898485 Al 990303 (Basic)

EP 898485 A1 990512 EP 898485 B1 030502

WO 96028215 960919

APPLICATION (CC, No, Date): EP 96905523 960216; WO 96US2097 960216

```
PRIORITY (CC, No, Date): US 403009 950310
DESIGNATED STATES: DE; FR; GB; IT; SE
INTERNATIONAL PATENT CLASS: A62B-007/00; A62B-009/02; A61M-016/04;
 A61M-016/20
NOTE:
  No A-document published by EPO
LANGUAGE (Publication, Procedural, Application): English; English; English
FULLTEXT AVAILABILITY:
                           Update
                                     Word Count
Available Text Language
      CLAIMS B (English)
                           200318
                                      1103
                           200318
                                      1185
                (German)
      CLAIMS B
                           200318
                                      1195
      CLAIMS B
                 (French)
                (English) 200318
                                      9175
      SPEC B
Total word count - document A
                                         0
Total word count - document B
                                     12658
Total word count - documents A + B
                                     12658
               (Item 26 from file: 349)
 6/3,AU/26
DIALOG(R) File 349: PCT FULLTEXT
(c) 2004 WIPO/Univentio. All rts. reserv.
00345702
       DEVICE HAVING STRUCTURE FOR INCREASING THE DURATION AND MAGNITUDE OF
 CPR
     NEGATIVE INTRA-THORACIC PRESSURE
DISPOSITIF DE REANIMATION CARDIO-PULMONAIRE A STRUCTURE AUGMENTANT LA DUREE
    ET L'INTENSITE D'UNE PRESSION INTRA-THORACIQUE NEGATIVE.
Patent Applicant/Assignee:
  LURIE Keith G,
  SWEENEY Michael,
  GOLD Barbara,
Inventor(s):
   LURIE Keith G ,
  SWEENEY Michael,
  GOLD Barbara
Patent and Priority Information (Country, Number, Date):
                        WO 9628215 A1 19960919
  Patent:
                        WO 96US2097 19960216 (PCT/WO US9602097)
  Application:
  Priority Application: US 95403009 19950310
Designated States: AL AM AT AU AZ BB BG BR BY CA CH CN CZ DE DK EE ES FI GB
  GE HU IS JP KE KG KP KR KZ LK LR LS LT LU LV MD MG MK MN MW MX NO NZ PL
  PT RO RU SD SE SG SI SK TJ TM TR TT UA UG US UZ VN KE LS MW SD SZ UG AZ
  BY KG KZ MD RU TJ TM AT BE CH DE DK ES FR GB GR IE IT LU MC NL PT SE BF
  BJ CF CG CI CM GA GN ML MR NE SN TD TG
Publication Language: English
Fulltext Word Count: 10995
```

```
6/3,AU/27 (Item 27 from file: 348)
DIALOG(R)File 348:EUROPEAN PATENTS
(c) 2004 European Patent Office. All rts. reserv.
```

00783455

RESPIRATOR BEATMUNGSGERAT

RESPIRATEUR

PATENT ASSIGNEE:

CARDIOPULMONARY CORPORATION, (1156111), 200 Cascade Boulevard, Milford, CT 06460, (US), (Proprietor designated states: all)

INVENTOR:

SCHROEDER, Gary, 24 Seasons Lane, North Londonderry, NH 03053, (US) BIONDI, James, W., 1601 Ridge Road, North Haven, CT 06473, (US) JOHNSTON, Douglas, M., 48 Winthrop Street, Winchester, MA 01890, (US LEGAL REPRESENTATIVE: Kirkham, Nicholas Andrew et al (83451), Graham Watt & Co., Riverhead, Sevenoaks, Kent TN13 2BN, (GB) PATENT (CC, No, Kind, Date): EP 796119 A1 970924 (Basic) EP 796119 B1 991027 WO 9617641 960613 EP 95944311 951204; WO 95US15706 951204 APPLICATION (CC, No, Date): PRIORITY (CC, No, Date): US 352658 941209 DESIGNATED STATES: DE; FR; GB; SE INTERNATIONAL PATENT CLASS: A61M-016/00 NOTE: No A-document published by EPO LANGUAGE (Publication, Procedural, Application): English; English; English FULLTEXT AVAILABILITY: Word Count Update Available Text Language 555 (English) 9943 CLAIMS B 562 9943 CLAIMS B (German) 646 9943 (French) CLAIMS B 3557 9943 (English) SPEC B 0 Total word count - document A Total word count - document B 5320 5320 Total word count - documents A + B (Item 28 from file: 349) 6/3,AU/28 DIALOG(R) File 349: PCT FULLTEXT (c) 2004 WIPO/Univentio. All rts. reserv. 00335129 RESPIRATOR RESPIRATEUR Patent Applicant/Assignee: CARDIOPULMONARY CORPORATION, Inventor(s): SCHROEDER Gary, BIONDI James W , JOHNSTON Douglas M Patent and Priority Information (Country, Number, Date): WO 9617641 A1 19960613 Patent: (PCT/WO US9515706) WO 95US15706 19951204 Application: Priority Application: US 94352658 19941209 Designated States: AU CA JP KR NZ AT BE CH DE DK ES FR GB GR IE IT LU MC NL PT SE Publication Language: English Fulltext Word Count: 5053 (Item 29 from file: 348) 6/3,AU/29 DIALOG(R) File 348: EUROPEAN PATENTS (c) 2004 European Patent Office. All rts. reserv.

00703210
DEVICE FOR ASSISTING CARDIOPULMONARY RESUSCITATION
VORRICHTUNG ZUR UNTERSTUTZUNG BEI KARDIOPULMONALER WIEDERBELEBUNG
DISPOSITIF D'ASSISTANCE A LA REANIMATION CARDIO-PULMONAIRE

PATENT ASSIGNEE:
CPRX, LLC., (4268230), 7615 Golden Triangle Drive, Suite A, Technology
Park #5, Eden Prairie, MN 55344, (US), (Proprietor designated states:

```
all)
INVENTOR:
  Lurie, Keith G., 4751 Girard Avenue South, Minneapolis, MN 55409, (US)
 Sweeney, Michael, 1525 Goodrich Avenue, St. Paul, MN 55105, (US)
 Gold, Barbara, 4751 Girard Avenue South, Minneapolis, MN 55409, (US
LEGAL REPRESENTATIVE:
  Harrison, David Christopher (31532), MEWBURN ELLIS York House 23 Kingsway
    , London WC2B 6HP, (GB)
PATENT (CC, No, Kind, Date): EP 728028 Al 960828 (Basic)
                              EP 728028 A1 970604
                              EP 728028 B1 030521
                              WO 95013108 950518
                                                   WO 94US12870
                              EP 95901822 941107;
APPLICATION (CC, No, Date):
PRIORITY (CC, No, Date): US 149204 931109
DESIGNATED STATES (Pub A): AT; BE; CH; DE; DK; ES; FR; GB; GR; IE; IT; LI;
  LU; MC; NL; PT; SE; (Pub B): DE; ES; FR; GB; IT; NL; SE
INTERNATIONAL PATENT CLASS: A61M-015/00; A61M-016/00;
                                                           A62B-007/00 ;
  A62B-009/06; A62B-018/02; A61H-031/00
NOTE:
  No A-document published by EPO
LANGUAGE (Publication, Procedural, Application): English; English; English
FULLTEXT AVAILABILITY:
                                     Word Count
Available Text Language
                           Update
                                       257
                           200321
                (English)
      CLAIMS B
                                        274
                           200321
      CLAIMS B
                  (German)
                           200321
                                       275
      CLAIMS B
                  (French)
                            200321
                                       5414
                 (English)
      SPEC B
                                          0
Total word count - document A
Total word count - document B
                                       6220
Total word count - documents A + B
            (Item 30 from file: 349)
 6/3, AU/30
DIALOG(R) File 349: PCT FULLTEXT
(c) 2004 WIPO/Univentio. All rts. reserv.
METHOD AND DEVICE FOR ASSISTING CARDIOPULMONARY RESUSCITATION
PROCEDE ET DISPOSITIF D'ASSISTANCE A LA REANIMATION CARDIO-PULMONAIRE
Patent Applicant/Assignee:
  LURIE Keith G,
   SWEENEY Michael,
   GOLD Barbara,
 Inventor(s):
   LURIE Keith G ,
   SWEENEY Michael,
   GOLD Barbara
 Patent and Priority Information (Country, Number, Date):
                         WO 9513108 A1 19950518
   Patent:
                         WO 94US12870 19941107 (PCT/WO US9412870)
   Application:
   Priority Application: US 93149204 19931109
 Designated States: AM AT AU BB BG BR BY CA CH CN CZ DE DK EE ES FI GB GE HU
   JP KE KG KP KR KZ LK LR LT LU LV MD MG MN MW NL NO NZ PL PT RO RU SD SE
   SI SK TJ TT UA UZ VN KE MW SD SZ AT BE CH DE DK ES FR GB GR IE IT LU MC
   NL PT SE BF BJ CF CG CI CM GA GN ML MR NE SN TD TG
 Publication Language: English
 Fulltext Word Count: 7094
```

6/3,AU/31 (Item 31 from file: 348)
DIALOG(R)File 348:EUROPEAN PATENTS

```
(c) 2004 European Patent Office. All rts. reserv.
00801713
Coronary sinus catheter
Koronarsinus Katheter
Catheter pour le sinus coronaire
PATENT ASSIGNEE:
  DAIG CORPORATION, (1027891), 14901 DeVeau Place, Minnetonka, Minnesota
    55345-2126, (US), (Proprietor designated states: all)
INVENTOR:
  Lurie, Keith G., 4751 Girard Avenue, South, Minneapolis, MN 55409, (US)
  Benditt, David G., No. 2 Circle West, Edina, Minnesota, (US)
  Shultz, Jeffrey J., 4600 Ewing Ave., N., Robbinsdale, MN 55422, (US)
  Ockuly, John D., 14901 DeVeau Place, Minnetonka, MN 55345, (US)
  Fleischhacker, John J., 14901 DeVeau Place, Minnetonka, MN 55345, (US
LEGAL REPRESENTATIVE:
  Splanemann Reitzner Baronetzky Westendorp Patentanwalte (100431),
    Rumfordstrasse 7, 80469 Munchen, (DE)
PATENT (CC, No, Kind, Date):
                              EP 745406
                                         Α2
                                              961204 (Basic)
                                              970205
                              EP 745406
                                         А3
                              EP 745406
                                         В1
                                              030813
APPLICATION (CC, No, Date):
                              EP 96102200 960214;
PRIORITY (CC, No, Date): US 457675 950601
DESIGNATED STATES: AT; CH; DE; ES; FR; GB; IT; LI; NL; SE
INTERNATIONAL PATENT CLASS: A61M-025/00; A61N-001/39; A61M-025/01
ABSTRACT WORD COUNT: 99
NOTE:
  Figure number on first page: 2
LANGUAGE (Publication, Procedural, Application): English; English; English
FULLTEXT AVAILABILITY:
Available Text Language
                            Update
                                      Word Count
                                        353
                            EPAB96
      CLAIMS A
                (English)
                                        198
      CLAIMS B
                            200333
                (English)
                                        203
      CLAIMS B
                 (German)
                            200333
      CLAIMS B
                 (French)
                            200333
                                        211
                                       3826
      SPEC A
                 (English)
                            EPAB96
      SPEC B
                 (English)
                            200333
                                       3855
                                       4180
Total word count - document A
                                       4467
Total word count - document B
Total word count - documents A + B
                                       8647
```

6/3,AU/32 (Item 32 from file: 348)

DIALOG(R) File 348: EUROPEAN PATENTS

(c) 2004 European Patent Office. All rts. reserv.

00644535

Cardiopulmonary resuscitation device
Kardiopulmonare Wiederbelebungsvorrichtung
Dispositif pour la reanimation cardio-pulmonaire
PATENT ASSIGNEE:

THE REGENTS OF THE UNIVERSITY OF CALIFORNIA, (221072), 300 Lakeside Drive, 22nd Floor, Oakland, California 94612-3550, (US), (applicant designated states: AT;BE;CH;DE;DK;ES;FR;GB;GR;IE;IT;LI;LU;MC;NL;PT;SE) AMBU INTERNATIONAL A/S, (965372), Sondre Ringvej 49, P.O. Box 215, 2600 Glostrup, Copenhagen, (DK), (applicant designated states: AT;BE;CH;DE;DK;ES;FR;GB;GR;IE;IT;LI;LU;MC;NL;PT;SE) INVENTOR:

```
Kohnke, Ole B., Vagtelvej 32, DK-2000 Frederiksberg, (DK)
 Cohen, Todd J., 4 Orchard Farm Road, Port Washington, New York 11050, (US
LEGAL REPRESENTATIVE:
  Tiedtke, Harro, Dipl.-Ing. et al (11949), Patentanwaltsburo
    Tiedtke-Buhling-Kinne & Partner Bavariaring 4, 80336 Munchen, (DE)
PATENT (CC, No, Kind, Date): EP 623334 A1 941109 (Basic)
                              EP 623334 B1 990609
APPLICATION (CC, No, Date): EP 94106492 940426;
PRIORITY (CC, No, Date): US-58195-930504
DESIGNATED STATES: AT; BE; CH; DE; DK; ES; FR; GB; GR; IE; IT; LI; LU; MC;
  NL; PT; SE
INTERNATIONAL PATENT CLASS: A61H-031/00;
ABSTRACT WORD COUNT: 161
LANGUAGE (Publication, Procedural, Application): English; English; English
FULLTEXT AVAILABILITY:
                                     Word Count
                           Update
Available Text Language
                           9923
                                        431
      CLAIMS B
                (English)
                                       . 439
                           9923
      CLAIMS B
                 (German)
                                        500
                            9923
      CLAIMS B
                 (French)
                                       4230
                            9923
      SPEC B
                 (English)
Total word count - document A
                                          0
Total word count - document B
                                       5600
Total word count - documents A + B
                                       5600
                (Item 33 from file: 348)
 6/3,AU/33
DIALOG(R) File 348: EUROPEAN PATENTS
(c) 2004 European Patent Office. All rts. reserv.
00539057
Device for external chest compression
Vorrichtung zur externen Kompression des Brustkastens
Dispositif pour la compression externe du thorax
PATENT ASSIGNEE:
  THE REGENTS OF THE UNIVERSITY OF CALIFORNIA, (221072), 300 Lakeside
    Drive, 22nd Floor, Oakland, California 94612-3550, (US), (applicant
    designated states: DE; ES; FR; GB; IT)
INVENTOR:
   Lurie, Keith G., 835 - 33rd Avenue, San Francisco, California 94121,
     (US)
  Cohen, Todd J., 1234 Stanyan Street, San Francisco, California 94117, (US
LEGAL REPRESENTATIVE:
  Harrison, David Christopher et al (31532), MEWBURN ELLIS York House 23
     Kingsway, London WC2B 6HP, (GB)
 PATENT (CC, No, Kind, Date): EP 509773 A1
                                              921021 (Basic)
                               EP 509773 B1
                                              980107
                               EP 92303367 920415;
APPLICATION (CC, No, Date):
 PRIORITY (CC, No, Date): US 686542 910417
 DESIGNATED STATES: DE; ES; FR; GB; IT
 INTERNATIONAL PATENT CLASS: A61H-031/00;
 ABSTRACT WORD COUNT: 111
 LANGUAGE (Publication, Procedural, Application): English; English; English
 FULLTEXT AVAILABILITY:
                            Update
                                       Word Count
 Available Text Language
                                         455
                             9802
       CLAIMS B
                 (English)
                                         436
                             9802
       CLAIMS B
                  (German)
                                         483
                             9802
                  (French)
       CLAIMS B
                                        4194
                 (English)
                             9802
       SPEC B
                                           0
 Total word count - document A
 Total word count - document B
                                        5568
```

5568

Total word count - documents A + B

(Item 34 from file: 349) 6/3, AU/34DIALOG(R) File 349: PCT FULLTEXT (c) 2004 WIPO/Univentio. All rts. reserv. 01105581 STRESS TEST DEVICES AND METHODS DISPOSITIFS D'EPREUVE D'EFFORTS ET PROCEDES Y RELATIFS Patent Applicant/Assignee: ADVANCED CIRCULATORY SYSTEMS INC, 7615 Golden Triangle Drive, Suite A, Technology Park #5, Eden Prairie, MN 55344, US, US (Residence), US (Nationality) Inventor(s): LURIE Keith G , 4751 Girard Avenue South, Minneapolis, MN 55409, US Legal Representative: GIBBY Darin J (et al) (agent), Townsend and Townsend and Crew LLP, Two Embarcadero Center, Eighth Floor, San Francisco, CA 94111-3834, US, Patent and Priority Information (Country, Number, Date): WO 200426101 A2 20040401 (WO 0426101) Patent: WO 2003US29210 20030919 (PCT/WO US03029210) Application: Priority Application: US 2002251080 20020920 Designated States: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE EG ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NI NO NZ OM PG PH PL PT RO RU SC SD SE SG SK SL SY TJ TM TN TR TT TZ UA UG UZ VC VN YU ZA (EP) AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL PT RO SE SI SK TR (OA) BF BJ CF CG CI CM GA GN GQ GW ML MR NE SN TD TG (AP) GH GM KE LS MW MZ SD SL SZ TZ UG ZM ZW (EA) AM AZ BY KG KZ MD RU TJ TM Publication Language: English Filing Language: English Fulltext Word Count: 5304 (Item 35 from file: 349) 6/3,AU/35

DIALOG(R) File 349:PCT FULLTEXT

(c) 2004 WIPO/Univentio. All rts. reserv.

00935977

NETWORK MONITORING SYSTEMS FOR MEDICAL DEVICES

SYSTEMES DE SURVEILLANCE EN RESEAU POUR DISPOSITIFS MEDICAUX

Patent Applicant/Assignee:

CARDIOPULMONARY CORPORATION, 200 Cascade Boulevard, Milford, CT 06460, US

, US (Residence), US (Nationality)

Inventor(s):

BIONDI James W , 1601 Ridge Road, North Haven, CT 06473, US,

FINDR Appen 153 Laurel Terrace Cheshire, CT 06410, US

BIONDI James W , 1601 Ridge Road, North Haven, CT 064/3, US, FAND Aaron, 153 Laurel Terrace, Cheshire, CT 06410, US Legal Representative:

MOORE Ronda P (agent), Testa, Hurwitz & Thibeault, LLP, High Street Tower, 125 High Street, Boston, MA 02110, US,

Patent and Priority Information (Country, Number, Date):

Patent: WO 200269181 A2-A3 20020906 (WO 0269181)
Application: WO 2002US4515 20020219 (PCT/WO US0204515)

Priority Application: US 2001791334 20010223

Designated States: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO RU SD SE SG SI SK SL TJ TM TN TR TT TZ UA UG UZ VN YU ZA ZM ZW

, F\

(EP) AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE TR (OA) BF BJ CF CG CI CM GA GN GQ GW ML MR NE SN TD TG (AP) GH GM KE LS MW MZ SD SL SZ TZ UG ZM ZW (EA) AM AZ BY KG KZ MD RU TJ TM Publication Language: English Filing Language: English Fulltext Word Count: 6734 6/3,AU/36 (Item 36 from file: 349) DIALOG(R) File 349: PCT FULLTEXT (c) 2004 WIPO/Univentio. All rts. reserv. 00837059 STIMULATORY DEVICE AND METHODS TO ELECTRICALLY STIMULATE THE PHRENIC NERVE DISPOSITIF ET METHODES DE STIMULATION PERMETTANT DE STIMULER LE NERF PHRENIQUE Patent Applicant/Assignee: CPRX LLC, 4330 Upton Avenue South, Minneapolis, MN 55410, US, US (Residence), US (Nationality) Inventor(s): ZIELINSKI Todd M , 48 27th Avenue S.E. #203, Minneapolis, MN 55414, US, LURIE Keith G , 4751 Girard Avenue South, Minneapolis, MN 55409, US, VOELCKEL Wolfgang, Krehbachgasse 13C, A-6410 Telfs, AT, PATTERSON Robert, 3761 Foss Road, Minneapolis, MN 55421, US, SAMNIAH Nemer, Khury Street 23, Haifa, IL, MCKNITE Scott, 4217 Bryant Avenue South, Minneapolis, MN 55409, US, LINDNER Karl, Gartenweg 21, A-6161 Natters, AT Legal Representative: GIBBY Darin J (et al) (agent), Townsend and Townsend and Crew LLP, 1200 Seventeenth Street, Ste 2700, Denver, CO 80202, US, Patent and Priority Information (Country, Number, Date): WO 200170332 A2-A3 20010927 (WO 0170332) Patent: WO 2001US8687 20010316 (PCT/WO US0108687) Application: Priority Application: US 2000533880 20000322 Designated States: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CR CU CZ DE DK DM DZ EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT TZ UA UG UZ VN YU ZA ZW (EP) AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE TR (OA) BF BJ CF CG CI CM GA GN GW ML MR NE SN TD TG (AP) GH GM KE LS MW MZ SD SL SZ TZ UG ZW (EA) AM AZ BY KG KZ MD RU TJ TM Publication Language: English Filing Language: English Fulltext Word Count: 19506 (Item 37 from file: 349)

6/3, AU/37DIALOG(R) File 349: PCT FULLTEXT

(c) 2004 WIPO/Univentio. All rts. reserv.

00454522

DEVICE AND METHOD FOR DETECTION AND TREATMENT OF SYNCOPE DISPOSITIF ET PROCEDE POUR LA DETECTION ET LE TRAITEMENT DE LA SYNCOPE Patent Applicant/Assignee:

PHARMATARGET INC,

Inventor(s):

LURIE Keith G , BENDITT David,

6/3,AU/38 (Item 38 from file: 349)
DIALOG(R)File 349:PCT FULLTEXT
(c) 2004 WIPO/Univentio. All rts. reserv.

00262876

METHODS AND PHARMACEUTICAL COMPOSITIONS FOR ENHANCED CARDIOPULMONARY RESUSCITATION

PROCEDES ET COMPOSITIONS PHARMACEUTIQUES FAVORISANT LA REANIMATION CARDIO-RESPIRATOIRE

Patent Applicant/Assignee:

Fulltext Word Count: 3486

REGENTS OF THE UNIVERSITY OF MINNESOTA,

Inventor(s):

LURIE Keith G ,

GOLD Barbara S

Patent and Priority Information (Country, Number, Date):

Patent: WO 9411045 A1 19940526

Application: WO 93US11034 19931115 (PCT/WO US9311034)

Priority Application: US 92977498 19921117

Designated States: AU CA JP KR AT BE CH DE DK ES FR GB GR IE IT LU MC NL PT

SE

Publication Language: English Fulltext Word Count: 5137

6/3,AU/39 (Item 39 from file: 349)

DIALOG(R) File 349: PCT FULLTEXT

(c) 2004 WIPO/Univentio. All rts. reserv.

00162658

CIRCULATORY ASSIST METHOD AND APPARATUS

PROCEDE ET APPAREIL D'ASSISTANCE CIRCULATOIRE

Patent Applicant/Assignee:

CARDIOPULMONARY CORPORATION,

Inventor(s):

BIONDI James W ,

MENTELOS Richard A

Patent and Priority Information (Country, Number, Date):

Patent: WO 8909041 A1 19891005

Application: WO 89US1356 19890331 (PCT/WO US8901356)

Priority Application: US 88810 19880331

Designated States: AT AU BE CH DE DK FI FR GB IT JP KR LU NL NO SE

Publication Language: English Fulltext Word Count: 7912

```
Description
Set
        Items
                AU=(LURIE K? OR LURIE, K? OR MENK V? OR MENK, V? OR ZIELIN-
         1789
S1
             SKI T? OR ZIELINSKI, T? OR BIONDI J? OR BIONDI, J?)
                KEITH(2W)LURIE OR VERN(2W)MENK OR TODD(2W)ZIELINSKI OR JAM-
S2
             ES (2W) BIONDI
                RESUSC? OR RESPIRAT? OR BREATH? OR VENTILAT? OR CPR OR PEEP
      2545948
S3
              OR (POSITIVE OR NEGATIVE) (2N) PRESSUR?
          512
                S1:S2 AND S3
S4
                S4 AND VALV?
          110
$5
                S5 AND PY<2004
          110
S6
                RD (unique items)
           44
s7
? show files
File 155:MEDLINE(R) 1966-2004/May W2
         (c) format only 2004 The Dialog Corp.
       2:INSPEC 1969-2004/May W1
File
         (c) 2004 Institution of Electrical Engineers
       5:Biosis Previews(R) 1969-2004/May W2
File
          (c) 2004 BIOSIS
      6:NTIS 1964-2004/May W2
File
          (c) 2004 NTIS, Intl Cpyrght All Rights Res
       8:Ei Compendex(R) 1970-2004/May W1
File
          (c) 2004 Elsevier Eng. Info. Inc.
      34:SciSearch(R) Cited Ref Sci 1990-2004/May W2
File
          (c) 2004 Inst for Sci Info
File 434:SciSearch(R) Cited Ref Sci 1974-1989/Dec
          (c) 1998 Inst for Sci Info
      73:EMBASE 1974-2004/May W1
 File
          (c) 2004 Elsevier Science B.V.
      71:ELSEVIER BIOBASE 1994-2004/May W1
 File
          (c) 2004 Elsevier Science B.V.
 File 144:Pascal 1973-2004/May W1
          (c) 2004 INIST/CNRS
       35:Dissertation Abs Online 1861-2004/Apr
 File
          (c) 2004 ProQuest Info&Learning
       65:Inside Conferences 1993-2004/May W2
 File
          (c) 2004 BLDSC all rts. reserv.
       94:JICST-EPlus 1985-2004/Apr W3
 File
          (c) 2004 Japan Science and Tech Corp(JST)
       95:TEME-Technology & Management 1989-2004/Apr W4
 File
          (c) 2004 FIZ TECHNIK
       99:Wilson Appl. Sci & Tech Abs 1983-2004/Apr
 File
           (c) 2004 The HW Wilson Co.
 File 481:DELPHES Eur Bus 95-2004/May W1
          (c) 2004 ACFCI & Chambre CommInd Paris
 File 583:Gale Group Globalbase(TM) 1986-2002/Dec 13
           (c) 2002 The Gale Group
```

7/3,K/1 (Item 1 from file: 155)

DIALOG(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

13853409 PMID: 9554651

Optimizing standard cardiopulmonary resuscitation with an inspiratory

impedance threshold valve .

Lurie K G; Mulligan K A; McKnite S; Detloff B; Lindstrom P; Lindner K H -- Cardiac -- Arrhythmia Center, Cardiovascular Division, University of Minnesota, Minneapolis, USA.

Chest (UNITED STATES) Apr 1998 , 113 (4) p1084-90, ISSN 0012-3692

Journal Code: 0231335

Document type: Journal Article

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

Optimizing standard cardiopulmonary resuscitation with an inspiratory impedance threshold valve .

Lurie K G; Mulligan K A; McKnite S; Detloff B; Lindstrom P; Lindner K H Apr 1998 ,

 $\dots$  to assess whether intermittent impedance of inspiratory gas exchange improves the efficiency of standard cardiopulmonary resuscitation ( CPR ). BACKGROUND: Standard CPR relies on the natural elastic recoil of the chest to transiently decrease intrathoracic pressures and thereby promote venous blood return to the heart. To further enhance the negative during the "relaxation" phase of CPR, we intrathoracic pressures tested the hypothesis that intermittent impedance to inspiratory gases increases coronary perfusion pressures and vital during standard CPR organ perfusion. METHODS: CPR was performed with a pneumatically driven automated device in a porcine model of ventricular fibrillation. Eight pigs were randomized to initially receive standard CPR alone, while seven pigs plus intermittent impedance to standard CPR received initially inspiratory gas exchange with a threshold valve set to -40 cm H2O. The ratio was 5:1 and the compression rate was compression: ventilation 80/min. At 7-min intervals the impedance threshold valve (ITV) was either added or removed from the ventilation circuit such that during the 28 min CPR , each animal received two 7-min periods of CPR with the ITV and two 7-min periods without the valve . RESULTS: Vital organ blood flow was significantly higher during CPR performed with the ITV than during CPR valve . Total left ventricular blood flow performed without the (mean+/-SEM) (mL/min/g) was 0.32+/-0.04...

... vital organ blood flow and coronary perfusion pressure. CONCLUSIONS: Intermittent impedance to inspiratory flow of respiratory gases during standard CPR significantly improves CPR efficiency during ventricular fibrillation. These studies underscore the importance of lowering intrathoracic pressures during the relaxation phase of CPR.

Descriptors: Cardiopulmonary Resuscitation --methods--MT; \*Ventricular Fibrillation--therapy--TH; Animals; Biomechanics; Cardiopulmonary Resuscitation --instrumentation--IS; Coronary Circulation; Evaluation Studies; Heart Arrest--physiopathology--PP; Heart Arrest--therapy--TH; Pressure...

7/3,K/2 (Item 2 from file: 155)

DIALOG(R) File 155: MEDLINE(R)

<sup>(</sup>c) format only 2004 The Dialog Corp. All rts. reserv.

PMID: 9420954 13726764 Recent advances in mechanical methods of cardiopulmonary resuscitation .

Lurie K G Cardiac Arrhythmia Center, University of Minnesota, Minneapolis, USA. Acta anaesthesiologica Scandinavica. Supplementum (DENMARK)

Journal Code: 0370271 111 p49-52, ISSN 0515-2720

Document type: Journal Article

Languages: ENGLISH Main Citation Owner: NLM Record type: Completed

Recent advances in mechanical methods of cardiopulmonary resuscitation .

Lurie K G 1997 ,

CPR techniques and devices have been developed and tested Several new since the first report of manual closed-chested cardiopulmonary resuscitation ( CPR ) nearly four decades ago. These devices and techniques include vest CPR, interposed abdominal counterpulation CPR, active compression-decompression CPR , an impedance threshold valve , intra-aortic balloon pump and phased thoracic-abdominal counterpulsation. Many of these new mechanical advances...

--methods--MT; Abdomen Resuscitation Descriptors: Cardiopulmonary Circulation; Blood Pressure; Cardiopulmonary --physiology--PH; Blood Resuscitation --instrumentation--IS; Counterpulsation--instrumentation--IS ; Counterpulsation--methods--MT; Equipment Design; Heart Arrest--therapy --TH; Inhalation...

(Item 3 from file: 155) 7/3, K/3

DIALOG(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

12545842 PMID: 7882467

Improving active compression-decompression cardiopulmonary resuscitation with an inspiratory impedance valve .

Lurie K G; Coffeen P; Shultz J; McKnite S; Detloff B; Mulligan K Cardiac Arrhythmia Center, University of Minnesota, Minneapolis. Circulation (UNITED STATES) Mar 15 1995 , 91 (6) p1629-32, ISSN

Journal Code: 0147763 0009-7322 Document type: Journal Article

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

Improving active compression-decompression cardiopulmonary resuscitation with an inspiratory impedance valve .

Lurie K G; Coffeen P; Shultz J; McKnite S; Detloff B; Mulligan K

Mar 15 1995,

(ACD) cardiopulmonary compression-decompression Active BACKGROUND: ( CPR ) has recently been demonstrated to provide resuscitation significantly more blood flow to vital organs during cardiac...

... the hypothesis that intermittent impedance to inspiratory gas exchange during the decompression phase of ACD CPR enhances vital organ blood flow. METHODS AND RESULTS: ACD CPR was performed with a pneumatically driven automated compression-decompression device in a porcine model of ventricular fibrillation (VF). Nine pigs were randomized to receive ACD CPR alone, while 8 pigs received ACD CPR plus intermittent impedance to

inspiratory gas exchange with a threshold valve set to 40 cm H2O. Results comparing 2 minutes of ACD CPR alone versus ACD CPR with the inspiratory impedance threshold valve (ITV) revealed significantly higher mean (+/- SEM) coronary perfusion pressures (diastolic aortic minus diastolic right atrial pressures) in the ITV (31.0 + /- 2.3 mm Hg) group versus with ACD CPR alone (21 + /- 3.6 mm Hg) (P < .05). Total left ventricular and cerebral blood flows...

 $\dots$  +/- 0.095 and 0.47 +/- 0.06 mL/min per gram, respectively, with ACD plus the ITV versus 0.45 +/- 0.1 and 0.32 +/- 0.016 mL/min per gram, respectively, with ACD CPR alone (P < .05). Similar improvements in the ITV group were observed after 7 minutes of ACD CPR . After 16 minutes of VF and  $\overline{13}$  minutes of ACD  $\overline{\text{CPR}}$  , 6 of 8 pigs in the ITV group were successfully resuscitated with less than three successive 150-J shocks, whereas only 2 of 9 pigs with ACD CPR alone were resuscitated with equivalent energy levels (P < .02). With up to three additional and successive 200-J shocks, all pigs in the ITV group and 7 of 9 pigs with ACD alone were resuscitated (P = .18). CONCLUSIONS: Intermittent impedance to inspiratory flow of respiratory gases during ACD CPR significantly improves coronary perfusion pressures and vital organ blood flow and lowers defibrillation energy requirements...

Descriptors: Cardiopulmonary Resuscitation --methods--MT; \*Heart Arrest --therapy--TH; Animals; Cardiopulmonary Resuscitation --instrumentation Arrest--etiology--ET; Heart Arrest--physiopathology--PP; Heart Pulmonary Gas Exchange; Regional Blood Flow; Swine; Ventilation -Perfusion Fibrillation--complications--CO; Ventricular

Fibrillation--physiopathology--PP

(Item 4 from file: 155) 7/3,K/4

DIALOG(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

PMID: 12682493

Feasibility and effects of transcutaneous phrenic nerve stimulation combined with an inspiratory impedance threshold in a pig model of hemorrhagic shock.

Samniah Nemer; Voelckel Wolfgang G; Zielinski Todd M; McKnite Scott;

Patterson Robert; Benditt David G; Lurie Keith G

Cardiac Arrhythmia Center, Department of Medicine/Cardiovascular Division, University of Minnesota Medical School, MMC 508, AHC, 420 Delaware Street SE, Minneapolis, MN 55455, USA.

Apr 2003 , 31 (4) p1197-202, Critical care medicine (United States) Journal Code: 0355501 ISSN 0090-3493

Document type: Journal Article

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

Samniah Nemer; Voelckel Wolfgang G; Zielinski Todd M ; McKnite Scott; Patterson Robert; Benditt David G; Lurie Keith G

Apr 2003,

... rate of ten per minute while the airway was intermittently occluded with an inspiratory threshold valve between positive ventilations . Hemodynamic variables were monitored for 30 mins. MEASUREMENTS AND MAIN RESULTS: Phrenic nerve stimulation in combination with the inspiratory threshold valve significantly (p < .001) improved right and left ventricular diameter compared with hypovolemic shock values by...

... 5% and 20 +/- 2.5%, respectively. Moreover, phrenic nerve stimulation together with the inspiratory threshold **valve** also increased transacrtic, transpulmonary, and transmitral **valve** blood flow by 48 +/- 6.6%, 67 +/- 13.3, and 43 +/- 8.2%, respectively (p...

... Hg, respectively). CONCLUSIONS: This feasibility study suggests that phrenic nerve stimulation with the inspiratory threshold **valve** may improve cardiac preload and, subsequently, key hemodynamic variables in porcine model of severe hemorrhagic...

Descriptors: Cardiopulmonary Resuscitation --instrumentation--IS; \*Phrenic Nerve; \*Shock, Hemorrhagic--therapy--TH; \*Transcutaneous Electric Nerve Stimulation; Animals; Combined Modality Therapy; Echocardiography, Transesophageal; Feasibility Studies; Hemodynamic Processes; Respiratory Mechanics; Shock, Hemorrhagic--physiopathology--PP; Swine

7/3,K/5 (Item 5 from file: 155)

DIALOG(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

12215199 PMID: 12556262

Evaluation of a prototypic inspiratory impedance threshold valve designed to enhance the efficiency of cardiopulmonary resuscitation .

Lurie Keith G; Barnes Thomas A; Zielinski Todd M; McKnite Scott H

Lurie Keith G; Barnes Thomas A; Zielinski Todd M; McKnite Scott H Cardiac Arrhythmia Center, Cardiovascular Division, Department of Medicine, University of Minnesota Medical School, Minneapolis 55455, USA. lurie002@tc.umn.edu.

Respiratory care (United States) Jan 2003 , 48 (1) p52-7, ISSN 1020-1324 Journal Code: 7510357

0020-1324 Journal Code: 7510357 Document type: Journal Article

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

Evaluation of a prototypic inspiratory impedance threshold valve designed to enhance the efficiency of cardiopulmonary resuscitation .

Lurie Keith G; Barnes Thomas A; Zielinski Todd M; McKnite Scott H

Jan 2003,

OBJECTIVE: Assess a prototype inspiratory impedance threshold valve (ITV) designed to enhance vital organ circulation during standard and active compression/decompression cardiopulmonary resuscitation (CPR). BACKGROUND: The ITV attaches to commonly used airway assist devices and decreases intrathoracic pressure during the decompression (chest recoil) phase of CPR by creating a vacuum within the thorax, which increases venous blood flow to the heart...

... test was developed to determine the inspiratory impedance under various inspiratory flow conditions. RESULTS: The **valve** passed all minimum ASTM and ISO performance tests. During cardiac arrest in pigs the ITV...

... 2)O should be sufficient to decrease intrathoracic pressure during the decompression phase of standard CPR. Clinical studies are now underway.

Descriptors: Cardiopulmonary Resuscitation --instrumentation--IS;
Animals; Cardiopulmonary Resuscitation --methods--MT; Equipment Design;

Heart Arrest--therapy--TH; Swine

7/3,K/6 (Item 6 from file: 155)

DIALOG(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

12145454

Mechanical devices for cardiopulmonary resuscitation: an update.

Cardiac Arrhythmia Center, University of Minnesota, Box 508, 420 Delaware

Street SE, Minneapolis, MN 55455, USA. lurie002@tc.umn.edu Emergency medicine clinics of North America (United States)

20 (4) p771-84, ISSN 0733-8627 Journal Code: 8219565 Document type: Journal Article; Review; Review, Tutorial

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

Mechanical devices for cardiopulmonary resuscitation : an update. Lurie Keith

... technique correctly have limited its overall effectiveness. This has prompted the development of newer lifesaving CPR techniques and devices. compression-decompression, and the impedance threshold valve, offer a such as the benefit when compared with the Kouwenhoven technique. It is clear, however,

... in the Kouwenhoven technique. Americans spend nearly \$500,000,000 annually on this form of CPR training and retraining. Given the less than 5% survival rate for the 300,000 patients...

... benefits will be recognized and will lead to the adoption of more effective means to resuscitate patients.

Descriptors: Cardiopulmonary Resuscitation --instrumentation--IS

(Item 7 from file: 155) 7/3,K/7

DIALOG(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

Vasopressor response in a porcine model of hypothermic cardiac arrest is 12126281 compression-decompression

resuscitation using the inspiratory impedance threshold valve . Raedler Claus; Voelckel Wolfgang G; Wenzel Volker; Bahlmann Ludger; Baumeier Wolfgang; Schmittinger Christian A; Herff Holger; Krismer Anette C

; Lindner Karl H; Lurie Keith G Care Critical Leopold-Franzens-University, Innsbruck, Austria. claus.raedler@uibk.ac.at p1496-502, table of contents, ISSN 0003-2999 Journal Code: 1310650

Document type: Journal Article

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

... in a porcine model of hypothermic cardiac arrest is improved with active compression-decompression cardiopulmonary resuscitation using the

...Bahlmann Ludger; Baumeier Wolfgang; Schmittinger Christian A; Herff inspiratory impedance threshold valve. Holger; Krismer Anette C; Lindner Karl H; Lurie Keith G

active combination Dec 2002, a normothermic cardiac arrest, ( CPR ) resuscitation compression-decompression (ACD) cardiopulmonary with the inspiratory threshold valve (ITV) significantly improves vital

blood flow, but this technique has not been studied during hypothermic cardiac arrest. Accordingly, we evaluated the hemodynamic effects of ACD + ITV CPR before, and after, the administration of vasopressin in a porcine model of hypothermic cardiac arrest...

... After 10 min of untreated ventricular fibrillation, 14 animals were randomly assigned to either ACD CPR with the ITV (n = 7) or to standard CPR (n = 7). After 8 min of CPR, all animals received 0.4 U/kgvasopressin IV, and CPR was maintained for an additional 10 min in each group; defibrillation was attempted after 28 min of cardiac arrest, including 18 min of CPR . Before the administration of vasopressin, mean +/- SEM common carotid blood flow was significantly higher in the ACD + ITV CPR (67 +/- 13 versus 26 +/- 5 mL/min, respectively; P < 0.025). After vasopressin was given at minute 8 during CPR , mean +/- SEM coronary perfusion pressure was significantly higher in the ACD + ITV group, but did...

...seven animals in the ACD + ITV group versus none of seven animals in the group (not significant). During hypothermic cardiac arrest, ACD with the ITV improved common carotid blood flow compared with STD alone. Moreover, after the administration of vasopressin, coronary CPR perfusion pressure was significantly higher during ACD + ITV CPR , but not during STD CPR . IMPLICATIONS: New strategies are needed to improve the efficiency of cardiopulmonary resuscitation ( CPR ) in hypothermic cardiac arrest. Active compression-decompression CPR with the inspiratory improved carotid blood flow (and coronary perfusion threshold valve pressure with vasopressin) compared with standard CPR .

Descriptors: Cardiopulmonary Resuscitation --methods--MT; \*Heart Arrest, duced; \*Hemodynamic Processes--drug effects--DE; \*Vasopressins Induced; --pharmacology--PD

(Item 8 from file: 155) 7/3,K/8

DIALOG(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

PMID: 11975053 11789514

Bringing back the nearly dead. The hope and the challenge.

Cardiac Arrhythmia Center, University of Minnesota, USA. Minnesota medicine (United States) Apr 2002, 85 (4) p39-42,

0026-556X Journal Code: 8000173 Document type: Journal Article

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

Lurie Keith

Despite widespread use of cardiopulmonary resuscitation , sudden cardiac arrest outside of a hospital setting results in death most of the time. to improve resuscitation outcomes, University of Minnesota researchers have focused their efforts on understanding cardiopulmonary physiology and improving resuscitation technologies and procedures. This article describes new technologies, designed to be used in conjunction with CPR , that promote recovery from cardiac arrest. Active compression-decompression CPR , which involves use of a suction cup device to draw more blood into the heart...

... the lungs, has been shown to double 1-year survival rates. The

(ITV), when attached to an impedance threshold valve inspiratory endotracheal tube or face mask, has been shown to increase... Resuscitation --mortality--MO; \*Heart Descriptors: Cardiopulmonary Arrest--mortality--MO; Cardiopulmonary Resuscitation --instrumentation--IS ; Equipment Design; Minnesota; Survival Rate; Treatment Outcome

(Item 9 from file: 155) 7/3, K/9

DIALOG-(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

PMID: 11940794 11761267

Augmentation of ventricular preload during treatment of cardiovascular collapse and cardiac arrest.

Zielinski Todd ; Voelckel Wolfgang; McKnite Scott; Lurie Keith G ;

Department of Medicine, Cardiovascular Division, Cardiac Arrhythmia Center, University of Minnesota, Minneapolis, MN, USA. lurie002@tc.umn.edu Critical care medicine (United States) Apr **2002** , 30 Journal Code: 0355501 pS162-5, ISSN 0090-3493

Document type: Journal Article; Review; Review Literature

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

Lurie Keith G ; Zielinski Todd ; Voelckel Wolfgang; McKnite Scott; Plaisance Patrick

Apr 2002,

... heart during prolonged hypotension. This article describes the potential value of a new impedance threshold valve for the treatment of cardiac arrest and hypotension. The valve was designed to create a vacuum within the thorax during the decompression phase of cardiopulmonary or during inhalation. By transiently blocking inspiratory resuscitation decompression phase of cardiopulmonary , after phrenic nerve-stimulated gasping, or during the exchange gas spontaneous ventilation , the impedance- valve concept may have clinical value in the treatment of patients in cardiac arrest, hemorrhagic shock... Descriptors: Cardiopulmonary Resuscitation --instrumentation--IS; \*Heart Arrest--therapy--TH; \*Hypotension--therapy--TH; Animals; Cardiopulmonary Resuscitation --methods--MT; Shock--therapy--TH

\_\_\_\_ (Item 10 from file: 155) 7/3,K/10

DIALOG(R) File 155:MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

PMID: 11919340

11743363 cardiopulmonary compression-decompression active with the inspiratory threshold valve in a young porcine of Effects resuscitation model of cardiac arrest.

Lurie Keith G ; Sweeney Mike; McKnite Scott; Zielinski Todd; Lindstrom Paul; Peterson Colleen; Wenzel Volker; Lindner Voelckel Wolfgang G;

Karl H Center, Cardiovascular Division, Department of Arrhythmia Cardiac Minneapolis, Minnesota, Minnesota, University οf Medicine, wolfgang.voelckel@uibk.ac.at

Apr 2002 , 51 (4) p523-7, ISSN Pediatric research (United States)

Journal Code: 0100714 0031-3998 Document type: Journal Article

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

compression-decompression cardiopulmonary active with the inspiratory threshold valve in a young porcine οf Effects resuscitation model of cardiac arrest.

Lurie Keith G ; Sweeney Mike; McKnite Scott; Zielinski Todd; Lindstrom Paul; Peterson Colleen; Wenzel Volker; Lindner Voelckel Wolfgang G;

Active compression-decompression (ACD) cardiopulmonary resuscitation ( Apr 2002, CPR ) with the inspiratory threshold valve (ITV) has been recently recommended by the American Heart Association for treatment of adults in...

... been used in a pediatric population. Thus, this study was designed to evaluate ACD + ITV CPR in a young porcine model of cardiac arrest. After 10 min of ventricular fibrillation, and 8 min of standard CPR , ACD + ITV CPR was performed in seven 4- to 6-wk-old pigs (8-12 kg); defibrillation was attempted 8 min later. Within 2 min after initiation of ACD + ITV CPR , mean (+/- SEM) coronary perfusion pressure increased from 18 +/- 2 to 24+/- 3 mm Hg (p = 0.018). During standard versus ACD + ITV CPR , mean left ventricular myocardial and total cerebral blood flow was 59 +/- 21 versus 126 +/- 32...

... animals were successfully defibrillated, and survived >15 min. In conclusion, the combination of ACD + ITV CPR significantly increased both coronary perfusion pressure and vital organ blood flow after prolonged standard CPR in this young porcine model of ventricular fibrillation.

Descriptors: Cardiopulmonary Resuscitation ; \*Heart Arrest--therapy--TH ; Adult; Animals; Blood Circulation; Blood Gas Analysis; Blood Pressure; Resuscitation --instrumentation--IS; Cardiopulmonary Cardiopulmonary Resuscitation -- methods -- MT; Disease Models, Animal; Swine

(Item 11 from file: 155)

DIALOG(R)File 155:MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

PMID: 11772887

Use of an inspiratory impedance valve improves neurologically intact survival in a porcine model of ventricular fibrillation.

Lurie Keith G ; Zielinski Todd ; McKnite Scott; Aufderheide Tom;

Voelckel Wolfgang Cardiac

Arrhythmia Center, Department of Medicine, University of Minnesota, Minneapolis 55455, USA. klurie@resqcpr.com 2002 , 105 (1) p124-9, ISSN

Circulation (United States) Jan 1 Journal Code: 0147763 1524-4539

Contract/Grant No.: 1R43-HL-65851; HL; NHLBI

Document type: Journal Article

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

Use of an inspiratory impedance valve improves neurologically intact survival in a porcine model of ventricular fibrillation.

Lurie Keith G ; Zielinski Todd ; McKnite Scott; Aufderheide Tom; Voelckel Wolfgang

BACKGROUND: This study evaluated the potential for an inspiratory Jan 1 2002, threshold valve (ITV) to improve 24-hour survival and impedance

neurological function in a pig model of cardiac...

... neurological function. After 6 minutes of ventricular fibrillation (VF), followed by 6 minutes of cardiopulmonary resuscitation (CPR) with either a sham or an active valve, anesthetized pigs received 3 sequential 200-J shocks. If VF persisted, they received epinephrine (0.045 mg/kg), 90 seconds of CPR, and 3 more 200-J shocks. A total of 11 of 20 pigs (55%) in the sham versus 17 of 20 (85%) in the active valve group survived for -24 hours (P<0.05). Neurological scores were significantly higher with the valve ; the cerebral performance score (1=normal, 5=brain death) was 2.2+/-0.2 with the sham ITV versus 1.4+/-0.2 with the active valve (P<0.05). A total of 1 of 11 in the sham versus 12 of 17 in the active group had completely normal neurological function (P<0.05). Peak end-tidal CO2 (PETCO2) values were significantly higher with the active valve (20.4+/-1.0) than the sham (16.8+/-1.5) (P<0.05). PETCO2...

 $\dots$  correlated with increased survival (P<0.05). CONCLUSIONS: Use of a ITV during standard CPR significantly improved 24-hour survival rates and neurological recovery. PETCO2 and systolic blood pressure were also significantly higher in the active valve group. These data support further evaluation of ITV during standard CPR .

Resuscitation --instrumentation--IS; Cardiopulmonary \*Nervous System--physiopathology--PP; \*Ventricular Fibrillation--therapy --TH...; mortality--MO; Heart Arrest--physiopathology--PP; Heart Arrest Hemodynamic Processes; Oxygen--blood--BL; Respiratory Mechanics; Swine; Treatment Outcome; Ventricular Fibrillation--mortality --therapy--TH; --MO; Ventricular Fibrillation--physiopathology--PP

(Item 12 from file: 155) 7/3,K/12

DIALOG(R)File 155:MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

PMID: 11524335 11427221

Improving standard cardiopulmonary resuscitation with an inspiratory impedance threshold valve in a porcine model of cardiac arrest.

Lurie K G ; Voelckel W G; Zielinski T ; McKnite S; Lindstrom P;

Peterson C; Wenzel V; Lindner K H; Samniah N; Benditt D

Department of Medicine, Cardiovascular Division, Cardiac Arrhythmia enter, University of Minnesota, Minneapolis 55455, USA. Center,

lurie002@tc.umn.edu

Sep 2001, 93 (3) p649-55, Anesthesia and analgesia (United States) Journal Code: 1310650 ISSN 0003-2999

Document type: Journal Article

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

Improving standard cardiopulmonary resuscitation with an inspiratory impedance threshold valve in a porcine model of cardiac arrest.

Lurie K G ; Voelckel W G; Zielinski T ; McKnite S; Lindstrom P; Peterson C; Wenzel V; Lindner K H; Samniah N; Benditt

Sep 2001, the efficiency of standard cardiopulmonary resuscitation ( ), we evaluated the potential value of impeding respiratory gas To improve exchange selectively during the decompression phase of standard CPR in a porcine model of ventricular fibrillation. After 6 min of untreated cardiac arrest, anesthetized farm pigs weighing 30 kg were randomized to be treated with either standard CPR with a sham valve (n = 11) or standard CPR plus a functional inspiratory impedance threshold valve (ITV(TM)) (n =

- 11). Coronary perfusion pressure (CPP) (diastolic aortic minus right atrial pressure) was...
- ... primary endpoint. Vital organ blood flow was assessed with radiolabeled microspheres after 6 min of  $\dot{\text{CPR}}$  , and defibrillation was attempted 11 min after starting  $\mbox{CPR}$  . After 2 min of  $\mbox{CPR}$  , mean +/- SEM CPP was 14 +/- 2 mm Hg with the sham valve versus 20 +/- 2 mm Hg in the ITV group (P < 0.006). Significantly higher CPPs were maintained throughout the study when the\_ ITV was used. After 6 min of CPR , mean +/- SEM left ventricular and global cerebral blood flows were 0.10 +/- 0.03 and...

... of 11 in the ITV group (not significant). In conclusion, use of an inspiratory impedance valve during standard CPR resulted in a marked increase in CPP and vital organ blood flow after 6 min...

Descriptors: Cardiopulmonary Resuscitation -- instrumentation -- IS; \*Heart Arrest--therapy--TH; \* Respiration , Artificial--instrumentation--IS; Animals; Blood Gas Analysis; Hemodynamic Processes--physiology--PH; Regional Blood Flow--physiology--PH; Respiratory Mechanics--physiology --PH; Swine

(Item 13 from file: 155) 7/3,K/13

DIALOG(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

PMID: 11436523 11347587

Mechanical advances in cardiopulmonary resuscitation .

Lurie K ; Plaisance P; Sukhum P; Soleil C

Arrhythmia Center, Cardiovascular Division, Department of Medicine, University of Minnesota Medical School, Box 508, UM-AHC, 420 Delaware Street SE, Minneapolis, MN 55455, USA. lurie002@tc.umn.edu

Jun **2001** , 7 (3) Current opinion in critical care (United States) p170-5, ISSN 1070-5295 Journal Code: 9504454

Document type: Journal Article; Review; Review, Tutorial

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

Mechanical advances in cardiopulmonary resuscitation .

Lurie K ; Plaisance P; Sukhum P; Soleil C

Jun 2001,

... high mortality rates for patients in cardiac arrest, the American Heart Association and the European Resuscitation Council developed a new set of guidelines in 2000 to help advance several new and promising cardiopulmonary resuscitation ( CPR ) techniques and devices. This is the first time these organizations have taken such a bold...

... standard closed-chest cardiac massage. The new techniques, interposed abdominal counterpulsation and active compression decompression CPR , each provide greater blood flow to the vital organs in animal models of CPR and lead to higher blood pressures in patients in cardiac arrest. In some clinical studies...

...have resulted in a significant increase in survival after cardiac arrest in comparison with standard CPR . Three of the four new CPR devices that were recommended in the new guidelines also provide superior vital organ blood flow and increased blood pressures in comparison with standard CPR . that improve the efficiency of CPR three devices circumferential vest, an active compression decompression CPR device, and valve used in combination with the active an inspiratory impedance CPR device. The fourth device type, one that compression decompression

compresses the thorax using an automated mechanical piston compression mechanism, was recommended to reduce the number of personnel required to CPR . However, no studies on the automated mechanical compression devices have showed an improvement in hemodynamic variables or survival in comparison with standard CPR . Taken together, these new technologies represent an important step forward in the evolution of CPR from a pair of hands to devices designed to enhance CPR efficiency. Each of these advances is described, and the recent literature about each of them...

Descriptors: Cardiopulmonary Resuscitation --instrumentation--IS; ardiopulmonary Resuscitation --methods--MT; Cardiopulmonary Cardiopulmonary Resuscitation --trends--TD; Efficiency; Equipment Design; Guidelines; United States

(Item 14 from file: 155) 7/3, K/14

DIALOG(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

PMID: 11273935 11233374

The effects of positive end-expiratory pressure during active with the decompression cardiopulmonary resuscitation inspiratory threshold valve .

Voelckel W G; Lurie K G; Zielinski T; McKnite S; Plaisance P; Wenzel

V; Lindner K H

Arrhythmia Center, Cardiovascular Division, Department of Cardiac Medicine, University of Minnesota, Minneapolis 55455, USA.

Anesthesia and analgesia (United States) Apr 2001, 92 (4) p967-74,

ISSN 0003-2999 Journal Code: 1310650

Document type: Journal Article

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

pressure during active positive end-expiratory The effects of resuscitation with the cardiopulmonary decompression compression inspiratory threshold valve .

Voelckel W G; Lurie K G; Zielinski T; McKnite S; Plaisance P; Wenzel V; Lindner K H

Apr 2001,

The use of an inspiratory impedance threshold valve (ITV) during active compression-decompression (ACD) cardiopulmonary resuscitation (CPR) improves perfusion pressures, and vital organ blood flow. We evaluated the effects of positive end-expiratory pressure ( PEEP ) on gas exchange, and coronary perfusion pressure gradients during ACD + ITV CPR in a porcine cardiac arrest model. All animals received pure oxygen intermittent ventilation (IPPV) at a 5:1 compressionpressure positive ratio during ACD + ITV CPR . After 8 min, pigs were ventilation randomized to further IPPV alone (n = 8), or IPPV with increasing levels of **PEEP** (n = 8) of 2.5, 5.0, 7.5, and 10 cm H(2)0...

...pressure decreased in the IPPV group from 150 +/- 30 at baseline after 8  $\,$ min of CPR to 110 +/- 25 torr at 24 min, but increased in the PEEP group from 115 +/- 15 to 170 +/- 25 torr with increasing levels of PEEP  $(\tilde{P} < 0.02$  for comparisons within groups). Mean +/- SEM diastolic aortic minus diastolic left ventricular pressure gradient was significantly (P < 0.001) higher after the administration of PEEP (24 +/- 0 vs 17 +/- 1 mm Hg with 5 cm H(2)O of PEEP, and 26 +/- 0 vs 17 +/- 1 mm Hg with 10 cm H(2)O of PEEP), whereas the diastolic aortic minus right atrial pressure gradient (coronary perfusion pressure) was comparable between...

... aortic pressures were significantly (P < 0.05) higher with 10 cm H(2)0 when compared with IPPV alone (68 +/- 0 vs 59 +/- 2 mm Hg). In of CPR was performed with devices designed to improve conclusion, when venous return to the chest, increasing PEEP levels improved oxygenation. significantly increased the diastolic aortic minus left PEEP ventricular gradient and did not affect the decompression phase aortic minus right atrial pressure gradient. These data suggest that  ${\tt PEEP}$  reduces alveolar collapse during ACD + ITV  ${\tt CPR}$ , thus leading to an increase in indirect myocardial compression. IMPLICATIONS: Inspiratory active compression-decompression cardiopulmonary during improves perfusion pressures, and vital organ blood flow resuscitation during cardiac arrest. Increasing levels of positive end-expiratory during performance of active compression-decompression pressure resuscitation with an inspiratory impedance cardiopulmonary improves oxygenation, and increases the diastolic aortic-left ventricular pressure gradient and systolic arterial blood...

Descriptors: Cardiopulmonary Resuscitation --instrumentation--IS; \*Decompression--instrumentation--IS; \* Positive - Pressure Respiration

--instrumentation--IS

7/3,K/15 (Item 15 from file: 155)

DIALOG(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

11064292 PMID: 11098948

Improving the efficiency of cardiopulmonary resuscitation with an inspiratory impedance threshold valve.

Lurie K ; Zielinski T ; McKnite S; Sukhum P

Cardiac Arrhythmia Center, Cardiovascular Division, University of Minnesota, Minneapolis, USA. lurie@newcpr.com

Critical care medicine (UNITED STATES) Nov 2000 , 28 (11 Suppl) pN207-9, ISSN 0090-3493 Journal Code: 0355501

Document type: Journal Article

Languages: ENGLISH
Main Citation Owner: NLM
Record type: Completed

Improving the efficiency of cardiopulmonary resuscitation with an inspiratory impedance threshold valve .

Lurie K ; Zielinski T ; McKnite S; Sukhum P

Nov 2000,

In an effort to improve the efficiency of cardiopulmonary resuscitation ( CPR ), a new inspiratory impedance threshold valve has been developed to enhance the return of blood to the thorax during the chest decompression phase. This new device enhances negative intrathoracic pressure during chest wall recoil or the decompression phase, leading to improved vital CPR and active standard perfusion during both organ compression-decompression  $\mathsf{CPR}$  . With active compression-decompression  $\mathsf{CPR}$ addition of the impedance threshold valve results in sustained diastolic pressures of >55 mm Hg in patients in cardiac arrest. The new shows promise for patients in asystole or shock refractory ventricular fibrillation, when enhanced return of ...

...chest is needed to "prime the pump." The potential long-term benefits of this new valve remain under study.

Descriptors: Airway Resistance; \*Cardiopulmonary Resuscitation -- instrumentation--IS

(Item 16 from file: 155)

DIALOG(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

10709944 PMID: 10825624

Use of an inspiratory impedance threshold valve during cardiopulmonary resuscitation : a progress report.

Lurie K ; Voelckel W; Plaisance P; Zielinski T ; McKnite S; Kor D;

Sugiyama A; Sukhum P Cardiac Arrhythmia Center, Cardiovascular Division, University of Minnesota, Minneapolis 55455, USA. lurie002@tc.umn.edu

May 2000 , 44 (3) p219-30, ISSN 0300-9572 Resuscitation (IRELAND) Journal Code: 0332173

Document type: Journal Article; Review; Review, Tutorial

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

Use of an inspiratory impedance threshold valve during cardiopulmonary resuscitation : a progress report.

Lurie K ; Voelckel W; Plaisance P; Zielinski T ; McKnite S; Kor D; Sugiyama A; Sukhum P

May 2000 ,

active studies the mechanism οf Building on compression-decompression (ACD) cardiopulmonary resuscitation , a new inspiratory impedance threshold valve has been developed to enhance the return of blood to the thorax during the decompression phase of CPR . Use of this device results in a greater negative intrathoracic pressure during chest wall decompression. This leads to improved vital organ perfusion during both standard and ACD CPR . Animal and human studies suggest that this simple device increases cardiopulmonary circulation by harnessing more efficiently the kinetic energy of the outward movement of the chest wall during standard CPR or active chest wall decompression. When used in conjunction with ACD CPR during clinical evaluation, addition of the impedance valve resulted in sustained systolic pressures of greater than 100 mmHg and diastolic pressures of greater than 55 mmHg. The new valve may be beneficial in patients in asystole or shock refractory ventricular fibrillation, when enhanced return...

...chest is needed to 'prime the pump'. The potential long-term benefits of this new valve remain under investigation.

Airway Resistance; \*Cardiopulmonary Descriptors: --instrumentation--IS

(Item 17 from file: 155) 7/3,K/17

DIALOG(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

10598623 PMID: 10704165

during Inspiratory impedance active compression-decompression cardiopulmonary resuscitation : a randomized evaluation in patients in cardiac arrest.

Plaisance P; Lurie K G; Payen D

Department of Anesthesiology and Critical Care, Lariboisiere University Hospital, Paris, France. plaisance#claranet.fr

2000 , 101 (9) p989-94, Circulation (UNITED STATES) Mar 7 Journal Code: 0147763

Document type: Clinical Trial; Journal Article; Randomized Controlled Trial

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

Inspiratory impedance during active compression-decompression cardiopulmonary resuscitation : a randomized evaluation in patients in cardiac arrest.

Plaisance P; Lurie K G; Payen D

Mar 7 2000,

BACKGROUND: Blood pressure is severely reduced in patients in cardiacarrest receiving standard cardiopulmonary resuscitation ( CPR ). Although improves acute hemodynamic active compression-decompression (ACD) CPR parameters, arterial pressures remain suboptimal with this technique. We CPR in patients with a new inspiratory threshold valve performed ACD (ITV) to determine whether lowering intrathoracic pressures during the would enhance venous blood return and "relaxation" phase of ACD CPR efficiency. METHODS AND RESULTS: This prospective, overall CPR randomized, blinded trial was performed in prehospital mobile intensive care units in Paris, France. Patients in nontraumatic cardiac arrest received ACD CPR plus the ITV or ACD CPR alone for 30 minutes during advanced cardiac life support. End tidal CO(2) (ETCO(2...

...13.1+/-0.9, 25.0+/-1.4, and 36.5+/-1.5 with ACD CPR alone versus 19.1+/-1.0, 43.3+/-1.6, and 56.4+/-1.7 with ACD plus valve (P<0.001 between groups). ROSC was observed in 2 of 10 patients with ACD CPR alone after 26.5+/-0.7 minutes versus 4 of 11 patients with ACD CPR plus ITV after 19.8+/-2.8 minutes (P<0.05 for time from intubation to ROSC). Conclusions-Use of an inspiratory resistance valve in patients in cardiac arrest receiving ACD CPR increases the efficiency of CPR, leading to diastolic arterial pressures of >50 mm Hg. The long-term benefits of this new CPR technology are under investigation.

Descriptors: Airway Resistance; \*Cardiopulmonary Resuscitation --methods --MT; \*Heart Arrest--physiopathology--PP; \*Heart Arrest--therapy--TH; \* Respiratory Physiology...; Blood Circulation; Blood Pressure; Carbon Dioxide; Differential Threshold; Double-Blind Method; Middle Aged;

Prospective Studies; Respiration; Tidal Volume

7/3,K/18 (Item 18 from file: 155)

DIALOG(R) File 155: MEDLINE(R)

(c) format only 2004 The Dialog Corp. All rts. reserv.

10521636 PMID: 10625164

Utilization of a model lung system to assess the effects of an inspiratory impedance threshold valve on the relationship between active decompression and intra-thoracic pressure.

Sugiyama A; Lurie K G; Maeda Y; Satoh Y; Imura M; Hashimoto K Department of Pharmacology, Yamanashi Medical University, Nakakoma-gun, Japan. atsushis@res.yamanashi-med.ac.jp

Resuscitation (IRELAND) Nov 1999, 42 (3) p231-4, ISSN 0300-9572

Journal Code: 0332173

Document type: Journal Article

Languages: ENGLISH

Main Citation Owner: NLM Record type: Completed

Utilization of a model lung system to assess the effects of an inspiratory impedance threshold valve on the relationship between active decompression and intra-thoracic pressure.

Sugiyama A; Lurie K G ; Maeda Y; Satoh Y; Imura M; Hashimoto K Nov 1999 ,

Use of an inspiratory impedance valve has recently been shown to increase the efficacy of standard and active compression-decompression cardiopulmonary resuscitation . We evaluated the effects of a prototypic valve on the relationship between the active decompression and impedance intra-thoracic pressure using a mechanical model lung system. Intermittent inspiratory flow of respiratory gases during the impedance to decompression phase of active compression-decompression cardiopulmonary resuscitation significantly decreased the intra-thoracic pressure, while was almost zero cm H2O during the cardiopulmonary cycle when the impedance threshold valve was not the pressure was resuscitation functioning. Thus, this mechanical model will help in evaluating the valve as well as in optimizing its function by simulating various forms of lung disease.

Descriptors: Cardiopulmonary Resuscitation --methods--MT; \*Lung --physiology--PH; Cardiopulmonary Resuscitation --instrumentation--IS; Models, Structural

7/3,K/19 (Item 1 from file: 5)
DIALOG(R)File 5:Biosis Previews(R)
(c) 2004 BIOSIS. All rts. reserv.

0014465073 BIOSIS NO.: 200300433792

Apparatus and methods for enhancing cardiopulmonary blood flow and ventilation

AUTHOR: Lurie Keith G (Reprint); Zielinski Todd M

JOURNAL: Official Gazette of the United States Patent and Trademark Office

Patents 1273 (2): Aug. 12, 2003 2003

MEDIUM: e-file

PATENT NUMBER: US 6604523 PATENT DATE GRANTED: August 12, 2003 20030812

PATENT CLASSIFICATION: 128-20524 PATENT ASSIGNEE: CPRX LLC

PATENT COUNTRY: USA

ISSN: 0098-1133 (ISSN print)

DOCUMENT TYPE: Patent RECORD TYPE: Abstract LANGUAGE: English

Apparatus and methods for enhancing cardiopulmonary blood flow and ventilation

AUTHOR: Lurie Keith G ...

... Zielinski Todd M 2003

...ABSTRACT: and devices for increasing cardiopulmonary circulation induced by chest compression and decompression when performing cardiopulmonary resuscitation are provided. According to one method, a pressure responsive inflow valve is coupled to a patient's airway. Chest compressions and chest decompressions are performed. During chest decompression the inflow valve prevents respiratory gases from entering the lungs until a certain negative intrathoracic pressure level is exceeded at which time the one inflow valve opens. In this way, the inflow valve assists in increasing the magnitude and duration of negative intrathoracic pressure during decompression to enhance the amount of blood flow into the heart and lungs. Further, the patient is supplied with a pressurized respiratory gas through the inflow valve when the inflow valve opens to ventilate the patient.

respiratory gas CHEMICALS & BIOCHEMICALS: ... METHODS & EQUIPMENT: cardiopulmonary resuscitation --... ...pressure responsive inflow valve --... ... ventilation enhancing apparatus... ... ventilation enhancing method 7/3,K/20 (Item 2 from file: 5) DIALOG(R) File 5:Biosis Previews(R) (c) 2004 BIOSIS. All rts. reserv. BIOSIS NO.: 200300079533 0014120814 Use of an impedance threshold valve to treat hemorrhagic shock in spontaneously breathing pigs. AUTHOR: Zielinski Todd M (Reprint); Lurie Keith G (Reprint); McKnite Scott H (Reprint); Raedler Claus; Idris Ahamed; Voelckel Wolfgang AUTHOR ADDRESS: Univ of Minnesota, Minneapolis, MN, USA\*\*USA JOURNAL: Circulation 106 (19 Supplement): pII.367 November 5, 2002 2002 MEDIUM: print CONFERENCE/MEETING: Abstracts from Scientific Sessions Chicago, IL, USA November 17-20, 2002; 20021117 SPONSOR: American Heart Association ISSN: 0009-7322 \_(ISSN print) DOCUMENT TYPE: Meeting; Meeting Abstract RECORD TYPE: Citation LANGUAGE: English Use of an impedance threshold valve to treat hemorrhagic shock in spontaneously breathing pigs. AUTHOR: Zielinski Todd M ... ... Lurie Keith G 2002 DESCRIPTORS: ...ORGANISMS: female, animal model, spontaneously breathing METHODS & EQUIPMENT: impedance threshold valve --(Item 3 from file: 5) 7/3,K/21 DIALOG(R) File 5:Biosis Previews(R) (c) 2004 BIOSIS. All rts. reserv. BIOSIS NO.: 200300078176 0014119457 Standard CPR versus active compression-decompression CPR with an impedance threshold valve in patients with out-of-hospital cardiac arrest. AUTHOR: Wolcke Benno B (Reprint); Mauer Dietmar K (Reprint); Schoefmann Mark F (Reprint); Teichmann Heinke (Reprint); Provo Terry A; Lindner Karl H; Dick Wolfgang F (Reprint); Lurie Keith G AUTHOR ADDRESS: Clin of Anaesthesiology, Johannes Gutenberg-University, Mainz, Germany\*\*Germany JOURNAL: Circulation 106 (19 Supplement): pII-538 November 5, 2002 2002 MEDIUM: print CONFERENCE/MEETING: Abstracts from Scientific Sessions Chicago, IL, USA November 17-20, 2002; 20021117 SPONSOR: American Heart Association ISSN: 0009-7322 (ISSN print) DOCUMENT TYPE: Meeting; Meeting Abstract

RECORD TYPE: Citation LANGUAGE: English

Standard CPR versus active compression-decompression CPR with an impedance threshold valve in patients with out-of-hospital cardiac

... AUTHOR: Lurie Keith G

2002

DESCRIPTORS:

METHODS & EQUIPMENT: cardiopulmonary pulmonary resuscitation { CPR }---

(Item 4 from file: 5) 7/3,K/22 DIALOG(R) File 5: Biosis Previews (R) (c) 2004 BIOSIS. All rts. reserv.

BIOSIS NO.: 200200477250 0013883739

Automatic variable positive expiratory pressure valve and methods AUTHOR: Lurie Keith G; Voelckel Wolfgang (Reprint); Zielinski Todd

AUTHOR ADDRESS: Telfs, Austria \*\* Austria

JOURNAL: Official Gazette of the United States Patent and Trademark Office

Patents 1260 (5): July 30, 2002 2002

MEDIUM: e-file

PATENT NUMBER: US 6425393 PATENT DATE GRANTED: July 30, 2002 20020730

PATENT CLASSIFICATION: 128-20024 PATENT ASSIGNEE: CPRX LLC

PATENT COUNTRY: USA ISSN: 0098-1133

DOCUMENT TYPE: Patent RECORD TYPE: Abstract LANGUAGE: English

Automatic variable positive expiratory pressure valve and methods AUTHOR: Lurie Keith G ...

# ... Zielinski Todd

2002

ABSTRACT: The invention provides exemplary methods and valves used to alter a person's breathing . In one method, an exit valve is interfaced with a person's airway. The exit valve is configured such that respiratory gases are prevented from exiting the person's lungs when the exit valve is closed and are permitted to exit the person's lungs when the exit valve is opened. The exit valve is configured to open when a valve actuating pressure is met or exceeded. In a further step, the valve actuating pressure is varied over time. DESCRIPTORS:

METHODS & EQUIPMENT: automatic variable positive expiratory pressure valve --...

... breathing altering methods

7/3,K/23 (Item 5 from file: 5) DIALOG(R) File 5:Biosis Previews(R) (c) 2004 BIOSIS. All rts. reserv.

BIOSIS NO.: 200200288555 0013695044

Comparison of an active versus sham impedance threshold valve on survival in patients receiving active compression decompression cardiopulmonary resuscitation for out-of-hospital cardiac arrest

AUTHOR: Plaisance P (Reprint); Lurie Keith; Ducros L; Soleil C; Payen D

AUTHOR ADDRESS: Lariboisiere Univ Hosp, Paris, France\*\*France JOURNAL: Circulation 104 (17 Supplement): pII.765 October 23, 2001 2001 MEDIUM: print CONFERENCE/MEETING: Scientific Sessions 2001 of the American Heart Association Anaheim, California, USA November 11-14, 2001; 20011111 SPONSOR: American Heart Association ISSN: 0009-7322 DOCUMENT TYPE: Meeting; Meeting Abstract RECORD TYPE: Citation LANGUAGE: English .\_\_\_\_\_ Comparison of an active versus sham impedance threshold valve on survival in patients receiving active compression decompression cardiopulmonary resuscitation for out-of-hospital cardiac arrest ... AUTHOR: Lurie Keith 2001 DESCRIPTORS: METHODS & EQUIPMENT: active compression decompression cardiopulmonary resuscitation --... ...active impedance threshold valve --... ...inspiratory impedance threshold valve --7/3,K/24 (Item 6 from file: 5) DIALOG(R) File 5: Biosis Previews(R) (c) 2004 BIOSIS. All rts. reserv. .0013495822 BIOSIS NO.: 200200089333 CPR device having valve for increasing the duration and magnitude of negative intrathoracic pressures AUTHOR: Lurie K G ; Sweeney M; Gold B AUTHOR ADDRESS: Minneapolis, Minn., USA\*\*USA JOURNAL: Official Gazette of the United States Patent and Trademark Office Patents 1205 (1): p101 Dec. 2, 1997 1997 MEDIUM: print PATENT NUMBER: US 5692498 PATENT DATE GRANTED: Dec. 2, 1997 19971202 PATENT CLASSIFICATION: 128-205.24 PATENT ASSIGNEE: CPRX, INC. PATENT COUNTRY: USA ISSN: 0098-1133 DOCUMENT TYPE: Patent RECORD TYPE: Citation LANGUAGE: English CPR device having valve for increasing the duration and magnitude of negative intrathoracic pressures AUTHOR: Lurie K G ... 1997 DESCRIPTORS: ...MAJOR CONCEPTS: Respiratory System... ... Respiration MISCELLANEOUS TERMS: CARDIOPULMONARY RESUSCITATION ; ... ... CPR ; ... ... VALVING SYSTEM

7/3,K/25 (Item 7 from file: 5)
DIALOG(R)File 5:Biosis Previews(R)
(c) 2004 BIOSIS. All rts. reserv.

0012809662 BIOSIS NO.: 200000527975

Apparatus and methods for assisting cardiopulmonary resuscitation AUTHOR: Lurie Keith G; Sweeney Michael (Reprint); Gold Barbara

AUTHOR ADDRESS: St. Paul, MN, USA\*\*USA

JOURNAL: Official Gazette of the United States Patent and Trademark Office

Patents 1234 (3): May 16, 2000 2000 ---

MEDIUM: e-file

PATENT NUMBER: US 6062219 PATENT DATE GRANTED: May 16, 2000 20000516

PATENT CLASSIFICATION: 128-20524 PATENT ASSIGNEE: CPRX LLC

PATENT COUNTRY: USA ISSN: 0098-1133

DOCUMENT TYPE: Patent RECORD TYPE: Abstract LANGUAGE: English

Apparatus and methods for assisting cardiopulmonary resuscitation

AUTHOR: Lurie Keith G ...

2000

- ...ABSTRACT: and devices for increasing cardiopulmonary circulation induced by chest compression and decompression when performing cardiopulmonary resuscitation are provided. Cardiopulmonary circulation is increased according to the invention by impeding airflow into a patient's lungs to enhance the extent and duration of negative intrathoracic pressure during decompression of the patient's chest. Enhanced extent and duration of negative of intrathoracic pressure thus promotes venous blood flow into the heart and lungs from the peripheral venous vasculature...
- ...one embodiment, impeding the airflow into the patient's lungs is accomplished by placing a ventilation tube in the patient's airway. The ventilation tube contains either a flow restrictive orifice disposed within or connected in series with a lumen of the ventilation tube, or a pressure-responsive valve within a lumen of the tube to impede the inflow of air. In a preferred...

  DESCRIPTORS:

...ORGANISMS: PARTS ETC: respiratory system

METHODS & EQUIPMENT: cardiopulmonary resuscitation { CPR }--

7/3,K/26 (Item 8 from file: 5)
DIALOG(R)File 5:Biosis Previews(R)
(c) 2004 BIOSIS. All rts. reserv.

0012672778 BIOSIS NO.: 200000391091

Heart failure mask and methods for increasing negative intrathoracic pressures

AUTHOR: Lurie Keith G (Reprint

AUTHOR ADDRESS: Minneapolis, MN, USA\*\*USA

JOURNAL: Official Gazette of the United States Patent and Trademark Office

Patents 1231 (5): Feb. 29, 2000 2000

MEDIUM: e-file

PATENT NUMBER: US 6029667 PATENT DATE GRANTED: February 29, 2000 20000229 PATENT CLASSIFICATION: 128-20716 PATENT ASSIGNEE: CPRX LLC, Minneapolis,

MN, USA PATENT COUNTRY: USA ISSN: 0098-1133

DOCUMENT TYPE: Patent

RECORD TYPE: Abstract LANGUAGE: English

Heart failure mask and methods for increasing negative intrathoracic pressures

AUTHOR: Lurie Keith G ...

2000

- ...ABSTRACT: around the patient's mouth and nose, with the mask including a one-way expiration valve and an inspiratory threshold valve. The ---- threshold valve is biased to open when a threshold pressure within the mask is in the range...
- ...3 cm H2 O to about -25 cm H2 O. With this arrangement, the patient breathes while the mask is sealed to the face, with the respiratory gasses being prevented from entering the patient's lungs during inhalation until the patient produces...
- ...3 cm H2 O to about -25 cm H2 O. At this point, the inspiratory valve opens to allow respiratory gasses into the lungs.

  DESCRIPTORS:
  - ...METHODS & EQUIPMENT: increasing  $\ensuremath{\text{negative}}$  intrathoracic  $\ensuremath{\text{pressures}}$  , therapeutic method

7/3,K/27 (Item 9 from file: 5)
DIALOG(R)File 5:Biosis Previews(R)
(c) 2004 BIOSIS. All rts. reserv.

0012299681 BIOSIS NO.: 200000017994

The pneumatic pump mechanism of cardiopulmonary resuscitation AUTHOR: Voelckel Wolfgang G (Reprint); Lurie Keith G (Reprint)

AUTHOR ADDRESS: Cardiac Arrhythmia Ctr, Univ of Minnesota, Minneapolis, MN, USA\*\*USA

JOURNAL: Circulation 100 (18 SUPPL.): pI.663 Nov. 2, 1999 1999

MEDIUM: print

CONFERENCE/MEETING: 72nd Scientific Sessions of the American Heart Association Atlanta, Georgia, USA November 7-10, 1999; 19991107

ISSN: 0009-7322

DOCUMENT TYPE: Meeting; Meeting Abstract

RECORD TYPE: Citation LANGUAGE: English

The pneumatic pump mechanism of cardiopulmonary resuscitation

... AUTHOR: Lurie Keith G

1999

DESCRIPTORS:

METHODS & EQUIPMENT: active compression-decompression cardiopulmonary resuscitation --...

...cardiopulmonary resuscitation --...

...inspiratory impedance threshold valve -MISCELLANEOUS TERMS: ... positive end expiratory pressure --

7/3,K/28 (Item 10 from file: 5)
DIALOG(R)File 5:Biosis Previews(R)
(c) 2004 BIOSIS. All rts. reserv.

0012252387 BIOSIS NO.: 199900512047

Improving active compression decompression cardiopulmonary resuscitation
 with an impedance threshold valve in patients in cardiac arrest
AUTHOR: Plaisance Patrick (Reprint); Payan Didier (Reprint); Lurie Keith G

AUTHOR ADDRESS: Lariboisiere Univ. Hosp., Paris, France\*\*France JOURNAL: Circulation 98 (17 SUPPL.): pI477 Oct. 27, 1998 1998

MEDIUM: print

CONFERENCE/MEETING: 71st Scientific Sessions of the American Heart Association Dallas, Texas, USA November 8-11, 1998; 19981108

SPONSOR: The American Heart Association - - -

ISSN: 0009-7322

DOCUMENT TYPE: Meeting; Meeting Abstract

RECORD TYPE: Citation LANGUAGE: English

Improving active compression decompression cardiopulmonary resuscitation with an impedance threshold valve in patients in cardiac arrest

...AUTHOR: Lurie Keith G

1998

DESCRIPTORS:

METHODS & EQUIPMENT: active compression decompression cardiopulmonary resuscitation --...

...impedance threshold valve --

7/3,K/29 (Item 11 from file: 5)
DIALOG(R)File 5:Biosis Previews(R)
(c) 2004 BIOSIS. All rts. reserv.

0011222963 BIOSIS NO.: 199800017210

Optimizing standard cardiopulmonary resuscitation with an inspiratory impedance threshold valve

AUTHOR: Mulligan Katherine A (Reprint); Lurie Keith G (Reprint); McKnite Scott H (Reprint); Detloff Barry L S (Reprint); Lindstrom Paul J (Reprint); Lindner Karl H

AUTHOR ADDRESS: Univ. Minn., Minneapolis, MN, USA\*\*USA JOURNAL: Circulation 96 (8 SUPPL.): pI365 10/21/97 1997

MEDIUM: print

CONFERENCE/MEETING: 70th Scientific Sessions of the American Heart Association Orlando, Florida, USA November 9-12, 1997; 19971109

ISSN: 0009-7322

DOCUMENT TYPE: Meeting; Meeting Abstract

RECORD TYPE: Citation LANGUAGE: English

Optimizing standard cardiopulmonary resuscitation with an inspiratory impedance threshold valve

... AUTHOR: Lurie Keith G

1997

DESCRIPTORS:

METHODS & EQUIPMENT: cardiopulmonary resuscitation --...

 $\ldots$  inspiratory impedance threshold  $\ \mathbf{valve}$  , therapeutic method

7/3,K/30 (Item 12 from file: 5)
DIALOG(R)File 5:Biosis Previews(R)
(c) 2004 BIOSIS. All rts. reserv.

0010118284 BIOSIS NO.: 199698586117

Optimizing cardiopulmonary resuscitation with an inspiratory threshold

AUTHOR: Lurie Keith G; Shultz Jeffery; Coffeen Paul; McKnite Katherine Mulligan Scot; Detloff Barry; Lugtu Carlos; Lindstrom Paul

AUTHOR ADDRESS: Univ. Minn., Minneapolis, MN, USA\*\*USA JOURNAL: Circulation 92 (8 SUPPL.): pI760 1995 1995

CONFERENCE/MEETING: 68th Scientific Session of the American Heart Association Anaheim, California, USA November 13-16, 1995; 19951113

ISSN: 0009-7322

DOCUMENT TYPE: Meeting; Meeting Abstract

RECORD TYPE: Citation LANGUAGE: English

Optimizing cardiopulmonary resuscitation with an inspiratory threshold

AUTHOR: Lurie Keith G ...

1995

DESCRIPTORS:

...MAJOR CONCEPTS: Respiratory System...

### ... Respiration

7/3, K/31(Item 13 from file: 5) DIALOG(R) File 5:Biosis Previews(R) (c) 2004 BIOSIS. All rts. reserv.

0009934868 BIOSIS NO.: 199598402701

Histopathological changes in the right ventricle and their relation to pulmonary haemodynamics in patients with mitral valve stenosis

AUTHOR: Zielinski Tomasz (Reprint); Wasiutynski Aleksander; Korewicki Jerzy; Rajecka Aldona; Pogorzelska Hanna; Fiejka Elzbieta; Kotlinski Zbigniew; Biederman Andrzej

AUTHOR ADDRESS: 2nd Dep. Valvular Heart Diseases, Inst. Cardiol., Alpejska str. 42, 04-628 Warsaw, Poland\*\*Poland

JOURNAL: Cor et Vasa 37 (2): p92-98 1995 1995

ISSN: 0010-8650

DOCUMENT TYPE: Article RECORD TYPE: Citation LANGUAGE: English

... changes in the right ventricle and their relation to pulmonary haemodynamics in patients with mitral valve stenosis

AUTHOR: Zielinski Tomasz ...

1995

DESCRIPTORS:

... MAJOR CONCEPTS: Respiratory System...

#### ... Respiration ;

7/3, K/32(Item 14 from file: 5) DIALOG(R) File 5:Biosis Previews(R) (c) 2004 BIOSIS. All rts. reserv.

0009817825 BIOSIS NO.: 199598285658

Prognostic significance of changes in the compliance of the pulmonary venous system after isosorbide dinitrate in patients with mitral stenosis AUTHOR: Pogorzelska Hanna (Reprint); Korewicki Jerzy; Zielinski Tomasz;

Rajecka Aldona; Biederman Andrzej

AUTHOR ADDRESS: 2nd Dep. Heart Valve Disease, Natl. Inst. Cardiol., ul.

Alpejska 42, 04-628 Warsaw, Poland\*\*Poland

JOURNAL: International Journal of Cardiology 49 (1): p9-15 1995 1995

ISSN: 0167-5273

DOCUMENT TYPE: Article RECORD TYPE: Abstract LANGUAGE: English

...ABSTRACT: severe pulmonary hypertension. This condition can also influence the clinical and hemodynamic outcome of mitral valve replacement (MVR). This study has been aimed at assessing whether changes in the pulmonary venous...

DESCRIPTORS:

...MAJOR CONCEPTS: Respiratory System...

#### ... Respiration

7/3,K/33 (Item 1 from file: 34)
DIALOG(R)File 34:SciSearch(R) Cited Ref Sci
(c) 2004 Inst for Sci Info. All rts. reserv.

12188616 Genuine Article#: 739JG No. References: 18

Title: Comparison of standard cardiopulmonary resuscitation versus the combination of active compression-decompression cardiopulmonary resuscitation and an inspiratory impedance threshold device for out-of-hospital cardiac arrest

Author(s): Wolcke BB; Mauer DK; Schoefmann MF; Teichmann H; Provo TA; Lindner KH; Dick WF; Aeppli D; Lurie KG (REPRINT)

Corporate Source: Box 508, UMHC, 420 Delaware St SE/Minneapolis//MN/55455 (REPRINT); Univ Mainz, Sch Med, Anesthesiol Clin, D-6500 Mainz//Germany/; Leopold Franzens Inst, Dept Anesthesia & Intens Care Med, Innsbruck//Austria/; Adv Circulatory Syst Inc, Eden Prairie//MN/; Univ Minnesota, Div Biostat, Minneapolis//MN/; Univ Minnesota, Sch Publ Hlth, Minneapolis//MN/; Univ Minnesota, Dept Emergency Med, Minneapolis//MN/; Hennepin Cty Med Ctr, Minneapolis//MN/55415

Journal: CIRCULATION, 2003 , V108, N18 (NOV 4), P2201-2205

ISSN: 0009-7322 Publication date: 20031104

Publisher: LIPPINCOTT WILLIAMS & WILKINS, 530 WALNUT ST, PHILADELPHIA, PA 19106-3621 USA

Language: English Document Type: ARTICLE (ABSTRACT AVAILABLE)

Title: Comparison of standard cardiopulmonary resuscitation versus the combination of active compression-decompression cardiopulmonary resuscitation and an inspiratory impedance threshold device for out-of-hospital cardiac arrest

...Author(s): BB; Mauer DK; Schoefmann MF; Teichmann H; Provo TA; Lindner KH; Dick WF; Aeppli D; Lurie KG (REPRINT)
, 2003

Abstract: Background-Active compression-decompression (ACD) CPR combined with an inspiratory impedance threshold device (ITD) improves vital organ blood flow during cardiac arrest. This study compared survival rates with ACD+ITD CPR versus standard manual CPR (S- CPR).

Methods and Results-A prospective, controlled trial was performed in Mainz, Germany, in which a...

- ...with out-of-hospital arrest of presumed cardiac pathogenesis were sequentially randomized to ACD+ITD CPR or S- CPR by the advanced life support team after intubation. Rescuers learned which method of CPR to use at the start of each work shift. The primary end point was 1-hour survival after a witnessed arrest. With ACD+ITD CPR (n=103), return of spontaneous circulation and 1- and 24-hour survival rates were 55%, 51%, and 37% versus 37%, 32%, and 22% with S- CPR (n=107) (P=0.016, 0.006, and 0.033, respectively). One- and 24-hour survival rates in witnessed arrests were 55% and 41% with ACD+ITD CPR versus 33% and 23% in control subjects (P=0.011 and 0.019), respectively. One
- ...patients with a witnessed arrest in ventricular fibrillation were 68% and 58% after ACD+ITD CPR versus 27% and 23% after S- CPR (P=0.002 and 0.009), respectively. Patients randomized greater than or equal to10 minutes after the call for help to the ACD+ITD CPR had a 3 times higher 1- hour survival rate than control subjects (P=0.002). Hospital discharge rates were 18% after ACD+ITD CPR versus 13% in control subjects (P=0.41). In witnessed arrests, overall neurological function trended higher with ACD+ITD CPR versus control subjects (P=0.07).

Conclusions-Compared with S- CPR, ACD+ITD CPR significantly improved short-term survival rates for patients with out-of-hospital cardiac arrest. Additional studies are needed to evaluate potential long-term benefits of ACD+ITD  $\ CPR$ .

...Identifiers--PORCINE MODEL; VENTRICULAR-FIBRILLATION; LIFE-SUPPORT; VALVE; HYPOTHERMIA; GUIDELINES; SURVIVAL

7/3,K/34 (Item 2 from file: 34)
DIALOG(R)File 34:SciSearch(R) Cited Ref Sci
(c) 2004 Inst for Sci Info. All rts. reserv.

10362478 Genuine Article#: 505PJ No. References: 0

Title: Measurement of intrathoracic pressures during basic and advanced cardiac life support while performing active compression decompression cardiopulmonary resuscitation with an inspiratory impedance threshold valve

Author(s): Plaisance P; Soleil C; Ducros L; Lurie K; Vicaut E; Payen D
Corporate Source: Lariboisiere Univ Hosp, Paris//France/; CPRx
 LLC, Minneapolis//MN/

Journal: CRITICAL CARE MEDICINE, 2001 , V29, N12,S (DEC), PA73-A73

ISSN: 0090-3493 Publication date: 20011200

Publisher: LIPPINCOTT WILLIAMS & WILKINS, 530 WALNUT ST, PHILADELPHIA, PA 19106-3621 USA

Language: English Document Type: MEETING ABSTRACT

...Title: intrathoracic pressures during basic and advanced cardiac life support while performing active compression decompression cardiopulmonary resuscitation with an inspiratory impedance threshold valve

Author(s): Plaisance P; Soleil C; Ducros L; Lurie K; Vicaut E; Payen D, 2001

7/3,K/35 (Item 3 from file: 34)
DIALOG(R)File 34:SciSearch(R) Cited Ref Sci
(c) 2004 Inst for Sci Info. All rts. reserv.

Genuine Article#: 505PJ No. References: 0 Title: Use of an inspiratory impedance threshold valve for rapid treatment of cardiovascular collapse secondary to heart shock in spontaneously breathing pigs Author(s): Lurie K ; Zielinski T ; McKnite S Corporate Source: Univ Minnesota, Minneapolis//MN/55455 Journal: CRITICAL CARE MEDICINE, 2001 , V29, N12, S (DEC), PA55-A55 Publication date: 20011200 ISSN: 0090-3493 Publisher: LIPPINCOTT WILLIAMS & WILKINS, 530 WALNUT ST, PHILADELPHIA, PA -----1-91-06--3621 -USA-Language: English Document Type: MEETING ABSTRACT Title: Use of an inspiratory impedance threshold valve for rapid treatment of cardiovascular collapse secondary to heart shock in spontaneously breathing pigs Author(s): Lurie K ; Zielinski T ; McKnite S 2001

7/3,K/36 (Item 4 from file: 34) DIALOG(R)File 34:SciSearch(R) Cited Ref Sci (c) 2004 Inst for Sci Info. All rts. reserv. Genuine Article#: 505PJ No. References: 0 Title: Use of an inspiratory impedance threshold valve for the rapid treatment of hemorrhagic shock in spontaneously breathing pigs Author(s): Lurie K ; Zielinski T ; McKnite S Corporate Source: Univ Minnesota, Minneapolis//MN/55455 Journal: CRITICAL CARE MEDICINE, 2001, V29, N12,S (DEC), PA13-A13 ISSN: 0090-3493 Publication date: 20011200 Publisher: LIPPINCOTT WILLIAMS & WILKINS, 530 WALNUT ST, PHILADELPHIA, PA 19106-3621 USA Language: English Document Type: MEETING ABSTRACT

Title: Use of an inspiratory impedance threshold valve for the rapid treatment of hemorrhagic shock in spontaneously breathing pigs Author(s): Lurie K; Zielinski T; McKnite S, 2001

7/3,K/37 (Item 5 from file: 34)
DIALOG(R)File 34:SciSearch(R) Cited Ref Sci
(c) 2004 Inst for Sci Info. All rts. reserv.

09435208 Genuine Article#: 388ZD No. References: 0

Title: Active compression-decompression cardiopulmonary resuscitation with the inspiratory threshold valve: A new concept for pediatric resuscitation?

Author(s): Voelckel WG; Lurie KG; Sweeney M; McKnite S; Zielinski T; Lindstrom P; Peterson C; Wenzel V; Lindner KH

Corporate Source: Innsbruck Univ, A-6020 Innsbruck//Austria/; Univ Minnesota, Dept Med, Cardiac Arrhythmia Ctr, Minneapolis//MN/55455; Dept Anesthesiol, Minneapolis//MN/; Cardiac Arrhythmia Ctr, Minneapolis//MN/; Dept Anesthesiol & Intens Care Med, Innsbruck//Austria/

Journal: CRITICAL CARE MEDICINE, 2000, V28, N12,S (DEC), PA65-A65

ISSN: 0090-3493 Publication date: 20001200

Publisher: LIPPINCOTT WILLIAMS & WILKINS, 530 WALNUT ST, PHILADELPHIA, PA 19106-3621 USA

Language: English Document Type: MEETING ABSTRACT

Title: Active compression-decompression cardiopulmonary resuscitation with the inspiratory threshold valve : A new concept for pediatric resuscitation ?

Author(s): Voelckel WG; Lurie KG; Sweeney M; McKnite S; Zielinski T; Lindstrom P; Peterson C; Wenzel V; Lindner KH

7/3,K/38 (Item 6 from file: 34)

(c) 2004 Inst for Sci Info. All rts. reserv.

Genuine Article#: 367QE No. References: 0

Title: Improving standard CPR with an inspiratory impedance threshold valve

Author(s): Lurie KG; Voelckel WG; Zielinski TM; McKnite SH; Peterson C; Lindner KH; Benditt DG

Corporate Source: Univ Minnesota, Minneapolis//MN/; Leopold Franzens Univ, Innsbruck//Austria/

Journal: CIRCULATION, 2000 , V102, N18,S (OCT 31), P438-438

ISSN: 0009-7322 Publication date: 20001031

Publisher: LIPPINCOTT WILLIAMS & WILKINS, 530 WALNUT ST, PHILADELPHIA, PA 19106-3621 USA

Language: English Document Type: MEETING ABSTRACT

Title: Improving standard CPR with an inspiratory impedance threshold valve

Author(s): Lurie KG; Voelckel WG; Zielinski TM; McKnite SH; Peterson C; Lindner KH; Benditt DG

(Item 7 from file: 34) 7/3,K/39

DIALOG(R)File 34:SciSearch(R) Cited Ref Sci (c) 2004 Inst for Sci Info. All rts. reserv.

Genuine Article#: 276RX No. References: 0 08385952

Title: Effects of positive end expiratory pressure on oxygenation and coronary perfusion pressure during ACD CPR with the inspiratory threshold valve

Author(s): Voelckel WG; Lurie KG; Plaisance P; Krismer AC; Wenzel V Corporate Source: INNSBRUCK UNIV, /A-6020 INNSBRUCK//AUSTRIA/; UNIV MINNESOTA, /MINNEAPOLIS//MN/; LARIBOISIERE HOSP, /PARIS//FRANCE/

Journal: CRITICAL CARE MEDICINE, 1999, V27, N12,S (DEC), P25-25

ISSN: 0090-3493 Publication date: 19991200

Publisher: LIPPINCOTT WILLIAMS & WILKINS, 530 WALNUT ST, PHILADELPHIA, PA 19106-3621

Language: English Document Type: MEETING ABSTRACT

Title: Effects of positive end expiratory pressure on oxygenation and coronary perfusion pressure during ACD CPR with the inspiratory threshold valve

Author(s): Voelckel WG; Lurie KG; Plaisance P; Krismer AC; Wenzel V 1999

7/3,K/40 (Item 1 from file: 73) DIALOG(R)File 73:EMBASE

(c) 2004 Elsevier Science B.V. All rts. reserv.

11287826 EMBASE No: 2001302000

Improving standard cardiopulmonary resuscitation with an inspiratory impedance threshold valve in a porcine model of cardiac arrest

Voelckel K.G.; Lurie W. G.; Zielinski T.; McKnite S.; Lindstrom P.;

Peterson C.; Wenzel V.; Lindner K.H.; Samniah N.; Benditt D.

Dr. K.G. Voelckel, Dept. of Med./Cardiovascular Div., University of Minnesota Med. Sch., MMC 508, 420 Delaware St. SE, Minneapolis, MN 55455 United States

AUTHOR EMAIL: lurie002@tc.umn.edu

Anesthesia and Analgesia (ANESTH. ANALG.) (United-States) -- 2001, 93/3

CODEN: AACRA ISSN: 0003-2999 DOCUMENT TYPE: Journal ; Article

LANGUAGE: ENGLISH SUMMARY LANGUAGE: ENGLISH

NUMBER OF REFERENCES: 16

Improving standard cardiopulmonary resuscitation with an inspiratory
impedance threshold valve in a porcine model of cardiac arrest
 Voelckel K.G.; Lurie W. G.; Zielinski T.; McKnite S.; Lindstrom P.;
Peterson C.; Wenzel V.; Lindner K.H.; Samniah N.; Benditt...

To improve the efficiency of standard cardiopulmonary resuscitation (  $\mathtt{CPR}$  ), we evaluated the potential value of impeding respiratory gas exchange selectively during the decompression phase of standard  $\mathtt{CPR}$  in a porcine model of ventricular fibrillation. After 6 min of untreated cardiac arrest, anesthetized farm pigs weighing 30 kg were randomized to be treated with either standard  $\mathtt{CPR}$  with asham  $\mathtt{valve}$  (n = 11) or standard  $\mathtt{CPR}$  plus a functional inspiratory impedance threshold  $\mathtt{valve}$  (ITV(TM)) (n = 11).Coronary perfusion pressure (CPP) (diastolic aortic mius right atrial pressure) was...

...primary endpoint. Vital organ blood flow was assessed with radiolabeled microspheres after 6 min of CPR , and defibrillation was attempted 11 min after starting CPR . After 2 min of CPR , mean +/- SEM CPP was 14 +/- 2 mm Hg with the sham valve versus 20 +/- 2 mm Hg in the ITV group (P < 0.006). Significantly higher CPPs were maintained throughout the study when the ITV was used. After 6 min of CPR , mean +/-SEM left ventricular and global cerebral blood flows were 0.10 +/- 0.03 and...

...of 11 in the ITV group (not significant). In conclusion, use of an inspiratory impedance **valve** during standard **CPR** resulted in a marked increase in CPP and vital organ blood flow after 6 min...

\*heart arrest--therapy--th; \* resuscitation

...gas exchange; heart ventricle fibrillation--therapy--th; coronary artery blood flow; defibrillation; treatment outcome; heart valve; nonhuman; female; animal experiment; animal model; controlled study; article; priority journal 2001

7/3,K/41 (Item 2 from file: 73)
DIALOG(R)File 73:EMBASE

(c) 2004 Elsevier Science B.V. All rts. reserv.

10915459 EMBASE No: 2000412772

Recent advances in active compression-decompression cardiopulmonary resuscitation

Sukhum P.; Voelckel W.; Lurie K.G.

Dr. K.G. Lurie, AHC, 420 Delaware St. SE, Minneapolis, MN 55455 United

States

Bailliere's Best Practice and Research in Clinical Anaesthesiology (BAILLIERE'S BEST PRACT. RES. CLIN. ANAESTHESIOL.) (United Kingdom) 2000

CODEN: BBPAF ISSN: 1521-6896 DOCUMENT TYPE: Journal; Review

LANGUAGE: ENGLISH SUMMARY LANGUAGE: ENGLISH

NUMBER OF REFERENCES: 26

Recent advances in active compression-decompression cardiopulmonary resuscitation

Sukhum P.; Voelckel W.; Lurie K.G.

...methods and devices have been developed to enhance the efficiency and efficacy of standard cardiopulmonary resuscitation ( CPR ). One new approach, active compression-decompression (ACD) CPR was developed to lower the intrathoracic pressure during the decompression phase of CPR , thereby enhancing venous blood return to the thorax. Over the past decade the ACD CPR device has been extensively evaluated in animals and humans. ACD CPR is the only new approach for improving CPR efficacy with a mechanical device that has achieved clinical relevance. More recently, an inspiratory impedance threshold valve (ITV(TM)) has been developed that causes a further reduction in intrathoracic pressures, augmenting the efficiency of both standard and ACD CPR . Consequently, ACD CPR and the impendance valve were recently recommended by the American Heart Association. Clinical trials are underway to determine the... DEVICE BRAND NAME/MANUFACTURER NAME: ResQ- Valve /CPRxLLC/United States; ITV; Combitube MEDICAL DESCRIPTORS:

## \* resuscitation

...therapy--dt; thorax pressure; venous return; cardiovascular equipment; biomedical technology assessment; staff training; medical education; valve; compression; decompression; technique; cardiopulmonary hemodynamics; medical research; treatment outcome; biomedical engineering; review; priority journal 2000

7/3,K/42 (Item 3 from file: 73)

DIALOG(R)File 73:EMBASE

(c) 2004 Elsevier Science B.V. All rts. reserv.

10777899 EMBASE No: 2000257951

Active compression-decompression cardiopulmonary resuscitation Plaisance P.; Sukhum P.; Lurie K.G.

Dr. K.G. Lurie, Cardiac Arrhythmia Center, Department of Medicine, Univ. of Minnesota Medical School, 420 Delaware Street SE, Minneapolis, MN 55455 United States

AUTHOR EMAIL: lurie002@tc:umn.edu

Current Opinion in Critical Care ( CURR. OPIN. CRIT. CARE ) (United States) 2000. 6/3 (200-206)

States) 2000, 6/3 (200-206) CODEN: COCCF ISSN: 1070-5295

DOCUMENT TYPE: Journal; Review

LANGUAGE: ENGLISH SUMMARY LANGUAGE: ENGLISH

NUMBER OF REFERENCES: 51

Active compression-decompression cardiopulmonary resuscitation Plaisance P.; Sukhum P.; Lurie K.G.

Despite the practice of standard closed-chest standard cardiopulmonary

resuscitation for more than four decades, survival rates for patients in cardiac arrest remain dismally low. In recent years, several new cardiopulmonary resuscitation ( CPR ) techniques and devices have been developed to improve upon the relative inefficiencies of standard CPR . One technique, active compression-decompression (ACD) CPR, is based upon the concept that lowering intrathoracic pressure during the CPR decompression phase enhances venous return by 'priming the pump' for the next compression phase. ACD CPR can significantly improve short- and long-term survival rates over standard CPR if performed by well-trained rescue personnel.\_Building\_upon-ACD\_\_CPR-, an inspiratory-impedance-threshold valve has more recently been developed that further decreases decompression phase intrathoracic pressure. The ITV(TM) and ACD CPR in combination provide even greater benefit over standard CPR or ACD CPR alone. These devices are becoming more widely accepted and used. (C) 2000 Lippincott Williams and... MEDICAL DESCRIPTORS:

\* resuscitation ; \*survival rate 2000

7/3,K/43 (Item 4 from file: 73)
DIALOG(R)File 73:EMBASE
(c) 2004 Elsevier Science B.V. All rts. reserv.

07054208 EMBASE No: 1997336052

M20: Recent advances in mechanical methods of cardiopulmonary resuscitation

Lurie K.G.

K.G. Lurie, Cardiac Arrhythmia Center, University of Minnesota, Minneapolis, MN United States
Acta Anaesthesiologica Scandinavica, Supplement ( ACTA ANAESTHESIOL. SCAND. SUPPL. ) (Denmark) 1997, 41/111 (49-52)
CODEN: AASXA ISSN: 0515-2720
DOCUMENT TYPE: Journal; Conference Paper
LANGUAGE: ENGLISH SUMMARY LANGUAGE: ENGLISH
NUMBER OF REFERENCES: 28

M20: Recent advances in mechanical methods of cardiopulmonary resuscitation Lurie K.G.

Several new CPR techniques and devices have been developed and tested since the first report of manual closed-chested cardiopulmonary resuscitation (CPR) nearly four decades ago. These devices and techniques include vest CPR, interposed abdominal counterpulation CPR, active compression-decompression CPR, an impedance threshold valve, intra-aortic balloon pump and phased thoracic-abdominal counterpulsation. Many of these new mechanical advances...

\*intensive care; \* resuscitation artificial ventilation; brain; conference paper; heart; human; priority journal 1997

7/3,K/44 (Item 1 from file: 35)
DIALOG(R)File 35:Dissertation Abs Online
(c) 2004 ProQuest Info&Learning. All rts. reserv.

01901217 ORDER NO: AADAA-I3058682

Evaluation of a phrenic nerve stimulator for the treatment of cardiac arrest and shock

Author: Zielinski, Todd Michael

Dearee: Ph.D. Year: 2002

Corporate Source/Institution: University of Minnesota (0130) Source: VOLUME 63/07-B OF DISSERTATION ABSTRACTS INTERNATIONAL.

PAGE 3379. 71 PAGES

ISBN:

0-493-74125-9

Author: Zielinski, Todd Michael

Year: 2002

...research work focuses on utilizing methods and devices to improve central venous return during cardiopulmonary resuscitation and/or traumatic injuries that suffer from hemorrhagic shock. The animal model used for this...

...optimal level of -10 to -15 mmHg by use of an impedance threshold valve (ITVT, CPRxLLC, Minneapolis, MN) that partially occludes the airway during the period of the...

... The application of this method produces a stimulated gasp during the decompression phase of cardiopulmonary resuscitation or during the expiratory gas exchange phase of the respiratory cycle (during positive pressure ventilation ) under hemorrhagic shock conditions. In either situation, when the diaphragm is stimulated to contract, intrathoracic...

...out of the left ventricle to sustain or increase vital organ perfusion pressures during cardiopulmonary resuscitation or in patients suffering from hemorrhagic shock.

```
Description
Set
        Items
                AU=(LURIE K? OR LURIE, K? OR MENK V? OR MENK, V? OR ZIELIN-
           40
S1
             SKI T? OR ZIELINSKI, T? OR BIONDI J? OR BIONDI, J?)
                KEITH(2W) LURIE OR VERN(2W) MENK OR TODD(2W) ZIELINSKI OR JAM-
S2
             ES(2W)BIONDI
                RESUSC? OR RESPIRAT? OR BREATH? OR VENTILAT? OR CPR OR PEEP
       633463
S3
              OR (POSITIVE OR NEGATIVE) (2N) PRESSUR?
           33
                S1:S2 AND S3
S4
                S4 AND PY<2004
           33
S5
                RD (unique items)
           23
S6
? show files
File 16:Gale Group PROMT(R) 1990-2004/May 13
          (c) 2004 The Gale Group
File 160:Gale Group PROMT(R) 1972-1989
          (c) 1999 The Gale Group
File 148: Gale Group Trade & Industry DB 1976-2004/May 13
          (c) 2004 The Gale Group
File 149:TGG Health&Wellness DB(SM) 1976-2004/May W1
          (c) 2004 The Gale Group
File 621: Gale Group New Prod. Annou. (R) 1985-2004/May 12
          (c) 2004 The Gale Group
File 444: New England Journal of Med. 1985-2004/May W2
          (c) 2004 Mass. Med. Soc.
File 441:ESPICOM Pharm&Med DEVICE NEWS 2004/May W2
          (c) 2004 ESPICOM Bus. Intell.
File 369: New Scientist 1994-2004/May W1
          (c) 2004 Reed Business Information Ltd.
File 370:Science 1996-1999/Jul W3
          (c) 1999 AAAS
File 129: PHIND (Archival) 1980-2004/May W1
          (c) 2004 PJB Publications, Ltd.
File 130:PHIND(Daily & Current) 2004/May 13
          (c) 2004 PJB Publications, Ltd.
File 135:NewsRx Weekly Reports 1995-2004/May W1
          (c) 2004 NewsRx
       98:General Sci Abs/Full-Text 1984-2004/May
File
          (c) 2004 The HW Wilson Co.
      15:ABI/Inform(R) 1971-2004/May 13
File
          (c) 2004 ProQuest Info&Learning
```

?

(Item 1 from file: 16) 6/3,K/1 DIALOG(R)File 16:Gale Group PROMT(R) (c) 2004 The Gale Group. All rts. reserv.

Supplier Number: 53533584 (USE FORMAT 7 FOR FULLTEXT) 06068018

ZOLL Medical Corp. Announces Election of New Director.

Business Wire, p1021

Jan 8, 1999

Record Type: Fulltext Language: English

Document Type: Newswire; Trade

376 Word Count:

(USE FORMAT 7 FOR FULLTEXT)

TEXT:

...Jan. 8, 1999--ZOLL Medical Corporation (Nasdaq: ZOLL) announced today that it has elected Dr. James W. Biondi to its Board of Directors. Officer and President since June, 1992. Cardiopulmonary Corp. designs, develops and assembles advanced software driven ventilators used for the treatment of anesthesia and intensive care patients. Dr. Biondi also currently serves...

...Company."

ZOLL Medical Corporation designs, manufactures and markets an integrated line of proprietary non-invasive resuscitation devices and disposable electrodes. Used by health care professionals to provide both types of cardiac resuscitation -- pacing and defibrillation--these products are essential in the emergency treatment of cardiac arrest victims

19990108

(Item 2 from file: 16) 6/3, K/2DIALOG(R) File 16:Gale Group PROMT(R) (c) 2004 The Gale Group. All rts. reserv.

Supplier Number: 44698537 03384660 A HEART REVIVER, TANGLED IN RED TAPE

U.S. News & World Report, p19

May 23, 1994

Record Type: Abstract Language: English Document Type: Magazine/Journal; General Trade

ABSTRACT:

The effectiveness of the Ambu CardioPump in resuscitating heart attack victims may be difficult to prove. The device is based on the design...

...was used 4 years ago to revive a man who collapsed of heart failure. Cardiologist Keith Lurie adapted the design for the Ambu CardioPump. Early data indicate that people treated with the... 19940523

(Item 3 from file: 16) 6/3, K/3DIALOG(R) File 16: Gale Group PROMT(R) (c) 2004 The Gale Group. All rts. reserv.

Supplier Number: 41725634 (USE FORMAT 7 FOR FULLTEXT) 01439495 Health Talk: AMA says save the aspirin for the hangover Drug Store News, v0, n0, pIP7 Dec 10, 1990

Language: English Record Type: Fulltext Abstract

Document Type: Magazine/Journal; Trade

Word Count: 257

... seems that toilet plungers may become a normal fixture in some households with heart patients.

Keith Lurie, M.D., of the University of California at San Francisco Medical Center reported a case...

...with a history of heart problems, collapsed at his home. His son, poorly trained in CPR, attempted to restore his father's breathing and pulse without success. He then grabbed a toilet plunger and used it to compress

...new technique: the mother had used the plunger on the man six months earlier to resuscitate him. Both times the man survived.

The son later suggested to physicians that toilet plungers...
19901210

6/3,K/4 (Item 1 from file: 148)
DIALOG(R)File 148:Gale Group Trade & Industry DB
(c)2004 The Gale Group. All rts. reserv.

15357099 SUPPLIER NUMBER: 96414405 (USE FORMAT 7 OR 9 FOR FULL TEXT)

ZOLL and ResQSystems Sign Agreement to Commercialize Revolutionary New

Device That Improves Cardiopulmonary Resuscitation -- CPR --.

Business Wire, 2140

Jan 14, 2003

LANGUAGE: English RECORD TYPE: Fulltext WORD COUNT: 1072 LINE COUNT: 00094

ZOLL and ResQSystems Sign Agreement to Commercialize Revolutionary New Device That Improves Cardiopulmonary Resuscitation -- CPR ---.

WIRE)--Jan. 14, 2003

ZOLL Medical Corporation (Nasdaq: ZOLL), a manufacturer of non-invasive cardiac resuscitation devices, and ResQSystems Inc. a manufacturer of circulatory enhancement products, today announced that the companies...

In connection with the distribution agreement, ZOLL made a \$1,250,000 equity investment in...the distribution agreement, ZOLL has acquired exclusive rights to distribute the ResQPOD for the cardiac resuscitation market in the U.S., Canada and Europe. The ResQPOD is CE approved for sale...rate for victims of sudden cardiac arrest when used in conjunction with active compression/decompression CPR. Specifically, the ResQPOD increases blood flow to the heart and brain during CPR, which extends the window of ...patient's chance for complete neurological recovery. Studies are ongoing to demonstrate effectiveness during traditional CPR.

"The addition of the ResQPOD to our product line is an important step forward in...

...ResQSystems is an innovative company with a very solid foundation of clinical expertise in cardiac resuscitation. We are very optimistic about this partnership's ability to make a significant impact on cardiac resuscitation with the introduction of ...been recognized as the technical leader in devices that have revolutionized the field of cardiac

resuscitation , in both the pre-hospital and hospital markets. ZOLL's acceptance of the ResQPOD is an important endorsement of our technology," said Keith G. Lurie , M.D., Founder and Chief Executive of ResQSystems. "Their commitment and innovation is noteworthy and...in Burlington, MA, designs, manufactures and markets an integrated line of proprietary, non-invasive cardiac resuscitation devices and disposable electrodes. Used by health care professionals to provide both types of cardiac resuscitation - pacing and defibrillation - these products are essential in the emergency treatment of cardiac arrest victims...ZOLL, including the use of funds by ResQSystems, the impact of ResQPOD technology on cardiac resuscitation , ZOLL's ability to capitalize on existing relationships and other statements contained herein regarding matters...

#### 20030114

(Item 2 from file: 148) 6/3, K/5DIALOG(R)File 148:Gale Group Trade & Industry DB (c) 2004 The Gale Group. All rts. reserv.

(USE FORMAT 7 OR 9 FOR FULL TEXT) SUPPLIER NUMBER: 94037745 15169899 Draeger Medical and Cardiopulmonary Corp. Sign Exclusive Agreement for Distribution of Ventilator Management System Throughout North America.

Business Wire, 2017

Nov 7, 2002

RECORD TYPE: Fulltext LANGUAGE: English

LINE COUNT: 00049 WORD COUNT: 532

Draeger Medical and Cardiopulmonary Corp. Sign Exclusive Agreement for Distribution of Ventilator Management System Throughout North America. Nov. 7, 2002

Draeger Medical, Inc., a leading provider of medical systems and services for ventilation , and Cardiopulmonary Corp., a leading developer of ventilator management system software, announced that the companies have signed a distribution agreement providing Draeger Medical, Inc. with the exclusive right to sell Cardiopulmonary Corp.'s Bernoulli(TM) Ventilator Management System in Long Term Acute and Sub Acute Care markets throughout North America.

Christopher...Corp. will provide an encompassed solution for our customers, combining Draeger Medical's expertise in ventilation with Cardiopulmonary Corp.'s extensive knowledge of ventilator management systems. Together we can achieve our ambitious goals to grow within the Long Term...

... America. We are convinced that we found the best partner for a long, rewarding association."

James W. Biondi , M.D., Chief Executive Officer of Cardiopulmonary Corp., stated, "We are pleased to have Draeger Medical, a world class leader in critical care ventilation , as our partner for the distribution of the Bernoulli(TM) Ventilator Management System in the Long Term Acute and Sub Acute Care markets in North America. We look forward to a long, successful association in the distribution of our advanced respiratory management software and in the establishment of new standards of care in ventilation ."

About Cardiopulmonary Corp.

Cardiopulmonary Corp., located in Milford, Connecticut, is a leading developer of medical information technology for applied respiratory care. Cardiopulmonary develops, licenses, and markets the Bernoulli(TM) Ventilator Management System that provides continuous central station and remote wireless surveillance for most critical care and home care

ventilators . Cardiopulmonary is committed to the advancement of the state of the art for applied respiratory care by the introduction of superior technology to improve patient outcomes. For more information please...

#### 20021107

6/3,K/6 (Item 3 from file: 148)
DIALOG(R)File 148:Gale Group Trade & Industry DB
(c)2004 The Gale Group. All rts. reserv.

11317737 SUPPLIER NUMBER: 55660066

A comparison of standard cardiopulmonary resuscitation and active compression-decompression resuscitation for out-of-hospital cardiac

Plaisance, Patrick; Lurie, Keith G.; Vicaut, Eric; Adnet, Frederic; Petit, Jean-Luc; Epain, Daniel; Ecollan, Patrick; Gruat, Renaud; Cavagna, Patrice; Biens, Jean; Payen, Didier
New England Journal of Medicine, 341, 8, 569(7)

August 19, 1999

ISSN: 0028-4793 LANGUAGE: English RECORD TYPE: Abstract

A comparison of standard cardiopulmonary resuscitation and active compression-decompression resuscitation for out-of-hospital cardiac arrest.

... Lurie, Keith G

ABSTRACT: People in cardiac arrest who receive active compression-decompression cardiopulmonary resuscitation (CPR) are more likely to survive than those who receive standard CPR. During active compression-decompression CPR, a hand-held suction device is used to raise the chest in between compressions. This... ...flow through the heart. Researchers randomly assigned 750 patients in cardiac arrest to receive standard CPR or active compression-decompression CPR. Those who received active compression-decompression CPR were twice as likely to be alive one year later and also more likely to...

DESCRIPTORS: CPR (First aid... 19990819

6/3,K/7 (Item 4 from file: 148)
DIALOG(R)File 148:Gale Group Trade & Industry DB
(c)2004 The Gale Group. All rts. reserv.

09389643 SUPPLIER NUMBER: 19214231 (USE FORMAT 7 OR 9 FOR FULL TEXT) Randomised comparison of epinephrine and vasopressin in patients with out-of-hospital ventricular fibrillation.

Lindner, Karl H.; Dirks, Burkhard; Strohmenger, Hans-Ulrich; Prengel, Andreas W.; Lindner, Ingrid M.; Lurie, Keith G.

Lancet, v349, n9051, p535(3)

Feb 22, 1997

ISSN: 0099-5355 LANGUAGE: English RECORD TYPE: Fulltext; Abstract

WORD COUNT: 2368 LINE COUNT: 00205

... Lurie, Keith G.

ABSTRACT: Vasopressin may be better than epinephrine for resuscitating cardiac arrest patients for whom direct-current shock therapy is

ineffective. Of 40 patients who...

in animals have suggested that intravenous vasopressin is associated with better vital-organ perfusion and resuscitation rates than is epinephrine in the treatment of cardiac arrest. We did a randomised comparison...

...primary drug therapy for cardiac arrest. The endpoints of this double-blind study were successful resuscitation (hospital admission), survival for 24 h, survival to hospital discharge, and neurological outcome (Glasgow coma...

...significantly larger proportion of patients treated with vasopressin than of those treated with epinephrine were resuscitated successfully from out-of-hospital ventricular fibrillation and survived for 24 h. Based upon these...

...pharmacological therapies have been examined. Interest in the possible value of vasopressin treatment during cardiopulmonary resuscitation arose after the observation that there is a large release of vasopressin immediately after a...

...standard treatment protocols, for advanced cardiac life support according to the guidelines of the European Resuscitation Council and the American Heart Association.1,2

Patients enrolled in this study lived in...

...physician specialising in emergency care.

Cardiac arrest was defined as the absence of both spontaneous respiration and palpable carotid pulse. Patients with cardiopulmonary arrest were included in the study if the...

 $\dots$ 60-90 s after drug administration. If the study drug failed to restore spontaneous circulation, resuscitation was continued according to the standard guidelines.1,2 Patients remaining in cardiac arrest after...

...report.8 A study protocol check, by means of an onset tape recording of all resuscitation -related events, was made by a supplementary member of the rescue team. The call-response...

... of the accident. In witnessed cardiac arrests, the time from collapse to start of cardiopulmonary resuscitation was recorded. Restoration of spontaneous circulation was defined as the return of a spontaneous palpable

... Hg for an undefined period at any time after administration of the study drug). Successful resuscitation was defined as a return of spontaneous circulation, and on admission to hospital spontaneous circulation...

...Student's t test for continuous data. The primary endpoint of the study was successful resuscitation , defined as survival to intensive-care unit admission without the need for closed-chest cardiopulmonary resuscitation after return of spontaneous circulation. Before the study we calculated the sample size required based...

...detect with 80% probability, at a one-sided significance of 005, an increase in successful resuscitation rate from 30% with standard epinephrine treatment to 45%; the calculation indicated that 19 patients...

...remaining cases the medical history remained unclear. 63% of the arrests were witnessed, but cardiopulmonary resuscitation was initiated by a

bystander at the site of the incident in only 23% of...

- $\dots$ 2). However, more patients in the vasopressin group than in the epinephrine group were successfully resuscitated (to hospital admission) and a significantly greater proportion survived for at least 24 h (table...
- ...without further advanced cardiac life support), there was a return of spontaneous circulation and successful resuscitation in two (10%) epinephrine-treated and seven (35%) vasopressin-treated patients (p<0001). Immediately after resuscitation and during the further clinical treatment, we observed no side-effects (such as sustained splanchnic...
- ...of those treated with vasopressin than those given epinephrine as the initial vasopressor during cardiopulmonary resuscitation and advanced cardiac life support survived for 24 h.

The results of this preliminary study...

...results from patients with refractory cardiac arrest in whom vasopressin was given when all other resuscitation efforts had failed.5 In that series of case reports, eight patients with in-hospital...

...no neurological deficit.

Our study had some limitations. Since no previous investigation of vasopressin for resuscitation of the fibrillating human heart was available, we used only one dose of vasopressin in ...

- ...algorithm. At present, nothing is known about the pharmacokinetics of repeated vasopressin administration during cardiopulmonary resuscitation in human beings. Because of the lack of information, epinephrine was administered in the vasopressin...
- ... This study was supported by a grant from the Laerdal Foundation, Norway. References
- 1 European Resuscitation Council. Adult advanced cardiac life support: the European resuscitation guidelines 1992. BMJ 1993; 306: 1589-93.
- 2 Emergency Cardiac Care Committee and Subcommittees, American Heart Association. Guidelines for cardiopulmonary resuscitation and emergency cardiac care, III: adult advanced cardiac life support. JAMA 1992; 268: 2199-41...
- ... Ensinger H, Hetzel WD, Ahnefeld FW, Georgieff M. Stress hormone response during and after cardiopulmonary resuscitation . Anesthesiology 1992; 77: 662-68.
- 4 Lindner KH, Haak T, Keller A, Bothner U, Lurie KG. Release of endogenous vasopressors during and after cardiopulmonary resuscitation . Br Heart J 1996; 75: 145-50.
- 5 Lindner KH, Prengel AW, Brinkmann A, Strohmenger...AW, Pfenninger EG, et al. Vasopressin improves vital organ blood flow during closed-chest cardiopulmonary resuscitation in pigs. Circulation 1995; 91: 215-21. 7 Lindner KH, Brinkmann A, Pfenninger EG, Lurie...
- ...hemodynamic variables, organ blood flow, and acid-base status in a pig model of cardiopulmonary resuscitation . Anesth Analg 1993; 77: 427-35.
  - 8 Cummins RO. The Utstein style for uniform reporting...

...dose and standard dose adrenaline do not alter survival compared with placebo in cardiac arrest. Resuscitation 1995; 30: 243-49.

13 Lindner KH, Ahnefeld FW, Schuermann W, Bowdler IM. Epinephrine and norepinephrine in cardiopulmonary resuscitation : effects on myocardial oxygen delivery and consumption. Chest 1990; 97: 1458-62.

14 Ditchey RV...

...of epinephrine to improve the balance between myocardial oxygen supply and demand during close-chest **resuscitation** in dogs. Circulation 1988; 78: 382-89.

\_ ----- - ----

## 19970222

6/3,K/8 (Item 5 from file: 148)
DIALOG(R)File 148:Gale Group Trade & Industry DB
(c)2004 The Gale Group. All rts. reserv.

(USE FORMAT 7 OR 9 FOR FULL TEXT) SUPPLIER NUMBER: 18297440 08715977 The Ontario trial of active compression-decompression cardiopulmonary resuscitation for in-hospital and prehospital cardiac arrest. Stiell, Ian G.; Hebert, Paul C.; Wells, George A.; Laupacis, Andreas; Vandemheen, Katherine; Dreyer, Jonathan F.; Eisenhauer, Mary A.; Gibson, John; Higginson, Lyall A.J.; Kirby, Ann S.; Mahon, Jeffrey L.; Maloney, Justin P.; Weitzman, Brian N. JAMA, The Journal of the American Medical Association, v275, n18, p1417(7) May 8, 1996 RECORD TYPE: Fulltext; Abstract LANGUAGE: English ISSN: 0098-7484 LINE COUNT: 00459 WORD COUNT: 5464

The Ontario trial of active compression-decompression cardiopulmonary resuscitation for in-hospital and prehospital cardiac arrest.

ABSTRACT: Active compression-decompression cardiopulmonary resuscitation (ACD CPR) does not appear to be more effective than regular CPR. During ACD CPR, the rescuer uses a suction device that allows the chest to expand, or decompress, following each compression. Research has suggested that this may improve blood flow and ventilation. Researchers followed 773 people who developed cardiac arrest in a hospital and 1,011 people... ... the community and were transported to a hospital. Approximately half of both groups received regular CPR and half received ACD CPR. ACD CPR did not improve survival rates at one hour or at hospital discharge. This was true...

 $\dots$  as age, type of arrhythmia that led to cardiac arrest or how soon they received  $\mbox{CPR}$  . Many of the rescuers found it very difficult to administer ACD  $\mbox{CPR}$  .

AUTHOR ABSTRACT: Objective. - To compare the impact of active compression-decompression (ACD) cardiopulmonary resuscitation (CPR) and standard CPR on the outcomes of in-hospital and prehospital victims of cardiac arrest. Design. - Randomized controlled...

...total of 1784 adults who had cardiac arrest. Intervention. - Patients received either standard or ACD CPR throughout resuscitation. Main Outcome Measures. - Survival for 1 hour and to hospital discharge and the modified Mini-Mental State Examination (MMSE). Results. - All characteristics were similar in the standard and ACD CPR groups for the 773 in-hospital patients and the 1011 prehospital patients. For in-hospital patients, there were no significant differences between the standard (n=368) and ACD (n=405) CPR groups in survival for 1 hour (35.1 % vs 34.6%; P=.89), in survival...

...there were also no significant differences between the standard (n=510) and ACD (n=501) CPR groups in survival for 1 hour (16.5% vs 18.2%; P=.48), in survival...

...of clinically important subgroups failed to identify any patients who appeared to benefit from ACD CPR. Conclusions. - ACD CPR did not improve survival or neurologic outcomes in any group of patients with cardiac arrest.

#### TEXT:

IN THE 35 YEARS since the introduction of closed-chest cardiopulmonary resuscitation CPR ),(1) there has been much research into advanced cardiac life support (ACLS) measures.(2) Nevertheless...

...promptly respond to airway management and defibrillation.(3) Recent evaluations of pharmacologic therapy for cardiac resuscitation have been disappointing.(4) Consequently, there has been renewed interest in the development of new techniques for performing basic CPR .(5-7) One promising approach, active compression-decompression (ACD) CPR, involves a suction device that allows the rescuer to lift up and expand (decompress)

...9) The ACD device is commercially available in many countries and is frequently employed in resuscitation efforts for cardiac arrest.

Recent studies suggest increased myocardial and cerebral blood flow as well as increased ventilation in animal resuscitated with ACD CPR compared with standard CPR .(10-18) In human studies, researchers have also demonstrated significantly better hemodynamic responses and ventilatory profiles during ACD CPR .(19-25)

The most clinically important measures of benefit for cardiac arrest interventions are long...

...neurologic function determined in large, carefully conducted, randomized, controlled trials. Published clinical trials of ACD CPR used on patients who collapse outside the hospital have produce conflicting results.(26,27) Two small trial of in-hospital patients showed strong trends toward improved survival wit ACD CPR but lacked sufficient power to detect an important difference between groups.(28,29) This study was designed to compare the impact of ACD and standard CPR on the survival and neurologic outcomes of both in-hospital and prehospital victims of cardiac...

...the study if they had cardiac arrest and required chest compressions in the course of resuscitation . Included were patients who had cardiac arrest while in 1 of 5 tertiary care hospitals...

...age of 16 years; had a terminal illness; were known to have been without basic CPR for more than 15 minutes; had acute trauma or exsanguination; had a recent sternotomy; were...

...in the study during the same hospital admission; or were judged to have received inappropriate CPR (eg, respiratory arrest with detectable pulse).

Informed consent was not obtained, because of the urgency of the...

...the American Heart Association for basic cardiac life support and ACLS.(2) In-hospital basic CPR was provided by nurses, respiratory therapists, orderlies, and physicians, and ACLS was directed by staff physicians in emergency departments and by senior medical residents on wards. Patients who collapsed outside the hospital received basic CPR from citizen bystanders, first-responding firefighters or police officers, or ambulance officers; the latter transported...

...but not endotracheal intubation or intravenous therapy.

Patients were randomly assigned to receive either standard CPR or

ACD CPR according to the presence of a control dummy object or an ACD CPR de vice (Cardiopump, Ambu International A/S, Copenhagen, Denmark) in sealed containers available on cardiac...

...which depended by chance on the location of each cardiac arrest.

In-hospital staff (nurses, respiratory therapists, orderlies, and physicians) and prehospital staff (ambulance officers, firefighters, and police officers) were all fully trained in standard CPR and required regular testing. All staff were taught to perform ACD CPR during sessions that included lectures, videotapes, and practice with manikins. Competence was assessed by a...

...and update memos were distributed throughout the study, and research nurses monitored the performance of CPR whenever this was feasible. The study was preceded by a 1-month run-in period...

...randomization containers had the ACD device, to provide the staff with experience in performing ACD CPR and to test study procedures.

Outcome Measures

The primary outcome measure was successful lresuscitation to survival for 1 hour, defined as the continuous presence of a spontaneous and measurable

...the need for vasopressor or antiarrhythmic agents) for at least 1 hour from the time CPR was discontinued; such patients were usually stable enough to be admitted to the intensive care...

...grade 5, brain dead). Other outcomes assessed were the return of any detectable pulse during resuscitation, presence of injuries related to CPR, and problems with use of the ACD device noted by rescuers. Assessment of survival outcomes...

...chi.sup.2) test for difference in proportions and the following assumptions: baseline rate of resuscitation to survival for 1 hour, 30%; absolute difference in rate of survival for 1 hour...treat basis, ie, according to the randomization group rather than according to the type of CPR actually received. An interim analysis of survival with the O'Brien-Fleming technique of grouped...

...the hypothesis that there was no difference between study groups for the primary end point, resuscitation to survival for 1 hour. Similarly, (chi.sup.2) analysis was used to test the...

...Survival outcomes in clinically important a priori subgroups (based on initial cardiac rhythm, time to CPR, time from CPR to ACLS, duration of CPR, cause of the arrest, and age) were compared using (chi.sup.2) analysis or the...

...included in the model. Adjustment was made for the following variables: age, sex, time to CPR, time from CPR to ACLS, duration of CPR, witnessed vs unwitnessed arrest, cause, initial rhythm, current or past medical diagnoses of respiratory disease or ischemic heart disease, hospital, and treatment

RESULTS

During the study period, from June...

...Among the in-hospital patients, 82 were eligible but not randomized (33 Of whom were resuscitated), and among the prehospital patients 238 were eligible but not randomized (31 of whom were resuscitated). The urgency of cardiac arrest resuscitation combined with the need to have the ACD device readily available on each cardiac arrest...

...n=39, n=7), acute trauma (n=14, n=31), more than 15 minutes without CPR n=0, n=31), initially treated in nonstudy ambulance (n=0, n=21), prehospital patient randomized in hospital n=0, n=14), inappropriate CPR (n=13, n=0), sternotomy (n=7, n=0), terminal illness (n=4, n=6... ...4), and arrest in the recovery room n=2, n=0). For standard vs ACD CPR, respectively, the percentages of these ineligible patients who were resuscitated were 69% (53/77) vs 48% (26/54) in hospital and 5% (3/62) vs

...hospital and prehospital patients, demographic and medical characteristics were similar in the standard and ACD CPR groups (Table 1). Overall, the in-hospital patients differed from the prehospital patients with regard to sex, witnessed arrest, initial rhythm of pulseless electrical activity or asystole, respiratory cause, and most current diagnoses, as well as most time intervals and the frequency of administration of most resuscitation drugs.

For both in-hospital and prehospital patients, there was no difference between the standard and ACD CPR groups in the proportions resuscitated to survival for 1 hour or survival to hospital discharge (Table 2). For both the...

- ...the analysis. After multivariate adjustment, the odds ratios and 95% confidence intervals in the ACD CPR group (compared with the standard CPR group) were, among in-hospital patients, 1.01 (0.72-1.41) for survival for...
- ...both in-hospital and prehospital patients, there was no difference between the standard and ACD CPR groups in the neurologic status of the survivors as reflected by MMSE scores or cerebral performance categories (Table 3). There were no differences between the standard and ACD CPR groups in the percentage who had any return of pulse among in-hospital patients (52...
- ...visceral injuries documented by radiography or autopsy was not different between the standard and ACD CPR groups: 4% for both groups among in-hospital patients and 3% vs 2% among prehospital patients. Both in-hospital and prehospital CPR providers rated ACD CPR as difficult or very difficult to perform in 18% of cases and noted problems with...

In no clinically important a priori subgroup among either in-hospital or prehospital patients...

- ...for 1 hour or until hospital discharge better in the group randomized to receive ACD CPR (Table 4). A post hoe subgroup was created by excluding patients from the ACD CPR group who were rated by the providers to have had inadequate decompression. This analysis also revealed that there were no significant differences between the standard and ACD CPR groups either among in-hospital patients for survival for 1 hour (35% vs 37%; P...
- ...hospital discharge (4% vs 5%; P=.39). Finally, when assessed according to the type of CPR actually used rather than on an intention-to-treat basis, there were no significant differences...
- ...survival outcome among in-hospital or prehospital patients. COMMENT

We found no improvements with ACD CPR in immediate or longer-term survival for patients with cardiac arrest who were treated either...

...outcome scales was no better in survivors of cardiac arrest who were treated by ACD CPR than in those treated by standard CPR. Further analysis of the data did not reveal any important subgroup of patients who appeared to benefit from ACD CPR, regardless of whether they were initially treated in or outside the hospital. Similarly, ACD CPR was shown to have no effect on survival after we controlled for possible confounding factors by multivariate analysis.

A substantial body of research supports the hypothesis that ACD CPR should be associated with improved survival. In animal models, ACD CPR has been shown to produce much better cardiovascular hemodynamic responses than standard CPR, including increased cerebral perfusion pressure, increased velocity time integral (an analogue of cardiac output), increased

- ...11,17) Furthermore, several investigators have demonstrated improved myocardial and cerebral blood flow with ACD CPR, while others have shown improved minute ventilation. (11,12,14-16,18) These researchers have speculated that the effectiveness of ACD CPR can be attributed to the "thoracic pump" theory of blood flow, whereby there is a generalized pressure increase in intrathoracic vessels during CPR compressions. (36,37) The negative intrathoracic Pressure associated with the decompression phase of ACD CPR may lead to greater venous return and more efficient ventricular filling, thus increasing stroke volume...
- ...humans, physiologic data from victims of cardiac arrest also indicate impressive hemodynamic improvements with ACD CPR compared with standard CPR. It appears that ACD CPR leads to increased aortic systolic blood pressure, increased end-tidal carbon dioxide levels, and increased coronary perfusion pressure. (19,21,23,25) Several investigators have shown that ACD CPR is associated with increased diastolic filling times, increased velocity time integral of transmitral flow, and...
  ...published clinical trials have shown strong trends toward better
- ...published clinical trials have shown strong trends toward better survival and neurologic outcomes with ACD CPR both in and outside the hospital. None of these studies had sufficient numbers of patients...
- ...St Paul, Minn, Lurie and colleagues (26) found strong trends toward better survival with ACD CPR and statistically better outcomes in those treated within 10 minutes. Schwab and associates (27) failed to find any improvement with ACD CPR in either Fresno, Calif (N=253), or San Francisco, Calif (N=607). Two smaller trials...
- $\ldots$  as well as strong trends toward better survival to discharge in patients treated with ACD  $\ensuremath{\texttt{CPR}}$  .

Why did use of ACD CPR in our study fail to improve patient survival despite expectations that had been raised by...

- ...humans, particularly those with coronary artery disease. Kern and associates (48) have demonstrated that during CPR, myocardial blood flow below coronary lesions is substantially reduced and does not correlate well with...
- ...long-term survival. Interestingly, none of the animal studies that demonstrated hemodynamic responsiveness with ACD CPR assessed the impact on survival. One other investigator was unable to find even hemodynamic benefits with ACD CPR in an animal model.(50)

Could features of our study design have led to a failure to identify potential benefits of ACD CPR The randomization of patients with cardiac arrest can be challenging when the clinical situation is...might have led to a finding of clinically important improvement in outcomes for the ACD

CPR group, we believe this is unlikely. For both patient populations, the 95% confidence intervals of...

...rates suggest a maximum possible improvement of 3.5% in survival to discharge with ACD CPR. A systematic overview incorporating our results and those of the previous studies did not demonstrate an overall benefit for survival with ACD CPR either in or outside the hospital Figure). In addition, the data from our study did not indicate trends favoring ACD CPR in any clinically significant subgroup or better outcomes for ACD CPR after multivariate adjustment.

An important consideration not seen in drug trials is whether the intervention...

- ...case a device, was properly implemented throughout the study. For a technique such as ACD CPR to be effective in everyday clinical practice, it must be readily learned and properly performed...
- ...train more than 1000 rescuers, including hospital staff, ambulance workers, and firefighters, to perform ACD CPR in many different situations. We are confident that our rigorous training, testing, retraining, and monitoring...
- ...are aware that an important proportion of rescuers noted fatigue and discomfort when performing ACD CPR and that this technique requires more work than standard CPR .(51) Of greater concern is that the ACD device did not adhere to the chest...
- ...hoe subgroup analysis excluding patients with inadequate decompression also failed to demonstrate benefit from ACD CPR . Some in-hospital patients randomized to undergo ACD CPR did not actually undergo this technique because of very brief resuscitations . Again, however, on analysis according to the treatment actually performed, no improvement in survival was found with ACD CPR .

Our study did not address the use of ACD CPR in 2 important groups of patients with cardiac arrest, those under the age 16 years...

- ...of ambulance services in Ontario, our prehospital patients had relatively long intervals from collapse to CPR, from CPR to ACD CPR, and from CPR to ACLS. Our study did, however address the use of ACD CPR in many different clinical scenarios, including in-hospital patients, who tended to have more prearrest morbidity but were resuscitated very rapidly, as well as prehospital patients, who had fewer documented medical problems. This study was, to our knowledge, the largest clinical of CPR yet conducted. We believe, therefore, that the diversity of our patient population, our large sample...
- ...arrest, regardless of the setting. Our study did not demonstrate a beneficial effect of ACD CPR on the survival or neurologic outcome of patients with cardiac arrest. We were unable to identify any subgroup of patients or any circumstance in which ACD CPR was associated with a better outcome.

This study was supported by grant 07992N from the...

- ...and My-Linh Tran, the data management team; to Silvia Visentin for manuscript assistance; to **Keith Lurie**, MD, for review of the manuscript; and to the hundreds of **respiratory** therapists, orderlies, nurses, physicians, ambulance officers, firefighters, and police officers in Ottawa-Carleton and London...
- ...1064-1067. 2. Emergency Cardiac Care Committee and Subcommittees, American Heart Association. Guidelines for cardiopulmonary resuscitation

and emergency cardiac care. JAMA 1992;268(theme issue): 2171-2298. 3. Niemann JT. Cardiopulmonary resuscitation. N Engl J Med. 1992;327:1075-1080. 4. Stiell IG, Wells GA, Hebert PC...

...Acad Emerg Med, 1995; 2:264-273. 5. Halperin HR, Weisfeldt ML. New approaches to CPR: four hands, a plunger, or a vest. JAMA 1992; 2672W2941. 6. Sack JB, Kesselbrenner MB, Bregman D. Survival from in-hospital cardiac arrest with interposed abdominal counterpulsation during cardio-pulmonary resuscitation . JAMA 1992;267:379-385. 7. Halperin HR, Tsitlik JE, Gelfand M, et al. A preliminary study of cardiopulmonary resuscitation by circumferential compression of the chest with use of a pneumatic vest. N Engl J Med. 1993; 329:762-768. 8. Lurie KG, Lindo C, Chin J. CPR: the P stands for plumber's helper. JAMA. 1990=:1661. 9. Lurie KG. Active compression-decompression CPR: a progress report. Resuscitation. 1994;28: 115-122. 10. Cohen TJ, Tucker KJ, Redberg RF, et al. Active compression-decompression resuscitation : a novel method of cardiopulmonary resuscitation . Am Heart J. 1992;124:1145-1150, 11. Lindner KH, Pfenninger EG, Lurie KG, Schuermann W, Lindner IM, Ahnefeld FW. Effects of active compression-decompression resuscitation on myocardial and cerebral blood flow in pigs. Circulation. 1993;88:1254-1263. 12. Tucker KJ, Khan JH, Savitt MA. Active compression-decompression resuscitation : effect on pulmonary ventilation. Resuscitation . 1993;26:12r>-131. 13. Chang MW, Coffeen P, Lurie KG, et al. Augmentation of...

...diastolic coronary flow velocity: the mechanism of improved myocardial perfusion during active compression-decompression cardiopulmonary resuscitation? Circulation 1993;88:I-193. Abstract. 14. Chang MW, Coffeen P, Lurie KG, Shultz JJ, Bache RJ, White CW. Active compression-decompression CPR improves vital organ perfusion in a dog model of ventricular fibrillation. Chest. 1994; 106:1250-1259. 15. Idris AH, Wenzel V, Tucker KJ, Orban DJ. Chest compression ventilation: a comparison of standard CPR and active-compression/decompression CPR. Acad Emerg Med. 1994;1:Al7-al8. Abstract. 16. Carli PA, De La Coussaye JE, Riou B, Sassine A, Eledjarn JJ. Ventilatory effects of active compression-decompression in dogs. Ann Emerg Med. 1994;24:890,-894. 17...

...Khan J, Idris A, Savitt MA. The biphasic mechanism of blood flow during cardio-pulmonary **resuscitation**: a physiologic comparison of active compression-decompression and high-impulse manual external cardiac massage. Ann...

...Simultaneous active compression-decompression and abdominal binding increase carotid blood flow additively during cardiopulmonary resucitation (CPR) in pigs. Resuscitation . 1994;28\$M. 19. Cohen TJ, Tucker KJ, Lurie KG, et al. Active compression-decompression: a new method of cardiopulmonary resuscitation . JAMA 1992;267:2916-2923. 20. Tucker KJ, Redberg RF, Schiller NB, Cohen TJ. Active compression-decompression resuscitation : analysis of transmitral flow and left ventricular volume by transesophageal echocardiogmphy in humans. J Am...

...1485-1493. 21. Guly UM, Robertson CE. Does active decompression improve the haemodynamic state during CPR?' Resuscitation . 1994;28:S27. Abstract. 22. Malzer R, Knappitsch G, Zeiner A, Sterz F, Laggner AN. Active compression-decompression resuscitation: effects on hemodynamics and pulmonary ventilation in 20 patients. Resuscitation . 1994; 28:S5. Abstract. 23. Rivers EP, McGeorge FT, Martin GB, et al. Hemodynamic comparison of mechanical, standard, and active compression-decompression CPR in human cardiac arrest. Acad Emerg Med. 1994;1:Al9-A20. Abstract. 24. Shultz JJ, Coffeen P, Sweeney M, et al. Evaluation of standard and active compression-decompression CPR in an acute human model of ventricular

fibrillation. Circulation. 1994;89.W"93. 25. Orliaguet...

...D, Sauval P, Delpech P. End-tidal carbon dioxide during out-of-hospital cardiac arrest resuscitation : comparison of active compression-decompression and standard CPR . Ann Emerg Med. 1995; 25:48-51. 26. Lurie KG, Shultz JJ, Callaham ML, et al. Evaluation of active compression-decompression CPR in victims of out-of-hospital cardiac arrest. JAMA 1994;271:1405-1411. 27. Schwab TM, Callaham ML, Madsen CD, Utecht TA. A randomized clinical trial of active compression-decompression CPR vs standard CPR in out-of-hospital cardiac arrest in two cities. JAMA 1995; 273:1261-1268. 28. Cohen TJ, Goldner BG, Maccaro PC, et al. A comparison of active compression-decompression cardiopulmonary resuscitation with standard cardiopulmonary resuscitation for cardiac arrests occurring in the hospital N Engl J Med. 1993X%: 1918-1921. 29. Tucker KJ, Galli F, Savitt MA, Kahsai, D Bresnahan L, Redberg RF. Active compression-decompression resuscitation: effect on resuscitation success after in-hospital cardiac arrest. J Am Coll Cardiol. 1994;24:201-209. 30...

...Mini-Mental State 3MS) Examination. J Clin Psychiatry 1987; 48:314-318. 31. The Brain Resuscitation Clinical Trial II Study Group. A randomized clinical trial of calcium entry blocker administration to...

...MT, Maughan WL, Effron M, Freund P, Weisfeldt ML. Mechanisms of blood flow during cardiopulmonary resuscitation . Circulation. 1980; 61:345-352. 37. Chandra N, Weisfeldt ML, Tsitlik J, et al. Augmentation of carotid flow during cardiopulmonary resuscitation by ventilation at high airway pressure simultaneous with chest compression. Am J Cardiol. 1981;48:1053-1063. 38. Tucker KJ, ldris A. Clinical and laboratory investigations of active compression-decompression cardiopulmonary resuscitation . Resuscitation . 1994; 28:1-7. 39. Pell ACH, Pringle SD, Guly UM, Steedman DJ, Robertson CE. Assessment of the active compression-decompression device (ACD) in cardiopulmonary resuscitation using transoesophageal echocardiography. Resuscitation . 1994;27:137-140. 40. Kosnik JW, Jackson RE, Keats S, Tworek RM, Freeman SB...

...RL. The effects of graded doses of epinephrine on regional myocardial blood flow during cardiopulmonary resuscitation in swine. Circulation. 1987;75:491-497. 42. Brown CG, Werman HA, Davis EA, Hamlin...

...Ashton JA. Comparative effects of graded doses of epinephrine on regional brain blood flow during CPR in a swine model. Ann Emerg Med. 1986;15:1138-1144. 43. Gonzalez ER, Ornato...

...Garnett AR, Levine RL, Young DS, Racht EM. Dose-dependent vasopressor response to epinephrine during **CP**R in human beings. Ann Emerg Med. 1989;18:920,-926. 44. Paradis NA, Martin GB...

...The effect of standard— and high-dose epinephrine on coronary perfusion pressure during prolonged cardiopulmonary resuscitation . JAMA 1991;265:1139-1144. 45. Brown CG, Martin DR, Pepe PE, et al. A...artery lesions on the relationship between coronary perfusion pressure and myocardial blood flow during cardiopulmonary resuscitation in pigs. Am Heart J. 1990;120:324-M. 49. Paradis NA, Martin GB, Rivers EP, et al. Coronary perfusion pressure and the return of spontaneous circulation in human cardiopulmonary resuscitation . JAMA. 1990;263:1106-1113. 50. Halperin HR, Chandra NC, Blair DM, Tsilik JE. The...

 $\dots$  force applied to the sternum determines vascular pressures during active compression-decompression and standard cardiopulmonary  $\ {\bf resuscitation}$  .

Circulation. 1994;90:1-5. Abstract. 51. Shultz JJ, Mianulli MJ, Gisch TM, Coffeen PR...

...GC, Lurie KG. Comparison of exertion required to perform standard and active compression-decompression cardiopulmonary resuscitation.

Resuscitation . 1995; W.23-31.

DESCRIPTORS: CPR (First aid...

19960508

6/3,K/9 (Item 6 from file: 148)
DIALOG(R)File 148:Gale Group Trade & Industry DB
(c)2004 The Gale Group. All rts. reserv.

08501248 SUPPLIER NUMBER: 17997375 (USE FORMAT 7 OR 9 FOR FULL TEXT) FDA gets feedback on informed consent waiver. (Medical News & Perspectives) Marwick, Charles

JAMA, The Journal of the American Medical Association, v275, n5, p347(1)
Feb 7, 1996
ISSN: 0098-7484 LANGUAGE: English RECORD TYPE: Fulltext

WORD COUNT: 878 LINE COUNT: 00075

... she said.

One of the leaders of those who initially drew attention to the issue, **Keith Lurie**, MD, associate professor of medicine, University of Minnesota, Minneapolis, said the proposal fell far short...

...comments were in favor of the proposal. Biros is chair of the Coalition of Acute Resuscitation and Critical Care Researchers, which supports a waiver for this type of research.

The FDA...

## 19960207

6/3,K/10 (Item 7 from file: 148)
DIALOG(R)File 148:Gale Group Trade & Industry DB
(c)2004 The Gale Group. All rts. reserv.

08230431 SUPPLIER NUMBER: 16646403 (USE FORMAT 7 OR 9 FOR FULL TEXT)
Research in emergency circumstances. (Medical News & Perspectives)
Marwick, Charles
JAMA, The Journal of the American Medical Association, v00000273, n9,
p687(2)
March 1, 1995
ISSN: 0098-7484 LANGUAGE: English RECORD TYPE: Fulltext; Abstract
WORD COUNT: 1796 LINE COUNT: 00147

... dismutase (PEG-SOD) in severe closed head injury; the use of active compression-decompression cardiopulmonary resuscitation (ACD- CPR) with a suction device in cardiac arrest; the use of hypothermia in acute head injury; and a study of immediate vs delayed fluid resuscitation in hypotensive patients with penetrating body injury.

"These studies are all based on sound science...

...Medical Center, Charlotte, NC. Short-term survival is improved in some patients treated with ACD- CPR; survival is also improved in patients in hemorrhagic shock where additional fluids were not given...

...s a question of justice," he declared.

The issue was put even more bluntly by **Keith Lurie**, MD, of the University of Minnesota Medical School, Minneapolis. Lurie is the principal investigator of the study on the cardiopulmonary **resuscitation** device, another of the studies summarized at the meeting (JAMA. 1994;271:1405-1411). "The...

...We have been compromising the health of all Americans by not permitting research on cardiac resuscitation to proceed in a scientifically sound fashion. If you have a cardiac arrest after leaving...them of the most advanced care. We have come to a grinding halt on cardiac resuscitation research. The regulations must be changed. We need action and we need it quickly."

In...

### 19950301

6/3,K/11 (Item 8 from file: 148)
DIALOG(R)File 148:Gale Group Trade & Industry DB
(c)2004 The Gale Group. All rts. reserv.

O7612681 SUPPLIER NUMBER: 15998072 (USE FORMAT 7 OR 9 FOR FULL TEXT)
Compression-decompression CPR: the Biomotor. (cardiopulmonary resuscitation) (includes reply) (Letter to the Editor)
Lerman, Sam I.; Olson, Carin M.; Lurie, Keith G.

JAMA, The Journal of the American Medical Association, v272, n19, p1477(2)
Nov 16, 1994
DOCUMENT TYPE: Letter to the Editor ISSN: 0098-7484 LANGUAGE:
ENGLISH RECORD TYPE: FULLTEXT

Compression-decompression CPR: the Biomotor. (cardiopulmonary resuscitation) (includes reply) (Letter to the Editor) ... Lurie, Keith G.

LINE COUNT: 00084

### TEXT:

WORD COUNT:

...premature termination by the Food and Drug Administration (FDA) of trials of compression-decompression cardiopulmonary resuscitation (CPR), because of lack of informed consent.

The addition of a suction phase to conventional CPR is a trivial, innocuous detail that should not require consent. The developers of the Ambu...

...might be minor ecchymoses.

1052

In any case, the use of alternate pressure and suction for CPR is described in the August 5,1939, Wiener Medizinische Wochenschrift by Dr Rudolph Eisenmenger, Facharzt fur physikalische Therapie, Vienna, Austria.

His device, which he called a Biomotor, was a cuirass ventilator that applied alternate positive and negative air pressure to the torso, and was used extensively throughout Europe for mine rescue and other victims...

- ...He compared his device with "the American Iron Lung" stating that both were equally good **ventilators** but that only the Biomotor could circulate blood during cardiac arrest, and his illustration showed...
- ...the pressure phase. This is probably the earliest description of the "thoracic pump" theory of CPR and merits a trial for any low-cardiac-output syndrome where counterpulsation might help, since compression of the extremities during cardiac diastole is equivalent to

negative pressure over the torso.

I hope that the FDA will realize that the minimal vacuum of...

...can do no more harm than traditional vacuum cupping. The evaluation of active compression-decompression CPR in victims of out-of-hospital cardiac arrest must be continued.

Sam I. Lerman, MD

Southfield, Mich [1.] Olson CM. The letter or the spirit: consent for research in CPR . JAMA. 1994;271: 1445-1447. [2.] Lurie KG, Shultz JJ, Callaham ML, et al. Evaluation of active compressiondecompression CPR in victims of out-of-hospital cardiac arrest. JAMA. 1994;271: 1405-1411. In Reply...

...the Biomotor, an early device that alternately applied pressure and suction to the torso to **ventilate** the lungs and circulate blood.

How the FDA handles the particular case of active compression-decompression CPR is really a secondary issue. More important is the general need for researchers, regulators, ethicists, and the concerned public to develop workable mechanisms by which resuscitation research can proceed while patients' rights and safety are protected.

Carin M. Olson, MD Contributing...

...Dr Lerman is correct that studies evaluating the addition of a suction phase to conventional CPR should not require consent as the patients are pulseless, without a palpable blood pressure, and...

...that approach during our recent clinical trials to determine the efficacy of active compression-decompression CPR but were told (and continue to be told) by FDA officials that the handheld suction...

...the living and the nearly dead.

Lerman is also correct that active chest decompression during CPR improves vital organ blood flow.[1] However, he is incorrect about his description of the...

...a controlled fashion. Unlike many previous devices designed to improve the dismal results with standard CPR, the Ambu device is lightweight, and its use does not take any more time to initiate than standard CPR. The time element is critical. No device, including the Ambu device, will work unless CPR is initiated very soon after cardiac arrest and unless it is effectively incorporated into an...

...Lerman. Unfortunately, the regulators at the FDA do not appear to know the history of  $\mbox{CPR}$  or the reality of modern  $\mbox{CPR}$ . Until these kinds of devices and drugs are allowed to shed their "significant risk" status...

... Thus, in the United States, these patients remain victims of both cardiac and regulatory arrest.

Keith G. Lurie , MD
University of Minnesota
Minneapolis

[1.] Shultz JJ, Coffeen P, Sweeney M. Evaluation of standard and active compression-decompression CPR in an acute human model of ventricular fibrillation. Circulation. 1994;89:684-693. [2.] Hans H. Device for promoting respiration, US patent number 2 067 268. Filing date March 1934, in Wiesbaden, Germany. [3.] Luile KE. Active compression-decompression CPR: a progress report. Resuscitation0. In press.

...DESCRIPTORS: CPR (First aid

6/3,K/12 (Item 9 from file: 148)

DIALOG(R) File 148: Gale Group Trade & Industry DB (c) 2004 The Gale Group. All rts. reserv.

07587178 SUPPLIER NUMBER: 15925023 (USE FORMAT 7 OR 9 FOR FULL TEXT)

Active compression-decompression CPR . (includes reply) (Letter to the

Editor)

Mazziotti, Alexander; Lurie, Keith G.

JAMA, The Journal of the American Medical Association, v272, n17, p1325(2)

Nov 2, 1994

DOCUMENT TYPE: Letter to the Editor ISSN: 0098-7484 LANGUAGE:

ENGLISH RECORD TYPE: FULLTEXT

WORD COUNT: 1006 LINE COUNT: 00083

Active compression-decompression CPR . (includes reply) (Letter to the Editor)

... Lurie, Keith G.

#### TEXT:

To the Editor.--Dr Lurie and colleagues[1] conclude that active compression-decompression (ACD) cardiopulmonary resuscitation (CPR) appears to be more effective than standard CPR in certain subsets under study. This statistical inference is dependent on matching baseline characteristics as...

... infarction in an otherwise healthy person is the most likely condition to have a successful CPR outcome. On the other hand, if the pathway to arrest is pulmonary embolus, massive cerebral...

...to obtain with data concerning patients who arrest in hospital.[2] In comparing forms of CPR, we must not forget that a major determining factor in their success following an arrest...

...the patient since this governs the relative probability that death can be reversed by the CPR procedures.

Alexander Mazziotti, MD, Phd Hawthorne, NJ [1.] Lurie KG, Shultz JJ, Callaham ML, et al. Evaluation of active compressiondecompression CPR in victims of out-of-hospital cardiac arrest. JAMA. 1993;271: 1405-1411. [2.] Cohen TJ, Goldner BG, Maccaro PC, et al. A comparison of active compressiondecompression cardiopulmonary resuscitation with standard cardiopulmonary resuscitation for cardiac arrest occurring in the hospital. N Engl J Med. 1993;329: 1918-1921...

...challenges in designing and executing a study to determine the effectiveness of different methods of CPR. When comparing two treatment groups, it is essential that both methods of CPR are performed correctly, in similar patient populations, and that the study design enables adequate data...

...variables associated with the research, as described by the Utstein conference on uniform standards for CPR research.[1]

In our evaluation of the effectiveness of ACD CPR in patients with out-of-hospital cardiac arrest, our study was designed to maximize the...

...out the importance of similar clinical characteristics between groups. In our study, both the standard CPR group and the ACD CPR group had very similar baseline characteristics in terms of age, sex, prior cardiac history, presenting rhythm, 911 call-response interval, and use of

bystander CPR and epinephrine. Given the space limitations, we did not present a detailed report of the...

...excluded from this study. Approximately 60% of the 130 patients enrolled in the study had CPR initiated within less than 10 minutes after collapse (downtime <10 minutes). The detailed clinical characteristics...

...than 10 minutes and less than 4 minutes. We observed a significant increase in immediate resuscitation in both subgroups. These results are similar to recent studies comparing ACD CPR with standard CPR in patients with in-hospital cardiac arrests.[2,3] Regardless of whether these kinds of...

...were critical and relevant.

Although I agree with Mazziotti that one major determinant for successful resuscitation is the overall clinical status, probably the most important variables in a large clinical study...

...groups are those associated with the test site itself Choosing a test site in which CPR is delivered in an expeditious, efficient, and carefully controlled manner by qualified and well-trained...

 $\dots$ a well-managed emergency medical services system is crucial when evaluating any new method of  $\ensuremath{\mathsf{CPR}}$  .

Keith G. Lurie , MD University of Minnesota Minneapolis [1.] Cummins RO, Chamberlain DA, Abraynson NS, et al. Recommended...

...2.] Cohen TJ, Goldner BG, Maccaro PC, et al. A comparison of active compressiondecompression cardiopulmonary resuscitation with standard cardiopulmonary resuscitation for cardiac arrests occurring in the hospital. N Engl J Med. 1993;329: 1918-1921...

...Tucker KJ, Galli F, Savitt MA, Kahui D, Bresnahan L, Redberg RF. Active compression-decompression resuscitation: effects on resuscitation success after inhospital arrest. J Am Coll Cardiol. 1994;24:201-209.

DESCRIPTORS: CPR (First aid...
19941102

6/3,K/13 (Item 10 from file: 148)
DIALOG(R)File 148:Gale Group Trade & Industry DB
(c)2004 The Gale Group. All rts. reserv.

O7281080 SUPPLIER NUMBER: 15469653 (USE FORMAT 7 OR 9 FOR FULL TEXT)

Evaluation of active compression-decompression CPR in victims of out-of-hospital cardiac arrest. (cardiopulmonary resuscitation )

Lurie, Keith G.; Shultz, Jeffrey J.; Callaham, Michael L.; Schwab,

Theresa M.; Gisch, Terry; Rector, Thomas; Frascone, Ralph J.; Long, Linda JAMA, The Journal of the American Medical Association, v271, n18, p1405(7)

May 11, 1994

ISSN: 0098-7484 LANGUAGE: ENGLISH RECORD TYPE: FULLTEXT; ABSTRACT WORD COUNT: 5512 LINE COUNT: 00428

Evaluation of active compression-decompression CPR in victims of out-of-hospital cardiac arrest. (cardiopulmonary resuscitation ) Lurie, Keith G ...

ABSTRACT: Active compression-decompression (ACD) cardiopulmonary resuscitation (CPR) appears to be more effective than standard CPR in

some cases of cardiac arrest that occurs outside of a hospital. ACD CPR involves the use of a hand held suction device which is applied to the surface...

...return of spontaneous circulation and neurological function of 77 cardiac arrest patients who received standard CPR and 53 cardiac arrest patients who received ACD CPR were compared. Those who received ACD CPR had a 59% chance of surviving until admittance to an intensive care unit when the...

...response time was less than 10 minutes. The corresponding figure for those who received standard CPR was 33%. Thirty-one percent of ACD CPR patients returned to normal neurological function. Twenty percent of those receiving standard CPR returned to normal neurological function. However, the number of patients studied was too small to...

...be drawn from this result. Thirty-eight percent of the 32 patients who received ACD  $\,$  CPR  $\,$  within 10 minutes of cardiac arrest survived until hospital discharge compared with 20% of the 49 patients who received standard  $\,$  CPR  $\,$ .

AUTHOR ABSTRACT: Objective.--Active compression-decompression (ACD) cardiopulmonary resuscitation (CPR) appears to improve ventilation and coronary perfusion when compared with standard CPR. The objective was to evaluate potential benefits of this new CPR technique in patients with out-of-hospital cardiac arrest in St Paul, Minn. Design.--Ten...

...000. Patients.--All nonnothermic victims of nontraumatic cardiac arrest older than 8 years who received CPR . Main Outcome Measures.--Return of spontaneous circulation, admission to the intensive care unit (ICU), return

...discharge with return of baseline neurological function, and complications. Results.—Seventy-seven patients received standard CPR and 53 patients received ACD CPR. The mean emergency medical services call response interval was less than 3.5 minutes. When all patients were considered, a higher percentage of ACD CPR patients had a return of spontaneous circulation and were admitted to the ICU vs standard CPR (45%vs31%, and 40%vs 26%, respectively), but these trends were not statistically significant (P...

...significant differences were found between hospital discharge rates (1 2 [23%] of 53 for ACD  $\tt CPR$  vs 13 [17%] of 77 for standard  $\tt CPR$ ), return to baseline neurological function (10 [19%] of 53 for ACD  $\tt CPR$  vs 13 [17%] of 77 for standard  $\tt CPR$ ), or return to baseline neurological function at hospital discharge (nine [17%] of 53 for ACD  $\tt CPR$  vs 12 [16%] of 77 for standard  $\tt CPR$ ). Return of spontaneous circulation, ICU admission, and neurological recovery in both  $\tt CPR$  groups were highly correlated with downtime (time from collapse to emergency medical system personnel arrival

...less than 10 minutes' downtime, survival to the ICU was 59% (19/32) with ACD CPR and 33% (16/49) with standard CPR (P<.02), return to baseline neurological function was 31% (10/32) with ACD CPR and 20% (10/49) with standard CPR (P=.27), and hospital discharge rate was 38% (12/32) with ACD CPR and 20% (10/49) with standard CPR (P=.17). Complication rates in patients admitted to the hospital were similar in both groups. Conclusions.—This study demonstrates that ACD CPR appears to be more effective than standard CPR in a well-defined subset of victims of out-of-hospital cardiac arrest during the critical early phases of resuscitation . Based on this study, a larger study should be performed to

evaluate the potential long-term benefits of ACD  $\,$  CPR . (JAMA. 1994;271:1405-1411)  $\,$  TEXT:

DESPITE the widespread application of standard cardiopulmonary resuscitation ( CPR ), the overwhelming majority of victims of out-of-hospital cardiac arrest the within hours. The...

...dismal.[1,2] After describing the report of a patient in cardiac arrest who was resuscitated by family members using a standard household plunger, we recently developed a new method of CPR termed active compression-decompression (ACD) CPR.[3,4] Subsequent studies in animals and humans using a handheld suction device applied to the chest during CPR indicated that ACD CPR, when compared with standard CPR, improves multiple hemodynamic and respiratory parameters during ventricular fibrillation, asystole, and electromechanical dissociation. Building on these observations, we conducted this study to provide estimates of the potential risks and benefits of ACD CPR vs. standard CPR in victims of out-of-hospital cardiac arrest.

METHODS

CPR Device and Training

All ACD CPR was performed with a lightweight 1.4-lb (0.6-kg) device (Ambu CardioPump, Ambu...

...Figure). The gauge is designed to ensure depth of compression equivalent to that with standard CPR (3.8 to 5.1 cm [1.5 to 2 in]). It is marked with...

...the study, including children older than 8 years, received chest compressions with both methods of  $\ensuremath{\mathsf{CPR}}$  .

The study was conducted in conjunction with the St Paul (Minn) Fire Department. The fire...

...fire department emergency medical services (EMS) personnel were required to have special training on ACD CPR by St Paul-Ramsey EMS prior to beginning the study. During these sessions, standard CPR techniques were reviewed and ACD CPR was demonstrated. The first session included an instructional video, a didactic talk about the study...

...lifting up" during active decompression, which has a fundamentally different feel when compared with standard CPR, and the importance of patient randomization. During these training sessions, all EMS personnel were required to demonstrate ACD CPR competency on a mannequin in a simulated cardiac arrest prior to using the ACD device on patients. A second training session reemphasizing standard and ACD CPR technique was given prior to the scheduled crossover of EMS teams from one type of CPR to the other.

Study Site and Subjects
The study was approved by the Institutional Review...

...use the ACD device and those on the west side were assigned to use standard CPR . After approximately every 40 patients or 75 days, there was a crossover between the east and west sides of St Paul, and the alternate method of CPR was used. During the course of the study, standard CPR was used for a total of 5 months by EMS personnel from the east and west sides of the city, and ACD CPR was also used by the same EMS personnel, at different times, for a total of 5 months. Performance of either standard CPR or ACD CPR was determined by whether the first rescue vehicle to the scene was based on the east side or west side. Once it had been determined which method of CPR should be performed, the appropriate method was initiated and used throughout the arrest.

The decision to initiate CPR on a victim was a clinical decision made according to previously established St Paul-Ramsey...

...downtime, body tone and temperature, presence of a known terminal illness or a do-not- resuscitate order, and the initial rhythm on the defibrillator monitor. When ACD CPR was used, it was continued as needed during patient transport and in the emergency department. The decision to stop CPR or to admit the patient to the intensive care unit (ICU) was made-by-emergency department physicians based on whether or not victims could be resuscitated and sufficiently stabilized to be transported to the ICU. In an effort to eliminate outcome...

...the results until after the study. Furthermore, the investigators did not discuss which method of CPR was used with medical personnel caring for the patients once they were admitted to the...arrest, treatment in the field, nature of arrest, whether it was witnessed, use of bystander CPR, ROSC, baseline neurological function (as determined by being alert and oriented to person, place, and time), complications from CPR, and ACD CPR device function. The presenting rhythm, evaluated after a "quick look" with defibrillator patches, was obtained before initiating CPR in about half of the cases and after several minutes of CPR in the rest. Both BLS and ALS EMS personnel were dispatched immediately after a 911 call. Whichever service arrived first initiated the appropriate method of CPR. All ALS response units (n=9) have defibrillation capabilities. Only two of 18 BLS units...

...prospective study, we also performed a retrospective analysis to determine the success rate of standard CPR during the same 10-month period in the year prior to this current study. Records... ...the 911 responses by the fire rescue personnel were reviewed. In those cases where standard CPR was performed, data collected were related to ROSC, survival to the ICU, and whether they...

...patient inclusion criteria as in the prospective study.

Because of the emergent setting during which CPR was performed, consent requests were not made to families of patients receiving ACD CPR. However, no family member or bystander objected to the use of the ACD CPR device in any patient during the study. During the first 5 months of the study...

...were not blinded to results in order to monitor any potential negative effects of ACD CPR on a day-to-day basis. Following completion of the first full crossover and review of the preliminary data (which demonstrated no significant adverse effects from ACD CPR), all investigators were blinded to the results until the completion of the study, with the...

...that the US Food and Drug Administration (FDA) wanted all clinical trials using the ACD CPR device terminated. Given the lack of adverse outcomes at that time, we were granted permission...

...subjects who had the greatest likelihood of recovery and to compare the two methods of CPR . Fisher's Exact Test was used for all analyses when expected values were less than...

...Simon.[10] The 95% CI was calculated as the difference in outcome proportions between ACD CPR and standard CPR. Prior to beginning the study, we decided that patients who received both methods of CPR by fire rescue personnel, despite random assignment to one specific method, would not be included...

...data analysis. In addition, we predetermined that patients who were treated with one method of CPR, despite random assignment to the other method of CPR, would be analyzed by the method of treatment received.

The planned enrollment in this study...

#### ... RESULTS

Of the 130 out-of-hospital arrests during the study period, 77 received standard CPR and 53 received ACD CPR. Standard CPR was used 36 times (47%) by first EMS rescuers on the east side of St Paul and 41 times (53%) on the west side: ACD CPR was used 29 times (55%) on the east side and 24 times (45%) on the west side of St Paul. Three patients received both methods of CPR and none survived to be admitted to the ICU. Eight patients received standard CPR despite random assignment to ACD CPR. Four of these eight had witnessed arrests with downtimes of zero minutes, and two others...

 $\dots$ 5 and 6 minutes. The remaining two victims who did not receive the method of CPR to which they were assigned had unwitnessed arrests and estimated downtimes of 10 to 20...

...the ICU (one after an ROSC), and one received less than 15 seconds of standard CPR, was defibrillated, and had a full recovery.

The treatment groups were similar with respect to...

...two groups were also similar with regard to number of witnessed arrests, performance of bystander CPR, response intervals, presenting rhythm documented by the first responders, the dosage and ...first defibrillation in patients presenting with ventricular fibrillation, the number of defibrillation attempts, and total CPR duration (Table 1). The downtime between CPR groups was relatively short, but averaged nearly 2 minutes longer in the ACD CPR group compared with the standard CPR group P<.05) (Table 1). The proportion of victims with downtimes less than 10 minutes was similar between CPR groups (61% for ACD CPR vs 63% for standard CPR). At least 1 mg of epinephrine was administered to 77% of the ACD group and...

...than 1 mg was also similar in both groups. In addition, the total duration of CPR was similar between both groups.

[TABULAR DATA 1 OMITTED]

Comparison of CPR efficacy between the two methods of CPR was made using several different endpoints. Results related to ROSC, ICU admission rates, return to...

...hospital while alert and oriented are shown in Table 2. When all patients who received  $\mbox{CPR}$  by the fire rescue personnel were compared, regardless of whether arrests were witnessed, there was a trend toward improvement in the rates of ROSC and ICU admission with ACD  $\mbox{CPR}$  compared with standard  $\mbox{CPR}$ . Overall, 40% of the patients in the ACD  $\mbox{CPR}$  group were admitted to the ICU vs 26% in the standard  $\mbox{CPR}$  group (P<.10). Details related to the outcome of each patient who was admitted to...

...ICU admission, return to baseline neurological function, and hospital discharge, regardless of the method of CPR, we examined the relationship of these endpoints and different clinical variables using data from both...

...ROSC and were admitted to the ICU with downtimes less than 4 minutes after ACD CPR (73%) compared with standard CPR (33%) (P<.05). In patients with downtimes between 4 and 9 minutes, ACD CPR appeared to be more effective, but the differences between the two methods of CPR were less pronounced. Six patients with unknown downtimes were admitted to the ICU, and three of these six patients, all in the standard CPR group, had

a full recovery.

[TABULAR DATA 5 OMITTED]

Similar potential benefits of ACD CPR were observed when analysis was limited to victims of witnessed arrests (Table 5). In witnessed arrests, 50% of the patients in the ACD CPR group were admitted to the ICU vs 31% in the standard CPR group (P<.10). A significant improvement in the rates of ROSC and ICU admission differences...

...witnessed arrests with less than 10 minutes of downtime, 59% of patients in the ACD CPR group vs 33% of patients in the standard CPR group were admitted to the ICU (P<.02; 95% CI, 4% to 48%). Based on...

...patients in the ACD group and 20% of the the 49 patients in the standard CPR group were discharged from the hospital (P=. 17; 95% CI, -2% to 38%).

The number...

...of patients who remained comatose after ICU admission was similar regardless of the method of  $\mbox{CPR}$  (eight of 21 patients after ACD  $\mbox{CPR}$  vs six of 20 patients after standard  $\mbox{CPR}$ ; P=.6).

Potential complications as a result of use of either CPR method were monitored throughout the study. Chest roentgenograms were obtained in all patients admitted to the ICU. In the standard CPR group, there were seven patients with rib and/or sternal fractures, one patient with a...

...arrival of the first response team, 17 (22%) of the 77 patients in the standard  $\mbox{CPR}$  group and in 13 (25%) of the 53 patients in the ACD  $\mbox{CPR}$  group had evidence of vomiting. During or after  $\mbox{CPR}$ , an additional five patients in the standard group and four patients in the ACD group...

...the device and the sternum secondary to a friction burn. One patient in the standard CPR group also had a superficial denuding of skin over the sternum, but the difference between statistically significant P<.01).

In the 53 patients in whom the ACD CPR device was used, paramedic unit captains reported that suction was good to excellent 46 times...

...patients older than 8 years in nontraumatic, normothermic out-of-hospital cardiopulmonary arrest who received CPR during the same 10-month period in the year prior to our study. During that time, 53 (36%) of patients who received CPR had an ROSC, 32 (22%) were admitted to the ICU, 14 (9%) were alert and...

...retrospectively obtain reliable information related to whether the arrests were witnessed, the use of bystander CPR, the call response interval, the initial rhythm, or the duration of downtime.

COMMENT

Outcomes Analyses

The purpose of this study was to prospectively examine the efficacy of ACD CPR in patients with out-of-hospital cardiac arrest. The results demonstrate that in two groups...

...characteristics, there was a trend toward increased rates of ROSC and ICU admission after ACD  $\,$  CPR  $\,$  when compared with standard  $\,$  CPR  $\,$  In patients with less than 10 minutes between collapse and arrival of the first response...

...to the scene, there was a significant increase in the ICU admission rates with ACD  $\,$  CPR  $\,$  (59%) compared with standard  $\,$  CPR  $\,$  (33%) (P<.02). Improvement in short-term survival in victims of out-of-hospital cardiac arrest of this magnitude has not been reported since the first description of manual  $\,$  CPR  $\,$  more than three decades ago.[11-14]

The duration between the time of collapse and the initiation of CPR

was found to be highly associated with a positive outcome, similar to observations by others who have found standard CPR to be most effective when initiated less than 4 minutes after cardiac arrest.[11] Therefore, we performed subset analysis on patients with relatively short downtimes and found ACD CPR was significantly more effective than standard CPR with less than 4 minutes of CPR: more than 80% of the patients had an ROSC after ACD CPR compared with 33% after standard CPR (P<.01), and 73% of the patients were admitted to the ICU after ACD CPR compared with 33% after standard CPR (P<.05). Although analysis of patients with downtimes from 4 to 9 minutes suggests that the use of ACD CPR may extend the window of opportunity between the time of arrest and the initiation of CPR that can ultimately lead to a successful outcome, more patients will be needed to demonstrate...

...minutes, return to baseline neurological function was observed in 31% of the patients after ACD  $\,$  CPR and 20% of the patients after standard  $\,$  CPR  $\,$  (P=.27). Included in the standard  $\,$  CPR  $\,$  group were two patients who received chest compressions for less than 30 seconds prior to...

 $\dots$  comatose or neurologically impaired after admission to the ICU was similar with both methods of  $\ensuremath{\,\text{CPR}}$  .

No significant differences in the complication rates were observed in patients admitted to the hospital with the use of ACD  $\,$  CPR  $\,$  compared with standard  $\,$  CPR  $\,$ , with one exception. There was a significant increase in localized hematomas in patients receiving ACD  $\,$  CPR  $\,$ . The contact point between the device and the chest wall has subsequently been redesigned to

...demonstrate that suction was adequate to good in more than 90% of patients when ACD CPR was performed. Despite the presence of significant chest hair or large breasts, adequate suction could...

...in the vast majority of patients.

This study adds to the growing evidence that ACD CPR may improve outcomes for some patients in cardiac arrest.[4,5,8,15-17] Two recent in-hospital studies demonstrated a similar improvement in the ICU admission rate between ACD CPR and standard CPR.[15,16] There were too few patients to know with certainty about long-term outcomes...

...the studies were terminated. In May 1993, the FDA stopped all clinical trials of ACD CPR in the United States until safety and efficacy are assessed in a large multicenter in...

...being enrolled in the study. Thus, it will not be possible to further evaluate ACD CPR efficacy in patients in out-of-hospital cardiac arrest for several years in the United States. Larger in-hospital and prehospital studies will be needed to know definitively whether ACD CPR will improve long-term clinical outcomes.

Study Variables

The evaluation of any type of CPR efficacy is dependent on the effectiveness and structure of the entire EMS system. St Paul...personnel included paramedics who were capable of delivering early defibrillation. All EMS personnel have annual CPR training and received training immediately prior to beginning this study and prior to the first...

...the St Paul adult population has received formal training, at least one time, in standard CPR . Thus, all of these factors, when considered as a whole, may contribute to the potential benefits of ACD CPR observed in St Paul.

To determine whether participation in our study altered ICU admission

rates in the standard CPR group compared with historical controls, we examined the records of all victims of nontraumatic, normothermic cardiac arrest who received standard CPR during the same 10-month period from the previous year. The total number of patients...

...compared with 17% during our study (P<.1). Although the ICU admission rates with standard CPR were similar, the improvement in neurological function in patients with standard CPR in our study group suggests that there may have been a "training effect" or Hawthorne effect from being in a study. The importance of training with both methods of CPR cannot be overemphasized. In our study, we underscored the notable differences in feel and practice between standard CPR and ACD CPR during the training to help ensure correct practice of the two techniques.

We intentionally designed ...

 $\dots$ had arrived at the scene and, despite extensive training and patient assignment to receive ACD  $\ \ CPR$ , neglected to use the ACD device at the moment of the arrest. Careful review of...

...first responders. Clinical outcomes of these eight patients were similar to others who received standard CPR . Nonetheless, the likelihood for treatment assignment errors, with the unassigned use of standard CPR since it does not involve taking out an additional piece of equipment, remains a potential problem for any study comparing manual CPR with an alternative method.

Conclusions

This study demonstrates that ACD  $\,$  CPR  $\,$  appears to be more effective than standard  $\,$  CPR  $\,$  in a well-defined subset of victims of out-of-hospital cardiac arrest during the critical initial phases of  $\,$  resuscitation  $\,$ . Based on this study, a larger study should be performed to evaluate the potential long-term benefits of ACD  $\,$  CPR  $\,$ .

We thank the members of the St Paul Fire Department and St Paul-Ramsey Emergency...

# ...manuscript.

References

[1.] Emergency Cardiac Care Committee and Subcommittees, American Heart Association. Guidelines for cardiopulmonary resuscitation and emergency cardiac care. JAMA. 1992;268:2171-2298. [2.] Becker LB, Smith DW, Rhodes...

...rates. Ann Emerg Med. 1993;22:86-91. [3.] Lurie KG, Lindo C, Chin J. CPR: the P stands for plumber's helper. JAMA. 1990;264:1661. [4.] Cohen TJ, Tucker KJ, Lurie KG, et al. Active compression-decompression: a new method of cardiopulmonary resuscitation. JAMA. 1992;267:2916-2923. [5.] Shultz JJ, Coffeen P, Sweeney M, et al. Evaluation of standard and active compression-decompression CPR in an acute human model of ventricular fibrillation. Circulation. 1994;89:684-693. [6.] Chang...

...Shultz JJ, Bache R.J, White CW. Tissue perfusion during standard vs active compression decompression CPR in the dog. Chest. In press. [7.] Lindner K, Pfenninger E, Lurie KG, Schurmann W, Lindner I. Effects of active compression-decompression resuscitation on myocardial and cerebral blood flow in pigs. Circulation. 1993;88:1254-1263. [8.] Rivers...

... Smithline HA, Lurie KG, Nowak RM. A Comparison of mechanical, standard and active compression-decompression CPR in out-of-hospital cardiac arrest patients. Circulation. 1993;88:I-193. Abstract. [9.] Cumniins...

... Ann Intern Med. 1986; 105: 429-435. [11.] Eisenberg MS, Bergner L,

Hallstrom A. Cardiac resuscitation in the community: importance of rapid provision and implications for program planning. JAMA. 1979;241...

- ...1067. [13.] Mateer Jr, Stueven HA, Thompson BM, Aprahamian C, Darin JC. Pre-hospital IAC- CPR versus standard CPR: paramedic resuscitation of cardiac arrests. Am J Emerg Med. 1985;3:143-146. [14.] Brown CG, Martin...
- ...Cohen TJ, Goldner BG, Maccaro PC, et al. A comparison of active compression-decompression cardiopulmonary resuscitation with standard cardiopulmonary resuscitation for cardiac arrests occurring in the hospital. N Engl J Med. 1993;329: 1918-1921...
- ...Tucker KJ, Galli F, Savitt MA, Kahsai D, Bresnahan L, Redberg RF. Active compression-decompression resuscitation: effects on resuscitation success after in-hospital arrest. Circulation. 1993;88: I-10. Abstract. [17.] Malzer R, Knappitsch G, Donanovits H, Sterz F. Active decompression during external cardiac massage: will the rescue breathing become superfluous? Intensivmedizin Notfallmedizin. 1993;30: 260-261. Abstract. From

DESCRIPTORS: CPR (First aid... 19940511

6/3,K/14 (Item 11 from file: 148)
DIALOG(R)File 148:Gale Group Trade & Industry DB
(c) 2004 The Gale Group. All rts. reserv.

05917157 SUPPLIER NUMBER: 12437884 (USE FORMAT 7 OR 9 FOR FULL TEXT)

Active compression-decompression: a new method of cardiopulmonary

resuscitation.

Cohen, Todd J.; Tucker, Kelly J.; Lurie, Keith G.; Redberg, Rita F.; Dutton, John P.; Dwyer, Kathy A.; Schwab, Theresa M.; Chin, Michael C.; Gelb, Alan M.; Scheinman, Melvin M.; Schiller, Nelson B.; Callaham, Michael

JAMA, The Journal of the American Medical Association, v267, n21, p2916(8) June 3, 1992

ISSN: 0098-7484 LANGUAGE: ENGLISH RECORD TYPE: FULLTEXT; ABSTRACT WORD COUNT: 5157 LINE COUNT: 00437

Active compression-decompression: a new method of cardiopulmonary resuscitation . . . . Lurie, Keith G

ABSTRACT: A mechanical device that allows doctors to decompress the chest actively during cardiopulmonary resuscitation (CPR) rather than passively may be more effective in restoring heart function in patients who are...

...received conventional care for at least 10 minutes. Each patient was randomized to receive either CPR with an active compression-decompression (ACD) device or traditional CPR for two minutes; then they were switched to the alternate method. Blood pressure in eight patients increased significantly when they were switched from CPR to ACD- CPR. Doppler echocardiography during ACD- CPR showed that blood flow from the heart increased, compared to CPR. The echocardiogram also showed that the mitral valve, which controls the flow of blood into the left ventricle, opened much more widely during the relaxation phase of ACD- CPR, compared to CPR. ACD- CPR restored a stable rhythm in three of the patients, but none survived.

AUTHOR ABSTRACT: Objective. -- To described and compare with standard

cardiopulmonary resuscitation (CPR) in humans a new form of CPR that involves both active compression and active decompression of the chest. Design.--Patients in cardiac...

...failed were randomized to receive 2 minutes of either standard or active compression-decompression (ACD) CPR using a custom, hand-held suction device, followed by 2 minutes of the alternate technique. The ACD device was applied midsternum and used to perform CPR according to the guidelines of the American Heart Association: 80 compressions per minute, compression depth of 3.8 to 5 cm, 50% duty cycle, and constant-volume ventilation. Mechanical Thumper CPR was also compared in five patients. End-tidal carbon dioxide ([ETCO.sub.2]) concentrations and...

...or -] SD [ETCO.sub.2] was 4.3 [+ or -] 3.8 mm Hg with standard CPR and 9.0 [+ or -] 3.9 mm Hg with ACD CPR (P<.0001). Systolic arterial pressure with standard CPR was 52.5 [+ or -] 14.0 mm Hg and with ACD CPR , 88.9 [+ or -] mm Hq (P<.003). The velocity time integral increased from 7.3 [+or -] 2.6 cm with standard CPR to 17.5 [+ or -] 5.6 cm with ACD CPR (P<.0001), and diastolic filling times increased from 0.23 [+ or -] .09 seconds with standard PCP to 0.37 [+ or -]. 12 seconds with ACD CPR (P<.004). Mechanical Thumper CPR consistently underperformed both standard and ACD CPR . Minute ventilation obtained in four patients during ACD CPR without endotracheal ventilation was 6.6 [+ or -] 0.9 L/min. After 1 hour of standard CPR failed, three of 10 patients randomized to ACD CPR rapidly converted to a hemodynamically stable rhythm following 2 minutes for ACD CPR . Conclusion. -- ACD CPR is a simple manual technique that improved cardiopulmonary circulation in 10 patients during cardiac arrest. Although ACD CPR may have produced a return of spontaneous circulation in three patients refractory to standard measures...

### TEXT:

Despite the nearly universal application of standard cardiopulmonary resuscitation ( CPR ), most out-of-hospital cardiac arrest patients do not survive.[1-5] In an effort...

The standard method of manual CPR , first described by Kouwenhoven et al[25] more than three decades ago, relies on the...

...and passive decompression of the chest wall. The importance of an active decompression phase of CPR was recently suggested by an anecdotal report of successful cardiac resuscitation using a "plumber's helper" (household drain plunger) applied to the anterior chest wall.[26...

...that a simple suction device could assist chest wall expansion and improve the hemodynamics during CPR, active compression-decompression (ACD) resuscitation was compared with standard CPR in a canine model of cardiac arrest.[27] In eight dogs, cardiac output, systolic aortic pressure, coronary artery perfusion pressure, and minute ventilation were significantly augmented with ACD resuscitation compared with standard CPR.

Based on these results, we proceeded to test the same technique in humans. The purpose of this study was to prospectively compare ACD resuscitation with standard methods of CPR in a randomized fashion in 10 humans during cardiac arrest.

METHODS

# ACD Resuscitation

The ACD device consists of a rubber suction header, bellows, and handle, with a radius...

...both force and depth of compression to ensure chest compressions similar

to those with standard CPR . Preliminary mannequin testing was performed to ensure compression equivalent to that with standard CPR . The monitoring gauge was marked with three compression target levels: 29.25 kg for a...

...kg for an average man, and 49.5 kg for a large man. For ACD  $\ensuremath{\mathtt{CPR}}$  , the device was aligned midsternum at the level of the nipples; compression was performed in...

... Fire Department fire fighters and paramedics on all patients. On arrival in the emergency department, resuscitation was directed by either the attending physician or senior resident physician according to ACLS guidelines.[29] Patients were intubated orotrachaelly (if not already intubated), and bag ventilation with a 100% fraction of inspired oxygen was used.

While standard ACLS was being performed, a special ACD code team prepared for a randomized trial of ACD vs standard CPR . Once patients were monitored with intra-arterial pressure transducers, transesophageal echocardiography, and capnometry, if they... ...randomized (via a random numbers table) to receive 2 minutes of either standard or ACD CPR followed sequentially by 2 minutes of the alternate technique. Constant-volume hand-assisted bag ventilation with 100% oxygen was provided by a registered respiratory therapist. Both methods of CPR were performed at 80 compressions per minute (metronome synchronized) with a 50% duty cycle in accordance with AHA guidelines.[28] After the 4-minute experimental CPR protocol, hand-assisted bag ventilation was stopped in four patients and ACD resuscitation was performed for 1 additional minute

while minute ventilation was measured using a volume spirometer. After 1 minute, hand-assisted ventilation was resumed. To discourage operator bias, when possible, standard CPR was performed by an ACLS-certified physician independent of the ACD code team. In addition...

...trial.

Samples for arterial blood gas measurements were collected before beginning the randomized trial of CPR and after completion of each 2-minute CPR segment; arterial placement was confirmed by return of well-oxygenated blood from the pressure catheter...

- ...concentrations were recorded at baseline and at 30-second intervals during 2 minutes of each CPR technique. Transmitral Doppler flow was recorded using a Sono 500 ultrasound system with a 21362A... ...the protocol. In addition, two-dimensional transesophageal echocardiographic imaging was performed before and after each CPR method. Random number sequences were used to code Doppler echocardiographic tapes to enable data analysis...
- ...ACD code team leader coordinated the protocol and monitored the depth and force of ACD CPR performed by another team member. A cardiologist placed the transesophageal probe and recorded two-dimension...
- ...data. A third member secured a femoral arterial line for pressure minutes. A fourth member was responsible for calibrating ... Throughout the protocol the emergency department attending or resident physician maintained complete control of the resuscitative efforts. Decisions to terminate resuscitation and postresuscitation supportive measures were made by the emergency attending or resident physician. Patients did...
- ...before and after data collection. No patients received sodium bicarbonate at any time during their resuscitation .

Data Collection and Analysis

Forward transmitral flow (from the mitral valve leaflet tips) was continuously...

...analyzed off-line by an echocardiography not present at the arrest and blind to the CPR techique. Echocardiographic measurements included the trasmitral valve velocity time integral, left ventricular and left atrial

...concentrations were recorded every 30 second during 2 minutes of standard, ACD, and mechanical Thumper CPR. Hemodynamic and capnometry data were determined for each technique after 30, 60, 90, and 120...

...examined to determine details of treatment in the field, time between arrest and commencement of **resuscitation**, and transport time from the site of the arrest to the emergency department.

RESULTS

Patient...

...emergency department (patient 1) and one in the coronary care unit (patient 9). The experimental CPR protocol was started approximately 30 minutes after patients arrived in the emergency department. In seven of 10 cases, standard CPR was performed by an ACLS-certified physician who was not part of the special ACD...

...five patients, right ventricular displacement was quantitatively determined during compression during both ACD and standard  $\tt CPR$  (via transesophageal echocardiographic imaging). Displacement of the right ventricle during the compression phase of ACD  $\tt CPR$  was 4.3 [+ or -] 1.3 cm vs. 3.6 [+ or -] 1.5 cm with standard  $\tt CPR$  (not significant). No randomized standard  $\tt CPR$  data were obtained in patient 10 because of successful resuscitation after randomization to ACD  $\tt CPR$ .

Table 1 shows the characteristics of each patient. The causes of arrest, as indicated by...

...asystole (one patient), or electrochemical dissociation (three patients). The time between arrest an when prehospital CPR was started varied considerably (0 to 20 minutes). The mean interval from the time of

...carbon dioxide concentrations were measured in eight of 10 patients during both ACD had standard CPR. The mean [ETco.sub.2] concentration increased from 4.3 [+ or -] 3.8 mm Hg with standard CPR to 9.0 [+ or -] 3.9 mm Hg with ACD CPR (P<.0001) (Fig 2).

Femoral arterial pressures were recorded in eight of 10 patients. The systolic arterial pressure increased from 52.5 [+ or -] 14.0 mm Hg with standard CPR to 88.9 [+ or -] 24.7 mm Hg with ACD CPR (P<.003) (Fig 3). There was no appreciable difference in diastolic arterial pressure between CPR techniques (Fig 3). Arterial pressure waveforms during standard CPR were of lower amplitude and more blunt than those during ACD CPR. A dicrotic notch was evident during ACD CPR but not during standard CPR (Fig 4).

No significant differences in arterial blood gas measurements were observed between the various  $\mbox{CPR}$  methods (Table 2). The mean initial arterial pH was 6.9 [+ or -] 0.18. Initial...

...was no significant difference between arterial blood gas measurements obtained after 2 minutes of standard  $\mbox{CPR}$  and those obtained after 2 minutes of ACD  $\mbox{CPR}$  .

Spirometry in four patients during ACD CPR without endotracheal ventilation revealed a minute ventilation of 6.6 [+ or -] 0.4 L/min

(range, 6.0 to 7.8 L/min). This is equivalent to a **ventilatory** volume of approximately 80 mL per compression. Negative inspiratory force was measured in one patient...by transesophageal Doppler echocardiography revealed a significant improvement in forward cardiac blood flow with ACD CPR compared with either standard or mechanical Thumper CPR. The transmitral valve velocity time integral increased from 7.3 [+ or -] 2.6 cm with standard CPR to 17.5 [+ or -] 5.6 cm with ACD CPR (P<.0001) (Fig 5). The mean diastolic filling time, determined by measuring either the left...

...was increased during the decompression phase from 0.23 [+ or -] 0.09 second with standard CPR to 0.37 [+ or -] 0.12 seconds with ACD CPR (P<.004) (Fig 6). In addition, there was a qualitative increase in left atrial size during the decompression (diastole) with ACD CPR compared with passive chest relaxation with standard CPR. Spontaneous contrast on two-dimensional transesophageal echocardiographic is an indicator of stasis of blood flow.[32] This spontaneous contrast was common during standard CPR but tended to clear (indicating improved blood flow) in all patients with ACD CPR.

Transesophageal two-dimensional echocardiographic imaging during standard CPR revealed that the right ventricle was compressed and the atrioventricular valves were closed. Figure 7...

...valve, appearing to facilitate ventricular filling.

Comparison With Mechanical Thumper

In addition to comparing standard CPR with ACD CPR, physiologic measurements were made in five patients who underwent mechanical Thumper CPR immediately prior to the randomized CPR trial. The compression depth was set (by the attending emergency physician) according to the manufacturer...

...generated lower systolic arterial pressures and [ETCO.sub.2] concentrations than both standard and ACD  $\,$  CPR  $\,$ . Figure 4 displays the arterial pressure recordings from a representative patient (patient 5), demonstrating a...

 $\ldots$  improvement in systolic arterial pressures as one progresses from mechanical Thumper to standard to ACD  $\ensuremath{\mathtt{CPR}}$  .

Electromechanical Effects of ACD CPR

In three of 10 patients (patients 1, 5, and 10) who underwent prolonged resuscitation with standard CPR (>1 hour), ACD CPR applied for only 2 minuted restored a hemodynamically stable rhythm. No patient in whom ACD CPR failed was resuscitated by standard CPR. Sinus rhythm was restored within less than 2 minutes after the application of ACD CPR in two patients (patients 1 and 10), and patient 5 converted from ventricular fibrillation to...

...later time due to either incessant tachyarrhythmias associated with hemodynamic instability or concern that prolonged **resuscitation** had resulted in severe brain damage.

COMMENT

This study demonstrates that ACD CPR, a simple manual technique, significantly improves cardiopulmonary circulation in humans during cardiac arrest compared with standard CPR. In contrast to previous techniques that require complicated machinery, an additional operator, or an awake patient, ACD CPR is a relatively simple variation on standard CPR. [7,9,15] The rate and depth and compression are those recommended by the AHA for standard manual CPR. [28] The device can be used with minimal training, requires no setup time, is used...

...been shown to be a reliable predictor of coronary perfusion pressure and

of likelihood of **resuscitation** from cardiac arrest.[35,42] The [ETCO.sub.2] concentration was increased from baseline in all of the four patients for whom it was recorded during ACD **CPR**. Such increases were not observed with either standard or mechanical Thumper **CPR**. There were no significant changes in arterial blood gas measurements with any technique in this...

...End-tidal carbon dioxide concentration during cardiac arrest has been shown to predict successful initial resuscitation with a sensitivity of 45% and a specificity of 94% in a similar patient population at our institution. [43] The average [ETCO.sub.2] concentration obtained with ACD CPR in these patients (9 mm Hg) has been previously associated with a 28% chance of initial resuscitation in our patient population, but the level obtained with standard CPR has been associated with a chance of initial resuscitation lower than 1%. [35,43] In fact, ACD CPR initially resuscitated 30% of patients in this study.

A significant increase in systolic arterial pressure was observed with ACD CPR compared with standard and mechanical Thumper CPR. Such increases in systolic arterial pressure have been associated with improved cerebral perfusion in humans...

- ...sub.2] concentration, functional improvements were quantitatively observed via transesophageal Doppler echocardiography imaging during ACD CPR. The velocity time integral (an analogue of cardiac output) and prolonged diastolic filling were augmented with ACD CPR compared with standard and mechanical Thumper CPR. These techniques of measurement have been validated and are highly accurate at cardiac outputs as...
- ...31] Spontaneous contrast on echocardiography is an indicator of vascular stasis and was common during CPR .[32] However, ACD CPR usually produced a clearing of spontaneous contrast, indicating improved blood flow. We speculate that ACD CPR produces a negative intrathoracic pressure during decompression and thereby improves venous return, transmitral ventricular filling, and cardiac output.

ACD CPR without hand-assisted orotracheal ventilation resulted in ventilation greater than 6 L/min. The significance of this observation remains unknown, but perhaps ACD CPR assists ventilation during cardiac arrest. No significant change in [PCO.sub.2] was observed after a short intervention of ACD compared with standard CPR.

There were a number of limitations to this study. First, patients had already undergone prolonged **resuscitation** before entry into the trial and thus had an extremely small chance of successful outcome...

...impact of the ACD device on survival is predicated on its application as soon as CPR is begun. Although ACD CPR restored a hemodynamically stable rhythm in three of 10 patients who underwent prolonged resuscitation , conclusions abou the impact of ACD CPR on survival cannot be made from these data. Second, the compression force of both standard and ACD CPR might have been variable across different operators and techniques. We attempted to control for this by closely and constantly monitoring compression rate and depth, having noninvestigators perform standard CPR , using a calibrated compression gauge with ACD CPR (to ensure comparable compression to standard CPR ), and comparing the technique with mechanical Thumper CPR in half the patients. The blood pressures produced in our patients by standard CPR were similar to those reported by other investigators.[33,34,44,45] Additionally, systolic blood pressures comparable to those produced by ACD CPR cannot be achieved by increasing compression force if the rate is held constant. [46] Since... ...no significant difference in right ventricullar displacement during the compression phase of standard or ACD CPR , we believe that the

improvements in cardiopulmonary circulation probably resulted from active chest decompression. Our...

...was designed to measure the short-term physiologic and hemodynamic effects of ACD vs standard CPR in a randomized fashion. We did not assess the effects of ACD CPR on either regional perfusion or long-term survival. We did, however, measure the efficacy of...

...concentration, which has previously been shown to correlate well with coronary-perfusion-pressure-and-initial--resuscitation..[35-42]\_Fourth,\_\_\_epinephrine was given to patients prior to the data-collection period, and

...variables. However, our study was a crossover design in which half the patients received ACD CPR first and half received standard CPR first; this design should cancel out any such effects.

In conclusion, ACD resuscitation offers a variation on standard manual CPR that converts the decompression phase from a passive to an active process. With ACD resuscitation, cardiovascular pulmonary and systemic hemodynamics were significantly improved in this small study of patients late in cardiac arrest. Further studies are necessary to determine the effects of ACD CPR on regional perfusion and long-term survival.

This study was supported in part by an...

## ...Denmark.

We gratefully acknowledge the assistance of the following individuals and members of the Cardiopulmonary Resuscitation Working Group: Sheryl Anderson, RN, Tina Bailey, RN, Christopher Barton, MD, Robert Buscho, MD, Kanu...

...Weber, MD, and Nancy West, RN.

References

- [1] Eisenberg MS, Bergner L, Hallstrom A. Cardiac resuscitation in the community: importance of rapid provision and implications for program planning. JAMA. 1979;241...
- ...2:1223-1225. [5]Bedell SE, Delbanco TL, Cook EF, Epstein FH. Survival after cardiopulmonary resuscitation in the hospital. N Engl J Med. 1983;309:569-576. [6]Del Guercio LRM...
- ...White BC, et al. Perfusion of cerebral cortex by use of abdominal counterpulsation during cardiopulmonary resuscitation. Am J Emerg Med. 1984;2:391-393. [9]Chandra N, Weisfeld M, Tsitlik J, et al. Augmentation of cardic flow during cardiopulmonary resuscitation by ventilation at high airway pressure simultaneous with chest compression. Am J Cardiol. 1981-48: 1053-1063...
- ...intrathoraric pressure. Circulation. 1991;84: 279-286. [11] Berryman CR, Phillips GM. Interposed abdominal compression- CPR in human subjects. Ann Emerg Med. 1984;13:226-229. [12] Kaplan BC, Civetta JM...
- ...Criley JM, Blaufuss AH, Kissel GL. Cough-induced cardiac compression: self-administered form of cardiopulmonary resuscitation . JAMA. 1976;236:1246-1250. [14]Sack JB, Kesselbrenner MB, Jarrad A, Bregman D. Effect of interposed abdominal counterpulsation on resuscitation outcome during asystole and electromechanical dissociation. J Am Coll Cardiol. 1991;17:179a. Abstract. [15]Spalding JMK, Smith AC. Clinical Practice and Physiology of Artificial Respiration . Oxford, England: Blackwell Scienctific Publications; 1963. [16]Krischer JP, Fine EG, Weisfeldt ML, et al. Comparison of prehospital conventional and simultaneous compression-

ventilation cardiopulmonary resuscitation. Crit Care Med. 1989;17:1263-1269. [17] Bircher N, Safar P. Comparison of standard and |new' closed-chest CPR and open-chest CPR in dogs. Crit Care Med. 1981;9:384-385. [18] Niemann JT, Rosborough ...JP, Ung S, et al. Hemodynamic effects of continuous abdominal binding during cardiac arrest and resuscitation . Am J Cardiol. 1984;53:269-274. [19] Niemann JT, Rosborough JP, Niskanen RA, et al. Mechanical |cough' cardiopulmonary resuscitation during cardiac arrest in dogs. Am J Cardiol. 1985;55:199-204. [20] Halperin HR, Guerci AD, Chandra N, et al. Vest inflation without simultaneous ventilation during cardiac arrest in dogs: improved survival from prolonged cardiopulmonary resuscitation . Circulation. 1986;74: 1407-1415. [21] Bircher N, Safar P. Stewart R. A comparison of standard, MAST-augmented and open-chest CPR in dogs: a preliminary investigation. Crit Care Med. 1980;8:147-152. [22] Berryman CR, Phillips GM. Interposed abdominal compression- CPR in human subjects. Ann Emerg Med. 1984;13:226-229. [23] Howard M, Carrubba C, Foss F, et al. Interposed abdominal compression- CPR: its effects on parameters of coronary perfusion in human subjects. Ann Emerg Med. 1987;16...

...Weisfeldt ML, Guerci AD, Nagel G, Chandra N. Comparison of prehospital conventional and simultaneous compression—ventilation cardiopulmonary resuscitation. Crit Care Med. 1989; 17:1263-1269. [25]Kouwenhoven WB, Jude JR, Knickerbocker GG. Closed chest cardiac massage. JAMA. 1960;173:1064-1067. [26]Lurie KG, Lindo C, Chin J. CPR: the P stands for plumber's helper. JAMA. 1990;264:1661. [27]Cohen TJ, Tucker KJ, Redberg RF, et al. Active compression—decompression resuscitation: a new method of cardiopulmonary resuscitation. Circulation. 1991;84:II-9. Abstract. [28]American Heart Association. Standards and guidelines for cardiopulmonary resuscitation ( CPR ) and emergency cardiac care (ECC). JAMA. 1986;255:2905-2973. [29]Fisher DC, Sahn DJ...

...Martin GB, Nowak RM. Aortic-carotic artery pressure differences and cephalic perfusion pressure during cardiopulmonary resuscitation in humans. Crit Care Med. 1991;19:1012-1017. [34]McDonald JL. Systolic and mean arterial pressures during manual and mechanical CPR in humans. Ann Emerg Med. 1982;11:292-295. [35]Callaham M, Barton C. Prediction of outcome of cardiopulmonary resuscitation from ent-tidal carbon dioxide concentration. Crit Care Med. 1990;18:358-362. [36]Garnett AR, Ornato JP, Gonzales ER, Johnson EB. End-tidal carbon dioxide monitoring during cardiopulmonary resuscitation . JAMA. 1987;257:512-515. [37]Sanders AB, Atlas M. Ewy GA, Kern KB, Bragg...

...Rackow EC, Grundler WG. End-tidal [Co.sub.2] as a guide to successful cardiopulmonary resuscitation: a preliminary report. Crit Care Med. 1985;13:910-911. [39]Gudipati CV, Weil MH, Bisera UJ, Deshmukh HG, Rackow EC. Expired carbon dioxide: a noninvasive monitor of cardiopulmonary resuscitation, Circulation. 1988;77:234-239. [40]Sanders AB, Ewy GA, Bragg S, Atlas M, Kern KB. Expired [PCO.sub.2] as a prognostic indicator of successful resuscitation from cardiac arrest. Ann Emerg Med. 1985;14:948-952. [41]Weil MH, Bisera J...

...Kern KB, Otto CW, Milander MM, Ewy GA. End-tidal carbon dioxide monitoring during cardiopulmonary resuscitations: a prognostic indicator for survival. JAMA. 1989;262:1347-1351. [43]Callaham M. Barton C...

...The effect of epinephrine on the ability of [ETCO.sub.2] readings to predict initial resuscitation from cardiac arrest. Crit Care Med. In press. [44]Chandra NC, Tsitlik JE, Halperin HR, Guercia AD, Weisfeldt ML. Observations of hemodynamics during human cardiopulmonary resuscitation. Crit Care Med. 1990;18:929-934. [45]Martin GB, Carden DL, Nowak RM,

Lewinter...

- ...Johnston W, Tomlanovich MC. Aortic and right atrial pressures during standard and simultaneous compression and **ventilation CPR** in human beings. Ann Emerg Med. 1986;15:125-130. [46]Oranto JP, Levine RL...
- ...applied chest compression force on systemic arterial pressure and end-tidal carbon dioxide concentration during CPR in human beings. Ann Emerg Med. 1989;18:732-737. Todd J. Cohen, MD; Kelly J. Tucker, MD; Keith G. Lurie, MD; Rita F. Redberg, MD; John P. Dutton; Kathy A. Dwyer, RN; Theresa M. Schwab...
- ...Melvin M. Scheinman, MD; Nelson B. Schiller, MD; Michael L. Callaham, MD; for the Cardiopulmonary Resuscitation Working Group From the Department of Medicine and the Cardiovascular Research Institute (Drs Cohen, Tucker...
- ...Cornell University Medical College, Manhasset, NY. A partial listing of the members of the Cardiopulmonary **Resuscitation** Working Group appears in the acknowledgments at the end of the article. Presented at the...

DESCRIPTORS: CPR (First aid... 19920603

6/3,K/15 (Item 12 from file: 148)
DIALOG(R)File 148:Gale Group Trade & Industry DB (c)2004 The Gale Group. All rts. reserv.

04905571 SUPPLIER NUMBER: 10405375 (USE FORMAT 7 OR 9 FOR FULL TEXT)
CPR: the P stands for plumber's helper. (cardiopulmonary resuscitation)
(letter to the editor)

Lurie, Keith G.; Lindo, Clinton; Chin, Jerome

JAMA, The Journal of the American Medical Association, v264, n13, p1661(1) Oct 3, 1990

DOCUMENT TYPE: letter to the editor ISSN: 0098-7484 LANGUAGE:

ENGLISH RECORD TYPE: FULLTEXT WORD COUNT: 405 LINE COUNT: 00033

CPR: the P stands for plumber's helper. (cardiopulmonary resuscitation) (letter to the editor)
Lurie, Keith G ...

# TEXT:

CPR: The P Stands for Plumber's Helper To the Editor. -- Though novel methods of cardiac resusscitation exist, the traditional cardiopulmonary resuscitation (CPR) techniques recommended by the American Heart Association have a proven track record. [1] This is...

- ...collapsed in front of his family. He was unrousable. His son, poorly trained in traditional CPR, attemted to ventilate his father, but the patient did not respond. The son then attempted manual chest compression, but his father reportedly remained pulseless and breathless. The son then remembered that his mother had resuscitated her husband 6 months earlier with a toilet plunger. Thus, the son ran upstairs, took...
- ...minutes until the paramedics arrived. By that time the patient had begun to move and **breath** on his own. He was found to be incontinent of urine, though no signs of...
- ... effective chest compressor, but the suction between the chest wall

and the plunger generated significant negative pressure and served to ventilate the patient as well. The son, delighted that his mother's toilet plunger technique had...

...all the beds in our coronary care unit. We recommended that he take a basic CPR course but had to admit that it's hard to argue with success.

Keith G. Lurie, MD Clinton Lindo, MD Jerome Chin, MD Medical Center University of California San Francisco

[1.] Standard's and guidelines dor cardiopulmonary resuscitation (CPR) and emergency cardiac care (ECC). JAMA. 1980;244:453-509.

...DESCRIPTORS: CPR (First aid 19901003

6/3,K/16 (Item 1 from file: 149)
DIALOG(R)File 149:TGG Health&Wellness DB(SM)
(c) 2004 The Gale Group. All rts. reserv.

01766289 SUPPLIER NUMBER: 20581012 (USE FORMAT 7 OR 9 FOR FULL TEXT)
Optimizing standard cardiopulmonary resuscitation with an inspiratory
impedance threshold valve.

Lurie, Keith G. ; Mulligan, Katherine A.; McKnite, Scott; Detloff, Barry; Lindstrom, Paul; Lindner, Karl H Chest, v113, n4, p1084(7)

April,

1998

PUBLICATION FORMAT: Magazine/Journal; Refereed ISSN: 0012-3692 LANGUAGE: English RECORD TYPE: Fulltext TARGET AUDIENCE: Professional WORD COUNT: 3674 LINE COUNT: 00327

Optimizing standard cardiopulmonary resuscitation with an inspiratory impedance threshold valve.

Lurie, Keith G ...

### TEXT ·

...to assess whether intermittent impedance of inspiratory gas exchange improves the efficiency of standard cardiopulmonary  ${\tt resuscitation}$  (  ${\tt CPR}$  ).

Background; Standard CPR relies on the natural elastic recoil of the chest to transiently decrease intrathoracic pressures and thereby promote venous blood return to the heart. To further enhance the negative intrathoracic pressures during the "relaxation" phase of CPR, we tested the hypothesis that intermittent impedance to inspiratory gases during standard CPR increases coronary perfusion pressures and vital organ perfusion.

Methods: CPR was performed with a pneumatically driven automated device in a porcine model of ventricular fibrillation. Eight pigs were randomized to initially receive standard CPR alone, while seven pigs initially received standard CPR plus intermittent impedance to inspiratory gas exchange with a threshold valve set to -40 cm (H.sub.2)O. The compression: ventilation ratio was 5:1 and the compression rate was 80/min. At 7-min intervals the impedance threshold valve (ITV) was either added or removed from the ventilation circuit such that during the 28 min of CPR, each animal received two 7-min periods of CPR with the ITV and two 7-min periods without the valve. Results: Vital organ blood flow was significantly higher during CPR performed with the ITV than during CPR performed without the valve. Total left ventricular blood flow (mean (+ or -) SEM) (mL/min/g...

...vital organ blood flow and coronary perfusion pressure.

Conclusions: Intermittent impedance to inspiratory flow of respiratory gases during standard CPR significantly improves CPR efficiency during ventricular fibrillation. These studies underscore the importance of lowering intrathoracic pressures during the relaxation phase of CPR . (CHEST 1998; 113:1084-90)

Key words: active compression-decompression CPR; cardiac arrest; cardiopulmonary resuscitation; heart; impedance threshold valve; ventricular fibrillation

Abbreviations: ACD=active compression-decompression; CPP=coronary perfusion pressure; CPR = cardiopulmonary resuscitation; ITV=impedance threshold valve; NS=not significant

The potential value of increasing negative intrathoracic pressure during the decompression phase of cardiopulmonary resuscitation ( CPR ) with a new technique termed active compression-decompression (ACD) CPR has been described recently. 1-5 ACD CPR enhances the bellows-like action of the chest. Use of this method is associated with improved hemodynamic status in animal models and humans when compared with conventional manual CPR .(1-5) More recently, we demonstrated that the efficacy of ACD CPR could be further improved by insertion of an inspiratory impedance threshold valve (ITV) into the respiratory circuit. (6) In a porcine model of ventricular fibrillation, we observed that use of the ITV during ACD CPR , which physiologically mimics the clinical Mueller maneuver, lowers intrathoracic pressure during the decompression phase, thereby enhancing vital organ blood flow and lowering defibrillation energy requirements when compared with ACD CPR alone.(6) In the present study, we hypothesized that the use of an inspiratory impedance valve during standard closed-chest CPR, which also relies on the bellows-like action of the thorax, would enhance the negative intrathoracic pressure generated by the natural recoil of the chest during the decompression phase. As such, the...

...present investigation was to test this hypothesis by insertion of an inspiratory ITV into the **respir**atory circuit. We describe the measurements of central aortic pressures, coronary perfusion pressures, vital organ blood...

 $\dots$ induction of ventricular fibrillation, 5,000 U of sodium heparin was administered IV.

Closed-chest CPR was performed with a 6.5-cm circular compression pad positioned over the sternum. The... ...7100/66 computer; Apple Computer; Cupertino, Calif).(6)

The protocol was designed to compare standard CPR alone with standard CPR plus an inspiratory ITV. Each pig served as its own control. The experimental protocol is...termed "time 0." At this point, the pigs were assigned randomly to initially receive either CPR alone or CPR plus the ITV. The endotracheal tube (ET tube high-low JET, Mallinckrodt Inc; St. Louis) was immediately disconnected from the mechanical ventilator and the tube cuff pressure was assessed to ensure that it was adequate to seal the trachea. After 3 min of ventricular fibrillation, during which time no chest compressions or ventilation was performed, CPR was initiated with the automated device. The compression rate was 80/min with a 50...

 $\dots$  and that during the decompression phase the pad did not impede chest wall relaxation. (6)

Ventilatory support and automated standard CPR were performed simultaneously during CPR. Ventilation was provided by manual bag ventilation (Ambu bag; Glostrup, Denmark) and oxygen (8 L/min) as previously described.(3) Ventilatory support was continued throughout all experiments using manual bag ventilation with 10 L oxygen

supplementation. Hand-held **ventilation** was utilized after preliminary experiments showed that it was easier to interpose manual **ventilatory** efforts at the end of the decompression phase with the bag **ventilation** than with mechanical **ventilation**. Moreover, the mechanical **ventilators** available to us (including the Harvard animal **ventilator** (Harvard Apparatus; Dover, Mass) and the Siemens **ventilator** (Siemens; Munich Germany), which we have previously used, (1, 3, 6) had a significant amount of resistance to inspiration. That inspiratory resistance prevented us from testing our overall hypothesis. During **CPR**, lrespirations were delivered continuously at a rate of 16/min (one **breath** every five chest compressions) at a constant tidal volume of approximately 450 mL. As previously described, **ventilations** were delivered during the decompression phase of **CPR**.(1,6)

The ITV in this study consisted of two 20 cm (H.sub.2)O threshold valves (Ambu Anesthesia PEEP Valve 20, No. 194011000; Ambu, Inc; Glostrup, Denmark) connected in series between the endotracheal tube...

...the Ambu bag such that during the decompression phase, but in the absence of manual ventilation, the valves opened only with greater than -40~cm (H.sub.2)0 of inspiratory...

...than -40 cm (H.sub.2)0 of intrathoracic pressure was required for inspiration of respiratory gases during four of every five compression cycles during performance of CPR with the ITV. With standard CPR and without active bag ventilation, use of these threshold valves in series resulted in effectively no inspiratory movement of respiratory gases during the decompression phase of CPR. As shown in the protocol time line, at 7-min intervals, the ITV was either added or removed from the ventilation circuit such that during the 28 min of CPR, each animal received two 7-min periods of CPR with the valve and two 7-min periods without the valve.

Once CPR alone or CPR plus the ITV was initiated, the same method was performed continuously for 7 min. Radiolabeled...

... values are expressed as mean (+ or -) SEM. RESULTS

Seven pigs were randomized to initially receive  $\mathtt{CPR}$  with the ITV and eight pigs received  $\mathtt{CPR}$  initially without the ITV. There were no significant differences in the compression forces between groups...ITV.

(Figure 2 ILLUSTRATION OMITTED)

(TABULAR DATA 1 NOT REPRODUCIBLE IN ASCII)

During performance of CPR, there were no significant differences in aortic systolic pressure during the compression phase of CPR when the ITV was used (Table 1). Differences in the coronary perfusion pressures (CPPs) (diastolic...

...and Figs 3 and 2c (bottom)). The mean CPP during the entire 28 min of CPR tended to be higher during CPR with the ITV (14.8 (+ or -) 1.3) than during CPR without the ITV (12.5 (+ or -) 1.5; p=0.07).

(Figure 3 ILLUSTRATION OMITTED...

...yet statistically significant decrease in the CPP each time the ITV was removed from the **respiratory** circuit (Fig 2c (bottom)). In contrast, each time the ITV was added to the **respiratory** circuit, the mean CPP remained constant.

Use of the ITV during standard CPR also increased vital organ blood flow. The mean ventricular blood flow throughout the entire experiment was significantly higher during CPR +ITV than during CPR -ITV (+ITV, 0.32 (+ or -) 0.04; -ITV, 0.23 (+ or -) 0.03; p (is...

...with the measurement of the CPP, each time that the ITV was removed from

the respiratory circuit, there was a statistically significant decrease in the left ventricular blood flow within that...

...similar manner, the mean cerebral blood flow throughout the entire experiment was significantly higher during CPR with the valve when compared with no valve (+ITV, 0.23 (+ or -) 0.02; -ITV... ...02; p (is less than) 0.05). The cerebral blood flow was significantly higher during CPR with the ITV than without the ITV at two of the four time points (Fig...

...was also examined. The mean endocardial/epicardial ratio throughout the experiment was significantly higher during CPR with the ITV (0.95 (+ or -) 0.11) than without the ITV (0.81 (+ or...

...and 23 min, the pH was significantly higher in the group that started initially with CPR +ITV. Correspondingly, at 9 and 23 min, the P(CO.sub.2) was significantly lower in the group that started CPR +ITV.

DISCUSSION

Closed chest manual cardiac massage or standard CPR depends, in part, on the natural resilience of the chest wall to refill the heart with blood following each compression phase. This transient period of negative intrathoracic pressure is a critical aspect of any method of CPR . When the inflow of respiratory gases is impeded by an inspiratory threshold valve, equilibration of the negative intrathoracic pressure generated by the elastic recoil of the chest occurs to a greater extent by enhanced venous return and not by movement of respiratory gases. Results from the current study demonstrate that myocardial perfusion is increased by 40% during standard CPR in the presence of the ITV compared with standard CPR alone. The results further suggest that endocardial blood flow is increased with the use of the ITV. Overall, these results imply that insertion of an ITV into the respiratory circuit during standard CPR enhances the return of venous blood to the thoracic area. These findings are consistent with an earlier study in which the ITV was found to enhance the efficacy of ACD CPR .(6) Together, these investigations suggest that intermittent impedance to inspiration during a performance of any method of CPR , which relies at least in part on either passive or active elastic recoil of the chest wall to enhance venous return, should significantly increase overall CPR efficacy.

In this study, the beneficial effects of the ITV, as demonstrated by the prevention...

...decrease in the CPP or vital organ perfusion when the ITV was added to the respiratory circuit, were most pronounced each time the ITV was removed from the respiratory circuit (Fig 2). Given the similar measurements of vital organ blood flow and CPP obtained 2 min after initiation of CPR between both groups, these results suggests that other factors, in particular the initial profound neurohormonal...underestimate the potential benefit of the ITV. Moreover, they suggest that there is a minimum negative intrathoracic pressure threshold during the decompression phase that must be overcome, at which point myocardial perfusion increases in a nonlinear rate. In this fashion, the increase in negative intrathoracic pressure during the decompression phase appears to "afterload" the left and right heart, facilitating venous return...

...the arterioles and the interstitium, the relative rates of right heart filling at a given **negative** intrathoracic **pressure**, and the relative responsiveness of the arterial and venous tree to subtle shifts in maximal **negative** intrathoracic **pressure**.

Despite our current inability to fully understand the physiologic factors involved in enhancement of myocardial perfusion with the ITV, the

results highlight the potential value of maximizing efforts to decrease negative intrathoracic pressure during the decompression or "relaxation" phase of CPR to enhance overall venous return and ultimately cardiac perfusion and overall CPR efficacy. Increasing negative intrathoracic pressures during the decompression, in addition to efforts aimed at maximizing positive intrathoracic pressures during the compression phase, appears to be important when optimizing the potential mechanical benefits of...

...to increase systemic arterial pressures, augmentation of right heart filling is an essential part of CPR. Enhancement of right heart filling, though difficult to assess by measurement of the calculated CPPs... ...right ventricular infarction as well as during cardiac arrest. Based on the present study, maximizing negative intrathoracic pressure during the decompression phase of CPR appears to be an effective way to help increase right heart filling and overall venous return.

The potential value of enhancing of **negative** intrathoracic **pressure** during passive relaxation of the chest wall by the use of an ITV is highly...

...the heart and the compliance of the ventricular wall. Use of an impedance valve during CPR serves to "prime the pump" and is one of several new techniques available to enhance venous return to the heart during cardiac arrest and CPR. Although venous return during "optimal" mechanical CPR may be provided by the combination of the ITV and ACD CPR, (6) the present study suggests that even in the absence of new CPR techniques, the ITV holds potential promise to improve the efficacy of standard CPR.

ACKNOWLEDGMENT: The authors would like to thank Gail Rosenbaum for her assistance in preparing this...

# ... REFERENCES

- (1) Lindner KH, Pfenninger E, Lurie KG, et al. Effects of active compression-decompression resuscitation on myocardial and cerebral blood flow in pigs. Circulation 1993; 88:1254-63
- (2) Cohen TJ, Tucker KL, Lurie KG, et al. Active compression-decompression: a new method of cardiopulmonary resuscitation . JAMA 1992; 267:2916-23
- (3) Chang MW, Coffeen P, Lurie KG, et al. Active compression-decompression CPR improves vital organ perfusion in a dog model of ventricular fibrillation. Chest 1994; 106:1250-59
- (4) Lurie KG. Active compression-decompression, cardiopulmonary resuscitation: a progress report. Resuscitation 1994; 28:115-22
- (5) Guly UM, Robertson CE. Active decompression improves the haemodynamic state during cardiopulmonary resuscitation. Br Heart J 1995; 73:372-76
- (6) Lurie KG, Coffeen P, Shultz J, et al. Improving active compression-decompression cardiopulmonary resuscitation with an inspiratory impedance valve. Circulation 1995; 91: 1629-32
- (7) Lindner KH, Haak T, Keller A, et al. Release of endogenous vasopressors during and after cardiopulmonary resuscitation . Br Heart J 1996; 75:145-50
  - (\*) From the Cardiac Arrhythmia Center (Dr. Lurie, Ms...

# ... American Heart Association.

Manuscript received April 16, 1997; revision accepted September 10, 1997.

Reprint requests: Keith Lurie , MD, UMHC, Box 508, 420 Delaware Street SE, Minneapolis, MN 55409

DESCRIPTORS: Cardiac resuscitation -- 19980400

6/3,K/17 (Item 2 from file: 149)

DIALOG(R) File 149:TGG Health&Wellness DB(SM)(c) 2004 The Gale Group. All rts. reserv.

01743388 SUPPLIER NUMBER: 19931529 (USE FORMAT 7 OR 9 FOR FULL TEXT)
Nonpharmacologic treatment of atrial fibrillation: current and evolving
strategies.

Iskos, Demosthenes; Fahy, Gerard J.; Lurie, Keith G.; Sakaguchi, Scott; Adkisson, Wayne O.; Benditt, David G

Chest, v112, n4, p1079(12)

Oct, 1997

PUBLICATION FORMAT: Magazine/Journal; Refereed ISSN: 0012-3692

LANGUAGE: English RECORD TYPE: Fulltext TARGET AUDIENCE: Professional

WORD COUNT: 8723 LINE COUNT: 00750

# ... Lurie, Keith G

of overt accessory pathways. Am J Cardiol 1992; 69:493-97 (78) Guidelines for cardiopulmonary resuscitation and emergent cardiac care: recommendations of the 1992 National Conference. JAMA 1992; 268:2211-13...

6/3,K/18 (Item 3 from file: 149)

DIALOG(R) File 149:TGG Health&Wellness DB(SM) (c) 2004 The Gale Group. All rts. reserv.

01570531 SUPPLIER NUMBER: 18423303

Vasopressin administration in refractory cardiac arrest.

Lindner, Karl H.; Prengel, Andreas W.; Brinkmann, Alexander; Strohmenger, Hans-Ulrich; Lindner, Ingrid M.; Lurie, Keith G.

Annals of Internal Medicine, v124, n12, p1061(4)

June 15,

1996

PUBLICATION FORMAT: Magazine/Journal ISSN: 0003-4819 LANGUAGE: English RECORD TYPE: Abstract TARGET AUDIENCE: Professional

... Lurie, Keith G.

ABSTRACT: Injecting vasopressin may prove to be a promising new technique during cardiopulmonary resuscitation when other measures fail. Vasopressin has been shown to work better than epinephrine, the standard...

...arrest. Doctors injected vasopressin in eight cases of cardiac arrest where prolonged efforts at cardiopulmonary resuscitation using standard techniques had failed. All incidents occurred within the hospital and in all but one, resuscitation was initiated within one minute of cardiac arrest. Five patients died, including two patients who...

DESCRIPTORS: CPR (First aid... 19960615

6/3,K/19 (Item 4 from file: 149)

DIALOG(R)File 149:TGG Health&Wellness DB(SM)

(c) 2004 The Gale Group. All rts. reserv.

01495168 SUPPLIER NUMBER: 15842419 (USE FORMAT 7 OR 9 FOR FULL TEXT)
Active compression-decompression CPR improves vital organ perfusion in a dog model of ventricular fibrillation.

Chang, Mark W.; Coffeen, Paul; Lurie, Keith G.; Shultz, Jeffrey; Bache, Robert J.; White, Carl W

Chest, v106, n4, p1250(10)

Oct,

1994

PUBLICATION FORMAT: Magazine/Journal ISSN: 0012-3692 LANGUAGE: English

RECORD TYPE: Fulltext TARGET AUDIENCE: Professional

WORD COUNT: 6861 LINE COUNT: 00582

Active compression-decompression CPR improves vital organ perfusion in a dog model of ventricular fibrillation.
... Lurie, Keith G

# TEXT:

Objectives: This study was designed to assess whether a new method of cardiopulmonary resuscitation (CPR), termed active compression-decompression CPR, or ACD-CPR, improves organ perfusion when compared with standard (S) CPR in a dog model of ventricular fibrillation.

Background: ACD- CPR has recently been shown to improve hemodynamic and respiratory parameters during cardiac arrest when compared with standard CPR. However, to our knowlege, the effects of ACD- CPR on tissue perfusion have not been investigated.

Methods: Ventricular fibrillation was induced in eight anesthetized, intubated animals. ACD- CPR and standard CPR were each performed twice in alternating order. All interventions were preceded by 1 min of ventricular fibrillation, in which no CPR was performed, and consisted of 6 min of CPR with either technique during which tissue perfusion was measured. Compressions were performed at 80/min...

- ...chest wall for both techniques. Epinephrine was administered at the beginning of each 6-min CPR interval. Hemodynamic monitoring of aortic and right atrial pressure was performed continuously and myocardial, cerebral...
- ...3 [+ or -] 55.5 ml/min/100 g, respectively (mean [ $\pm$  or -] SEM). Compared with standard CPR , ACD- CPR resulted in higher global left ventricular (22.5 [+ or -] 6.2 vs 14.1 [+ or...
- ...the frontal, parietal, and occipital lobes of the brain were all significantly improved by ACD- CPR . Aortic systolic (61.7 [+ or -] 4.1 vs 49.5 [+ or -] 3.1 mm Hg...
- ...pressure (12.9 [+ or -] 3.4 vs 10.4 [+ or -] 3.4 mm Hg, ACD- CPR vs standard CPR , p < 0.01) were all higher during ACD- CPR than during standard CPR .

Conclusions: We conclude that ACD-  $\mbox{\sc CPR}$  improves tissue perfusion and systemic hemodynamics compared with standard  $\mbox{\sc CPR}$  .

(Chest 1994; 106:1250-59) ACD- CPR = active

compression-decompression cardiopul- monary resuscitation ; S = standard
 Key words: cardiopulmonary resuscitation ; cerebral blood flow;
hemodynamics; left ventricular blood flow; renal blood flow

The standard method of cardiopulmonary  ${\tt resuscitation}$  (S- CPR ) has undergone few changes since its introduction by Kouwenhoven et al(1) more than three decades ago. Despite its nearly universal acceptance, the number

of patients who benefit from S- CPR is small (<20 percent), probably secondary to inadequate blood flow during **resuscitative** efforts.(2)(3)(4). While newer methods of CPR designed to enhance tissue perfusion have been investigated, (5)(6)(7)(8)(9)(10)(11...

current clinical S- CPR techniques. Recently, Lurie et al(15) described a patient who was successfully resuscitated using an ordinary bathroom plunger during CPR. This anecdotal report has stimulated the development of a new method of CPR using a handheld suction device which, when applied to the chest surface, allows active decompression as well as compression of the chest wall. Recent studies using active compression-decompression (ACD) CPR in humans during cardiac arrest demonstrated improvements in hemodynamic and respiratory parameters during ACD- CPR compared with S- CPR .(16)(17) To date, and to our knowledge, the effects of ACD- CPR on tissue perfusion have not been investigated. This study was designed to compare regional organ blood flows achieved with ACD- CPR and S- CPR, and to gain new insights into the basic mechanisms by which active decompression of the chest wall might improve CPR hemodynamics.

METHODS

Preparation

This study was approved by the University of Minnesota Committee on  ${\tt Animal}\ldots$ 

...administered as needed during surgery. Dogs were intubated with a 6-F endotracheal tube and **ventilated** with 10 L of supplemental oxygen at a minute **ventilation** required to maintain arterial pH between 7.3 and 7.4. Arterial blood gas monitoring was performed every 30 min to ensure adequacy of **ventilatory** parameters. The chest was shaved and animals were placed in the supine position until immediately...

...Oxnard, Calif) referenced to the level of the right atrium. For analysis of hemodynamics during CPR with each technique, data were acquired at the end of each minute of each intervention...end-expiration during compression (systole) and decompression (diastole) were averaged for six compressions over two respiratory cycles. Mean aortic and right atrial pressures were obtained electronically; 5,000 U of heparin was given IV prior to initiation of the study.

CPR Techniques

Both S- CPR and ACD- CPR were performed using a hand-held modified household plunger (internal diameter, 8 cm) shown schematically...

...compressions. For each experiment, a new suction device was used to ensure adequate suction. Standard CPR was defined as compression and release with no suction adherence of the plunger to the chest, thus allowing passive relaxation of the chest wall to resting position. During S- CPR only, suction was prevented by placing two 10 x 10-cm gauze pads between the chest wall and the suction cup. ACD- CPR was defined as compression and active withdrawal of the plunger with adequate suction to actively decompress the chest wall to an anteroposterior diameter approximately 10 percent beyond normal resting position. CPR was performed with the dogs in the left lateral oblique (45[degrees]) position. Compressions were...

...duty cycle. To ensure that the force of compressions was equal during both methods of <code>CPR</code> , two monitoring systems with continuous feedback to the person applying compressions were used. Direct measurements...

...designed to allow the comparison of tissue flows and hemodynamics during

multiple periods of ACD- CPR and S- CPR in the same animal. It was modeled in part from previous studies of CPR in animals by the Hopkins group(18) in which a short period of no CPR and relatively high-dose epinephrine were used. In each of seven dogs, both ACD- CPR and S- CPR were performed twice, 6 min per intervention, in alternating order. In one dog, ACD- CPR and S- CPR were each performed once. Each round of CPR was preceded by 1 min during which no CPR was performed. Using this experimental design, hemodynamic and organ blood flow measurements during each method of CPR were made twice in the same animal. Thus, comparison of tissue flows achieved with the two CPR techniques could be made with each animal serving as its own control.

Before cardiac arrest...

...adjusted as needed to maintain mean right atrial pressure at 3 to 8 mm Hg. Ventilatory support was continued throughout all experiments using manual bag ventilation with 10 L oxygen supplementation. Hand-held ventilation was utilized after preliminary experiments showed that it was easier to interpose manual ventilatory efforts at the end of the decompression phase with bag ventilation than with mechanical ventilation. Respirations were delivered at a rate of 16/min (one breath every five chest compressions) at a constant tidal volume required to maintain the same minute ventilation delivered during surgical preparation. Ventricular fibrillation was induced by a single 5-s application of...

...with the endocardium of the right ventricle. After 1 min of fibrillation, during which no CPR or ventilation was performed, either ACD- CPR or S- CPR was initiated. The decision to use S- CPR or ACD- CPR was made randomly at the beginning of each experiment. In four dogs, S- CPR was performed first, and in four dogs, ACD- CPR was performed first. Epinephrine was administered using a protocol similar to that of Michael et ...

...18) with a bolus (1 mg) directly into the left ventricle at the onset of  ${\tt CPR}$ , followed by a continuous infusion (8 [micro]g/kg/min) into the right atrium throughout the remaining 27 min of the experiment. The first  ${\tt CPR}$  method (either S-  ${\tt CPR}$  or ACD-  ${\tt CPR}$ ) was continued for 6 min during which blood flows and hemodynamics were measured. After 5...

...assess residual counts in the ventricle at the end of the intervention. After 6 min, CPR was stopped. After 1 min of no CPR and no ventilation, the alternate CPR technique was performed for 6 min. At the onset of this second round of CPR, a repeat bolus of epinephrine (1 mg) was administered into the left ventricle. Hemodynamic and...

...first intervention. In seven experiments, this cycle of 1 min of ventricular fibrillation with no CPR and 6 min of CPR was repeated two additional times alternating the two techniques for each intervention, for a total of four CPR interventions per dog. In one experiment, only two interventions were performed.

Tissue Flow Measurements Regional...

...15-[micro]m-diameter microspheres with techniques similar to those previously reported and validated during CPR in ...Studies have shown that tissue flows can be accurately measured within 1 min of instituting CPR and that peripheral blood flow and tissue perfusion remain relatively steady throughout the entire duration of CPR up to 50 min. (4) (18) For each intervention, approximately 2 x [10.sup.6...

...minute in the reference blood samples. The two determinations of tissue

blood flow for each CPR intervention were then averaged to provide a single value for S- CPR and ACD- CPR for each animal.

Statistical Analysis

'All values are expressed as mean values [+ or -] SEM. Statistical...

...0 [+ or -] 5.5 ml/min/100 g. Left ventricular flow during either method of CPR was significantly lower than during the baseline period (p < 0.01). However, during ACD- CPR , left ventricular flow (22.5 [+ or -] 6.2 ml/min/100 g) was significantly greater than during S- CPR (14.1 [+ or -] 2.1 ml/min/100 g, p < 0.01, ACD- CPR vs S- CPR).

[TABULAR DATA OMITTED]

[CHART OMITTED]

Average baseline total brain flow was 14.2 [+ or -] 2.1 ml/min/100 g. During S- CPR , the flow was 8.5 [+ or -] 2.3 ml/min/100 g (significantly lower than...

...this value increased to 12.0 [+ or -] 2.4 ml/min/100 g during ACD- CPR (p < 0.01, ACD- CPR vs S- CPR flows). The difference between ACD- CPR and baseline brain blood flow was not statistically significant (p = 0.24). Renal cortical flow fell dramatically during CPR with average flows of 476.3 [+ or -] 55.5 ml/min/100 g during baseline, 17.5 [+ or -] 5.0 ml/min/100 g during S- CPR , and 27.8 [+ or -] 5.0 ml/min/100 g during ACD-CPR (p < 0.05, ACD- CPR vs S- CPR flows). Thus, when compared with S-CPR , ACD- CPR resulted in a significant increase in total left ventricular perfusion, cerebral perfusion, and renal cortical flow. Furthermore, ACD- CPR resulted in cerebral blood flows that were statistically equivalent to baseline values.

Global mean left ventricular and cerebral blood flows were significantly greater during ACD- CPR than during S- CPR in each of the eight individual experiments. As shown in Figure 2, organ flows were improved with ACD- CPR throughout a broad range of measured flows. These differences were statistically significant in each experiment (p [less than or equal to] 0.02 ACD- CPR vs S- CPR ). Thus, whether tissue flows during resuscitation in an individual experiment were low or high, ACD- CPR resulted in greater perfusion than S- CPR . In the kidney, flow was improved with ACD- CPR in five of the seven animals (p < 0.02). In one experiment, renal cortical flows were no different between the two techniques, and in another, flow during S- CPR was higher than during ACD-CPR . In one experiment, renal blood flow was below the limit of detection with both ACD- CPR and S- CPR .

Improvement in organ perfusion seen with ACD- CPR is further supported by the time course of recovery of microsphere activity from the circulation...

...peak recovery of counts in the peripheral blood was the same for both methods of CPR , occurring 1.5 min after injection ...into the left ventricle. However, microspheres appeared more rapidly in the peripheral blood during ACD- CPR than during S- CPR . At 1.0 min after injection, 25.4 [+ or -] 6.8 percent of all counts recovered were seen with ACD- CPR vs 14.6 [+ or -] 5.3 percent during S- CPR (p = 0.02). After peak recovery, microspheres were also cleared from the peripheral circulation significantly faster with ACD- CPR than with S- CPR . With ACD- CPR , 13.1 [+ or -] 2.4 percent and 6.5 [+ or -] 1.9 percent of total...

...percent and 9.2 [+ or -] 1.6 percent at the same time points during S-CPR (p < 0.05, both time points). Taken together, these clearance data are consistent with a significantly higher peripheral blood flow state during ACD-CPR than during S-CPR and are consistent with the organ blood flow data discussed above.

Regional Tissue Perfusion

In addition to total organ blood flow, regional tissue perfusion was also significantly improved with ACD- CPR compared with S- CPR. Regional organ flow in the heart and brain are shown in Table 1. Epicardial, midmyocardial, and endocardial left ventricular flows were all significantly improved with ACD- CPR compared with S- CPR. During ACD-CPR, regional flows to the epicardium and mid-myocardium were >40 percent of baseline levels while flow to the endocardium reached nearly 30 percent of baseline. In contrast, during S- CPR, epicardial and midmyocardial flows were <30 percent of baseline and endocardial flows were only 16...

...flows decreased from 1.76 at baseline to 0.92 (p<0.02) during ACD- CPR and to 0.79 (p<0.01) during S- CPR . While the endocardial/epicardial ratio was greater during ACD- CPR compared with S- CPR , this difference was not statistically significant (p=0.20). In the brain, ACD- CPR resulted in flows to the frontal, parietal, and occipital lobes to nearly 85 percent of baseline levels, while flows during S- CPR reached only 60 percent of baseline.

Hemodynamics and Blood Gas Values

The hemodynamic data from these experiments are summarized in Table 2. Compared with S- CPR, ACD- CPR resulted in significantly higher aortic systolic and aortic mena pressures. Systolic right atrial and mean right atrial pressures were also significantly higher during ACD- CPR than during S- CPR. In contrast, there were no significant differences between diastolic aortic and diastolic right atrial pressures during CPR with the two techniques. Myocardial perfusion pressure, computed for each experiment as the diastolic aortic pressure minus the diastolic right atrial pressure, was significantly greater during ACD- CPR than during S- CPR. Left ventricular microsphere flow correlated with myocardial perfusion pressure for both ACD- CPR (r=0.845, p<0.01) and S- CPR (r=0.811, p<0.02).

[TABULAR DATA OMITTED]

Representative hemodynamic data acquired during ACD- and S-  $\tt CPR$  are shown in Figure 4. Simultaneously recorded force of compression and intrathoracic pressure tracings are...

...force of compression and similar peak intraesophageal pressure, aortic systolic pressures are higher with ACD- CPR than with S- CPR. Furthermore, during active decompression, somewhat greater negative pressures within the esophagus are achieved, suggesting increased negative intrathoracic pressures were generated with ACD- CPR. Also worth noting is the difference in the right atrial pressure tracings during diastole with...

...right atrial pressure appears to reach its nadir earlier and remain lower than with S-  $\mbox{CPR}$  for a greater proportion of diastole, despite similar duty cycles for the two techniques.

...28 blood gas samples taken during the last minute of baseline measurements and of each CPR intervention were analyzed from six of the eight experiments. Table 3 reveals there were no significant differences in the arterial blood gas data during ACD- CPR compared with S- CPR and that animals were adequately oxygenated throughout the experiment. When compared with baseline, animals were significantly more acidotic during S- CPR but not during ACD- CPR. During CPR with either technique, animals were significantly more hypocapneic than during baseline.

[TABULAR DATA OMITTED] Validation...

 $\dots$ radiolabeled microspheres in this acute model of ventricular fibrillation and to assess differences in ACD- CPR  $\,$  vs S- CPR  $\,$ , peripheral

clearance of microspheres was estimated by dividing the corrected counts obtained in each of...

...peripheral circulation by 3 min following their injection into the left ventricle during baseline, S- CPR , and ACD- CPR . The raw counts recovered from the left ventricle 5.5 min after initiation of each...

...These data suggest that adequate ejection of microspheres from the ventricle had occurred during both CPR techniques. These findings are consistent with previous work that validated the microsphere technique for measuring blood flow during CPR .(4)

[CHART OMITTED]

The data in this study represent means of values obtained during separate CPR interventions within individual experiments. It is possible that differences in blood flows seen with ACD- CPR vs S- CPR were affected by the particular time frame in a given experiment during which the intervention...

...of our model during the course of an experiment, mean flows achieved with both ACD- CPR and S- CPR early in each of the experiments (ie, the first two interventions) were compared with mean...

...Table 4). Also, the absolute differences and percentage of change in flows achieved with S- CPR and ACD- CPR early ...the model remained relatively stable throughout the experiments. Furthermore, the absolute differences in mean ACD- CPR and S- CPR flows remained constant throughout the experiment, suggesting that compared with S- CPR, ACD- CPR improved flows by a constant magnitude that was independent of time. Therefore, mean ACD- CPR tissue flows and hemodynamic parameters for the early and late periods were compared with mean S- CPR flows and hemodynamics.

[TABULAR DATA OMITTED]

DISCUSSION

This study demonstrates that compared with S-  $\mbox{CPR}$  , ACD-  $\mbox{CPR}$  improves blood flow to three vital organs and significantly improves systemic blood pressure in a...

...well as systolic blood pressure and calculated myocardial perfusion pressure were all improved with ACD-  $\mbox{CPR}$ . Despited wide variations in basal organ flow, improvements in flows to the heart and brain were seen with ACD-  $\mbox{CPR}$  in each of eight individual experiments that comprise this study.

The measured myocardial flow during S- CPR was comparable to that observed in previous reports.(4)(18) However, myocardial flows of 20 to 25 ml/min/100 g tissue, higher than those observed with S- CPR in this study, may be necessary to meet the heart's metabolic needs during ventricular fibrillation.(22) Previous authors suggest that flows during prolonged CPR of at least 10 to 20 percent of baseline are necessary for successful defibrillation and...

...are accurate, both the higher absolute flows and percentage of baseline flows achieved with ACD- CPR in our study suggests that ACD- CPR may provide a significant advantage over S- CPR in overcoming these critical threshold values.

The brain is extremely sensitive to anoxic insult with...

...patients demonstrate normal electroencephalograms and somatosensory-evoked potentials.(25)(26) In this study during ACD-  $\tt CPR$  , cerebral blood flows averaged nearly 80 percent of baseline flows. These levels of perfusion during ACD-  $\tt CPR$  were statistically equivalent to

baseline brain flows. In contrast, S- CPR resulted in 60 percent of baseline flows. Taken together, the significant increase in cerebral flows achieved with ACD- CPR over S- CPR might be important with regard to the potential recovery of neurologic function following a period of CPR.

The minimal metabolic requirements of the kidney are less well documented than for the heart...

...Blood flow is preferentially shunted from the kidney during ventricular fibrillation. Renal blood flow during CPR in the range of 1 percent of baseline values has been a consistent finding in...

...is comparable to those found previously. It is unlikely that the significant differences in ACD- CPR vs S- CPR renal blood flow during ventricular fibrillation would provide a greater chance of preserving renal function...

...after arrest.

The exact mechanisms responsible for improvement in organ flow and hemodynamics with ACD- CPR remain unclear. Indeed, the mechanisms by which circulation is sustained during S- CPR continues to be the subject of debate. Kouwenhoven et al(1) proposed that blood flow...

 $\dots$  significant laboratory data also support the thoracic pump theory, which suggests that blood flow during CPR is a result of a generalized increase in intrathoracic vascular pressures that is transmitted to...

 $\dots$ atrial pressure gradient occur predominantly during the relaxation phase of the chest compression cycle of  $\ CPR$  . Halperin et al(31) were able to demonstrate that myocardial flows depended on diastolic myocardial...

...significantly with alterations in intrathoracic pressures.

In this study, we have demonstrated that during ACD- CPR there is an improvement in myocardial perfusion pressure leading to greater myocardial flows during ACD- CPR (Tables 1 and 2). The tracings shown in Figure 4 suggest that the right atrial pressure during decompression in ACD- CPR remains lower for a greater duration than during S- CPR. This difference may be important and may account for the improvement in calculated myocardial perfusion...

...indirect measure of intrathoracic pressure, reveals a marked decrease in pressure during active decompression (greater negative intrathoracic pressure) with ACD- CPR (Fig 4). To our knowledge, demonstration of intrathoracic pressure alterations with ACD- CPR has not been reported previously. In preliminary studies, we have evaluated the effect of ACD-CPR on phasic coronary flow velocity. These studies reveal that peak late diastolic flow velocity during decompression is markedly augmented during ACD- CPR vs S- CPR (34)

[CHART OMITTED]

Based on these results, we speculate that ACD- CPR improves organ flow and systemic hemodynamics predominantly by increasing negative intrathoracic pressure during active decompression. The improvement in the aortic-to-right atrial pressure gradient and blood...intrathoracic pressure. Furthermore, during active decompression, the compliant thoracic venous bed is subjected to greater negative pressure both in duration and in magnitude. The resultant increase in the arterial to venous gradient ...

...and pressures during compression. Further studies investigating the underlying mechanisms of organ perfusion during ACD- CPR are the focus of our current laboratory efforts.

Limitations

A large variance in absolute organ flow was noted during both methods

- of  $\mbox{CPR}$ . This is likely due to variations in the efficacy of either method of  $\mbox{CPR}$  secondary to differences in the canine chest configuration from animal to animal as they affect...
- ...and decompression. Substantial variations in organ blood flow are commonly reported in animal studies of CPR . In our study, the use of paired observations in the same animal, each performed twice...
- ... The hypocarbia seen during the basal state, which was more pronounced during both methods of CPR, may be, in part, responsible. However, since baseline renal and myocardial blood flow are comparable...
- ...methodologic considerations regarding microsphere blood flow measurements. Furthermore, the measured vital organ flows during S- CPR in this study are comparable to those seen in previous reports using similar S- CPR techniques.(4)(18) The dose of epinephrine used in these studies was selected following the...
- ...regard are different from those of Lindner et al(35) in swine in which ACD-CPR was not shown to have beneficial effects on organ blood flow when utilized with high...
- ...investigation is the assumption that the systolic phases of compression were similar with the two CPR techniques. In this study, a hand-held compressive device was utilized. Preliminary studies convinced us that this method of chest compression more closely modeled the clinical application of CPR than the mechanical "thumper." We attempted to assure equal systolic compression with both techniques by...
- ...31)(36) Using constant monitoring, these parameters were kept as equal as possible. Both S- CPR and ACD- CPR were subjected to identical methods of data analysis. Given these considerations, we believe it is unlikely that the improvement seen in organ flows and hemodynamics with ACD- CPR in this study is due to differences in systolic compressive force.

Finally, application of results of a CPR study in an animal model to the clinical setting is limited, primarily due to differences...

- ...animals and humans. Chest dimensions are known to be important determinants of the effects of CPR on hemodynamics and organ flows.(2)(33)(37) The canine chest configuration is not ideal...
- ...may yield even better hemodynamic and myocardial perfusion results. Certainly, any alterations in currently accepted CPR techniques must be supported by proven benefits in the laboratory setting.

  CONCLUSIONS

ACD- CPR is a novel method of CPR. Based on this study, we conclude that ACD- CPR significantly improves vital organ perfusion and systemic blood pressure during CPR in a dog model of ventricular fibrillation. The mechanism by which ACD- CPR improves blood flow and CPR hemodynamics remains speculative, but it is likely due to the development of greater negative intrathoracic pressure during active decompression resulting in the active transport of greater blood volumes into the thoracic cavity and right side of the heart. Clinically relevant issues such as whether ACD- CPR leads to improved recovery of organ function or facilitates the return of spontaneous circulation following a period of CPR are currently ongoing in prehospital studies. We believe that further studies designed to evaluate these outcomes using this novel method of CPR, both in animal models and in the clinical setting, are warranted.

ACKNOWLEDGMENTS: The authors would...

(3) Niemann JT. Cardiopulmonary resuscitation . N Engl J Med 1992; 327:1075-80

(4) Eisenberg MS, Hallstrom A, Bergner L...AD, Chandra N, Herskowitz A, Tsitlik JE, Niskanen RA, et al. Vest inflation without simultaneous ventilation during cardiac arrest in dogs: improved survival from prolonged cardiopulmonary resuscitation . Circulation 1986; 74:1407-15 (7) Chandra NC, Beyar R, Halperin HR, Tsitlik JE, Wurmb...

...R, Bialek H. Perfusion of the cerebral cortex by use of abdominal counterpulsation during cardiopulmonary resuscitation . Am J Emerg Med 1984; 2:391-93

(9) Howard M, Carrubba C, Foss F, Janiak B, Hogan B, Guinness M. Interposed abdominal compression- CPR : its effects on parameters of coronary perfusion in human subjects. Ann Emerg Med 1987; 16...

...JP, Ung S, Criley JM. Hemodynamic effects of continuous abdominal binding during cardiac arrest and resuscitation . Am J Cardiol 1984; 53:269-74

(11) Bircher N, Safar P, Stewart R. A comparison of standard, MAST-augmented and open-chest CPR in dogs: a preliminary investigation. Crit Care Med 1980; 8:147-52

(12)Lilja GP, Clinton J, Mahoney B. MAST usage in cardiopulmonary resuscitation . Ann Emerg Med 1984; 13:833-35

(13) Niemann JT, Rosborough J, Hausknecht M, Brown D, Criley JM. Cough- CPR : documentation of systemic perfusion in man and in an experimental model: a 'window' to the mechanism of blood flow in external CPR . Crit Care Med 1980; 8:141-46

(14) Criley JM, Blaufuss AH, Kissel GL. Cough-induced cardiac compression: self-administered form of cardiopulmonary resuscitation . JAMA 1976; 236:1246-50

(15) Lurie KG, Lindo C, Chin J. CPR: the P stands for plumber's helper. JAMA 1990; 264:1661

(16) Cohen TJ, Tucker...

...RF, Dutton JP, Dwyer KA, et al. Active compression-decompression: a new

method of cardiopulmonary resuscitation . JAMA 1992; 267: 2916-23 (17) Cohen TJ, Tucker KJ, Redberg RF, Lurie KG, Chin MC, Dutton JP, et al. Active compression decompression resuscitation: a novel method of cardiopulmonary resuscitation . Am Heart J 1992; 124:1145-50

(18) Michael JR, Guerci AD, Koehler RC, Shi...

... Chandra N, et al. Mechanisms by which epinephrine augments cerebral and myocardial perfusion during cardiopulmonary resuscitation in dogs. Circulation 1984; 69:822-35

(19) Bache RJ, Schwartz JS. Myocardial blood flow... ...20:55-79

(22) Luce JM, Rizk NA, Niskanen RA. Regional blood flow during cardiopulmonary resuscitation in dogs. Crit Care Med 1984; 12:874-78 (23)White BC, Winegar CD, Wilson RF, Hoehner RJ, Trombley JH.

Possible role of calcium blockers in cerebral resuscitation . Crit Care Med 1983; 11:202-07

(24) Siesjo BK. Cell damage in the brain...

...JW, et al. Sequence of mitral valve motion and transmitral blood flow during manual cardiopulmonary resuscitation in dogs. Circulation 1987; 76:363-75

(28) Maier GW, Tyson GS Jr, Olsen CO...

...Davis JW, Conn EH, et al. The physiology of external cardiac massage: high-impulse cardiopulmonary resuscitation . Circulation 1984; 70:86-101

(29)Deshmukh HG, Weil MH, Gudipati CV, Trevino RP, Bisera J, Rackow EC. Mechanism of blood flow generated by precordial compression during CPR . Chest 1989; 95:1092-99

(30) Rudikoff MT, Maughan WL, Effron M, Freund P, Weisfeldt ML. Mechanisms of blood flow during cardiopulmonary resuscitation . Circulation 1980; 61:345-52

(31) Halperin HR, Tsitlik HE, Guerci AD, Mellits ED, Levin HR, Shi AY, et al. Determinants of blood flow to vital organs during cardiopulmonary resuscitation in dogs. Circulation 1986; 73:539-50

(32) Paradis NA, Martin GB, Goetting MG, Rosenberg...

...EP, Appleton TJ, et al. Simultaneous aortic, jugular bulb, and right atrial pressures during cardiopulmonary resuscitation in humans: insights into mechanisms. Circulation 1989; 80:361-68

(33) Ditchey RV, Winkler JV, Rhodes CA. Relative lack of coronary blood flow during closed-chest resuscitation in dogs. Circulation 1982; 66:297-302

(34) Chang MW, Coffeen P, Lurie KG, Voss...

...diastolic coronary flow velocity: the mechanism of improved myocardial perfusion during active compression-decompression cardiopulmonary resuscitation ? Circulation 1993; 88(suppl 1):I-193

(35) Lindner KH, Pfenninger EG, Lurie KG, Schurmann W, Lindner IM, Ahnefeld RW. Effects of active compression-decompression resuscitation myocardial and cerebral blood flow in pigs. Circulation 1993; 88:1254-63

(36) Standards and guidelines for cardiopulmonary resuscitation (

CPR ) and emergency cardiac care (ECC). JAMA 1986; 255: 2905-89

(37) Shultz JJ, Coffeen P, Pineda E, Chang M, Homans DC, Ulstad VK, et al. Standard vs active compression decompression CPR in an acute model of human ventricular fibrillation. Circulation 1992; 86(suppl 1):I-234

...DESCRIPTORS: CPR (First aid 19941000

6/3, K/20. (Item 5 from file: 149) DIALOG(R) File 149:TGG Health & Wellness DB(SM) (c) 2004 The Gale Group. All rts. reserv.

SUPPLIER NUMBER: 16408239 Multiple-sensor systems for physiologic cardiac pacing. (review article) Benditt, David G.; Mianulli, Marcus; Lurie, Keith; Sakaguchi, Scott; Adler, Stuart

Annals of Internal Medicine, v121, n12, p960(9) Dec 15,

1994

PUBLICATION FORMAT: Magazine/Journal ISSN: 0003-4819 LANGUAGE: English RECORD TYPE: Abstract TARGET AUDIENCE: Professional

... Lurie, Keith

...ABSTRACT: checking, defaulting to the stim-T sensor if the sensors are at odds. A minute ventilation and piezoelectric activity sensor combination is marketed under the name Legend Plus. Studies of the... 19941215

6/3,K/21 (Item 1 from file: 444)
DIALOG(R)File 444:New England Journal of Med.
(c) 2004 Mass. Med. Soc. All rts. reserv.

00116987

Copyright 1997 by the Massachusetts Medical Society

The Critically Ill Cardiac Patient: Multisystem dysfunction and management. Edited by Vladimir Kvetan and David R. Dantzker. 417 pp., illustrated. Philadelphia, Lippincott-Raven, 1996. \$125. ISBN 0-397-51465-4 (Book Reviews)

Lurie, Keith G.
The New England Journal of Medicine
Jun 26, 1997; 336 (26),p 1920
LINE COUNT: 00048 WORD COUNT: 00666

Lurie, Keith G. 1997 ;

TEXT

...presentation makes a complex subject easy to comprehend. Another fine chapter describes the use of **ventilatory** support in patients with cardiac failure. In some ways this chapter is more theoretical than others, although it discusses novel methods of **ventilatory** support for the critically ill -- for example, continuous **positive** airway **pressure** for the treatment of heart failure in patients without sleep apnea. Similarly solid contributions are...

...patients in the intensive care unit have serious cardiac arrhythmias and may ultimately require cardiopulmonary resuscitation, the next edition of this book would benefit from chapters on the recognition and management of common, serious cardiac arrhythmias and advances in cardiopulmonary resuscitation. In addition, points made in the book are no longer supported by the current literature...

...teaching tool and reference for physicians who manage cardiac disease in the intensive care unit.  $\mid$  Keith G. Lurie , M.D.University of MinnesotaMinneapolis, MN 55455

6/3,K/22 (Item 1 from file: 129)
DIALOG(R)File 129:PHIND(Archival)
(c) 2004 PJB Publications, Ltd. All rts. reserv.

00657518

CardioPump trial shows better results in heart attack Clinica 899 p19, March 13, 2000 ( 20000313) STORY TYPE: F WORD COUNT: 326

..., 20000313)

A cardiopulmonary resuscitation ( CPR ) technique that combines a one-way valve and a hand-held suction device can maintain...

...reported in a previous study that patients treated with the CardioPump suction device alone during CPR (made by Danish company Ambu International) had a 5% one-year survival rate and 6...

... discharge.

This is compared with 2% for both endpoints in the group treated with conventional CPR at the scene. However the American Heart Association warned that the device was not effective...

...in 1998.

Adding a valve increases the efficiency of active compression-decompression (ACDC), said Dr Keith Lurie , of the University of Minnesota Medical School. The Resusci -Valve impedance threshold valve has a silicone diaphragm that decreases the pressure in the chest during decompression. It fits between the ventilation bag and the face mask or endotracheal tube of a standard manual resuscitation bag.

In a study involving 21 patients, 10 had ACDC CPR without the valve and 11 with it. Four patients with the vatve returned to spontaneous...

6/3,K/23 (Item 1 from file: 135) DIALOG(R)File 135:NewsRx Weekly Reports (c) 2004 NewsRx. All rts. reserv.

0000044914 (USE FORMAT 7 OR 9 FOR FULLTEXT) Technique and Valve Improve CPR Heart Disease Weekly, March 22, 2000, p.9-10

DOCUMENT TYPE: Expanded Reporting LANGUAGE: English

RECORD TYPE: FULLTEXT 592

WORD COUNT:

Technique and Valve Improve CPR

A cardiopulmonary resuscitation ( CPR ) technique using devices developed at the University of Minnesota Medical School has been shown in

which is performed with a hand-held plunger-like device called the CardioPump. With this...

...of the chest to the brain and other organs during compression, just as in standard  $\ensuremath{\mathtt{CPR}}$  . Unlike standard  $\ensuremath{\mathtt{CPR}}$  , the pump actively pulls the chest back to its original position during decompression. It improves...

...study by a group that included the authors of the Circulation article showed that ACD CPR significantly improved long-term survival rates among patients who had cardiac arrest outside the hospital...

...19, 1999, New England Journal of Medicine .

The latest study introduced a valve to ACD CPR . During CPR the chest works like a bellows, and the valve improves the function of the bellows...

...greater vacuum effect, which pulls more blood back into the heart and thus improves overall CPR efficacy.

The study involved 21 patients, 10 who had ACD CPR without the valve, 11 with it. More patients returned to spontaneous circulation with

...arrest had near-normal blood pressures for up to 30 minutes or until

they were resuscitated . The mean blood pressure in the patients during CPR was 109/56. Normal pressure is about 120/80.

"These results are exciting," said Dr. Keith Lurie, associate professor of medicine in the division of cardiology at the university and co-developer...

...ability to maintain near-normal blood pressures with these new and simple mechanical devices during CPR, we should be able to resuscitate more patients who would otherwise not have a chance."

Lurie co-wrote the article with...

 $\dots$ States ever survive to hospital discharge, due in part to the inherent inefficiency of standard CPR ," Lurie said.

During standard CPR, the heart and brain get less than 30% of normal blood flow. With ACD CPR plus the valve, those organs get more than 60% of normal flow. The group will conduct further studies to determine the long-term benefits of this new CPRO technology.

This article was prepared by Heart Disease Weekly editors from staff and other reports.

SUBJECT HEADING: Cardiopulmonary Resuscitation 2000

```
Set
        Items
                 Description
                 AU=(LURIE K? OR LURIE, K? OR MENK V? OR MENK, V? OR ZIELIN-
S1
              SKI T? OR ZIELINSKI, T? OR BIONDI J? OR BIONDI, J?)
                 CPR OR (CARDIOPULMON? OR CARDIO() PULMON?) (W) (RESUSCIT? OR -
S2
              RESPIRAT? OR VENTILAT? OR CIRCULAT?)
                 PEEP OR PEP OR POSITIVE()(ASSIST? OR PRESSUR?)(2N)(BREATH?
S3
              OR VENTILAT? OR RESPIRAT?) OR POSITIVE()END()EXPIR?()PRESSURE
              OR (MEDICAL OR EMT OR FIRE) (2N) RESCUE?
S4
                 VACUUM? OR SUCTION? OR NEGATIVE() PRESSURE? OR EXTRACT?(3N) -
              (POSITIVE OR RESPIRAT? OR EXPIRAT? OR EXHAL?)
       207631---BAG:OR-BAGS-OR-SACK?-?-OR-SMARTBAG?-OR-SMART()BAG-OR-AMBUB-
              AG? OR AMBU OR POUCH?? OR BELLOW?
                 MANIPULAT? OR DECOMPRESS? OR COMPRESS?
S6
       691641
                 THORAX? OR THORAC? OR CHEST??? OR LUNG? ? OR PULMON? OR IN-
S7
        48505
              TRATHORA?
                 VENOUS (2N) (RETURN OR CIRCULAT?) OR (BLOODFLOW? OR BLOOD()F-
S8
          220
              LOW? OR BLOOD()CIRCULAT?)(2N)(RETURN? OR BACK)(2N)(HEART? OR -
              CARDIAC?) OR LOWER?() PRESSUR?(2N) (RIGHT() ATRIUM) OR LOWER?() P-
              RESSUR? (2N) (THORAX? OR THORAC?) () VENA() CAVA
S9
       778002
                 VALVE??? OR VALVING
                 HYPOTENS? OR HYPOTENT? OR LOW()BLOOD()PRESSURE OR HEAD()(T-
S10
        24310
              RAUMA? OR INJUR?) OR CARDIAC()ARREST OR HEART()ATTACK OR MYOC-
             ARD? () INFARCT? OR (HEMORRHAG? OR HAEMORRHAG?) () SHOCK? OR BLOO-
              D()LOSS??
                 METHOD? ?
      4081951
S11
                 SYSTEM? ?
S12
      2984682
                 TECHNIQUE? ?
S13
       221806
                 PROCEDURE? ?
S14
       198434
      2416756
S15
                 PROCESS??
S16
       145914
                 IC=(A62B? OR A61G? OR A61M?)
S17
           90
                 S2:S3 AND S5
S18
            0
                S17 AND S8
S19
            3
                 S2:S3 AND S8
S20
            3
                 S17 AND S4
S21
           28
                 S17 AND S9
S22
           28
                 S21 AND (S6:S7 OR S10:S16)
S23
            1
                 S17 AND S1
                 S19:S23
S24
           33
S25
                 IDPAT (sorted in duplicate/non-duplicate order)
? show files
File 347: JAPIO Nov 1976-2003/Dec(Updated 040402)
          (c) 2004 JPO & JAPIO
File 350: Derwent WPIX 1963-2004/UD, UM &UP=200431
          (c) 2004 Thomson Derwent
```

25/3,K/1 (Item 1 from file: 350)
DIALOG(R)File 350:Derwent WPIX
(c) 2004 Thomson Derwent. All rts. reserv.

016157247 \*\*Image available\*\*
WPI Acc No: 2004-315134/200429

XRPX Acc No: N04-251070

Respiratory valve apparatus used in endotracheal medical procedure, has channel is aligned with access port and endotracheal tube connection port to receive suction catheter in either first or second valve

assembly position

Patent Assignee: BAYRON H (BAYR-I); WINTHROP N (WINT-I)

Inventor: BAYRON H; WINTHROP N

Number of Countries: 100 Number of Patents: 002

Patent Family:

Patent No Kind Date Applicat No Kind Date Week
US 20040069308 Al 20040415 US 2002267383 A 20021009 200429 B
WO 200434946 A2 20040429 WO 2003US32588 A 20031009 200429

Priority Applications (No Type Date): US 2002267383 A 20021009 Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

US 20040069308 A1 12 A61M-016/00

WO 200434946 A2 E A61H-000/00

Designated States (National): AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO RU SD SE SG SK SL TJ TM TN TR TT TZ UA UG UZ VC VN YU ZA ZM ZW

Designated States (Regional): AT BE BG CH CY CZ DE DK EA EE ES FI FR GB GH GM GR HU IE IT KE LS LU MC MW MZ NL OA PT RO SD SE SI SK SL SZ TR TZ UG ZM ZW

Respiratory valve apparatus used in endotracheal medical procedure, has channel is aligned with access port and endotracheal tube connection port to receive suction catheter in either first or second valve assembly position

### Abstract (Basic):

- aligned with an access port and an endotracheal tube connection port (18) to receive a suction catheter in either a first valve assembly position or a second valve assembly position. A reciprocating valve assembly (11) reciprocates to open a resuscitation bag connection port (28) and close a respirator connection port (32).
- ... Used in endotracheal medical procedure .
- ...or insertion of catheter from sanitary self-contained enclosure. Offers compact, inexpensive and simple respiratory valve. Allows uninterrupted respiratory switch-over to resuscitation bag to maintain optimal ventilation. Prevents loss of positive end expiratory pressure in lungs. Prevents collapse of lungs. Prevents contact contamination of valve. Provides spring bias in reciprocating valve. Can connect different resuscitation bags.
- ... The figure shows the partial cross-sectional view of a respiratory valve assembly...
- ... Reciprocating valve assembly (11...

- ...Resuscitation bag connection port (28 ...Title Terms: VALVE ; ...International Patent Class (Main): A61M-016/00

```
DIALOG(R) File 350: Derwent WPIX
 (c) 2004 Thomson Derwent. All rts. reserv.
015310415
              **Image available**
WPI Acc No: 2003-371349/200335
Related WPI Acc No: 1995-193914; 1996-433571; 2000-421466; 2002-139260;
  2002-641994; 2002-681034; 2003-030322; 2003-310772; 2003-766762
XRAM Acc No: C03-098421
XRPX Acc No: N03-296207
  Increasing-blood-circulation-in-breathing-person, involves-interfacing
  valve system to airway to decrease respiratory gas flow to lungs and
  permitting person to inhale and exhale through system
Patent Assignee: CPRX LLC (CPRX-N)
Inventor: EURIE-K-G-
Number of Countries: 001 Number of Patents: 002
Patent Family:
Patent No
              Kind
                      Date
                              Applicat No
                                             Kind
                                                    Date
                                                             Week
US 20030037784 A1
                    20030227 US 93149203
                                                   19931109
                                              Α
                                                             200335 B
                              US 95403009
                                              Α
                                                  19950310
                              US 97950702
                                                  19971015
                                              Α
                              US 2000546252
                                                  20000410
                                              Α
                              US 2001854238
                                              Α
                                                  20010511
                              US 2002119203
                                              Α
                                                  20020408
                              US 2002224263
                                              Α
                                                  20021105
US 20040016428 A9
                    20040129
                              US 93149203
                                              Α
                                                  19931109
                                                             200413
                              US 95403009
                                              Α
                                                  19950310
                              US 97950702
                                              Α
                                                  19971015
                              US 2000546252
                                              Α
                                                  20000410
                              US 2001854238
                                              Α
                                                  20010511
                              US 2002119203
                                                  20020408
                              US 2002224263
                                                  20021105
Priority Applications (No Type Date): US 2002224263 A 20021105; US 93149203
  A 19931109; US 95403009 A 19950310; US 97950702 A 19971015; US 2000546252
  A 20000410; US 2001854238 A 20010511; US 2002119203 A 20020408
Patent Details:
Patent No Kind Lan Pg
                         Main IPC
                                      Filing Notes
US 20030037784 A1
                     54 A61M-016/00
                                      CIP of application US 93149203
                                      CIP of application US 95403009
                                      CIP of application US 97950702
                                      CIP of application US 2000546252
                                      CIP of application US 2001854238
                                      CIP of application US 2002119203
                                      CIP of patent US 5441658
                                      CIP of patent US 5692498
                                      CIP of patent US 6062219
US 20040016428 A9
                        A61M-016/00
                                      CIP of application US 93149203
                                      CIP of application US 95403009
                                      CIP of application US 97950702
                                     CIP of application US 2000546252
                                     CIP of application US 2001854238
                                     CIP of application US 2002119203
                                     CIP of patent US 5441658
                                     CIP of patent US 5692498
                                     CIP of patent US 6062219
                                     CIP of patent US 6526973
                                     CIP of patent US 6604523
Abstract (Basic):
```

the VS. During inhalation, the VS is produces a vacuum within

25/3, K/2

(Item 2 from file: 350)

the thorax to increase blood flow back to the right heart, increasing cardiac output and blood circulation.

to improve and sustain the duration of negative intrathoracic pressure and improve blood oxygenation and cardiopulmonary

25/3,K/7 (Item 7 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

013249583 \*\*Image available\*\*

WPI Acc No: 2000-421466/200036

Related WPI Acc No: 1995-193914; 1996-433571; 2002-139260; 2002-641994;

2002-681034; 2003-030322; 2003-310772; 2003-371349; 2003-766762

XRPX Acc No: N00-314350

Apparatus and methods for assisting cardiopulmonary resuscitation that-incorporates-a-transition-tube, which-connects-the-endotracheal-tubeto the ventilation bag , the ventilation valve serves to introduce air into the device

Patent Assignee: CPRX LLC (CPRX-N)

Inventor: GOLD B; (LURIE-K-G) SWEENEY M

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week 20000516 US 93149204 US 6062219 A Α 19931109 200036 B US 95403009 Α 19950310

US 97950702 Α 19971015

Priority Applications (No Type Date): US 97950702 A 19971015; US 93149204 A 19931109; US 95403009 A 19950310

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

US 6062219 . A 23 A62B-009/02 CIP of application US 93149204

CIP of application US 95403009

CIP of patent US 5551420 CIP of patent US 5692498

Apparatus and methods for assisting cardiopulmonary resuscitation that incorporates a transition tube, which connects the endotracheal tube to the ventilation bag , the ventilation valve serves to introduce air into the device

... Inventor: LURIE K G

Abstract (Basic):

- The device (35) for impeding airflow into a patients lungs . The device consists an endotracheal tube (36), which is placed into the patients trachea and ...
- ...passageway. Connected is a transition tube (38), which connects the endotracheal tube to the ventilation bag (28). The ventilation valve (26) serves to introduce air into the device. Attached or connected to the transition tube is an airflow responsive valve (24). The inflow valve is biased so that it opens when the negative intrathoracic pressure in the patients chest reaches a threshold amount.
- External chest compression and decompression as part of the cardiopulmonary resuscitation procedures .

...Responsive valve (24...

... Ventilation valve (26 ... Title Terms: METHOD ;

International Patent Class (Main): A62B-009/02

International Patent Class (Additional): A61M-016/00 ...

... A62B-007/10

25/3,K/8 (Item 8 from file: 350)
DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

013238175 \*\*Image available\*\*
WPI Acc No: 2000-410049/200035

Related WPI Acc No: 1996-392259; 1996-424248; 1997-132229; 1998-158486

XRPX Acc No: N00-306303

Resuscitator bag exhaust port with CO2 indicator that incorporates a regulator assembly that has a port for connecting to the bag

Patent-Assignee:-NELLCOR-PURITAN-BENNETT-INC -(NELL-N)-

Inventor: COLBURN J; GOOD R J

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week
US 6058933 A 20000509 US 96729618 A 19961010 200035 B
US 9855093 A 19980403

Priority Applications (No Type Date): US 9855093 A 19980403; US 96729618 A 19961010

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

US 6058933 A 11 A62B-009/02 CIP of application US 96729618 CIP of patent US 5749358

Resuscitator bag exhaust port with CO2 indicator that incorporates a regulator assembly that has a port for connecting to the bag

## Abstract (Basic):

A regulator assembly (50) has a port (52) for connecting to a resuscitator bag, and a port (54) for connecting to a patient. Port includes a tubular lumen (56), which extends into an exhaust housing (58). A one-way valve (60) seals off exhaust assembly, when air is forced from the bag through a slit one way valve to the patient. The exhaust port is configured to accept a Positive End Expiratory Pressure (PEEP) valve, and therefore has a PEEP port (62) in addition to an exhaust port.

.. A resuscitator bag exhaust port with CO2 indicator...

...One-way **valve** (60...

... **PEEP** port (62

... Title Terms: BAG;

International Patent Class (Main): A62B-009/02

25/3,K/9 (Item 9 from file: 350)
DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

012588260 \*\*Image available\*\*
WPI Acc No: 1999-394367/199933

XRPX Acc No: N99-294750

Residual pressure controller in piston ventilator, bellow type ventilator for hospitals and health care centers

Patent Assignee: NELLCOR PURITAN BENNETT (NELL-N)

-Inventor:--BAILEY-E;--JONES-M-B;--LURA-D-B------

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week US 5918597 A 19990706 US 987426 A 19980115 199933 B

Priority Applications (No Type Date): US 987426 A 19980115

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

US 5918597 A 10 A61M-016/00

Residual pressure controller in piston ventilator, bellow type ventilator for hospitals and health care centers

## Abstract (Basic):

The pressure sensor (98) coupled with patient circuit (20), senses the pressure and positive end expiratory pressure (PEEP) and produces the corresponding signal. The controller receives the PEEP signal, compares with the target pressure and operates the PEEP valve (22) to vent gas selectively from the signal duct (91). The PEEP is altered to achieve target pressure.

Patient circuit for delivering gas from piston and cylinder assembly, has an exhalation valve (24) connected to the PEEP valve by signal duct. The PEEP valve transmits a pneumatic signal for positioning the exhalation valve. An INDEPENDENT CLAIM is also included for method of providing breathable gas to patient...

- ...In piston ventilator and **bellow** type ventilator for controlling the residual pressure in patient's **lungs** during exhalation, for hospitals and health care centers...
- ...Monitors **PEEP** and regulates the exhalation **valve** to increase or decrease the resistance to exhalation phase of the patient's breath, permitting...
- ...sinusoidal flow of breathable gas by monitoring and controlling the amount of oxygen. The exhalation system permits pneumatic rather than mechanical control of the exhalation valve .
- $\ldots$  The figure shows the scheme of piston ventilator  $\ensuremath{\mbox{ system }}$  .
- ... PEEP valve (22...
- ...Exhalation valve (24 ...Title Terms: BELLOWS;

International Patent Class (Main): A61M-016/00

25/3,K/10 (Item 10 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

011929943 \*\*Image available\*\*
WPI Acc No: 1998-346853/199830

XRAM Acc No: C98-107057 XRPX Acc No: N98-270730

Patent Assignee: COATES D F (COAT-I); COATES M R (COAT-I)

Inventor: COATES D F; COATES M R

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week US 5762063 A 19980609 US 97861145 A 19970521 199830 B

Priority Applications (No Type Date): US 97861145 A 19970521

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

US 5762063 A 6 A62B-009/04

Bag - valve resuscitator attachment, for emergency and rescue work...

- ... Abstract (Basic): A medication introducing device is for connection between a bag valve mask apparatus used for pre-hospital emergency respiratory assistance and the upper portion of an endo-tracheal tube (24) in a patient undergoing CPR whose condition requires the administering of medications and when an intravenous line cannot be established...
- ...comprises a central housing (14) having an upper opening configured for airtight connection to the **b**ag **valve** mask apparatus, and a lower opening configured for airtight connection to the endo-tracheal tube...
- ...lower opening so that medications can be administered to the patient without disconnection of the  ${\tt bag-valve}$  mask apparatus and the concomitant interruption of  ${\tt CPR}$  .
- ... USE For emergency and rescue work where cardiac **pulmonary** resuscitation ( CPR ) is required...
- ...ADVANTAGE Allows administration of cardiac medications without interruption of CPR . Compact is size, is easy to easily connected between bag valve mask and endo-tracheal tube

Title Terms: BAG;

International Patent Class (Main): A62B-009/04

International Patent Class (Additional): A61M-016/10

25/3,K/15 (Item 15 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

009047363 \*\*Image available\*\*
WPI Acc No: 1992-174734/199221

XRPX Acc No: N92-131755

Resuscitator having directional control valve assembly - assembly includes housing including first cylindrical part secured to squeeze bag and having partial floor across it

-Patent-Assignee: SPECIALITY-PACKAGING LICENSING (SPEC-N); SPECIALTY- PACKAGING (SPEC-N)

Inventor: DALEIDEN J P

Number of Countries: 005 Number of Patents: 006

Patent Family:

_	aconc ramary	•							
E	Patent No	Kind	Date ·	Apı	plicat No	Kind	Date	Week	
Ĺ	JS 5109840	Α	19920505	US	91655642	A	19910214	199221	В
(	SB 2252734	Α	19920819	GB	922229	A	19920203	199234	
Ε	E 4204159	Α	19920820	DE	4204159	Α	19920213	199235	
F	R 2672807	A1	19920821	FR	921955	A	19920214	199242	
S	SE 9200421	A	19920815	SE	92421	A	19920213	199243	
G	B 2252734	В	19940615	GB	922229	A	19920203	199421	

Priority Applications (No Type Date): US 91655642 A 19910214

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes US 5109840 Α GB 2252734 21 A61M-016/20 A DE 4204159 A 7 A61M-016/00 GB 2252734 В 5 A61M-016/20 FR 2672807 Α1 A61M-016/20 SE 9200421 Α A61M-016/00

Resuscitator having directional control valve assembly...

- ...assembly includes housing including first cylindrical part secured to squeeze bag and having partial floor across it
- ...Abstract (Basic): In the resuscitation device a squeeze bag is provided which includes a check valve to ensure one-way flow into the bag from outside room air or through an oxygen feed/reservoir system as known in the prior art. Also provided is a directional control valve assembly communicating with the bag and comprising a housing including a first cylindrical part secured to the bag and having a partial floor across it, the floor being formed with a perpendicular threaded...
- ...A tubular patient prt is joined to the domed part of the valve housing and adapted to be coupled in gas flow communication to the patient. The patient port extending into the valve housing and including a tubular extension formed concentric with the valve housing and having a circular end seat. A unitary flexible duck-billed diaphgram valve is provided including a flexible outer normally flat peripheral portion and an inner duck-bill...
- ... USE/ADVANTAGE A PEEP valve which is integral with the resuscitation bag directional control valve system. It is more convenient, less costly and potentially more therapeutically effective than other devices...
- ...Abstract (Equivalent): A resuscitator which comprises a flexible squeeze bag having a one-way inlet valve for admitting air and/or oxygen to

the bag and a directional control valve assembly which permits air or oxygen to be forced under pressure to the patient, while allowing the patient to exhale through an outlet, wherein the directional control valve assembly includes an adjustable PEEP valve within a housing, wherein said assembly comprises a first tubular sleeve, associated with an exit port from said bag, which is threadably engaged with a second tubular sleeve associated with said housing, said housing...

...oxygen to the patient and a second passageway for exhausting exhaled air, a one-way valve located within said assembly and arranged to permit air and/or oxygen flow from said exit port through said first passageway, said one-way valve including a peripheral flange biased to close onto a seat against the patient's exhalation...

...variable by screwing said first sleeve relatively to the second sleeve to thereby vary the PEEP correspondingly...

... Title Terms: VALVE ;

International Patent Class (Main): A61M-016/20

... International Patent Class (Additional): A62B-007/04 ...

... A62B-009/02

25/3,K/21 (Item 21 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

004358052

WPI Acc No: 1985-184930/198531

XRPX Acc No: N85-138858

Respirator static pressure monitoring unit - has exhalation air passage leading to discharge valve opening at predetermined pressure

Patent Assignee: ITOH SEIKI KK (ITOH-N)

Inventor: ITOH K

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No Kind Date Applicat No Kind Date Week
DE 3447019 A 19850725 DE 3447019 A 19841222 198531 B

Priority Applications (No Type Date): JP 843128 A 19840113

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

DE 3447019 A 12

- ... has exhalation air passage leading to discharge valve opening at predetermined pressure
- ...Abstract (Basic): is for a closed-circuit respirator, i.e. of the regenerative type. From the exhalation **system** leading from the mask (1) to a cleaning canister (7) there branches off an exhalation...
- ...so as to weaken the dynamic pressure dependent on respiration. This leads to a discharge **valve** (16) for the static pressure, opening when the latter exceeds a predetermined **valve** .
- ...The passage can comprise a hose (13) from the exhalation **system** and connected to a **bag** (14) of elastic material, also a pipe (15) of smaller ID than the hose...
- ... USE For rescue and fire fighting work, avoiding excess pressure rise.
- ... Title Terms: VALVE ;

International Patent Class (Additional): A62B-007/02

25/3,K/24 (Item 24 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

004132346

WPI Acc No: 1984-277886/198445

XRPX Acc No: N84-207454

Manual resuscitation apparatus - has first valve allowing forced respiration, free exhalation and spontaneous breathing to take place Patent Assignee: INSPIRON CORP (INSP-N); INTERTECH RESOURCES INC (INTE-N)

-Inventor:--COOK-W-F-------

Number of Countries: 004 Number of Patents: 005

Patent Family:

raconic ramirry.	•						
Patent No	Kind	Date	Applicat No	Kind	Date	Week	
GB 2139099	Α.	19841107	GB '8311439	A	19830504	198445	B
DE 3416350	Α	19841108	DE 3416350	A	19840503	198446	
GB 2139099	В	19861126	GB 8411439	A	19840504	198648	
CA 1220111	Α	19870407				198718	
US 4774941	Α	19881004	US 86941573	A	19861211	198842	

Priority Applications (No Type Date): US 83491572 A 19830504; US 85766673 A 19850816

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

GB 2139099 A 5

- ... has first valve allowing forced respiration, free exhalation and spontaneous breathing to take place
- ...Abstract (Basic): The resuscitation appts. comprises a squeeze bag with a gas inlet and a gas outlet, and a specifically configured valve (30,32) joined to the bag over the gas outlet. The valve housing (18) includes a squeeze bag port (39) in flow communication with the gas outlet opening, a patient port (36) and...
- ...The valve disposed in the housing includes a portion (30a) for directing fluid from the squeeze bag through the patient port during inhalation or forced respiration and through the exhalation port during exhalation. Another portion (30b) of the valve closes off the exhalation port during inhalation or forced respiration such that fluid from the squeeze bag is directed to the patient...
- ... USE The resuscitator is used during medical procedures .
- ...Abstract (Equivalent): A resuscitation apparatus comprising: (a) hollow squeeze bag means having first and second ends defining, respectively, first and second openings in flow communications with the interior thereof; (b) a first valve housing in confined flow communication with and joined to the squeeze bag means adjacent the first opening in the first end thereof, said first valve housing having a tubular squeeze bag port in flow communication with said squeeze bag means, a tubular patient port located adjacent said squeeze bag port and defining an annular valve seat, and an exhalation port having a tubular section which extends outwardly from the patient...
- ...said ports being in selective flow communication with one another through the interior of said valve housing; (c) first diaphragm valve means disposed in said first valve housing adjacent to and for selective engagement with said annular valve seat, said first diaphragm valve means serving for controlling the flow of fluid to

and from a patient and comprising (i) one-way valve portion means for directing fluid to pass only from said squeeze bag port through said patient port during inhalation, and (ii) sealing portion means annularly disposed about said valve seat and extending, during inhalation, at least partially into the annular section of the exhalation port beyond said valve seat, said sealing portion means serving for preVenting fluid to pass through said exhalation port during inhalation and forced respiration, such that fluid from said squeeze bag port is directed through said first valve housing, said first valve means and said patient port to the patient; and (d) a second valve means in confined flow communication with and joined to the squeeze bag means adjacent the second opening in the second end thereof, said second valve means serving for allowing fluid to pass only into said squeeze bag means.

- ...Abstract (Equivalent): The device comprises a squeeze bag having a gas inlet and a gas outlet, and a valve joined to the bag over the gas outlet. The valve housing includes a squeeze bag port in flow communication with the gas outlet opening, a patient port and an exhalation...
- ...The valve disposed in the housing includes a portion for directing fluid from the squeeze bag through the patient port during inhalation or forced respiration and through the exhalation port during exhalation. Another portion of the valve closes off the exhalation port during inhalation or forced respiration such that fluid from the squeeze bag is directed to the patient...
- ... USE Resuscitation apparatus for use during medical procedures . esp. during cardio pulmonary resuscitation .

...Title Terms: VALVE ; International Patent Class (Additional): A61M-016/00 ...

... A62B-007/04

25/3,K/25 (Item 25 from file: 350) DIALOG(R)File 350:Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

003982959

WPI Acc No: 1984-128503/198421

XRPX Acc No: N84-095087

Breathing appliance for narcosis inhalation - has bellow in bottle automatic system and hand operated ventilation bag for automatic and manual ventilation

Patent-Assignee: JEHMLICH-K-(JEHM-I)-; VEB-KOMB-MED-LABORTECH-LEIPZIG-(MEDZ-

Inventor: HEYMANN P; STIEGLER F

Number of Countries: 004 Number of Patents: 005

Patent Family:

	-						
itent No	Kind	Date	Applicat No	Kind	Date	Week	
3329604	Α	19840517	DE 3329604	A	19830817	198421	В
32732	T	19840928				198443	
218731	A	19850213				198524	
8307449	A	19851216				198609	
3329604	Ċ	19910627				199126	
	atent No E 3329604 J 32732 D 218731 S 8307449 E 3329604	E 3329604 A J 32732 T D 218731 A G 8307449 A	E 3329604 A 19840517 J 32732 T 19840928 D 218731 A 19850213 B 8307449 A 19851216	E 3329604 A 19840517 DE 3329604 J 32732 T 19840928 D 218731 A 19850213 G 8307449 A 19851216	E 3329604 A 19840517 DE 3329604 A J 32732 T 19840928 D 218731 A 19850213 G 8307449 A 19851216	E 3329604 A 19840517 DE 3329604 A 19830817 J 32732 T 19840928 D 218731 A 19850213 G 8307449 A 19851216	E 3329604 A 19840517 DE 3329604 A 19830817 198421 J 32732 T 19840928 198443 D 218731 A 19850213 198524 G 8307449 A 19851216 198609

Priority Applications (No Type Date): DD 244800 A 19821112

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

DE 3329604 A 19

- ... has bellow in bottle automatic system and hand operated ventilation bag for automatic and manual ventilation
- ...Abstract (Basic): The **bellow** in bottle automatic **system** and the hand-operated ventilation **bag** form components of a circuit which also has a control for frequency and breathing time...
- ...switch-off delay with a multi-function switch. The switching unit, which comprises a switching valve with its associated hand-operated ventilator bag and an exhalation valve with PEEP valve is connected through a third converter with the bellow in bottle system and to a connection of an ether circuit component...
- ...Abstract (Equivalent): artificial respiration unit is for anaesthesia respiration with automatic and manual respiration. An artificial respiration system has a bellows and a housing for automatic operation and a hand respiration bag (2) for manual operation. A changeover circuit shifts from automatic to manual. The system (1) circuit has a control (3) equipped for frequency and breathing time relationships is provided with a changeover unit (4), consisting of a changeover valve (11) with the bag (2) and an exhaling valve (12) with a PEEP valve. The control signal input (S) of the valve (11) is fed to a 1st binary DC voltage-pressure converter (5...
- ...The control signal input (S) of the **valve** (12) is fed to a 2nd binary DC voltage-pressure converter (6) which is connected...
- ...A further connection is made to the breathing gas connection (10) and the gas flow valve (22) across the system (1). The control signal input (S) on the output side is connected to a 3rd...

... Title Terms: BELLOWS;

International Patent Class (Additional): A61M-016/00 ...

... A61M-017/00

25/3,K/26 (Item 26 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

003371462

WPI Acc No: 1982-M9494E/198239

Manually-actuable cardio - pulmonary resuscitator - has bellows mounted on patient's chest and coupled endotracheal tube by valve

Patent Assignee: PHYSIO CONTROL CORP (PHYS-N)

Inventor: ALFERNESS C A

-Number-of-Countries:-001-Number-of-Patents:-001-

Patent Family:

Patent No Kind Date Applicat No Kind Date Week
US 4349015 A 19820914 198239 B

Priority Applications (No Type Date): US 80206576 A 19801114

Patent Details:

Patent No Kind Lan Pg Main IPC Filing Notes

US 4349015 A 8

Manually-actuable cardio - pulmonary resuscitator - ...

- ...has bellows mounted on patient's chest and coupled endotracheal tube by valve
- ...Abstract (Basic): The bellows is placed on the chest of a patient and includes a closed chamber which is coupled by a conduit and a valve to an airway inserted into the patient's airway, and by a second valve and a conduit to an inflatable bladder forming part of an abdominal restraint secured about the patient's body. As the bellows is compressed the first valve couples the gas being expelled from the bellows into the patient's lungs.
- ...The patient's intrathoracic pressure is increased due to the combination of the manual force applied to the patient's chest through the bellows and the pressure generated in the patient's lungs. When the bellows is being decompressed following the removal of manual force, the valve couples gas from the patient's lungs and from the atmosphere back to the bellows.
- ... Title Terms: PULMONARY;

25/3, K/27 (Item 27 from file: 350)

DIALOG(R) File 350: Derwent WPIX

(c) 2004 Thomson Derwent. All rts. reserv.

003270862

WPI Acc No: 1982-B8845E/198208

Breathing apparatus with intermittent forced breathing facility - has valve combination including positive end - expiratory pressure

type glass dome valve

Patent Assignee: JEHMLICH K (JEHM-I); VEB MEDIZINTECH LEIPZIG (MEDZ )

-Inventor:-JEHMI-LICH-K;-MUELLER-R-

Number of Countries: 002 Number of Patents: 002

Patent Family:

Patent No Kind Date Applicat No Kind Date Week
DE 3104325 A 19820218 198208 B
DD 155685 A 19820630 198243

Priority Applications (No Type Date): DD 221964 A 19800619 Patent Details:
Patent No Kind Lan Pg Main IPC Filing Notes
DE 3104325 A 12

... has valve combination including positive end - expiratory pressure type glass dome valve

- ... Abstract (Basic): The breathing appts provides intermittent forced breathing by using existing equipment of ordinary breathing systems. This is achieved by employing a valve combination in the inspiration line which links a pressure/volume/time-control unit, via a three way junction with a breathing bag and a regulator valve and flowmeter respectively...
- ...A valve combination which includes positive endexpiratory pressure valve in the inspiration line is linked via a three way junction. This has a breathing bag on the one hand and a regulator valve and a flow meter on the other.

... Title Terms: VALVE ;

...International Patent Class (Additional): A61M-016/00

	Set S1	Items 47	
			SKI T? OR ZIELINSKI, T? OR BIONDI J? OR BIONDI, J?)
	S2	2609	CPR OR (CARDIOPULMON? OR CARDIO()PULMON?)(W)(RESUSCIT? OR - RESPIRAT? OR VENTILAT? OR CIRCULAT?) OR MANUAL?()RESUSC? OR E-
•			MERGENCY()MEDICAL?
	S3	6397	PEEP OR PEP OR POSITIVE()(ASSIST? OR PRESSUR?)(2N)(BREATH? OR VENTILAT? OR RESPIRAT?) OR POSITIVE()END()EXPIR?()PRESSURE
			OR (MEDICAL OR EMT OR FIRE) (2N) RESCUE?
3	S4	254253	
	S5	85564	(POSITIVE OR RESPIRAT? OR EXPIRAT? OR EXHAL?) BAG OR BAGS OR SACK? ? OR SMARTBAG? OR SMART()BAG OR AMBUB-
			AG? OR AMBU OR POUCH?? OR BELLOW?
	S6	436953	,
	s7	95888	THORAX? OR THORAC? OR CHEST??? OR LUNG? ? OR PULMON? OR IN- TRATHORA?
	S8	195291	
	S9	25685	
			RAUMA? OR INJUR?) OR CARDIAC()ARREST OR HEART()ATTACK OR MYOC-
			ARD?()INFARCT? OR (HEMORRHAG? OR HAEMORRHAG?)()SHOCK? OR BLOO-
			D()LOSS??
	S10	365290	the second of th
	S11	1308838	OR TELECOMMUNICAT? METHOD? ?
	S12	1143438	
	Š13	575888	
	S14	446770	
	S15	1016995	
	S16	39696	
	S17	1058	
		-	)FLOW??? OR BLOOD()CIRCULAT?)(2N)(RETURN? OR BACK)(2N)(HEART? OR CARDIAC?) OR LOWER?()PRESSUR?(2N)(RIGHT()ATRIUM) OR LOWER?-
			() PRESSUR? (2N) (THORAX? OR THORAC?) () VENA() CAVA
	S18	72	
	S19	49	
	S20	8	,
	S21	16	
	S22 S23	49 49	
	S24	49	IDPAT (sorted in duplicate/non-duplicate ords
	? sho	w files	, see a superior of the see a se
	File		S19:S22 IDPAT (sorted in duplicate/non-duplicate orde  PEAN PATENTS 1978-2004/May W01  2004 Furopean Patent Office
	m! 1		
	File		FULLTEXT 1979-2002/UB=20040513,UT=20040506
	?	(0)	2004 WIPO/Onivencia
	·		SECRETED
-			25€1€1
			ED. FED
			Hirs
			H173
		•	<i>√</i>
		•	

```
DIALOG(R) File 348: EUROPEAN PATENTS
(c) 2004 European Patent Office. All rts. reserv.
00804856
CPR DEVICE HAVING STRUCTURE FOR INCREASING THE DURATION AND MAGNITUDE OF
    NEGATIVE INTRA- THORACIC PRESSURE
HERZ-LUNGEN-WIEDERBELEBUNGSEINRICHTUNG MIT DER MOGLICHKEIT ZUM ERHOHEN DER
    DAUER UND DES BETRAGES DES NEGATIVEN INNEREN THORAXDRUCKS
DISPOSITIF DE REANIMATION CARDIO- PULMONAIRE A STRUCTURE AUGMENTANT LA
    DUREE ET L'INTENSITE D'UNE PRESSION INTRA- THORACIQUE NEGATIVE.
PATENT ASSIGNEE:
  CPRX, LLC., (4268230), 7615 Golden Triangle Drive, Suite A, Technology
    Park #5, Eden Prairie, MN 55344, (US), (Proprietor designated states:
    all)
INVENTOR:
  EURIE, Keith, G., 4751 Girard Avenue South, Minneapolis, MN 55409, (US)
  SWEENEY, Michael, 1525 Goodrich Avenue, St. Paul, MN 55105, (US)
  GOLD, Barbara, 4751 Girard Avenue South, Minneapolis, MN 55409, (US)
LEGAL REPRESENTATIVE:
  Sanderson, Michael John et al (35592), MEWBURN ELLIS York House 23
    Kingsway, London WC2B 6HP, (GB)
PATENT (CC, No, Kind, Date): EP 898485 A1
                                             990303 (Basic)
                              EP 898485 A1
                              EP 898485 B1 030502
                              WO 96028215 960919
                              EP 96905523 960216; WO 96US2097
APPLICATION (CC, No, Date):
PRIORITY (CC, No, Date): US 403009 950310
DESIGNATED STATES: DE; FR; GB; IT; SE
INTERNATIONAL PATENT CLASS: A62B-007/00; A62B-009/02; A61M-016/04;
  A61M-016/20
NOTE:
  No A-document published by EPO
LANGUAGE (Publication, Procedural, Application): English; English; English
FULLTEXT AVAILABILITY:
Available Text Language
                           Update
                                     Word Count
      CLAIMS B
               (English)
                           200318
                                     1103
      CLAIMS B
                (German)
                           200318
                                      1185
                                      1195
      CLAIMS B . (French)
                           200318
                                      9175
      SPEC B
                (English) 200318
Total word count - document A
                                         0
Total word count - document B
                                     12658
Total word count - documents A + B
                                     12658
CPR DEVICE HAVING STRUCTURE FOR INCREASING THE DURATION AND MAGNITUDE OF
    NEGATIVE INTRA- THORACIC PRESSURE
... LUNGEN-WIEDERBELEBUNGSEINRICHTUNG MIT DER MOGLICHKEIT ZUM ERHOHEN DER
    DAUER UND DES BETRAGES DES NEGATIVEN INNEREN THORAXDRUCKS
DISPOSITIF DE REANIMATION CARDIO- PULMONAIRE A STRUCTURE AUGMENTANT LA
    DUREE ET L'INTENSITE D'UNE PRESSION INTRA- THORACIQUE NEGATIVE.
INTERNATIONAL PATENT CLASS: A62B-007/00 ...
... A62B-009/02 ...
... A61M-016/04 ...
... A61M-016/20
LEGAL STATUS (Type, Pub Date, Kind, Text):
...Advanced Circulatory Systems , Inc. (4475370) 7615 Golden Triangle
                            Drive, Suite A, Eden Prairie, Minnesota 55344
```

24/3,K/5

(Item 5 from file: 348)

Application...

# ... SPECIFICATION THE INVENTION

1. Field of the Invention

The present invention relates generally to devices and methods used in conjunction with external chest compression and decompression as a part of cardiopulmonary resuscitation procedures. In particular, the present invention relates to devices and methods for increasing cardiopulmonary circulation induced by chest compression and decompression when performing cardiopulmonary resuscitation.

Worldwide, sudden cardiac arrest is a major cause of death and is the result of a variety of circumstances, including heart disease and significant trauma. In the event of a cardiac arrest, several measures have been deemed to be essential in order to improve a patient's

...possible to at least partially restore the patient's respiration and blood circulation. One common technique, developed approximately 30 years ago, is an external chest compression technique generally referred to as cardiopulmonary resuscitation (CPR). CPR techniques have remained largely unchanged over the past two decades.

With traditional CPR, pressure is applied to a patient's chest in order to increase intrathoracic pressure. An increase in intrathoracic pressure induces blood movement from the region of the heart and lungs towards the peripheral arteries. Such pressure partially restores the patient's circulation. Traditional CPR is performed by actively compressing the chest by direct application of an external pressure to the chest. After active compression, the chest is allowed to expand by its natural elasticity which causes expansion of the patient's chest wall. This expansion allows some blood to enter the cardiac chambers of the heart. The procedure as described, however, is insufficient to ventilate the patient. Consequently, conventional CPR also requires periodic ventilation of the patient. This is commonly accomplished by mouth-to-mouth technique or by using positive-pressure devices, such as a self-inflating bag which relies on...

In order to increase cardiopulmonary circulation induced by chest compression, a technique referred to as active compression — decompression (ACD) has been developed. According to ACD techniques, the active compression phase of traditional CPR is enhanced by pressing an applicator body against the patient's chest to compress the chest. Such an applicator body is able to distribute and apply force substantially evenly over a portion of the patient's chest. More importantly, however, the applicator body is sealed against the patient's chest so that it may be lifted to actively expand the patient's chest during the decompression step. The resultant negative intrathoracic pressure induces venous blood to flow into the heart and lungs from the peripheral venous vasculature of the patient.

Also of importance to the invention are ventilation sources that are used in connection with CPR techniques to properly ventilate the patient. One type of ventilation source is the AMBU bag available from AMBU International, Copenhagen, Denmark. The AMBU bag can also be used in connection with a positive end - expiratory pressure ( PEEP ) valve, available from AMBU International, to treat some patients with pulmonary and cardiac diseases. However, until the present invention, a positive end-expiratory pressure valve in connection with

a ventilation source has not been used with any CPR techniques . With both traditional CPR and ACD-CPR techniques , an increase in the amount of venous blood flowing into the heart and lungs from the peripheral venous vasculature would be desirable to increase the volume of oxygenated blood leaving the thorax during the subsequent compression phase. It would therefore be desirable to provide improved methods and apparatus for enhancing venous blood flow into the heart and lungs of a patient from the peripheral venous vasculature during both conventional CPR and ACD-CPR techniques . It would be particularly desirable\_to\_provide\_techniques\_which\_would\_enhance\_oxygenation\_and increase the total blood return to the chest during the decompression step of CPR and ACD-CPR, more particularly of ACD-CPR. This can be accomplished according to the present invention by augmentation of both negative and positive intrathoracic pressure, thereby amplifying the total intrathoracic pressure swing. An invention for providing this crucial improvement is described.

2. Description of the Background Art

ACD-CPR techniques are described in detail in Todd J. Cohen et al., Active Compression - Decompression Resuscitation: A Novel Method of Cardiopulmonary Resuscitation, American Heart Journal, Vol. 124, No. 5, pp. 1145-1150, November 1992; and Todd J. Cohen et al., Active Compression - Decompression: A New Method of Cardiopulmonary Resuscitation, The Journal of the American Medical Association, Vol. 267, No. 21, June 3, 1992.

The use of a vacuum -type cup for actively compressing and decompressing a patient's chest during ACD- CPR is described in a brochure of AMBU International A/S, Copenhagen, Denmark, entitled Directions for Use of AMBU(R) CardioPump(TM), published...

...connected a tubule that extends towards the opposite end of the tube and into a valve housing having an air inlet bore from which passages extend to the tubule and to an inflatable member. The bore contains valve means normally closing the adjacent ends of the passages, and means for opening the valve to admit air under pressure to those passages or to release it therefrom. The valve housing also has a bypass connecting the two passages and closed by a check valve preventing escape of air from the cuff to the inflatable member in case the outside...

# ...SUMMARY OF THE INVENTION

According to the invention, devices for increasing cardiopulmonary circulation induced by **chest compression** and **decompression** when performing cardiopulmonary resuscitation are provided. The devices may be used in connection with any generally accepted CPR **methods** or with active **compression** - **decompression** (ACD) CPR **techniques**. Preferably, the **methods** and devices will be used in connection with ACD-CPR.

Cardiopulmonary circulation is increased according to the invention by impeding airflow into a patient's lungs during the decompression phase. This increases the magnitude and prolongs the duration of negative intrathoracic pressure during decompression of the patient's chest, ie. increases the duration and degree that the intrathoracic pressure is below or negative with respect to the pressure in the peripheral venous vasculature. By enhancing the amount of venous blood flow into the heart and lungs, since equilibration of intrathoracic pressure during decompression occurs to a greater extent from enhanced venous return rather than rapid inflow of gases into the chest via the patient's airway, cardiopulmonary circulation is increased.

According to the present invention there is provided a valving

system for regulating airflow into a patient's lungs when performing
cardiopulmohary resuscitation wherein the patient's chest is
compressed and decompressed, the system comprising, a housing having
an upstream region and a downstream region, characterised by means
between...

...flow into the downstream region when ventilating the patient.

The inhibiting means may comprise a valve which allows airflow from the downstream region to the upstream region, the valve may include a diaphragm which is closed when the pressure in the downstream region is

... region to open the diaphragm and to allow air to flow to the patient's  ${f lungs}$  .

Conveniently the means for allowing air into the downstream region comprises a manually operable **valve** at the downstream region which is manually opened to allow air to flow unimpeded into...

...patient.

The means for allowing air into the downstream region may comprise a pressure responsive valve at the downstream region for allowing air into the downstream region when the pressure in...

...level in the range from -5 cm H2))O to -60 cm H2))O.

The **system** may further comprise a respiratory member connected to the housing at the upstream region for...

...air exhaust opening at the upstream region for exhausting air from the housing, and a **valve** in the exhaust opening which inhibits air from flowing into the housing through the exhaust opening.

Such a **system** may further comprise means for preventing air from exiting the housing through the exhaust opening during injection of air from the respiratory bag, which means may be a fish mouth **valve**, and a connection member connected to the housing at the downstream region for connecting the...

...connection member may include an endotracheal tube, a facial mask, or a laryngeal mask.

A valving system according to the invention may further comprise a respirator connected to the housing at the...

...airway tube may include an endotracheal tube.

Apparatus for assisting cardiopulmonary resuscitation may comprise a valving system as defined above together with an endotracheal tube of the type having a tube suitable...

...whereby airflow is impeded to a fixed or variable degree from entering the patient's lungs to enhance the extent and duration of negative intrathoracic pressure during decompression of the patient's chest to enhance venous blood flow into the heart and lungs from the peripheral venous vasculature when performing cardiopulmonary resuscitation.

The means for inhibiting air flow...

... the endotracheal tube.

Alternatively, the means for inhibiting air flow may comprise a pressure-responsive valve within the first lumen of the tube, the valve being biased to open to permit the inflow of air when the intrathoracic pressure falls below a threshold level in the range from 0 cm H2))O to...

...bypassing air round the inflow impeding means.

Apparatus for assisting cardiopulmonary resuscitation may comprise a valving system as defined above together with a compressible structure having a first opening and a second opening, a one-way valve for the intake of air included in or attached to the first opening, and means...

...a preselected volume of air, means for interfacing in a permanent or detachable manner said compressible structure to the patient, and means included in or attached to the second opening of the compressible structure to impede the flow of gases to the patient's lungs until a minimum intrathoracic pressure is exceeded, whereby a rise in intrathoracic pressure is slowed during decompression of the patient's chest and the extent and duration of negative intrathoracic pressure is enhanced in order to enhance venous blood flow into the heart and lungs from the peripheral venous vasculature when performing cardiopulmonary resuscitation.

The inflow impeding means may further...

...orifice disposed within or connected in series in a permanent or detachable manner with the **compressible** structure.

Alternatively the inflow impeding means may comprise a pressure-responsive valve, the valve being biased to open to permit the inflow of air when the intrathoracic pressure falls below a threshold level in the range from 0 cm H2))O to...

...or a laryngeal mask.

#### BRIEF DESCRIPTION OF THE DRAWINGS

. Fig. 1 is a graph illustrating thoracic pressure changes over time when compressing and decompressing a patient's chest according to the present invention.

Fig. 2A is a schematic view illustrating airflow through a ventilation circuit when **compressing** a patient's **chest** according to the present invention.

Fig. 2B is a schematic view illustrating airflow through a ventilation circuit when **decompressing** a patient's **chest** according to the present invention.

Fig. 3 is a schematic illustration of a first alternative embodiment of a device for impeding airflow into a patient's **lungs** according to the present invention.

Fig. 4A is a schematic illustration of a second alternative embodiment of the device for impeding airflow into a patient's **lungs** according to the present invention.

Fig. 4B is a schematic illustration of the device in...

...a common inhalation/exhalation port.

Fig. 5A is a schematic view of a one-way valve used in the device for impeding airflow according to the present invention.

Fig. 5B is a schematic view of the one-way valve in Fig. 5A that is held open after ACD-CPR has ceased.

Fig. 5C is a schematic view of a one-way valve that is closed until a threshold pressure is present in the tube according to the present invention.

Fig. 6A is a schematic view of a spring biased inflow valve and a spring biased expiration valve to be used in accordance with the present invention.

Fig. 6B is a schematic view of Fig. 6A showing the operation of the valves during outflow of air.

Fig. 6C is a schematic view of Fig. 6A showing the operation of the valves during inflow of air.

Fig. 7 is a schematic view of a single valve that is spring biased from both sides to be used as an inflow valve and an expiration valve according to the present invention.

Fig.  $\tilde{8}$  is a schematic view of a flow restricting...

...view of an exemplary embodiment of the device for impeding airflow into a patient's lungs according to the present invention.

Figs. 10A-10C are schematic views illustrating another embodiment of the present invention allowing for periodic patient ventilation through a

bypassing valve .

Fig. 11 is a schematic view of an exemplary valving system for regulating airflow into a patient's lungs according to the present invention. The valving system is shown with air being exhausted from a patient's lungs during compression of the patient's chest.

Fig. 12 illustrates the valving system of Fig. 11 during

decompression or resting of the patient's chest .

Fig. 13 illustrates the valving system of Fig. 11 with a pressure-responsive valve being opened when the negative intrathoracic pressure in the patient's chest exceeds a threshold amount during decompression of the patient's chest.

Fig. 14 illustrates the valving system of Fig. 11 with a diaphragm being opened during injection of air into the housing when ventilating

the patient.

Fig. 15 illustrates the valving system of Fig. 11 with a manually operable valve being opened to allow air into the patient's lungs upon return of spontaneous circulation.

Fig. 16A is a cutaway side view of exemplary valving system

according to the present invention.

Fig. 16B is a top view of a deflector and a fenestrated mount of the valving system of Fig. 16A.

Fig. 16C is an alternative embodiment of the valving system of

Fig. 16A.

Fig. 17 is a schematic view of an alternative embodiment of a valving system having a ball as a diaphragm.

## DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

According to the present invention, methods and devices for increasing cardiopulmonary circulation induced by chest compression and decompression when performing cardiopulmonary resuscitation are provided. Such methods and devices may be used in connection with any method of CPR in which intrathoracic pressures are intentionally manipulated to improve cardiopulmonary circulation. For instance, the present invention would improve standard manual CPR, "vest" CPR, CPR with a newly described Hiack Oscillator ventilatory system which operates essentially like an iron-lung-like device, interposed abdominal compression - decompression CPR, and active compression - decompression (ACD) CPR techniques. Although the present invention may improve all such techniques, the following description will refer primarily to improvements of ACD-CPR techniques in order to simplify discussion. However, the claimed devices are not exclusively limited to ACD-CPR techniques.

The proper performance of ACD-CPR to increase cardiopulmonary circulation is accomplished by actively compressing a patient's chest with anapplicator body. Preferably, this applicator body will be a suction -type device that will adhere to the patient's chest, such as the AMBU(R) CardioPump(TM), available from AMBU International, Copenhagen, Denmark. After the compression step, the adherence of the applicator body to the patient's chest allows the patient's chest to

be lifted to actively decompress the patient's chest. The result of such active compression - decompression is to increase intrathoracic pressure during the compression step, and to increase the negative intrathoracic pressure during the decompression step thus enhancing the blood-oxygenation process and enhancing cardiopulmonary circulation. ACD-CPR techniques are described in detail in Todd J. Cohen et al., Active Compression - Decompression Resuscitation: A Novel Method of Cardiopulmonary Resuscitation, American Heart Journal, Vol. 124, No. 5, pp. 1145-1150, November 1992; Todd J. Cohen et al., Active Compression - Decompression: A New Method of Cardiopulmonary Resuscitation, The Journal of the American Medical Association, Vol. 267, No. 21, June...

The present invention is especially useful in connection with ACD-CPR techniques. In particular, the invention improves ACD-CPR by providing methods and devices which impede airflow into a patient's lungs to enhance negative intrathoracic pressure during the decompression of the patient's chest, thus increasing the degree and duration of a pressure differential between the thorax (including the heart and lungs) and the peripheral venous vasculature. Enhancing negative intrathoracic pressure with simultaneous impedance of movement of gases into the airway thus enhances venous blood flow into the heart and lungs and increases cardiopulmonary circulation.

In a broad sense, the present invention provides for occluding a patient's airway to prevent foreign (outside) air from flowing to a patient's lungs during the active decompression step of ACD-CPR to enhance and sustain the duration of negative intrathoracic pressure and enhance blood oxygenation and cardiopulmonary circulation during both active decompression and the subsequent compression phase. The patient's airway may be occluded or inflow of gases impeded by any...

...of the present invention provides for allowing impeded air to flow into the patient's lungs during the active decompression step of ACD-CPR in order to provide some ventilation to the patient while still enhancing the extent and duration of negative intrathoracic pressure to enhance blood oxygenation. Impeding airflow to the patient's lungs may be accomplished by any flow restrictive element such as an orifice, a one-way valve, a spring biased or other valve which is set to open when the negative intrathoracic pressure is in the range from about 0 cm H2))O to -100 cm H2))O, or the like. A valve designed to open at a threshold pressure value may be either fixed or variable, i.e., the pressure at which the valve opens may be adjusted or may be permanently fixed.

Similarly, another aspect of the invention provides for air to be impeded from leaving the patient's lungs during compression of the patient's chest to further enhance cardiopulmonary circulation by enhancing intrathoracic pressure during the compression phase. Typically, air is impeded from leaving the lungs during the compression phase when the positive intrathoracic pressure is in the range from about 2 cm H2))0 to 50 cm H2...

...during ACD-CPR. Ventilation of the patient is performed at about every two to 10 compressions, preferably every five compressions, thus providing sufficient fresh air for adequate gas exchange with the blood in the lungs to the patient. Ventilating the patient may be accomplished by any device or method suitable such as by mouth-to-mouth resuscitation, by a compressible or collapsible structure, by a ventilatory bag such as the AMBU bag available from AMBU, Copenhagen, Denmark, or the like. Ventilation could also be superimposed on the

compression phase to further augment positive intrathoracic pressure. Furthermore, periodic ventilation could be performed either through the impeding step or by bypassing the impeding step altogether.

Referring now to Fig. 1, a graph illustrating thoracic pressure changes over time when compressing and decompressing the patient's chest is shown. Area 10 represents the amount of thoracic pressure during the compression phase of ACD-CPR. Cross-hatched area 12 represents the negative thoracic pressure during the decompression step of ACD-CPR without a flow restrictive means to restrict the flow of air into the patient's lungs. Double cross-hatched area 14 represents the increase in negative thoracic pressure when the patient's airway is occluded according to the present invention during the decompression step of ACD-CPR. The significance of the increase in negative intrathoracic pressure during the decompression step is that more venous blood is forced into the chest from the peripheral venous vasculature. Consequently, more blood is allowed to be oxygenated and more blood is forced out of the chest during the next compression.

In an exemplary embodiment, airflow may be impeded to the patient's lungs during decompression of the patient's chest by placing a ventilatory mask over the patient's mouth and nose. The ventilatory mask also has a pressure-responsive valve attached to prevent airflow to the patient's lungs until the negative intrathoracic pressure of the patient reaches a threshold amount. Also attached to the mask and the pressure-responsive valve is a ventilatory source to provide ventilation to the patient. The ventilatory source may be...

...is needed, the AMBU bag may be squeezed to force air into the patient's lungs . The AMBU bag is described in U. ...an AMBU bag, is used in connection with an improved endotracheal tube. A pressure-responsive valve or other flow restrictive element is placed between the AMBU bag and the endotracheal tube. Preferably, the valve will be positioned within a tube that connects the AMBU bag to the endotracheal tube...

...performed on the patient, the endotracheal tube is placed in the patient's trachea. During decompression of the patient's chest, the valve prevents airflow to the patient's lungs until the intrathoracic pressure reaches a threshold amount. Additionally, the AMBU bag may be used to ventilate the patient at a desired time. Also included in this embodiment is a one-way expiration valve. This valve allows for expiration of air from the patient during the compression step.

In a modification of either of the first two embodiments, a pressure-responsive expiration valve may also be inserted between the AMBU bag (or comparable ventilation source) and the mask or endotracheal tube. This valve works in a similar manner to the pressure-responsive valve which restricts airflow into the patient's lungs. However, the pressure-responsive expiration valve restricts airflow from the patient's lungs during the compression step of ACD-CPR. An equivalent valve is a positive end0 - expiratory pressure (PEEP) valve available from AMBU International, Copenhagen, Denmark. Use of such a pressure-responsive expiration valve during compression may further increase intrathoracic pressure and thereby force more blood out of the thorax.

In another alternative embodiment, an improved endotracheal tube is used to restrict airflow into the patient's lungs during the active decompression step. Included in the endotracheal tube is a flow restrictive element which operates to impede air from flowing into the patient's lungs. When the endotracheal tube is inserted into the patient's trachea and the patient's chest is actively decompressed, the flow restrictive element impedes air from flowing to the patient's

lungs slowing the rise in intrathoracic pressure and thus enhancing blood oxygenation.

When using the improved endotracheal tube during ACD-CPR...
...the endotracheal tube to force oxygen through the endotracheal tube and into the patient's lungs.

Referring now to Fig. 2A, a schematic view illustrating airflow through a ventilation circuit 20 when **compressing** a patient's **chest** according to the present invention is shown. During ACD-CPR, the **chest** is actively **compressed** forcing air out of the **lungs**. This air is allowed to expire through a one-way expiration **valve** 22 within a ventilation circuit 20.

Referring now to Fig. 2B, the same schematic is shown illustrating airflow through the ventilation circuit 20 when decompressing the patient's chest. When the patient's chest is actively decompressed, a negative intrathoracic pressure is created. When this pressure reaches a threshold amount, the inflow valve 24 will open causing air to flow through the ventilation circuit 20 into the patient's lungs. Air is allowed into the ventilation circuit 20 through a ventilation valve 26 and into a ventilation bag 28. From the ventilation bag 28, the air passes through the inflow valve 24 when the negative intrathoracic pressure reaches the threshold amount. The ventilation bag 28 is also used to manually ventilate the patient during ACD-CPR as required.

The method as discussed in connection with Figs. 2A and 2B requires the chest to be compressed in the range from about 3.5 cm to 5 cm per compression and at a rate from about 60 to 100 compressions per minute for adults.

Referring now to Fig. 3, a schematic illustration of a first alternative embodiment of a device 35 for impeding airflow into a patient's **lungs** according to the present invention is shown. The device 35 comprises an endotracheal tube 36...

...can comprise any type of ventilation source capable of ventilating the patient such as a compressible or collapsible structure. Preferably, the ventilation bag 28 consists of an AMBU bag. Attached or connected to the end of the ventilation bag 28 is a one-way ventilation valve 26. The ventilation valve 26 serves to introduce air into the device 35. Attached or connected to the transition tube 38 is an inflow pressure-responsive valve 24. The inflow valve 24 is biased so that it opens when the negative intrathoracic pressure in the patient's chest reaches a threshold amount. As shown, only one inflow valve 24 is included in the device 35. However, the invention is not limited to only one inflow valve 24. Alternatively, a plurality of inflow valves 24 could be connected in series along the ventilation tube 38. The inflow valve 24 is also not limited to being connected in the center of the transition tube 38, but may be positioned anywhere along the transition tube 38. The inflow valve 24 could be permanently attached to the ventilation bag 28 or transition tube 38 or could be detachable. Alternatively, the inflow valve 24 could be connected to the ventilation bag 28 itself or to the endotracheal tube 36.

The device 35 also contains a one-way expiration valve 22 which allows for air to be expired from the patient's lungs. This generally occurs during the compression phase of ACD-CPR. To insure that the air expired from the patient's lungs will exit through the expiration valve 22, a one-way fish mouth valve 37 (the preferred valve) or any other type of one-way valve can be placed between the inflow valve 24 and the expiration valve 22. Alternatively, the inflow valve 24 itself may be configured as a one-way valve. In either case, air flowing from the endotracheal tube 36 toward the ventilation bag 28 will be forced to expire through the expiration valve 22.

The device 35 may be further modified to include a pressure-responsive expiration valve (not shown) located between the endotracheal tube 36 and the transition tube 38. The pressure-responsive expiration valve works in a reverse manner to that of the inflow valve 24. Specifically, the pressure-responsive expiration valve is biased so that during the compression step of ACD-CPR, air will be allowed to expire from the patient's lungs only when the intrathoracic pressure reaches a threshold amount. The increase in intrathoracic pressure caused by the pressure-responsive expiration valve during compression may assist in forcing-more-blood-out-of-the-thorax - and reduce-atelectasis of the lungs .

The purpose of the ventilation bag 28 is to provide ventilation to the patient during ACD- CPR . When the ventilation bag 28 comprises an AMBU bag or similar bag used for ventilation, ventilation of the patient may be performed by merely squeezing the AMBU bag with a human hand. This forces air to the patient's lungs as desired.

Referring to Fig. 4A, a second alternative embodiment of the device for impeding airflow into a patient's lungs according to the present invention is shown. This particular embodiment is a modified and improved

...inflow lumen 42. Located within outflow lumen 40 is a one-way pressure-responsive expiration valve 44 which operates in a manner similar to that discussed in connection with Fig. 3, except that the expiration valve 44 is specifically designed as a one-way valve. Located within inflow lumen 42 is a one-way pressure-responsive inflow valve 45 which operates to impede airflow to the lungs as discussed in connection with Fig. 3, except that the inflow valve 45 is also specifically designed as a one-way  $\ \ \, valve \ .$  Also shown in inflow lumen 42 and outflow lumen 40 is an O-ring 46 which will be discussed subsequently. Inflow valve 45 and expiration valve 44 are designed as one-way valves so that during the compression phase, air can only be expired from the patient through the endotracheal tube 36 when the intrathoracic pressure reaches a threshold amount. At that moment, expiration valve 44 opens and air expires from the patient through the outflow lumen 40. During decompression, air cannot flow through the endotracheal tube 36 to the patient's lungs until the negative intrathoracic pressure reaches a threshold amount. At that moment, inflow valve 45 opens allowing air to flow through inflow lumen 42 to the patient's lungs . Air is prevented from entering through the outflow lumen 40 because of the one-way expiration valve 44.

Ventilation is possible with the embodiment disclosed in Figs. 4A and

4B if the...

...through the inflow lumen 42, through the endotracheal tube 36, and to the patient's lungs . In this embodiment, expiration valve 44 is designed so that during ventilation, expiration valve 44 will remain temporarily closed preventing air flowing through inflow lumen 42 escape through outflow lumen 40.

Fig. 5A is a schematic view of a one-way inflow valve 45 used in a device for impeding airflow according to the present invention. The inflow valve 45 operates so as to allow air only to flow in one direction. As shown, the spring biased inflow valve 45 is completely open. However, the invention also functions properly if the spring biased inflow valve 45 or the spring biased expiration valve 44 are not fully open. Upon successful completion of ACD-CPR, the O-ring 46 that is positioned above the inflow valve 45 is repositioned so that inflow valve 45 is held open as shown in Fig. 5B. Such a positioning of O-ring

...airflow to the patient once there is a return of spontaneous circulation and the inflow valve 45 is no longer needed. An O-ring 46 is also used in a similar manner to lock the one-way expiration valve 44 in an open position upon return of spontaneous circulation. Fig. 5C illustrates the one-way inflow valve 45 in a closed position. When closed, the inflow of air through the inflow valve 45 is occluded.

Fig. 6A illustrates an inflow valve 47 that is spring biased and an expiration valve 48 that is also spring biased. The inflow valve 47 and the expiration valve 48 are connected in series and may be used in the first alternative embodiment as...

...discussed following in connection with Fig. 9. As shown in Fig. 6C, during the active decompression step, the inflow valve 47 is biased such that it will open when the negative intrathoracic pressure reaches a threshold amount. During the compression phase of ACD-GPR the expiration valve 48 will open to allow air to expire from the patient's lungs when the intrathoracic pressure within the patient's chest reaches a threshold amount as shown in Fig. 6B. Since neither inflow valve 47 nor expiration valve 48 are one-way valves, a fish mouth valve 37 used in connection with a one-way expiration valve 22 as discussed in connection with Fig. 3 must be used. Other valves designed upon a similar principle as the fish mouth valve combination with a one-way expiration valve0 could also be used. Only one inflow valve 24 and one positive end pressure valve 44 are shown in Figs. 6A-6C. However, a plurality of inflow valves 47 and/or expiration valves 48 may be connected in a permanent or detachable manner in series to impede the inflow and outflow of air.

Although the valves in Figs. 6A-6C are shown as being spring-biased, any other valves designed upon a similar principle would work equally as well. The use of such valves as disclosed in Figs. 6A-6C is only one embodiment and valves constructed according to various other methods and materials is also within the scope of the invention.

As shown in Fig. 7, the inflow valve 47 and the expiration valve 48 may be combined into one joint valve 49 as shown. The joint valve 49 will operate in a manner similar to the two valves 47 and 48 as described in connection with Fig. 6.

Fig. 8 illustrates a flow...

...to be used to either impede the airflow into or out of a patient's lungs. The flow restricting orifice 50 operates so that during the decompression step of ACD-CPR airflow is impeded from entering into the patient's lungs, thus increasing the negative intrathoracic pressure. During the compression step, the flow restricting orifice 50 operates to increase the thoracic pressure in the patient's chest by restricting air from existing from the patient's lungs.

Fig. 9 illustrates an exemplary embodiment for impeding airflow into a patient's lungs according to the present invention. As shown, the device 51 comprises a ventilation bag 28 that is connected to a facial mask 52 by an inflow valve 24 and an expiration valve 22. Although the facial mask 52 is shown connected to the ventilation bag 28, the...

...52 can be used alone or in connection with the ventilation bag. Between the inflow valve 24 and the expiration valve 22 is a one-way fish mouth valve 37 or any other type of one-way valve to prevent air from exiting the patient's lungs and flowing to the ventilation bag 28. The ventilation bag 28 also contains a one-way ventilation valve 26 for allowing air to inflow into the device 51. The exemplary embodiment operates in...

During the decompression phase of ACD-CPR, air is prevented from entering into the patient's lungs through the threshold inflow valve 24 thus increasing the negative intrathoracic pressure. During the compression phase, air is allowed to expire from the patient's lungs through the expiration valve 22. Also, the patient can be ventilated during ACD- CPR by manually squeezing the ventilation bag 28. Consequently, the preferred embodiment serves to enhance cardiopulmonary circulation by increasing the negative intrathoracic pressure to force-more-blood-into-the-chest—from-the-peripheral-venous-vasculature.

Figs. 10A - 10C show another embodiment of the present invention...

...that is connected to the patient. The ventilation tube 60 has a one-way bypass valve 66 and a one-way pressure responsive valve 68. The ventilation tube 60 may also have a manual switch 70 attached to the bypass valve 66 and extending through a side of the ventilation tube 60. As shown in Fig...

responsive valve 68 opens when the threshold pressure of the valve 68 has been exceeded. At this point, the valve 68 opens allowing for ventilation of the patient. As shown in Fig. 10B, the one-way pressure responsive valve 68 may be bypassed altogether by manually placing the switch 70 in the open position so that the bypass valve 66 is opened allowing air to flow to the patient. Fig. 10C illustrates the operation of the bypass valve 66 with the switch 70 in an inactive mode. Here, the rescuer performing ventilation may do so without added resistance from the impedance step as in Fig. 10A. Instead, bypass valve 66 opens only when the pressure at the proximal end of the tube 62 is...

...pressure (0 nmHg), preferably in a range from about 0 mmHg to 5 mmHg. During decompression of the patient's chest, the one-way bypass valve 66 remains closed unless atmospheric pressure is exceeded. Thus, the patient is ventilated only when...

...of the tube 62 to exceed atmospheric pressure. The function of the one-way bypass valve 66 may be performed by many different threshold valve designs which are known in the art.

In another aspect of the invention, an exemplary valving system is provided for enhancing the duration and extent of negative intrathoracic pressure during the decompression phase of CPR while still providing adequate ventilation to the patient. The valving system is employed to slow the rapid equilibrium of intrathoracic pressure in the chest during decompression by impeding or inhibiting the flow of air into the patient's chest. Lowering of the intrathoracic pressure in this manner provides a greater coronary perfusion pressure and hence forces more venous blood into the thorax. The valving system can be employed in a variety of CPR methods where intrathoracic pressures are intentionally manipulated to improve cardiopulmonary circulation, including "vest" CPR, CPR incorporating a Heimlich ventilatory system, intraposed abdominal compression - decompression CPR, standard manual CPR, and the like, and will find its greatest use with ACD-CPR.

Referring to Figs. 11-15, an exemplary embodiment of a valving system 100 is shown schematically. The valving system 100 includes a housing 101 having an upstream region 102 and a downstream region 104...

...greater than atmospheric, is developed in the upstream region 102 when

ventilating the patient. The valving system 100 further includes a valve 108 having a plug 110. As described in greater detail hereinafter, the valve 108 is included to provide ventilation to the patient when opened. The valve 108 can be manually opened by axial translation or it can be automatically opened when...

...air is exhausted from the housing 101 through the air exhaust opening 114. An accordion valve 116, fishmouth valve, or the like is provided between the air intake opening 112 and the air exhaust opening 114. As described in greater detail hereinafter, the accordion valve 116 is used to prevent air that is injected into the air intake opening 112...

...provided in the downstream region 104 for preventing excess body fluids from entering into the **system** 100.

Operation of the valving system 100 during compression of a patient's chest is illustrated in Fig. 11. As the patient's chest is compressed, air is forced from the patient's lungs and into the downstream region 104. The air forced into the downstream region 104 is

...preferably at about 2 cm H2))O to 4 cm H2))O.

Operation of the valving system 100 during decompression (or resting) of the patient's chest is illustrated in Fig. 12. As the patient's chest is actively lifted (or allowed to expand on its own), air is drawn from the downstream region 104 and into the patient's lungs, thereby reducing the pressure in the downstream region 104. The resulting pressure differential between the...

...downstream region 104. In this way, air is inhibited from flowing into the patient's lungs during decompression of the patient's chest, thereby lowering the intrathoracic pressure to increase the coronary perfusion pressure and to force more venous blood into the thorax.

Various ways of providing ventilation to the patient using the valving system 100 are described in Figs. 13-15. Fig. 13 illustrates airflow into the downstream region 104 and to the patient's lungs during decompression of the patient's chest after a threshold amount of negative intrathoracic pressure has been reached. Ventilation in this manner is advantageous in that the valving system 100 can be employed to produce at least a threshold amount of intrathoracic pressure to enhance blood flow into the heart and lungs. Once such a pressure is reached, some air is allowed to flow to the patient's lungs to ventilate the patient.

Air is allowed to enter the downstream region 104 when the threshold amount of intrathoracic pressure is reached by configuring the valve 108 to be a threshold valve. The valve 108 can be configured in a variety of ways, with a primary function being that the valve 108 allows air to flow into the downstream region 104 when a threshold amount of intrathoracic pressure is reached. This is preferably accomplished by configuring the plug 110 to be flexible...

...lower pressure upstream region 102 into the downstream region 104 and to the patient's lungs. The plug 110 therefore acts as a one-way valve allowing air to flow from the upstream region 102 into the downstream region 104 when...40 cm H2))O, and more preferably at about 30 cm H2))O. Alternatively, the valve 108 can be placed in the downstream region 104 so that air flows into the downstream region 104 directly from the atmosphere when the valve 108 is open.

Ventilating the patient by injecting air into the upstream region 102 is...

...14. As air is injected through the intake opening 112, it passes into the accordion valve 116 and forces the valve 116 against a wall 120 and covers a hole 122 in the wall 120 to prevent airflow through the exhaust opening 114. When the accordion valve 116 is closed, air flows through a wall 124 of the valve 116 and into the upstream region 102. Alternatively, a fishmouth valve can be used in place of the accordion valve 116. Upon injection of the air into the upstream region 102, the pressure within the...

...created allowing air to flow into the downstream region 104 and into the patient's lungs. Preferably, the patient will be manually ventilated by injecting air into the intake opening 112 about every three to seven compressions of the chest, and more preferably about every five compressions of the chest.

Configuration of the valving system 100 upon return of spontaneous circulation is illustrated in Fig. 15. When the patient's circulation is restored, the valve 108 is manually opened by translating the valve 108 to remove the plug 110 from aperture 126. The upstream region 102 and

downstream...

...each of the regions 102, 104. Although shown extending through the upstream region 102, the valve 108 can alternatively be placed anywhere

along the downstream region 104.

The valve 108 can be configured as a pressure-responsive valve (see Fig. 13), as a manually operable valve (see Fig. 15), or both. Further, the valving system 100 can alternatively be provided with two or more valves that are similar to the valve 108. For example, one valve could be non-translatably held in the housing 101 and provided with a pressure-responsive plug 110, with the other valve being translatably mounted. In this manner, the valve with the flexible plug functions as a pressure-responsive valve and opens when the threshold pressure is reached, while the translatable valve functions to place the regions 102, 104 in communication upon manual operation after spontaneous circulation is achieved.

Referring to Figs. 16A and 16B, an exemplary embodiment of a valving system 130 will be described. The valving system 130 is constructed of a housing 132 having an intake opening 134, an exhaust opening...

- ...and a delivery opening 138. Included in the exhaust opening 136 is a one-way valve which allows air to flow from the housing 132 and out the exhaust opening 136. An accordion valve 140 is provided between the intake opening 134 and an exhaust opening 136 to prevent...
- ...AMBU bag), a ventilator, a mouthpiece or port for mouth-to-mouth breathing through the system 130, or the like. The delivery opening 138 is preferably configured for connection to an...
- ...downstream region 144, with the diaphragm 148 resting on the cylinder during ambient conditions. During **decompression** of the patient's **chest**, the reduction in pressure in the downstream region 144 draws the diaphragm 148 against the...
- ...to prevent exchange of air between the upstream region 142 and downstream region 144. During **compression** of the patient's **chest**, air is forced into the downstream region 144 to force the diaphragm 148 into the ambient pressure region 146 so that the air exhausted from the patient's **chest** can be exhausted through the exhaust opening 136.

As shown best in Fig. 16B, the valving system 130 is further provided with a fenestrated mount 150. In one aspect, the fenestrated

...a filter 159 can be provided to prevent excess body fluids from entering into the system 130.

system 130 further includes a threshold valve 160 at The valving the downstream region 144. When the pressure within the downstream region 144 is less than the threshold amount, the threshold valve 160 is opened to allow air to flow into the downstream region 144. The threshold valve 160 includes a spring 162 which is configured to extend when the threshold amount is reached. Alternatively, the threshold valve 160 can be configured similar to the valve 110. Other configurations which allow the air to enter the downstream region 144 when the desired intrathoracic pressure is reached or exceeded can also be provided. For example, in a further alternative, the diaphragm 148 can be constructed to function as a threshold valve to allow air to flow into the patient's lungs when a threshold amount of intrathoracic pressure is reached. The diaphragm 148 can be fashioned as a threshold valve by constructing the diaphragm 148 of an elastomeric material and by providing at least one...

- ...positioned beyond the periphery of the cylinder and in the upstream region 142. As a vacuum is created in the downstream region 144, the diaphragm is drawn into the downstream region...
- ...the threshold pressure is reached in the downstream region 144. Another alternative of a threshold valve 111 is illustrated in Fig. 16C. The valve 111 is pivot mounted within the downstream region 144 and is biased closed by a...
- ...When the threshold pressure within the downstream region 144 is reached, the spring 113 is **compressed** and air is drawn into the downstream region 144.

Referring back to Fig. 16A, the threshold valve 160 can optionally be provided within the housing 132 at the upstream region 142. The threshold valve 160 can further optionally be provided with an on/off switch for opening the valve 160 when spontaneous circulation is achieved. In this manner, a rescuer can open the valve 160 to allow for free exchange of air to the patient's lungs when needed. In one alternative as shown in Fig. 16C, the mount 150 can be...

...or close the diaphragm 148. If the diaphragm 148 were also fashioned as a threshold **valve** as previously described, the need for the **valves** 108 or 111 could be eliminated.

The housing 132 can conveniently be constructed in several...

...158 for removably connecting the portion of the housing having the intake opening 134, the valve 140, and the exhaust opening 136. Alternatively, a connection point can be provided near the mount 150 to provide easy access to the mount 150 for cleaning.

The valving system 130 can conveniently be incorporated with a variety of devices useful in CPR procedures. For example, the valving system 130 can be incorporated within a respiratory bag, such as an AMBU bag. Alternatively, the valving system 130 can be included as part of a respiratory circuit having both a respiratory bag and an endotracheal tube or other airway tube, with the valving system 130 positioned between the bag and the tube. In a further alternative, the valving system 130 can be added to an endotracheal tube alone. Alternatively, the valving system can be incorporated into a mask, an oralpharyngeal airway, a laryngeal mask or other ventilatory devices. Referring to Fig. 17, an alternative valving system 164 will be

described. The valving system 164 is shown schematically and operates essentially identically to the valving system 100, the difference being that the valving system 164 includes a ball or spherical member 166 as the diaphragm. During decompression of the patient's chest, the pressure in a downstream region 168 is less than the pressure in an upstream region 170 which draws the ball 166 over the downstream region 168. The valving system 164 can optionally be provided with a spring or other biasing mechanism to hold the ball 166 over the downstream region 168 during compression of the patient's chest until a threshold pressure is reached or exceeded in the downstream region 168 as previously...

#### ...CLAIMS B1

1. A valving system (100) for regulating airflow into a patient's lungs when performing cardiopulmonary resuscitation wherein the patient's chest is compressed and decompressed, the system comprising:

a housing (101) having an upstream region (102) and a downstream region

(104), characterised...

...allowing air to flow into the downstream region (104) when ventilating the patient.

2. The system of claim 1, wherein the inhibiting means comprises a valve which allows airflow from the downstream region (104) to the upstream region (102), wherein the valve includes a diaphragm (106) which is closed when the pressure in the downstream region (104) is less than or equal to the pressure in the upstream region (102).

3. The system of claim 2, wherein the diaphragm is a flexible membrane

(106) or a ball (166...

...118) to open the diaphragm and to allow air to flow to the patient's lungs .

4. The system of claim 3, wherein the means for allowing air into the downstream region (104) comprises a manually operable valve (108) at the downstream region (104) which is manually opened to allow air to flow...

...into the downstream region (104) upon return of spontaneous breathing by

the patient.

- 5. The system of claim 1, wherein the means for allowing air into the downstream region (104) comprises a pressure responsive valve (110) at the downstream region (104) for allowing air into the downstream region (104) when...
- ...in the range from -5 cm H2))O to -60 cm H2))O.
  - 6. The **system** of claim 1, further comprising a respiratory member connected to the housing at the upstream...
- ...the upstream region (102) for exhausting air from the housing (101), and further comprising a **valve** (44) in the exhaust opening which inhibits air from flowing into the housing (101) through the exhaust opening (114).

7. The system of claim 6, further comprising means (116) for preventing

air from exiting the housing (101...

- ...28), wherein the means for preventing air from exiting the housing is a fish mouth valve, and further comprising a connection member connected to the housing at the downstream region for...
- ...includes an endotracheal tube (36), a facial mask (52), or a laryngeal mask.

- 8. A valving system as claimed in claim 1 and further comprising: a respirator (28) connected to the housing...
- ...101) at the downstream region (104) for insertion into the patient's airway.
  - 9. The **system** of claim 8, wherein the respirator includes a respiratory bag (28) or a ventilation port...
- ...airway tube includes an endotracheal tube (36).
  - 10. Apparatus for assisting cardiopulmonary resuscitation comprising a valving system as claimed in claim 1 together with an endotracheal tube (36) of the type having...
- ...whereby airflow is impeded to a fixed or variable degree from entering the patient's lungs to enhance the extent and duration of negative intrathoracic pressure during decompression of the patient's chest to enhance venous blood flow into the heart and lungs from the peripheral venous vasculature when performing cardiopulmonary resuscitation.
  - 11. The apparatus of claim 10...
- ...apparatus of claim 10 wherein the means for inhibiting air flow comprises a pressure-responsive valve (110) within the first lumen of the tube (36), wherein the valve (110) is biased to open to permit the inflow of air when the intrathoracic pressure falls below a threshold level in the range from 0 cm H2))0 to...
- ...bypassing air round the inflow impeding means.
  - 13. Apparatus for assisting cardiopulmonary resuscitation comprising a valving system as claimed in claim 1 together with a compressible structure (28) having a first opening and a second opening, a one-way valve (26) for the intake of air included in or attached to the first ...volume of air;
  - means (36,52) for interfacing in a permanent or detachable manner said compressible structure to the patient; and
  - means (22) included in or attached to the second opening of the compressible structure to impede the flow of gases to the patient's lungs until a minimum intrathoracic pressure is exceeded, whereby a rise in intrathoracic pressure is slowed during decompression of the patient's chest and the extent and duration of negative intrathoracic pressure is enhanced in order to enhance venous blood flow into the heart and lungs from the peripheral venous vasculature when performing cardiopulmonary resuscitation.
  - 14. The apparatus of claim 13...
- ...50) disposed within or connected in series in a permanent or detachable manner with the lcompressible structure.
  - 15. The apparatus of claim 13, wherein the inflow impeding means comprises a pressure-responsive valve (110), wherein the valve (110) is biased to open to permit the inflow of air when the intrathoracic pressure falls below a threshold level in the range from 0 cm H2))O to...
- ...CLAIMS B1

```
(Item 7 from file: 348)
DIALOG(R) File 348: EUROPEAN PATENTS
(c) 2004 European Patent Office. All rts. reserv.
DEVICE FOR ASSISTING CARDIOPULMONARY RESUSCITATION
VORRICHTUNG ZUR UNTERSTUTZUNG BEI KARDIOPULMONALER WIEDERBELEBUNG
DISPOSITIF D'ASSISTANCE A LA REANIMATION CARDIO- PULMONAIRE
PATENT ASSIGNEE:
 CPRX, LLC., (4268230), 7615 Golden Triangle Drive, Suite A, Technology
    Park #5, Eden Prairie, MN 55344, (US), (Proprietor designated states:
INVENTOR:
  Lurie, Keith G., 4751 Girard Avenue South, Minneapolis, MN 55409, (US)
  Sweeney, Michael, 1525 Goodrich Avenue, St. Paul, MN 55105, (US)
  Gold, Barbara, 4751 Girard Avenue South, Minneapolis, MN 55409, (US)
LEGAL REPRESENTATIVE:
  Harrison, David Christopher (31532), MEWBURN ELLIS York House 23 Kingsway
    . London WC2B 6HP, (GB)
PATENT (CC, No, Kind, Date): EP 728028 Al
                                             960828 (Basic)
                              EP 728028 A1
                                             970604
                              EP 728028 B1
                                             030521
                              WO 95013108 950518
                                                   WO 94US12870 941107
APPLICATION (CC, No, Date): EP 95901822 941107;
PRIORITY (CC, No, Date): US 149204 931109
DESIGNATED STATES (Pub A): AT; BE; CH; DE; DK; ES; FR; GB; GR; IE; IT; LI;
  LU; MC; NL; PT; SE; (Pub B): DE; ES; FR; GB; IT; NL; SE
INTERNATIONAL PATENT CLASS: A61M-015/00 ; A61M-016/00 ; A62B-007/00 ;
  A62B-009/06; A62B-018/02; A61H-031/00
NOTE:
  No A-document published by EPO
LANGUAGE (Publication, Procedural, Application): English; English; English
FULLTEXT AVAILABILITY:
                           Update
                                      Word Count
Available Text Language
                           200321
                                       257
      CLAIMS B (English)
                           200321
                                        274
      CLAIMS B
                 (German)
                                        275
                           200321
      CLAIMS B
                  (French)
                           200321
                                       5414
      SPEC B
                 (English)
Total word count - document A
                                       6220
Total word count - document B
Total word count - documents A + B
                                       6220
DISPOSITIF D'ASSISTANCE A LA REANIMATION CARDIO- PULMONAIRE
 INTERNATIONAL PATENT CLASS: A61M-015/00 ...
 ... A61M-016/00 ...
 ... A62B-007/00 ...
 ... A62B-009/06 ...
 ... A62B-018/02
 LEGAL STATUS (Type, Pub Date, Kind, Text):
 ... Advanced Circulatory Systems , Inc. (4475370) 7615 Golden Triangle
                             Drive, Suite A, Eden Prairie, Minnesota 55344
  Grant...
 ... SPECIFICATION B1
     The present invention relates generally to devices used in conjunction
```

with external chest compression and decompression as a part of

cardiopulmonary resuscitation procedures . In particular, the present invention relates to devices for increasing cardiopulmonary circulation compression and decompression when performing induced by chest cardiopulmonary resuscitation.

arrest is a major cause of death and is Worldwide, sudden cardiac the result of a variety of circumstances, including heart disease and significant trauma. In the event of a cardiac arrest, several measures have been deemed to be essential in order to improve a patient's

...possible to at least partially restore the patient's respiration and blood circulation. One common technique, developed approximately 30 years ago, is an external chest compression technique generally referred to as cardiopulmonary resuscitation (CPR). CPR techniques have remained largely unchanged over the past two decades.

With traditional CPR, pressure is applied to a patient's chest in

order to increase intrathoracic pressure.

An increase in intrathoracic pressure induces blood movement from the region of the heart and lungs towards the peripheral arteries. Such pressure partially restores the patient's circulation. Traditional CPR is performed by actively compressing the chest by direct application of an external pressure to the chest . After active compression , the chest is allowed to expand by its natural elasticity which causes expansion of the patient's chest wall. This expansion allows some blood to enter the cardiac chambers of the heart. The procedure as described, however, is insufficient to ventilate the patient. Consequently, conventional CPR also requires periodic ventilation of the patient. This is commonly accomplished by mouth-to-mouth technique or by using positive-pressure devices, such as a self-inflating bag which relies on

...mask, endotracheal tube or other artificial airway. In order to increase cardiopulmonary circulation induced by chest

compression, a technique referred to as active compression decompression (ACD) has been developed. According to ACD techniques , the active compression phase of traditional CPR is enhanced by pressing an applicator body against the patient's chest to compress the chest . Such an applicator body is able to distribute and apply force substantially evenly over a portion of the patient's chest . More importantly, however, the applicator body is sealed against the patient's chest so that it may be lifted to actively expand the patient's chest during the decompression step. The resultant negative intrathoracic pressure induces venous blood to flow into the heart and lungs from the peripheral venous vasculature of the patient.

Also of importance to the invention are ventilation sources that are used in connection with CPR techniques to properly ventilate the patient. One type of ventilation source is the AMBU bag available from AMBU International, Copenhagen, Denmark. The AMBU bag can also be used in connection with a **positive end - expiratory pressure** ( Pi valve , available from AMBU International, to treat some patients pressure ( PEEP with pulmonary and cardiac diseases. However, until the present invention, a positive end-expiratory pressure valve in connection with a ventilation source has not been used with any CPR techniques .

With both traditional CPR and ACD-CPR techniques , an increase in the amount of venous blood flowing into the heart and lungs from the peripheral venous vasculature would be desirable to increase the volume of oxygenated blood leaving the thorax during the subsequent compression phase. It would therefore be desirable to provide improved apparatus for enhancing venous blood flow into the heart and lungs of a patient from the peripheral venous vasculature during both conventional CPR and ACD-CPR techniques. It would be particularly desirable to provide apparatus which would enhance oxygenation and increase the total blood return to the chest during the decompression step of CPR and ACD-CPR, more particularly of ACD-CPR. This can be accomplished according to the present invention by augmentation of both negative and positive intrathoracic pressure, thereby amplifying the total intrathoracic pressure swing. An invention for providing this crucial improvement is described.

ACD-CPR techniques are described in detail in Todd J. Cohen et al.,
Active Compression - Decompression Resuscitation: A Novel Method of
Cardiopulmonary Resuscitation, American Heart Journal, Vol. 124, No. 5,
pp. 1145-1150, November 1992; Todd J. Cohen et al., Active Compression Decompression: A New Method of Cardiopulmonary Resuscitation, The
Journal of the American Medical Association, Vol. 267, No. 21, June...

...and J. Schultz, P. Coffeen, et al., Circulation, in press, 1994.

The use of a vacuum -type cup for actively compressing and decompressing a patient's chest during ACD- CPR is described in a brochure of AMBU International A/S, Copenhagen, Denmark, entitled Directions for Use of AMBU(R) CardioPump(TM), published...

...773.

DE 24 53 490A discloses a ventilation device for connecting a patient to a **lung** ventilator, but is not intended to impede the airflow to the patient at any stage in its operation. US-A-5,050, 593 discloses the use of one-way valves in a triggering mechanism for a respirator.

According to the invention, devices for increasing cardiopulmonary circulation induced by **chest compression** and **decompression** when performing cardiopulmonary resuscitation are provided. The devices may be used in connection with any generally accepted CPR **methods** or with active **compression** - **decompression** (ACD) CPR **techniques**. Preferably, the devices will be used in connection with ACD-CPR.

Cardiopulmonary circulation is increased according to the invention by impeding air flow into a patient's lungs during the decompression phase. This increases the magnitude and prolongs the duration of negative intrathoracic pressure during decompression of the patient's chest, i.e., increases the duration and degree that the intrathoracic pressure is below or negative with respect to the pressure in the peripheral venous vasculature. By enhancing the amount of venous blood flow into the heart and lungs, since equilibration of intrathoracic pressure during decompression occurs to a greater extend from enhanced venous return rather than rapid inflow of gases into the chest via the patient's airway, cardiopulmonary circulation is increased.

A specific embodiment further provides means for impeding air from leaving the lungs during compression of the patient's chest to further enhance cardiopulmonary circulation by enhancing positive intrathoracic pressure during the compression phase.

When performing cardiopulmonary resuscitation to enhance circulation according to the invention, an operator compresses a patient's chest to force blood out of the patient's thorax. The patient's chest is then decompressed to induce venous blood to flow into the heart and lungs from the peripheral venous vasculature either by actively lifting the chest (via ACD-CPR) or by permitting the chest to expand due to its own elasticity (via conventional CPR). During the decompression step, air flow is impeded from entering into the patient's lungs which enhances negative intrathoracic pressure and increases the time during which the thorax is at a lower pressure than the peripheral venous vasculature. Thus, venous blood flow into the heart and lungs from the

peripheral venous vasculature is enhanced. This is because the intrathoracic pressure equilibrium during decompression occurs as a result of enhanced venous return rather than from inflow of air via the trachea. In a particular embodiment, compression and decompression of the patient's chest may be accomplished by pressing an applicator body against the patient's chest to compress the chest, and lifting the applicator to actively expand the patient's chest.

An apparatus for enhancing cardiopulmonary circulation comprises an improved endotracheal tube having a flow restrictive element for impeding air\_flow\_from\_the\_patient's\_lungs\_during\_chest\_decompression. The invention may provide a compressible structure having the flow restrictive element included in or attached to an opening of the compressible structure to impede the flow of gases to the patient's lungs. Also, a connector is provided for interfacing the compressible structure to the patient, preferably by attaching a facial mask or endotracheal tube to the...

...portions of the specification and drawings.

In the drawings:

Fig. 1 is a graph illustrating thoracic pressure changes over time when compressing and decompressing a patient's chest according to the present invention.

Fig. 2A is a schematic view illustrating air flow through a ventilation circuit when **compressing** a patient's **chest** according to

the present invention.

Fig. 2B is a schematic view illustrating air flow through a ventilation circuit when **decomp**ressing a patient's **chest** according to the present invention.

Fig. 3 is a schematic illustration of a first alternative embodiment of a device for impeding air flow into a patient's lungs according to

the present invention.

Fig. 4A is a schematic illustration of a second alternative embodiment of the device for impeding air flow into a patient's lungs according to the present invention.

Fig. 4B is a schematic illustration of the device in...

...a common inhalation/exhalation port.

Fig. 5A is a schematic view of a one-way valve used in the device for impeding air flow according to the present invention.

Fig. 5B is a schematic view of the one-way valve in Fig. 5A that is

held open after ACD-CPR has ceased.

Fig. 5C is a schematic view of a one-way valve that is closed until a threshold pressure is present in the tube according to the present invention.

Fig. 6A is a schematic view of a spring biased inflow valve and a spring biased expiration valve to be used in accordance with the present invention.

Fig. 6B is a schematic view of Fig. 6A showing the operation of the

valves during outflow of air.

Fig. 6C is a schematic view of Fig. 6A showing the operation of the

valves during inflow of air.

Fig. 7 is a schematic view of a single valve that is spring biased from both sides to be used as an inflow valve and an expiration valve according to the present invention.

Fig. 8 is a schematic view of an exemplary embodiment of the device for impeding air flow into a patient's lungs according to the present

invention.

Figs. 9A-9C are schematic views illustrating another embodiment of the present invention allowing for periodic patient ventilation through a bypassing **valve**.

According to the present invention, devices for increasing cardiopulmonary circulation induced by chest compression and decompression when performing cardiopulmonary resuscitation are provided. Such devices may be used in connection with any method of CPR in which intrathoracic pressures are intentionally manipulated to improve cardiopulmonary circulation. For instance, the present invention would improve standard manual CPR, "vest" CPR, CPR with a newly described Hiack Oscillator ventilatory system which operates essentially like an iron-lung-like device, interposed abdominal compression—decompression—CPR, and active compression—decompression—(ACD) CPR techniques. Although the present invention may improve all such techniques, the following description will refer primarily to improvements of ACD-CPR techniques in order to simplify discussion. However, the claimed devices are not exclusively limited to ACD-CPR techniques.

The proper performance of ACD-CPR to increase cardiopulmonary circulation is accomplished by actively compressing a patient's chest with an applicator body. Preferably, this applicator body will be a suction -type device that will adhere to the patient's chest , such as the AMBU(R) CardioPump(TM), available from AMBU International, Copenhagen, Denmark. After the compression step, the adherence of the applicator body to the patient's chest allows the patient's chest to be lifted to actively decompress the patient's chest . The result of such active compression - decompression is to increase intrathoracic pressure during the compression step, and to increase the negative intrathoracic pressure during the decompression step thus enhancing the blood-oxygenation process and enhancing cardiopulmonary circulation. ACD-CPR techniques are described in detail in Todd J. Cohen et al., Active Compression - Decompression Resuscitation: A Novel Method of Cardiopulmonary Resuscitation, American Heart Journal, Vol. 124, No. 5, pp. 1145-1150, November 1992; Todd J. Cohen et al., Active Compression - Decompression : A New Method of Cardiopulmonary Resuscitation, The Journal of the American Medical Association, Vol. 267, No. 21, June...

...Circulation, in press, 1994.

The present invention is especially useful in connection with ACD-CPR techniques. In particular, the invention improves ACD-CPR by providing devices which impede air flow into a patient's lungs to enhance negative intrathoracic pressure during the decompression of the patient's chest, thus increasing the degree and duration of a pressure differential between the thorax (including the heart and lungs) and the peripheral venous vasculature. Enhancing negative intrathoracic pressure with simultaneous impedance of movement of gases into the airway thus enhances venous blood flow into the heart and lungs and increases cardiopulmonary circulation.

In a broad sense, the present invention allows for occluding a patient's airway to prevent foreign (outside) air from flowing to a patient's lungs during the active decompression step of ACD-CPR to enhance and sustain the duration of negative intrathoracic pressure and enhance blood oxygenation and cardiopulmonary circulation during both active decompression and the subsequent compression phase. The patient's airway may be occluded or inflow of gases impeded by any...

...of the present invention allows for allowing impeded air to flow into the patient's lungs during the active decompression step of ACD-CPR in order to provide some ventilation to the patient while still enhancing the extent and duration of negative intrathoracic pressure to enhance blood oxygenation. Impeding air flow to the patient's lungs may be

accomplished by any flow restrictive element such as an orifice, a spring biased or other valve which is set to open when the negative intrathoracic pressure is in the range from about 0 mmHg to about -74 mmHg (about 0 cm H2))0 to -100 cm H2))0), a one-way valve, or the like. A valve designed to open at a threshold pressure value may be either fixed or variable, i.e., the pressure at which the valve opens may be adjusted or may be permanently fixed.

Similarly, another aspect of the invention allows for air to be impeded from leaving the patient's lungs during compression of the patient's chest—to—further—enhance—cardiopulmonary circulation—by enhancing intrathoracic pressure during the compression phase. Typically, air is impeded from leaving the lungs during the compression phase when the positive intrathoracic pressure is in the range from about 3.7 mmHg to

about 37 mmHg (about...

...during ACD-CPR. Ventilation of the patient is performed at about every two to 10 compressions, preferably every five compressions, thus providing sufficient fresh air for adequate gas exchange with the blood in the lungs to the patient. Ventilating the patient may be accomplished by any device or method suitable such as by mouth-to-mouth resuscitation, by a compressible or collapsible structure, by a ventilatory bag such as the AMBU bag available from AMBU, Copenhagen, Denmark, or the like. Ventilation could also be superimposed on the compression phase to further augment positive intrathoracic pressure. Furthermore, periodic ventilation could be performed either through the impeding step or by bypassing the impeding step altogether.

Referring now to Fig. 1, a graph illustrating thoracic pressure changes over time when compressing and decompressing the patient's chest is shown. Area 10 represents the amount of thoracic pressure during the compression phase of ACD-CPR. Cross-hatched area 12 represents the negative thoracic pressure during the decompression step of ACD-CPR without a flow restrictive means to restrict the flow of air into the patient's lungs. Double cross-hatched area 14 represents the increase in negative thoracic pressure when the patient's airway is occluded according to the present invention during the decompression step of ACD-CPR. The significance of the increase in negative intrathoracic pressure during the decompression step is that more venous blood is forced into the chest from the peripheral venous vasculature. Consequently, more blood is allowed to be oxygenated and more blood is forced out of the chest during the next compression.

Air flow may be impeded to the patient's lungs during decompression of the patient's chest by placing a ventilatory mask over the patient's mouth and nose. The ventilatory mask also has a pressure-responsive valve attached to prevent air flow to the patient's lungs until the negative intrathoracic pressure of the patient reaches a threshold amount. Also attached to the mask and the pressure-responsive valve is a ventilatory source to provide ventilation to the patient. The ventilatory source may be...

...is needed, the AMBU bag may be squeezed to force air into the patient's lungs . The AMBU bag is described in U.S. -A- 5,163,424.

In an alternative...

...an AMBU bag, is used in connection with an improved endotracheal tube. A pressure-responsive valve or other flow restrictive element is placed between the AMBU bag and the endotracheal tube. Preferably, the valve will be positioned within a tube that connects the AMBU bag to ... performed on the patient, the endotracheal tube is placed in the patient's trachea. During decompression of the patient's chest, the

valve prevents air flow to the patient's lungs until the
intrathoracic pressure reaches a threshold amount.

Additionally, the AMBU bag may be used to ventilate the patient at a desired time. Also included in this embodiment is a one-way expiration valve. This valve allows for expiration of air from the patient during the compression step.

In a modification of either of the first two embodiments, an pressure-responsive expiration valve may also be inserted between the AMBU bag (or comparable ventilation source) and the mask or endotracheal tube. This valve works in a similar manner to the pressure-responsive valve which restricts air flow into the patient's lungs. However, the pressure-responsive expiration valve restricts air flow from the patient's lungs during the compression step of ACD-CPR. An equivalent valve is a positive end - expiratory pressure (PEEP) valve available from AMBU International, Copenhagen, Denmark. Use of such an pressure-responsive expiration valve during compression may further increase intrathoracic pressure and thereby force more blood out of the thorax.

In another alternative embodiment, an improved endotracheal tube is used to restrict air flow into the patient's lungs during the active decompression step. Included in the endotracheal tube is a flow restrictive element which operates to impede air from flowing into the patient's lungs. When the endotracheal tube is inserted into the patient's trachea and the patient's chest is actively decompressed, the flow restrictive element impedes air from flowing to the patient's lungs slowing the rise in intrathoracic pressure and thus enhancing blood oxygenation.

When using the improved endotracheal tube during ACD-CPR...
...the endotracheal tube to force oxygen through the endotracheal tube and into the patient's lungs .

Referring now to Fig. 2A, a schematic view illustrating air flow through a ventilation circuit 20 when **compressing** a patient's **chest** according to the present invention is shown. During ACD-CPR, the **chest** is actively **compressed** forcing air out of the **lungs**. This air is allowed to expire through a one-way expiration **valve** 22 within a ventilation circuit 20.

Referring now to Fig. 2B, the same schematic is shown illustrating air flow through the ventilation circuit 20 when decompressing the patient's chest. When the patient's chest is actively decompressed, a negative intrathoracic pressure is created. When this pressure reaches a threshold amount, the inflow valve 24 will open causing air to flow through the ventilation circuit 20 into the patient's lungs. Air is allowed into the ventilation circuit 20 through a ventilation valve 26 and into a ventilation bag 28. From the ventilation bag 28, the air passes through the inflow valve 24 when the negative intrathoracic pressure reaches the threshold amount. The ventilation bag 28 is also used to manually ventilate the patient during ACD-CPR as required.

The method as discussed in connection with Figs. 2A and 2B requires the chest to be compressed in the range from about 3.5 cm to 5 cm per compression and at a rate from about 60 to 100 compressions per minute for adults.

Referring now to Fig. 3, a schematic illustration of a first alternative embodiment of a device 35 for impeding air flow into a patient's **lungs** according to the present invention is shown. The device 35 comprises an endotracheal tube 36...

...can comprise any type of ventilation source capable of ventilating the patient such as a **compressible** or collapsible structure. Preferably,

the ventilation bag 28 consists of an AMBU bag. Attached or connected to the end of the ventilation bag 28 is a one-way ventilation valve 26. The ventilation valve 26 serves to introduce air into the device 35. Attached or connected to the transition tube 38 is an inflow pressure-responsive valve 24. The inflow valve 24 is biased so that it opens when the negative intrathoracic pressure in the patient's chest reaches a threshold amount. As shown, only one inflow valve 24 is included in the device 35. However, the invention is not limited to only one inflow valve 24. Alternatively, a plurality of inflow valves 24—could\_be\_connected\_in\_series\_along\_the\_ventilation\_tube\_38. The inflow valve 24 is also not limited to being connected in the center of the transition tube 38, but may be positioned anywhere along the transition

transition tube 38, but may be positioned anywhere along the transition tube 38. The inflow valve 24 could be permanently attached to the ventilation bag 28 or transition tube 38 or could be detachable. Alternatively, the inflow valve 24 could be connected to the ventilation bag 28 itself or to the endotracheal tube 36.

The device 35 also contains a one-way expiration valve 22 which allows for air to be expired from the patient's lungs. This generally occurs during the compression phase of ACD-CPR. To insure that the air expired from the patient's lungs will exit through the expiration valve 22, a one-way fish mouth valve 37 (the preferred valve) or any other type of one-way valve can be placed between the inflow valve 24 and the expiration valve 22. Alternatively, the inflow valve 24 itself may be configured as a one-way valve. In either case, air flowing from the endotracheal tube 36 toward the ventilation bag 28 will be forced to expire through the expiration valve 22.

The device 35 may be further modified to include a pressure-responsive expiration valve (not shown) located between the endotracheal tube 36 and the transition tube 38. The pressure-responsive expiration valve works in a reverse manner to that of the inflow valve 24. Specifically, the pressure-responsive expiration valve is biased so that during the compression step of ACD-CPR, air will be allowed to expire from the patient's lungs only when the intrathoracic pressure reaches a threshold amount. The increase in intrathoracic pressure caused by the pressure-responsive expiration valve during compression may assist in forcing more blood out of the thorax and reduce atelectasis of the lungs.

The purpose of the ventilation bag 28 is to provide ventilation to the patient during ACD- CPR. When the ventilation bag 28 comprises an AMBU bag or similar bag used for ventilation, ventilation of the patient may be performed by merely squeezing the AMBU bag with a human hand. This forces air to the patient's lungs as desired.

Referring to Fig. 4A, a second alternative embodiment of the device for impeding air flow into a patient's **lungs** according to the present invention is shown. This particular embodiment is a modified and improved

pressure-responsive expiration valve 44 which operates in a manner similar to that discussed in connection with Fig. 3, except that the expiration valve 44 is specifically designed as a one-way valve. Located within inflow lumen 42 is a one-way pressure-responsive inflow valve 45 which operates to impede air flow to the lungs as discussed in connection with Fig. 3, except that the inflow valve 45 is also specifically designed as a one-way valve. Also shown in inflow lumen 42 and outflow lumen 40 is an O-ring 46 which will be discussed subsequently. Inflow valve 45 and expiration valve 44 are designed as one-way valves so that during the compression phase, air can only be expired from the patient through the endotracheal tube 36 when the

intrathoracic pressure reaches a threshold amount. At that moment, expiration valve 44 opens and air expires from the patient through the outflow lumen 40. During decompression, air cannot flow through the endotracheal tube 36 to the patient's lungs until the negative intrathoracic pressure reaches a threshold amount. At that moment, inflow valve 45 opens allowing air to flow through inflow lumen 42 to the patient's lungs. Air is prevented from entering through the outflow lumen 40 because of the one-way expiration valve 44.

Ventilation is possible with the embodiment disclosed in Figs. 4A and 4B if the...

...through the inflow lumen 42, through the endotracheal tube 36, and to the patient's lungs. In this embodiment, expiration valve 44 is designed so that during ventilation, expiration valve 44 will remain temporarily closed preventing air flowing through inflow lumen 42 escape through outflow lumen 40.

Fig. 5A is a schematic view of a one-way inflow valve 45 used in a device for impeding air flow according to the present invention. The inflow valve 45 operates so as to allow air only to flow in one direction. As shown, the spring biased inflow valve 45 is completely open. However, the invention also functions properly if the spring biased inflow valve 45 or the spring biased expiration valve 44 are not fully open. Upon successful completion of ACD-CPR, the O-ring 46 that is positioned above the inflow valve 45 is repositioned so that inflow valve 45 is held open as shown in Fig. 5B. Such a positioning of O-ring

...flow to the patient once there is a return of spontaneous circulation and the inflow valve 45 is no longer needed. An O-ring 46 is also used in a similar manner to lock the one-way expiration valve 44 in an open position upon return of spontaneous circulation. Fig. 5C illustrates the one-way inflow valve 45 in a closed position. When closed, the inflow of air through the inflow valve 45 is occluded.

Fig. 6A illustrates an inflow valve 47 that is spring biased and an expiration valve 48 that is also spring biased. The inflow valve 47 and the expiration valve 48 are connected in series and may be used in the first alternative embodiment as...

...discussed following in connection with Fig. 8. As shown in Fig. 6C, during the active decompression step, the inflow valve 47 is biased such that it will open when the negative intrathoracic pressure reaches a threshold amount. During the compression phase of ACD-CPR the expiration valve 48 will open to allow air to expire from the patient's lungs when the intrathoracic pressure within the patient's chest reaches a threshold amount as shown in Fig. 6B. Since neither inflow valve 47 nor expiration valve 48 are one-way valves, a fish mouth valve 37 used in connection with a one-way expiration valve 22 as discussed in connection with Fig. 3 must be used. Other valves designed upon a similar principle as the fish mouth valve combination with a one-way expiration valve could also be used. Only one inflow valve 24 and one positive end pressure valve 44 are shown in Figs. 6A-6C. However, a plurality of inflow valves 47 and/or expiration valves may be connected in a permanent or detachable manner in series to impede the inflow and outflow of air.

Although the valves in Figs. 6A-6C are shown as being spring-biased, any other valves designed upon a similar principle would work equally as well. The use of such valves as disclosed in Figs. 6A-6C is only one embodiment and valves constructed according to various other methods and materials is also within the scope of the invention.

As shown in Fig. 7, the inflow valve 47 and the expiration valve 48 may be combined into one joint valve 49 as shown. The joint valve 49 will operate in a manner similar to the two valves 47 and 48 as described in connection with Fig. 6.

Fig. 8 illustrates an exemplary embodiment for impeding air flow into a patient's lungs according to the present invention. As shown, the device 51 comprises a ventilation bag 28 that is connected to a facial mask 52 by an inflow valve 24 and an expiration valve 22. Although the facial mask 52 is shown connected to the ventilation bag 28, the...

- ...52 can be used alone or in connection with the ventilation bag. Between the inflow valve 24 and the expiration valve 22 is a one-way fish mouth valve 37 or any other type of one-way valve to prevent air from exiting the patient's lungs and flowing to the ventilation bag 28. The ventilation bag 28 also contains a one-way ventilation valve 26 for allowing air to inflow into the device 51. The exemplary embodiment operates in...
- During the decompression phase of ACD-CPR, air is prevented from entering into the patient's lungs through the threshold inflow valve 24 thus increasing the negative intrathoracic pressure. During the compression phase, air is allowed to expire from the patient's lungs through the expiration valve 22. Also, the patient can be ventilated during ACD-CPR by manually squeezing the ventilation bag 28. Consequently, the preferred embodiment serves to enhance cardiopulmonary circulation by increasing the negative intrathoracic pressure to force more blood into the chest from the peripheral venous vasculature.

Figs. 9A - 9C show another embodiment of the present invention...

- ...that is connected to the patient. The ventilation tube 60 has a one-way bypass valve 66 and a one-way pressure responsive valve 68. The ventilation tube 60 may also have a manual switch 70 attached to the bypass valve 66 and extending through a side of the ventilation tube 60. As shown in Fig...
- ...70 may be set in a closed position so that the one-way pressure responsive valve 68 opens when the threshold pressure of the valve 68 has been exceeded. At this point, the valve 68 opens allowing for ventilation of the patient. As shown in Fig. 10B, the one-way pressure responsive valve 68 may be bypassed altogether by manually placing the switch 70 in the open position so that the bypass valve 66 is opened allowing air to flow to the patient. Fig. 10C illustrates the operation of the bypass valve 66 with the switch 70 in an inactive mode. Here, the rescuer performing ventilation may do so without added resistance from the impedance step as in Fig. 10A. Instead, bypass valve 66 opens only when the pressure at the proximal end of the tube 62 is...
- ...pressure (0 mmHg), preferably in a range from about 0 mmHg to 5 mmHg. During decompression of the patient's chest, the one-way bypass valve 66 remains closed unless atmospheric pressure is exceeded. Thus, the patient is ventilated only when...
- ...of the tube 62 to exceed atmospheric pressure. The function of the one-way bypass valve 66 may be performed by many different threshold valve designs which are known in the art.

Although the foregoing invention has been described in...

... CLAIMS means (24) is exceeded,

whereby when performing cardiopulmonary resuscitation the extent and duration of negative intrathoracic pressure during the decompression of the patient's chest is enhanced in order to enhance venous blood flow into the heart and lungs from the peripheral venous vasculature.

2. The apparatus of claim 1, wherein the impeding means (24) further comprises a pressure-responsive valve, wherein the 1valve is biased to open to permit the inflow of air when the intrathoracic pressure falls below a threshold level in the range from 0 mm Hg to about...

...to 100 cm H2))O).

- 3. The apparatus of claim 2, wherein the pressure-responsive valve is in a lumen of an endotracheal tube.
- 4. The apparatus of any one of...

24/3,K/23 (Item 23 from file: 348)
DIALOG(R)File 348:EUROPEAN PATENTS

(c) 2004 European Patent Office. All rts. reserv.

#### 00640834

Method for supplying fresh gas during manual ventilation and a ventilator system for carrying out the method

Verfahren und Gerate fur Frischgasabgabe bei manueller Ventilation Procede et dispositif pour distribuer du gaz frais pendant ventilation manuelle

PATENT ASSIGNEE:

Siemens-Elema AB, (420950), Rontgenvagen 2, 171 95 Solna 1, (SE), (applicant designated states: CH; DE; ES; FR; GB; IT; LI; NL; SE)

INVENTOR:

Olsson, Sven-Gunnar, Villa Fortuna, S.32300 Arlov, (SE) Cewers, Goran, Mollevongsvagen 89, S-222 40 Lund, (SE)

Rydgren, Goran, Strandangsvagen 4, S-230 44 Bunkeflostrand, (SE)

PATENT (CC, No, Kind, Date): EP 621049 A1 941026 (Basic) EP 621049 B1 990303

EP 621049 B1 9903 APPLICATION (CC, No, Date): EP 93120320 931216;

PRIORITY (CC, No, Date): SE 93364 930205

DESIGNATED STATES: CH; DE; ES; FR; GB; IT; LI; NL; SE INTERNATIONAL PATENT CLASS: A61M-016/00; A61M-016/08

ABSTRACT WORD COUNT: 122

LANGUAGE (Publication, Procedural, Application): English; English; FULLTEXT AVAILABILITY:

Available Text Language Update Word Count CLAIMS B (English) 9909 1146 9909 1037 CLAIMS B (German) 9909 1353 CLAIMS B (French) SPEC B 9909 (English) 6381 Total word count - document A 0 Total word count - document B 9917 Total word count - documents A + B

Method for supplying fresh gas during manual ventilation and a ventilator system for carrying out the method INTERNATIONAL PATENT CLASS: A61M-016/00 ...

#### ... A61M-016/08

#### ...ABSTRACT A1

The invention relates to a **method** for supplying fresh gas in manual ventilation of a patient and a ventilator **system** (2) for carrying out the **method**, the supply of fresh gas to a breathing bag (8) being regulated. During inspiration, the...

...senses when the patient exhales, and an identical flow of gas is fed to the system via an inspiratory valve (26), said flow of fresh gas streaming into the breathing bag (8) and preventing expired gas from entering the breathing bag (8). An expiratory valve simultaneously opens to conduct expired gas out of the system. (see image in original document)

SPECIFICATION This invention relates to a **method** for supplying fresh gas, for use with a ventilator **s**ystem for manual ventilation of a patient in which a breathing bag is squeezed to impose an inspiration on the patient.

The invention also relates to a ventilator  $\ensuremath{\mathbf{system}}$  for carrying out the  $\ensuremath{\mathbf{method}}$  .

Ventilator systems are used for facilitating, supporting or imposing

inspiration and expiration on a patient. Manual ventilation...

...the breathing bag is connected to the patient's airways without any intermediate pressure exchange system, the physician is able to feel the response of the lungs to the action of the breathing bag. In other words, the physician can be said to communicate directly with the lungs. This is essential, particularly in anesthesia where the anesthetist wishes to control the entire respiratory process himself/herself.

In US-A-3,794,027 is described a manual ventilation system for anesthesia. The system comprises a breathing bag which the physician squeezes to push air through a patient tube...

- ...feel the way the patient is breathing. The bag must be periodically detached from the <code>system</code> , emptied and refilled with fresh gas to replace the gas re-breathed a plurality of times by the patient. In the patient tube there are also two check <code>valves</code> , near the patient, which control the direction of gas flow to and from the patient...
- ...an adverse effect on surgical staff.

  The object of the invention is to achieve a method which avoids the above-described disadvantages and in which the patient does not

re-breathe...

...own expired gas, with no loss of the physician's ability to communicate with the <code>lungs</code> .

Another object of the invention is to achieve a ventilator system for carrying out the method and which facilitates control of gas flow in the patient tube, making check valves and gas absorbers unnecessary.

One such **method** is achieved in accordance with the invention in that fresh gas is fed into the...

...of expired gas, and gas expired by the patient is conducted out of the ventilator <code>system</code> .

By replacing the gas inspired by the patient from the breathing bag with fresh gas...

...compared to the situation when the patient expires directly into the breathing bag. This filling method works equally well when the patient breathes spontaneously.

A refinement of the **method** is achieved in accordance with a preferred embodiment of the invention in that a parameter...

- ...Expired gas is prevented from entering the breathing bag and forced out of the ventilator system . The slightest change in expiratory flow from the patient affects the parameter measured, and control...
- ...the physician, i.e. it will feel to the physician as if the patient's lungs were communicating directly with the breathing bag, even though expired gas is conducted out of the ventilator system. Since expired gas is not re-breathed, no carbon dioxide filter is needed, and control ...
- ...of gas flow is achieved by control of the flow of fresh gas, making check valves unnecessary for controlling the direction of the gas flow.

In this context, it is an...bag has refilled and is again ready for the inspiration phase.

A refinement of the **method** is obtained in accordance with the invention in that an additional parameter is measured for...

...control of the flow of fresh gas and/or starting a functional check on

the  $\mbox{method}$ , an alarm being generated and/or an alternative ventilation mode started if at least one...

- ...regulating the supply of fresh gas. The safety feature obtained through functional control of the **method** means that if a fault occurs in e.g. measurement of the control parameter so...
- ...completely, an alarm is generated drawing the staff's attention to the fault. Alternately, the system could be automatically switched to some other method, involving the monitoring of some other control parameter, or some other ventilation mode, e.g. mechanical ventilation.

A ventilator **system** for carrying out the **method** is achieved by in accordance with the invention when the ventilator **system** as defined in claim 5.

It is an advantage if the ventilator system is designed so the ventilator unit comprises a controllable inspiratory valve connected to one end of the patient tube, a controllable expiratory valve connected to the other end of the patient tube and a control device connected to the parameter detector and to the valves for the purpose of controlling the valves according to the parameter.

In principle, it is sufficient for carrying out the <code>method</code> if the inspiratory <code>valve</code> passes a continuous flow and the <code>ventilator</code> <code>system</code> is controlled by regulation of the expiratory <code>valve</code>. The <code>ventilator</code> unit can be devised so the control device constitutes an integral part of

\*...further comprises a second detector for sensing gas flow or gas pressure at the inspiratory valve and a third detector for sensing gas flow or gas pressure at the expiratory valve, whereby the control device controls the valves according to the gas flows and/or gas pressures measured by the detectors. Measurement of flows, or pressures at the valves, makes it possible to control these valves more exact.

A refinement of the ventilator system is achieved in accordance with the invention in that the detectors sense gas flow, and...

...the gas volumes passing the respective detector during expiration, whereby the control device controls the **valves** so the determined gas volumes are essentially identical.

This ensures that the expired volume of...

...measurement of the gas flows also makes possible rapid detection of minor leaks in the  ${\tt system}$  .

In this context, it is an advantage if the control device continuously zeroes the first...

...with a long time constant, lasting up to several minutes.

A refinement of the ventilator **system** is achieved in accordance with the invention in that the control device controls the **valves** so a passing flow of fresh gas flows through the patient tube during expiration.

Passing...

...flushes out any expired gas left in the patient tube between the breathing bag and lungs , i.e. dead space is reduced throughout the entire system .

Here, it is an advantage if the ventilator <code>system</code> is devised so the control device controlls the <code>valves</code> so the flow of gas at the inspiratory <code>valve</code> is less than the flow of gas at the expiratory <code>valve</code> and a first pressure detector measures pressure in the breathing bag, whereby the control device regulates the inspiratory <code>valve</code>, when

pressure in the breathing bag drops below a first defined pressure, so a flow...

...the breathing bag is fed into the patient tube.

This would thereby gradually regulate the **system** towards increasingly lower pressure until a filling pressure is achieved. This regulatory **procedure** prevents the build-up of pressure in the **system**. Pressure in the breathing bag can be measured directly by a manometer in the breathing...

...the patient tube.

Alternately, it may be advantageous in certain instances to devise the ventilator system so the control device controls the valves so the flow of gas at the inspiratory valve is greater than the flow of gas at the expiratory valve and a second pressure detector measures pressure in the patient tube, whereby the control device regulates the expiratory valve, when pressure in the patient tube exceeds a second defined pressure, causing pressure to drop.

This would thereby gradually regulate the **system** towards a definable maximum pressure, i.e. a pop-off pressure, keeping the patient from being exposed to pressures greater than this.

A refinement of the ventilator **system** is achieved in accordance with to the invention in that the control device controls the **valves** so a passing flow of fresh gas flows through the patient tube during inspiration.

In the same way as during expiration, a flow of gas may be fed through the **system** during inspiration. A flow of gas can naturally be present even throughout the entire inspiratory...

...out any residual gas expired by the patient.

In order to improve control of the **system**, it is an advantage if the breathing bag comprises a flow **valve** which is controllable by the control device. If, for example, the inspiratory **valve** is slow, the flow **valve** could be used for obtaining the most exact gas flow possible.

An advantageous refinement of the ventilator **system** is achieved in accordance with the invention in that an additional detector is installed in...

- ...signal meets at least a second defined condition, whereby the control device sets the ventilator **system** in a safe state if the measurement signal meets the second defined condition.

  In this...
- ...of her/his expired gas. Moreover, this would result in a monitoring of the ventilator **system**'s function. If the new parameter's measurement signal meets certain conditions, e.g. that...
- ...defined second value for a specific period of time, the control device sets the ventilator **system** in a safe state. Safe state means that the device is transferred to a state...
- ...the device. The device could even automatically perform some safety measure, such as opening a **valve**, changing the control parameter or changing the **ventilation** mode. Even when it performs an automatic...
- ...from a detector measuring another parameter could be used as a control parameter, or the **system** could be switched to another ventilation mode, e.g. from manual to mechanical ventilation. In...

...generator to activate an alarm and/or a switch to switch control of the ventilator system to mechanical ventilation or to some other parameter.

The invention is described in greater detail...

...referring to five figures in which:

- FIG. 1 shows a first embodiment of the ventilator system according to the invention;
- FIG. 2 is a block diagram of a control device in the ventilator  $\ensuremath{\mathbf{system}}$  ;
- FIG. 3 illustrates a first regulation the ventilator system is capable of performing;
- FIG. 4 illustrates a second regulation the ventilator **system** is capable of performing and
- FIG. 5 shows a second embodiment of the ventilator **system** according to the invention.

The ventilator system 2 comprises a ventilator unit 4, a patient tube 6 and a breathing bag 8...

- ...When the manual ventilation mode is set on the control panel 10, a breathing bag valve 14, which can even be a manually adjustable valve, opens. A physician can compress the breathing bag 8 by squeezing it, thereby increasing pressure in the patient tube 6 so gas is forced into the patient's lungs. When the physician relaxes pressure on the breathing bag 8, gas can flow back, and...
- ...With this ventilation mode, the physician is continuously able to feel the action of the **lungs** and exercise complete control over the patient's respiration.

To keep the patient from re-breathing expired gas, the ventilator system 2 is controlled during spontaneous breathing and manual ventilation of the ventilator unit 4 in...

...18 shown in greater detail in FIG. 2.

The ventilator unit 4 also contains an inspiratory valve 26 and an expiratory valve 30, both controlled by the control device 18 and a first flow meter 32, a...

...breathing bag 8, it emits a first control signal which is sent to the inspiratory valve 26 via a first A/D converter 24, and a second control signal which is sent to the expiratory valve 30 via a second A/D converter 28. The valves 26, 30 are opened to permit the passage of a flow of gas according to the control signals.

The flow of gas through the inspiratory valve 26 is measured in the first flow meter 32, whose measurement signal is sent to...

- ...the onset of expiration, as described above. The control device 18 then opens the inspiratory valve 26 and the expiratory valve 30, regulating the flow in them so they are as close as possible to the expired flow. As a result, the flow of gas through the inspiratory valve 26 keeps the flow of expired gas from filling the breathing bag 8 and fills the breathing bag 8 with fresh gas. Expired gas is thereby forced out of the system through the expiratory valve. Changes in expiratory flow from the patient are immediately recorded by the pressure gradient detector 16, enabling the control unit 18 to correct control of the valves 26, 30. The breathing bag 8 is thereby filled with fresh gas in a way...
- ...patient were breathing directly into the breathing bag 8.

  In order to control the expiratory valve 30 as accurately as possible, the flow of gas at the expiratory valve is measured in the

second flow meter 36, and the measurement signal is sent to...

...with enough fresh gas, the microprocessor 22 can integrate the flows measured at the inspiration valve 26, the expiration valve 30 and the breathing bag 8. The integrals designate the volume of gas passed, and the control unit 18 can regulate the valves 26, 30 so the volumes are of equal magnitude.

The pressure gradient detector 16 is in this embodiment zeroed continuously to increase the **system** 's ability to measure small flows. This can be compared to an AC coupling with...

...of the changes registered. The pressure gradient detector 16 is zeroed before the breathing bag valve 14 opens in order to supply an reference output for flow at the breathing bag 8.

Moreover, pressure is measured in the patient tube 6 at the inspiratory valve 26 in the first pressure detector 33, whose measurement signal is fed to the microprocessor...

...the breathing bag 8 drops too much, additional fresh gas is supplied via the inspiratory valve 26.

The second pressure detector 40 is located by the expiratory valve 30 in the patient tube 6 and senses pressure at the expiratory valve 30. The measurement signal is sent to the microprocessor 22 via a fifth signal former 42. If pressure at the expiratory valve 30 exceeds a defined maximum pressure, i.e. the pop-off pressure, the expiratory valve 30 opens further in order to reduce excess pressure in the patient tube 6. The aim is to limit the buildup of pressure in the patient's

The microprocessor 22 can also control the breathing bag valve 14 via a third D/A converter 44. Use of this valve may be appropriate if the inspiratory valve 26 is not fast enough.

FIGURES 3 and 4 schematically illustrate two ways in which the microprocessor 22 can control the valves 26, 30. The signals are designated as follows: Ppopoff)) is the pop-off pressure, which...

...measured by the second presure detector 40, (PHI)E)) is the flow at the expiratory valve 30, (PHI)H)) is the breathing bag flow 8, (DELTA)PH)) is fall in the...during spontaneous breathing and (PHI) Iset)) is the reference value for flow at the inspiratory valve 26.

A regulation sufficient for controlling the supply of fresh gas to the breathing valve 8 during the expiratory phase is illustrated in FIG. 3. The value for expiratory flow...

- ...is sent to a first regulator 48 which sends a control signal to the expiratory valve 30 via the second D/A converter 28 in an effort to achieve an expiratory...
- ...to form a fault signal used by the first regulator 48 to control the expiratory valve 30. Pressure PE)) in the patient tube 6 at the expiratory value 30 is monitored...
- ...logic 52 first switches a first switch 54, and then assumes control of the expiratory valve 30.
  - . Another monitoring performed concerns pressure in the breathing bag  $8. \,$ As previously noted, filling...
- ...bag 8. If pressure in the breathing bag drops below filling pressure Pf)), the inspiratory valve 26 will admit an additional influx of fresh gas to fill the breathing bag 8...
- ...adder 56 to the pressure PI)) measured in the patient tube 6 at the inspiratory valve 26. The fault signal obtained is sent to a second

control logic 58 capable of...

- ...is typically- 5cm H2))O in relation to atmospheric pressure. During the expiratory phase, the **system** again automatically switches to normal pressure regulation. This takes place when the second control logic...
- ...PPEEP)) (DELTA)PH))), i.e. when spontaneous breathing is deemed to be present.

The ventilator **system** 2 can also be controlled so it supplies a passing flow of gas in the...

...both expiration and inspiration. The passing flow of gas flushes expired gas out of the **system**, thereby reducing the **system**'s dead space. To facilitate control of the passing flow of gas when the breathing bag 8 is filled, pressure in the **system** can either be regulated against the filling pressure Pf)) for the breathing bag or against the **system**'s maximum pressure Ppopoff)).

In the first instance, inspiratory flow is regulated so it is less than expiratory flow. For example, the passing flow at the inspiratory **valve** could be reduced to 2 liters/minute when the total passing flow is 3 liters...

...PH)), drops below the filling pressure Pf)) plus the end expiratory pressure PPEEP)), the inspiratory valve 26 opens to fill the breathing bag 8.

In the second instance, when the **system** is regulated against the pop-off pressure Ppopoff)), inspiratory flow is instead increased so it

...flow. When pressure in the patient tube PE)) exceeds pop-off pressure Ppopoff)), the expiratory valve 30 opens to bleed off surplus gas.

Since all flows are measured or calculated in the ventilator system 2, the microprocessor 22 can quickly determine whether the patient should be disconnected from the system, then stopping all gas flows. This is particularly important in conjunction with the administration of...

...anesthetic into the operating theatre.

In the corresponding manner, leakage from different parts of the system can be easily detected. Regulation of the entire system can even be managed according to readings from pressure sensors, since pressure and flow in the system are directly interrelated, and the value of one can be established from the value for the other.

A digitally controlled **system** has been described in the embodiment, but the **system** can also be devised as an analog circuit.

A second embodiment of the ventilator system is shown in FIG. 5. The ventilator system 64 comprises a ventilator unit 66, which could consist of e.g. a Servo Ventilator...

- ...66A and an expiratory section 66B. In the inspiratory section 66A there is an inspiration valve 86 which regulates the flow of gas into the patient tube 68, and in the expiratory section 66B there is an expiratory valve 88 which regulates the flow of gas out of the patient tube 68. A number...
- ...are installed between the control device 72 and the ventilator unit 66 for controlling the valves 86, 88. Control signals for the ventilation phases, i.e. whether the valves 86, 88 are to be open or closed and whether the valves 86, 88 are to be controlled according to pressure or flow, are sent to the ventilator unit 66 via first control line 90. When the valves 86, 88 are to be controlled according to flow, a first flow

control signal is...

- ...is sent to the expiratory section 66B via a third control line 94. When the **valves** 86, 88 are to be controlled according to pressure, a first pressure control signal is...
- ...can perform the regulation and control described in conjunction with FIGS. 1-4.

The ventilator **system** 64 functions as follows: In normal ventilation, a breathing bag **valve** 108 is closed, and the **system** operates like a normal ventilator. The breathing bag **valve** 108 is open in manual ventilation of the patient.

During the inspiratory phase, the control device 72 controls the ventilator unit 66 so the inspiratory valve 86 and the expiratory valve 88 are closed. The patient's inspiration is monitored by the physician who squeezes the breathing bag 70 which, since the valves 86, 88 are closed, is in direct contact, like a communicating vessel, with the patient's lungs. During inspiration, the physician can therefore feel the pressure in the patient's lungs in the breathing bag 70.

During expiration, the physician relaxes pressure on the breathing bag

...
...to the control device 72 which now controls the ventilator unit 66 so the inspiratory valve 86 and the expiratory valve 88 admit an

inspiratory flow and an expiratory flow respectively of the same magnitude as...

...pressure detector 82. The breathing bag 70 then fills with fresh gas from the inspiratory valve 86. The patient's expired gas is thereby unable to flow into the breathing bag 70 and is conducted away through the expiratory valve 88. Gas outflow through the expiratory valve 88 has the same flow profile as when the patient's lungs are emptied of gas. So the patient's lungs, even during expiration, will also feel to the physician as though they were communicating directly with the breathing valve 70, even though the expired volume is controlled via the expiratory valve 88. In other words, the physician controls the patient's respiration during both inspiration and...

- ...volume of flow into the breathing bag 70 during the same expiratory phase. This regulatory method effectively prevents the patient's expired gas from reaching the breathing bag 70. The inspiratory...
- $\ldots$  constant flows of gas from an external source of gas can be connected to the  $\operatorname{\mathbf{system}}$  .
  - In order to enhance patient safety, the ventilator **system** 64 contains a CO2)) detector 100 placed in the patient tube 68 by the patient...
- ...replaced with fresh gas. If this is not the case, there issome fault in the **system**, and the alarm is activated. To ensure that the alarm is triggered, even if the...
- ...very steeply when the patient begins exhaling, this circumstance can be used to trigger the **system** to start refilling the breathing bag 70 with fresh gas. Here, the filling **procedure** can be controlled in the way described above.

A direction-dependent flow meter 104 placed...

...signal line 106. The direction-dependent flow meter 104 senses gas flows towards the breathing valve 70. The direction-dependent flow meter 104 should only intermittently detect flow during the expiratory...

- ...detection lasting a given period of time, e.g. a few seconds, indicates that the **system** is not working properly, and an alarm is activated. The measurement signal from the direction...
- ...can still be sustained.

Alternately, the control device 72 can shift to controlling the ventilator system 64 according to some other control parameter, such as the measurement signal from the direction-dependent flow meter 104. This control redundancy for the control device 72 optimizes the ventilator system 's 64 function and patient safety.

The CO2)) detector 100 can be replaced, without any...

- CLAIMS 1. A **method** , for use with a ventilator **system** for manual ventilation of a patient in which a breathing bag is squeezed to impose...
- ...of expired gas, and gas expired by the patient is conducted out of the ventilator system (2).
  - 2. A **method** of claim 1, characterised in that a parameter related to the patient's expiration is...
- :..breathing bag (8), and gas flow is controlled according to the measured parameter.
  - 3. A method of claim 2, characterised in that one of the parameters gas flow, temperature, relative gas...
- $\ldots$  concentration of a specific gas is measured and serves as the control parameter.
  - 4. A method of claim 2 or 3, characterised in that an additional parameter is measured for starting control of the flow of fresh gas and/or starting a functional check on the method, an alarm being generated and/or an alternative ventilation mode started if at least one defined condition is met.
  - 5. A ventilator **system** (2; 64), for manual ventilation of a patient, comprising a patient tube (6; 68) connectable...
- ...bag (8; 70), and gas expired by the patient is conducted out of the ventilator system (2; 64).
  - 6. A ventilator of claim 5, characterised in that the ventilator unit (4; 66) comprises a controllable inspiratory valve (26; 86) connected to one end of the patient tube (6; 68), a controllable expiratory valve (30; 88) connected to the other end of the patient tube (6; 68) and a...
- ...device (18; 72) connected to the parameter detector (16; 82, 100, 104) and to the valves (26, 30; 86, 88), whereby the control device (18) controls the valves (26, 30; 86, 88) according to the parameter.
  - 7. A ventilator system of claim 6, characterised in that the ventilator unit (4) comprises a second detector (32) for sensing gas flow or gas pressure at the inspiratory valve (26) and a third detector (36) for sensing gas flow or gas pressure at the expiratory valve (30), whereby the control device (18) controls the valves (26, 30) according to the parameters gas flows or gas pressures measured by the detectors (16, 32 36).
  - 8. A ventilator **system** of claim 7, characterised in that the detectors (16, 32, 36) sense gas flow, and...
- ...the respective detector (16, 32, 36) during expiration, whereby the control device (18) controls the **valves** (26, 30) so the determined gas volumes are essentially identical.

- 9. A ventilator **system** of any of claims 5 8, characterised in that the control device (18) continuously zeroes the parameter detector (16).
- 10. A ventilator **system** of any of claims 6 9, characterised in that the control device (18; 72) controls the **valves** (26, 30; 86, 88) so a passing flow of fresh gas streams through the patient tube (6; 68) during expiration.
- 11. A ventilator system of claim 10, characterised in that the control device (18) controls the valves (26, 30) so the flow of gas at the inspiratory valve (26) is less than the flow of gas at the expiratory valve (30) and a first pressure detector measures pressure in the breathing bag (8), whereby the control device (18) regulates the inspiratory valve (26), when pressure in the breathing bag (8) drops below a first defined pressure, so...
- ...filling the breathing bag (8) is fed into the patient tube (6).
  - 12. A ventilator system of claim 10, characterised in that the control device (18) controls the valves (26, 30) so the flow of gas at the inspiratory valve (26) is greater than the flow of gas at the expiratory valve (30), and a second pressure detector (40) measures the pressure in the patient tube (6), whereby the control device regulates the expiratory valve (30), when pressure in the patient tube (6) exceeds a second defined pressure, causing pressure to drop.
  - 13. A ventilator **system** of any of claims 5 12, characterised in that the control device (18) controls the **valves** (26, 30) so a passing flow of fresh gas flows through the patient tube (6) during inspiration.
  - 14. A ventilator **system** of any of claims 5 13, characterised in that the breathing bag (8) comprises a flow **valve** (14) which is controllable by the control device (18).
  - 15. A ventilator system of any of claims 5 14, characterised in that an additional detector (100, 104) is...signal meets at least a second defined condition, whereby the control device sets the ventilator system (64) in a safe state if the measurement signal meets the second defined condition.
  - 16. A ventilator **system** of claim 15, characterised in that the control device (72) comprises a first comparator using...
- ...generator to activate an alarm and/or a switch to switch control of the ventilator **system** (64) to mechanical ventilation or to some other parameter.

24/3,K/27 (Item 27 from file: 348)

DIALOG(R) File 348: EUROPEAN PATENTS

(c) 2004 European Patent Office. All rts. reserv.

#### 00280742

CARDIOPULMONARY RESUSCITATION DEVICE.

KARDIOPULMONARE WIEDERBELEBUNGSVORRICHTUNG.

DISPOSITIF DE REANIMATION CARDIO- PULMONAIRE .

PATENT ASSIGNEE:

GARFIELD, Allan Samuel, (931920), 2 Lockerbie Court, East St. Kilda, VIC

3183, (AU), (applicant designated states:

AT; BE; CH; DE; FR; GB; IT; LI; LU; NL; SE)

### INVENTOR:

DE VRIEND, Max, Sylvain, 78 Balaclava Road, Balaclava, VIC 3183, (AU) COOK, David, Julian, 20a Alston Grove, East St. Kilda, VIC 3183, (AU) WHITE, Noam, 56 Balaclava Road, Balaclava, VIC 3183, (AU)

LEGAL REPRESENTATIVE:

Pfenning, Meinig & Partner (100961), Mozartstrasse 17, W-8000 Munchen 2, (DE)

PATENT (CC, No, Kind, Date):

EP 310613 A1 890412 (Basic) EP 310613 A1 890802

EP 310613 B1 911030

WO 8707844 871230

APPLICATION (CC, No, Date): EP 87903839 870610; WO 87AU170 870610

PRIORITY (CC, No, Date): AU 866459 860618

DESIGNATED STATES: AT; BE; CH; DE; FR; GB; IT; LI; LU; NL; SE

INTERNATIONAL PATENT CLASS: A61M-016/08; A61M-016/00; A61H-031/00 NOTE:

No A-document published by EPO

LANGUAGE (Publication, Procedural, Application): English; English; FULLTEXT AVAILABILITY:

	Language	Update	Word Count
CLAIMS B	(English)	EPBBF1	680
CLAIMS B	(German)	EPBBF1	600
CLAIMS B	(French)	EPBBF1	788
SPEC B	(English)	EPBBF1	4525
Total word coun	l word count - document A		0
Total word coun	word count - document B		6593
Total word count - documents A + B			6593

# DISPOSITIF DE REANIMATION CARDIO- PULMONAIRE . INTERNATIONAL PATENT CLASS: A61M-016/08 ...

#### ... A61M-016/00

...SPECIFICATION due to inadequate cardiac output. In adults, this arrest is most often due to (min) cardiac arrest (min) (e.g. myocardial infarction), whereas in children it is more often secondary to (min) respiratory arrest (min) or hypoxia e.g. asphyxia.

Basic CPR is the accepted technique out of hospital where advanced life support systems are not available. Examples of situations where basic CPR is essential include drowning, trauma, drug overdose, and myocardial infarction .

It has been shown that Basic CPR, when performed adequately, will satisfy the physiological criterion...

...tissues, in order to preserve their cellular function.

Basic CPR can be performed by two techniques: (a) (min)Old(min) CPR and (b) (min)New(min) CPR, which will be described...

- ...follows:
  - (a) (min)Old(min) CPR is well-established in the medical literature. The basic **technique** where no specialized equipment is available is to clear the airways of solid or fluid...
- ...10-15/min (e.g. mouth-to-mouth, or by mask), together with external cardiac compression at a rate of 80-100/min.

This ideally requires two trained operators. Although it...

...be performed by one trained operator, this is much less efficient due both to the **technique** itself and to the physical strain involved.

The basis for the **technique** is that the increase in **intrathoracic** 

pressure is transmitted to the heart; when performed properly, it has been shown to generate...

- ...output. This results in predominantly (min) forward(min) blood flow to the brain, as the **valves** in the great veins in the neck prevent reverse flow.
  - (b) (min) New(min) CPR...
- ...min)old(min) CPR, except that it recommends the simultaneous performance of both external cardiac compression and ventilation, resulting in a greatly enhanced forward blood flow and cardiac output, because of a greater increase in intrathoracic pressure that is transmitted in the heart. It is possible that coronary blood flow is...
- ...in training of a very high proportion of the community.

  In order for a CPR method to be of use, it must be
  - a) Simple to understand and perform.
  - b) Effective...
- ...community setting. Five subjects (7%) stated that they would not be prepared to use this method while 16 (23%) would use it only selectively, according to such influences as age of...practice in many hospitals, where a variety of devices may confront a person attempting resuscitation. Pulmonary ventilation is frequently inadequate when these devices are used during CPR, unless special instruction is given, and one frequently used system, bag valve -mask ventilation, had a 97% failure rate even after instruction (Lawrence and Sivaneswaran, op. cit...
- ...endotracheally or with an oesophageal obturator airway (JAMA, op. cit.).

However, most mouth-to-mask **methods** require the operator to hold the mask to the patient's face using both hands...

- ...operator must be present if cardiac massage is to be applied, which gravely limits this **method** . More commonly such emergencies occur in situations where face masks are not available.

  Whilst U...
- ...person to perform simultaneously the functions of
  - a) cardiac massage,
  - b) artificial respiration, and
  - c) suction of secretions from the airway, without placing the operator in contact with the patient's...
- ...with an oropharyngeal airway; the bottom wall being adapted to, in use, rest on the **chest** of a patient to support the pump; said wall structure being capable of contracting and...
- ...through the oropharyngeal airway, and pressure applied to the top wall

is transmitted to the **chest** of the patient via the bottom wall after contraction of the wall structure to effect...

...sectional view taken along line 4-4 of Figure 3 and showing one form of valve arrangement for the various inlets and outlets from the pump;

Figure 5 is a cross-sectional view of the valve housing section of the pump of Figure 2, but with an alternative form of valve for the various inlets and outlets;

Figure 6 is a cross-sectional view taken along...

- ... The side walls 3 and 4 are of a bellows construction such as to resiliently compress and expand as an axial force is applied to and released from the pump. Inner...
- ...via a gas inlet spigot 7 through the top wall 2 and one-way flap valve 8. When the operator applies hand pressure to the top face 2, as indicated by the arrow to axially compress the side walls 3 and 4, gas is expelled from gas chamber 5 through one-way flap valves 9 and 10 into gas outlet tubes 11 and 12 contained within and extending outwardly ...to be extracted and sucked through a waste-venting tube 13 and a one-way valve 14 into the waste chamber 6. From there waste can leave via a one-way flap valve 15 via a waste outlet tube 16 to a waste reservoir (not shown). Expulsion of waste in this way is assisted by subsequent compression of the pump. The top face of the pump may carry means such as straps...
- ...The underside of the bottom wall 1 is adapted to, in use, rest on the chest of a patient to support the pump.

  With reference to Figure 7, distal ends of...
- ...telescoping wall members with an internal spring biasing the structure to an expanded condition, and **compressible** under pressure, and expandable when pressure is removed, to function in a similar manner to ...
- ...sophisticated embodiment of the invention with reference to Figures 2 to 4, and its alternative **valve** arrangement as shown in Figures 5 and 6, the pump comprises a gas chamber 23...
- ... Figure 1, the side wall 22 is of a bellows construction such as to resiliently **compress** and expand as an axial force is applied to and released from the pump. The...
- ...and 22, and upper surface of interface 21 provides the gas chamber 23, and a. **compression** spring 24 is positioned centrally within the gas chamber to bias the side wall 22...
- ...wall, with a clamping band 32 being additionally applied to consolidate the connection. A further **compression** spring 33, having a lesser spring force than the biasing spring 24 in the gas...
- ...to act as the bottom wall of the pump which in use, rests on the **chest** of the patient to support the pump. In use axial pressure applied to the top wall 20 of the pump initially **compresses** the wall structures of the gas and waste chambers 23 and 29 to be then transmitted through the bottom wall to the **chest** of the patient to effect simultaneous cardiac massage and ventilation.

With reference to Figures 2 compressed against the biasing force of the spring 24 within the gas chamber 23 and gas...

...interface 21 and into a radial gas transfer port 41, past a gas outlet

check valve 42 to a gas outlet passage 43 and then onto a gas outlet tube leading...

- ...and into a radially waste transfer passage 45, and then past a waste outlet check valve 46 to a waste outlet passage 47 and then onto a suitable receptacle for disposal...
- ...through a gas inlet passage 48 in the interface 21, past a gas inlet check valve 49 into a gas inlet transfer passage 50 and onto a gas inlet port 51...
- ...passage 52 in the interface 21, which in turn communicates, via a waste inlet check **valve** 53, with a radial waste transfer port 54 and waste inlet port 55 leading to...
- ...release of increased pressure through the pump body, whilst the pump is situated on the <code>chest</code> of the patient, applies external cardiac massage or <code>compressions</code> .

There is a tendency at the pharyngeal piece within the patient for gas to flow...

- ...the waste-venting tube and back to the waste chamber, rather than into the respiratory system of the patient, and in order to prevent such from happening in the embodiment of Figure 2, a conical valve member 55a is provided within the waste chamber 29 on the inside wall of the...
- ...with the waste inlet port 55, such that, when the waste housing is collapsed the valve member closes the port 55 and thus any bypassing of the gas back through to the waste chamber 29 is resisted ensuring that the gas therefore flows into the respiratory system of the patient.

  Also, as shown in Figure 2, a bleed port 47a is provided...
- ...47, whereby, when waste is expelled through the waste outlet, and the waste outlet check valve 46 closes, air within the outlet can re-enter the waste chamber through the bleed port 47a to in effect release the vacuum, that is, raise the pressure within the waste chamber to match the outside pressure within the outlet 47.

In the embodiment of Figure 2 to 4, the check valves 42, 46, 49 and 53 are in the form of simple flap valves positioned within the respective passages and held in place at the inner ends of the...

- ...sleeves 56, whilst in the case of the gas and waste inlet passages, the check valves are captured between inner sleeves 57, at the inner end of the respective inlet passages, and outer sleeves 58, whereby the check valves are positioned midway along the length of those passages to ensure sufficient space for the flaps of the check valves to swing to an open position. Each check valve comprises a thin disc of semi-rigid material, with a circular slit cut around the...
- ...reversed flow or pressure.

In the alternative embodiment of Figures 5 and 6, the check valves consist of "curl-type" valves comprises a housing having a cylindrical wall 62, one end of which is closed by...

...the wall 63 has an aperture 68 therethrough which receives a stem 65 of a valve closure disc 66. A bulb 67 is formed on the free end of the stem 65 which, in the assembly of the check valve deforms when pushed through the aperture 68, but will prevent disengagement from within the aperture...with two outlets from the gas chamber, for example an additional identical gas outlet and valve arrangement on the opposite side of the waste inlet, and each communicating with its own...

- ...the neck extended backwards.
  - c) Quickly loosen or remove all clothing around the neck and chest
  - d) Where possible, clear the patient's mouth and airway of all visible fluid or...
- ...operator should be kneeling by the side of the patient, leaning over the patient's **chest** and device as shown.
  - c) Place the bottom of the pump on to the lower...
- ...the flat of each hand on top of the other, parallel to the patient's chest and crossed at 90(degree) to each other. The fingers of each hand should be...

# ...i.e.

- a) 1-second (min) ventilation (min), then
- b) 10x1/2-second (min) cardiac compressions (min) then
- c) 1-second (min) suction (min).
- (1) In a single action, firm **compression** straight downwards by the movement of both hands, will collapse the unit and inflate the patient's **chest**, i.e. a 1-second action (min) ventilation (min). Maintain this downward pressure to keep...
- ...to allow the sternum to rise whilst still keeping the pump deflated. This (min)cardiac compression (min) should take 1/2 second.
  - (3) Repeat step (2) a total of 10 times...
- ...Release pressure and allow the unit to re-expand over 1 second i.e. (min) suction (min). (Reduced pressure below an atmosphere pressure in the pump will allow air or O...
- ...chamber).
  - (5) Repeat step (1). From now on, this manoeuvre which inflates the patient's **lungs** will also empty the waste chamber of its contents through a conduit, and away from...
- ...6) Repeat steps (2) to (5), and so on.

Thus, a periodic sequence of manual compressions will co-ordinate a (min) ventilation(min), then maintain an inflated chest whilst performing 10 serial (min) cardiac compressions (min), in accordance with the current theory of (min) New(min) CPR, which is now...

...specialized equipment is accessible which has the features of:
Providing a combination of ventilation, cardiac compression, and
suctioning and the additional preferred feature of removal of airways
matter.

The resuscitator according to the...

# ...of:

- 1. Applying the principles of (min)New(min) CPR i.e. simultaneous maintenance of **chest** inflation and external cardiac **compression** (with the added advantage of regular automatic **suctioning**), to enhance cardiac output.
- 2. Providing a correctly positioned oropharyngeal airway that is firmly held...
- ...CLAIMS and that the bottom wall (1,30) is adapted to, in use, rest on the **chest** of a patient to support the pump and pressure applied to the top wall (2,20) is transmitted to the **chest** of the patient via the bottom wall (1,30) after contraction of the side wall...

...said inlets (7,48, 13, 52) and outlets (11, 12, 40, 16, 44) contain check valves (8, 10, 14, 15) to prevent reverse flow therethrough.

24/3,K/33 (Item 33 from file: 349)

DIALOG(R) File 349: PCT FULLTEXT

(c) 2004 WIPO/Univentio. All rts. reserv.

01015782 \*\*Image available\*\*

INEXSUFFLATOR

INEXSUFFLATEUR

Patent Applicant/Assignee:

ALYN WOLDENBERG FAMILY HOSPITAL, PO Box 9117, Kiryat HaYovel, 91090 Jerusalem, IL, IL (Residence), IL (Nationality), (For all designated

states except: US)

Patent Applicant/Inventor:

BEERI Eliezer, 16 Nelson Glick Street, 97233 Jerusalem, IL, IL

(Residence), IL (Nationality), (Designated only for: US)

MALKA Eliyahu Raphael, 7 HaSneh Street, 52372 Ramat Gan, IL, IL (Residence), IL (Nationality), (Designated only for: US)

SHUCHMAN Yisrael, 11/2 Mints Street, 97292 Jerusalem, IL, IL (Residence), IL (Nationality), (Designated only for: US)

Legal Representative:

KLEIN David (agent), Dekel Patent Ltd., Beit HaRof'im, 18 Menuha VeNahala Street, Room 27, 76209 Rehovot, IL,

Patent and Priority Information (Country, Number, Date):

Patent: WO 200345486 A1 20030605 (WO 0345486)

Application: WO 2002IL766 20020915 (PCT/WO IL0200766)

Priority Application: IL 145461 20010916; US 2001975943 20011015; US 2002211544 20020805

Designated States: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO

KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ OM PH PL PT RO RU SD SE SG SI SK SL TJ TM TN TR TT TZ UA UG US UZ VC VN YU ZA ZM ZW

(EP) AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LU MC NL PT SE SK TR

(OA) BF BJ CF CG CI CM GA GN GQ GW ML MR NE SN TD TG

(AP) GH GM KE LS MW MZ SD SL SZ TZ UG ZM ZW

(EA) AM AZ BY KG KZ MD RU TJ TM

Publication Language: English

Filing Language: English

Fulltext Word Count: 5339

Main International Patent Class: A61M-016/20

Fulltext Availability: Detailed Description

Claims

English Abstract

A manual inexsufflator (10) including a standard mechanical ventilator (16), a medical suction unit (14), and a piston-like sliding valve mechanism (18) which connects a patient ventilation interface (12) with either the ventilator or the suction unit (14). By sliding the valve mechanism (18) in and out the user selectively connects the patient to either the ventilator (16), for purposes of insufflation, or the suction unit (14), for purposes of exsufflation. The ventilator (16) may generate expiratory positive airway pressure...

# French Abstract

...un ventilateur mecanique classique (16), une unite d'aspiration medicale (14), et un mecanisme de valve (18) coulissant de type piston connectant une interface de ventilation (12) de patient soit au ventilateur soit a l'unite d'aspiration (14). Par coulissement du mecanisme de valve (18) a l'interieur et a l'exterieur, l'utilisateur connecte selectivement le patient soit...

Detailed Description ... from airways.

BACKGROUND OF THE INVENTION
Patients suffering from weakness of the muscles of the thoracic cage
and
diaphragm, as may occur in, for example, Duchenne Muscular Dystrophy or
Cervical Spine...

...to clear respiratory secretions from their lower respiratory tract, retained secretions may develop in their lungs. As retained secretions constitute a focus for infection, these patients are at high risk ... fatal, pneumonia, and are thus in need of assistance in expectorating their respiratory secretions.

Several techniques for assisting such patients are known. If the degree of muscle weakness is mild, physical therapy techniques such as "manually assisted coughing" may be effective. With this technique, the therapist enhances the efficacy of the patient's natural cough by means of a adequate pulmonary toilet.

For patients who are intubated with. an endotracheal tube, or have a permanent tracheostomy...

...which may be necessary for purposes of mechanical ventilation due to the severity of the **chest** wall muscle weakness), endotracheal **suction** is commonly used as a **technique** for secretion clearance.

Endotracheal suction is achieved by inserting a narrow gauge catheter into the patient's trachea via a larger gauge endotracheal tube or tracheostomy carmula, and then applying suction through the catheter. Secretions that are in proximity to the tip of the catheter are then sucked into the catheter and removed. This technique achieves secretion removal by utilizing a suction force to cause secretions to either adhere to the catheter tip or enter into the catheter, which is then withdrawn from the body while the suction force is maintained. It should be noted that the suction is generated within the suction catheter only, not within the endotracheal tube or tracheostomy cannula, and that it is executed...

...patient's respiratory cycle, be it inspiration or expiration.

There are several drawbacks to endotracheal suction as a means for clearing respiratory secretions. The procedure is invasive, thus requiring sterile technique for its performance, and may cause physical trauma to, or infection within, the patient's airways. Moreover, this technique can only be performed on those patients who are already intubated or tracheostomized, and is...

...patients, and for intubated patients who wish to avoid the above-mentioned drawbacks of endotracheal suction, a desirable mechanical method for removal of tracheobronchial secretions is that of mechanical insufflation-exsufflation (also known as inexsufflation... Fourth Edition, McGraw-Hill, 1979, defines exsufflation as "forcible expiration; forcible expulsion of air from lungs by a mechanical apparatus".

Most commonly, an inexsufflator is applied to a patient's respiratory...a cyclical fashion as follows: First, the inexsufflator mechanically pumps air into the patient's lungs until the lungs have expanded to their

maximum capacity (insufflation). Then, at the moment of peak insufflation, the inexsufflator rapidly sucks air out of the patient's lungs at a high ...an inexsufflator artificially simulates the action of a natural cough.

Thus, in contrast to endotracheal suction, inexsufflation is noninvasive (and thus does not require sterile technique or cause trauma to the airways), and achieves secretion removal by causing rapid airflow (at...have wealmess of their facial and glossopharyngeal muscles in addition to the weakness of their chest wall muscles, and they typically are unable to "hold in" a deep breath for a significant period of time. As such, after an inexsufflator completes the lung0 insufflation cycle, the insufflated air may rapidly dissipate through the patient's mouth and nose...onset of exsufflation is even marginally delayed the volume of air within the patient's lungs which will be available for mechanical exsufflation will be significantly diminished, resulting in an ineffective "cough".

Mechanical inexsufflation is particularly effective when it is augmented by the manual assisted cough **technique** described above. This is usually done by a single caregiver (often a physiotherapist or a member of the patient's family) who operates the inexsufflator while simultaneously applying abdominal/ chest thrusts timed to the exsufflation phase of the machine.

It is physiologically desirable that each...the machine. This mechanism is used to generate airflow alternately in two directions: into the lungs under positive pressure during insufflation, and out of the lungs under negative pressure during exsufflation. In the "automatic" version of this machine, model CA-3000, cycling from insufflation...ventilator for purposes of mechanical ventilation via an invasive or noninvasive ventilation interface, as their chest wall muscle weakness limits not only their ability to cough, but also their ability to...period encourages the collapse of smaller airways and alveoli, which traps secretions deep within the lung.

- 2) Standard inexsufflators are comprised of a built-in mechanism for generating airflow in two directions (both into and out-of the patient's lungs), which is ...3000 in 2002.
- 3) It is difficult for a caregiver performing the manual assisted cough **technique** simultaneously with mechanical inexsufflation to achieve optimal coordination with a manual inexsufflator. This is because...
- ...perform a different maneuver simultaneously: while one hand has to perform an "in-out" abdominal/ chest thrust on the patient, the other hand has to perform a "side-to-side" rotary...yet efficient and effective in artificially reproducing a coughing action to clear respiratory secretions from lungs and airways.

In general terms, the inexsufflator of the current invention may comprise three primary components: 1) a mechanical ventilator, 2) a suction unit, and 3) a sliding, piston-like, valve mechanism, which connects the above two components ... Any type of standard mechanical ventilator, including ventilators of the type used by patients with chest wall weakness for purposes of mechanical ventilation, may be used as part of the inexsufflator piston-valve and suction components of the current invention need be added so as to "convert" their ventilators into...

...also known as expiratory positive airway pressure, during the pause between inexsufflation cycles.

The piston- valve establishes airflow continuity between the patient interface and, depending on the valve 's orientation (i.e., piston "pushed in7' or piston "pulled ouf'), either the ventilator or the suction unit, both of which operate continuously. The operator of the inexsufflator causes the device to cycle between insuffiation and exsufflation by manually pulling the piston of the valve outward (when the ventilator is delivering a breath) and then pushing it inward (at the

...airflow continuity between the patient and either the mechanical ventilator (thus achieving insufflation) or the suction unit (thus ... has terminated, thus preventing alveolar or airway collapse

The "in-out" movement of the piston- valve parallels the arm action of an abdominal/ chest thrust as is done for purposes of assisted coughing. Thus, an operator performing an abdominal...exact coordination of the two actions by the operator, thus enhancing the efficacy of the procedure.

In an embodiment of the invention, an external mechanical ventilator may be used for generating...

...during the pause between insufflation-exsufflation cycles, by means of the mechanical ventilator.

The manual valve mechanism may be operated by an "in-out" or "push-pull" type of hand/arm...to generate an expiratory positive airway pressure and a volume-cycled mechanical ventilator, and a valve connected to the source of positive fluid pressure and the source of negative fluid pressure, the valve being adapted to selectively connect the patient interface unit with the ...negative fluid pressure. Further in accordance with a preferred embodiment of the present invention the valve includes a manual valve.

In accordance with a preferred embodiment of the present invention the manual valve includes a sliding element.

There is also provided in accordance with a preferred embodiment of...

...a source of negative fluid pressure, a source of positive fluid pressure, and a manual valve connected to the source of positive fluid pressure and the source of negative fluid pressure, the valve being adapted to selectively connect the patient interface unit with the source of positive fluid pressure and the source of negative fluid pressure, and the valve including a sliding element.

In accordance with a preferred embodiment of the present invention the...

... noninvasive ventilation interface.

In accordance with a preferred embodiment of the present invention the manual valve is adapted to substantially seal fluid flow from the source of positive fluid pressure to...that includes providing positive fluid pressure from the source of positive fluid pressure via the valve to the patient interface unit, and, within a predetermined period of time, substantially sealing fluid...

...generally simultaneously providing negative fluid pressure from the source of negative fluid pressure via the **valve** to the patient interface unit.

Still further in accordance with a preferred embodiment of the... preferred embodiment of the present invention the source of negative fluid pressure includes a medical **suction** unit.

BRIEF DESCRIPTION OF THE DRAWINGS
The present invention will be understood and appreciated more...negative fluid pressure may be provided, such as but not limited to, a standard medical suction unit, for example, an Accuvac Basic Aspirator (Gottlieb Weinnianti GmbR & Co.

Hamburg, Germany) a vacuum cleaner or any other suitable suction device. A source 16 of positive fluid pressure may be provided, such as but not limited to, a mechanical ventilator or an "AMBU" type manual resuscitator bag, for example. It is ...with any suitable control apparatus, sensors, recording devices and the like (not shown).

A manual valve 18 is preferably connected to the source 14 of negative fluid pressure and to the source 16 of positive fluid pressure. Valve 18 is adapted to selectively connect patient interface unit 12 with sources 14 or 16...

...and positive fluid pressure, respectively.

The following is one example of a construction of manual valve 18, although it is understood that the manual valve 18 is not limited to this construction. In the illustrated embodiment, manual valve 18 comprises a cylindrical housing 20 having a connector element 22 for connection to patient...

...at the interface between housing 20 and connector element 24 for varying the amount of negative pressure, i.e., controlling the amount of suction. Housing 20 may have an opening 27 that fluidly communicates with connector element 24. One...housing 20 (pressure sensor 28 is omitted for clarity in Figs. 2 and 3).

Manual valve 18 may comprise a sliding element 30 that may include a hollow cylindrical piston 32...from the source 14 of negative fluid pressure to patient interface unit 12. Thus, manual valve 18 may operate like a two-way valve.

A working cycle of inexsufflator 10 for providing air to a patient and suddenly causing. In Fig. 2, source 16 of positive fluid pressure supplies positive fluid pressure via manual valve 18 to patient interface unit 12, which pressure is forced into the airways and respiratory system of the patient. The positive pressure may be monitored by observing pressure sensor 28. In...

- ...to discern the onset and peak of insufflation. At or near the moment of maximal lung insufflation, as depicted by an increase in the pressure recorded on pressure sensor 28 or as discerned by observation of the patient's chest wall movement, the user initiates exsufflation as follows: Within a predetermined period of time, preferably...
- ...as to prevent air dissipation prior to the onset of exsufflation, the user moves manual valve 18 to the second orientation shown in Fig. 3. For example, the user may suddenly via manual valve 18 to patient interface unit 12. The sudden application of negative pressure to the lungs that have been insufflated with the positive pressure may generate a rapid airflow out of the lungs of the patient, thereby

achieving exsufflation. During the **process** of exsufflation, the user monitors pressure sensor 28 so as to discern the degree of **negative pressure** being generated within the patient's airways.

After a predetermined period of time, such as but not limited to about I second, or upon attainment of a desired degree of negative pressure within the airways, the manual valve may ...embodiment of the current invention, source 16 of positive fluid pressure is a hand-held "AMBU" type manual resuscitator bag, for example, an MR-100 Adult Resuscitator (Galerned Corp. Taiwan). In terms of this embodiment, the phase of insufflation is initiated by the user manually squeezing the manual resuscitator bag so as to generate positive pressure within the patient's airways, as depicted by pressure...LP-10 Volume Ventilator (Nellcor Puritan Bennet Inc. Pleasanton, CA) or an LTV-1000 Ventilator (Pulmonetic Systems, Colton, CA). A volume-cycled ventilator is a ventilator in which the amount of air...

### Claim

- ... positive airway pressure, a volume-cycled mechanical ventilator and a manual resuscitator; and
  - d) a valve connected to said source of positive fluid pressure and said source of negative fluid pressure, said valve being adapted to selectively connect said patient interface unit with said source of positive fluid...unit comprises a noninvasive ventilation interface.
  - 3 The inexuflator according to claim I wherein said  ${\bf valve}$  comprises a manual  ${\bf valve}$  .
  - 4 The inexuflator according to claim 3 wherein said manual **valve** is adapted to substantially seal fluid flow from said source of positive fluid pressure to fluid pressure via said **valve** to said patient interface unit, and, within a predetermined period of time, substantially seal fluid...
- ...generally simultaneously providing negative fluid pressure from said source of negative fluid pressure via said valve to said patient interface unit.
  - 6 The inexuflator according to claim I and ftirther comprising...
- ...and said negative fluid pressure.
  - 7 The inexuflator according to claim 3 wherein said manual **valve** comprises a sliding ...inexuflator according to claim I wherein said source of negative fluid pressure comprises a medical **suction** unit.
  - 13 An inexsufflator ... of negative fluid pressure;
  - c) a source of positive fluid pressure; and
  - d) a manual **valve** connected to said source of positive fluid pressure and said

source of negative fluid pressure, said manual **valve** being adapted to selectively connect said patient interface unit with 'said source of positive fluid pressure and said source of negative fluid pressure, and said manual **valve** 

comprising a sliding element.

14 The inexsufflator according to claim 13, wherein said patient

interface manual valve is adapted to substantially seal fluid flow from said source of positive fluid pressure to...inexuflator according to claim 13 wherein said source of negative fluid pressure comprises a medical suction unit.

24/3,K/36 (Item 36 from file: 349)
DIALOG(R)File 349:PCT FULLTEXT
(c) 2004 WIPO/Univentio. All rts. reserv.

00882196 \*\*Image available\*\*

FLOW CONTROL VALVE FOR MANUAL RESUSCITATOR DEVICES

VALVE DE REGLAGE DE DEBIT POUR DISPOSITIFS DE REANIMATION MANUELS

Patent Applicant/Assignee:

O-TWO SYSTEMS INTERNATIONAL INC, 7575 Kimbel Street, Mississauga, Ontario L5S 1C8, CA, CA (Residence), CA (Nationality), (For all

designated states except: US

Patent Applicant/Inventor:

BOWDEN Kevin D J, 43 Newton Drive, Orangeville, Ontario L9W 3E3, CA, CA (Residence), GB (Nationality), (Designated only for: US)

Legal Representative:

FIELD Paul (agent), Swabey Ogilvy Renault, Suite 1600, 1981 McGill College Avenue, Montreal, Quebec H3A 2Y3, CA,

Patent and Priority Information (Country, Number, Date):

Patent: WO 200215968 A2-A3 20020228 (WO 0215968)
Application: WO 2001CA1204 20010823 (PCT/WO CA0101204)

Priority Application: US 2000648143 20000825

Designated States: AE AG AL AM AT AU AZ BA BB BG BR BY BZ CA CH CN CO CR CU CZ DE DK DM DZ EC EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MA MD MG MK MN MW MX MZ NO NZ PH PL PT RO RU

SD SE SG SI SK SL TJ TM TR TT TZ UA UG US UZ VN YU ZA ZW

(EP) AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE TR

(OA) BF BJ CF CG CI CM GA GN GQ GW ML MR NE SN TD TG

(AP) GH GM KE LS MW MZ SD SL SZ TZ UG ZW

(EA) AM AZ BY KG KZ MD RU TJ TM

Publication Language: English Filing Language: English Fulltext Word Count: 4300

FLOW CONTROL VALVE FOR MANUAL RESUSCITATOR DEVICES

VALVE DE REGLAGE DE DEBIT POUR DISPOSITIFS DE REANIMATION MANUELS

Patent Applicant/Assignee:

O-TWO SYSTEMS INTERNATIONAL INC...

Main International Patent Class: A61M-016/20

International Patent Class: A61M-016/00

Fulltext Availability:
Detailed Description

Claims

English Abstract

An improved manual resuscitation device such as a bag - valve -mask (BVM) device with flow control valve to eliminate the danger of patient distention and aspiration of stomach contents during ventilation. The...

...patient face sealing edge, flexible manually squeezed bag with a one way intake and output valves in flow communication with a gas source and the mask inlet, and exhaust port for exhausting exhaled gas from the mask when the bag output valve is closed. The flow control valve is interposed between the mask and bag to automatically and variably limit the rate of...

...between a predetermined minimum flow rate and a maximum flow rate. A similar flow control valve can be included in any manual resuscitation device such as a pocket mask or face...

French Abstract

- ...perfectionne, par exemple un dispositif a masque et ballon d'anesthesie (BVM), equipe d'une valve de reglage de debit afin d'eliminer le risque de distension du patient et d...
- ...patient, un sac flexible manuellement comprime pourvu d'un orifice d'aspiration unidirectionnelle et de valves de sortie en communication d'ecoulement avec une source de gaz et l'entree du...
- ...et un orifice d'echappement pour l'evacuation du gaz exhale du masque lorsque la valve de sortie du sac est fermee. La valve de reglage de debit est interposee entre le masque et le sac afin de limiter...
- ...par exemple un masque de poche ou un ecran facial, peut etre equipe d'une valve de reglage de debit de ce type.

Detailed Description
FLOW CONTROL VALVE FOR MANUAL RESUSCITATOR DEVICES
TECHNICAL FIELD
The invention relates to a flow control valve for preventing gastric distention and aspiration of stomach contents due to excessive gas flow

...flow rate of pressurized air from a manually operated resuscitation device, such as a Bag- Valve -Mask device, pocket mask, face shield, or endotracheal tube.

BACKGROUND OF THE ART In the relevant art of pulmonary resuscitation using manually operated resuscitation devices, the Bag- Valve -Mask resuscitator (commonly referred to as a "BW") has been the primary method of ventilating the patient in respiratory arrest for some 40 years. The BVM device is...

...in U.S. Patent Nos. 4,532,923 and 4,622,964 to Flynn.

rates...

Cardio- pulmonaly resuscitation (CPR) can be administered mouth-to-mouth without protection but recently to protect the...

- ...medical personnel, use of various protective manually operated devices is common. For example, one way valves, patient exhalation valves and fabric shields are fitted to pocket masks and face shields in order to inhibit...
- ...BVM consists of a self inflating balloon at one end having a one way intake valve that allows gas to be drawn into the balloon as the balloon recoils after it has been manually squeezed by the user. The intake valve self seals when the inflated bag is squeezed, and opens when the bag is permitted to recoil naturally. On the other end of the balloon, a one way output valve permits the gas to leave the bag when squeezed 1 0 directing the flow of gas to the patient through a facemask, or other airway adjunct.

The output valve opens when the inflated bag is squeezed, and self seals when the bag is permitted to recoil naturally. The output valve when sealed diverts the exhausted gas from the patient out through an expiratory port on the valve housing. As a result of cyclical manual squeezing and recoil of the balloon, gas is...

...October
1986;15:1187-1192; Stone B.J. et al, The Incidence of Regurgitation
During Cardiopulmonary Resuscitation: 4 Comparison Between the Bag
Valve Mask and

Laryngeal Mask Airway Resuscitation 38 (1998) 3-6; Elling, B.A. et...
..Ventilation, Am. J. Emerg. Med. 1988;6:333-336; Manoranian, C.S. et al,
Bag-Valve -Mask Ventilation; Two Rescuers Are Better Than One:
Preliminary Report, Critical Care Medicine, 1985;13:122-123; Lande, S. et
al, Comparing Ventilatory Techniques During CPR, J.E.M.S. May 1982;
Harrison, R.R. et al, Mouth-to-Mouth Ventilaion: A Superior Method
ofRescue Breathing, Ann. Emerg. Med., 11:74776, February 1982].

Additionally, \_the\_requirements\_of\_ventilation\_have...

...care situations that tend to reduce the attention and level of care directed to ventilation **techniques** .

While normal breathing requires muscle action (diaphragm, intercostals and others) to

produce a **negative pressure** (subatmospheric or **vacuum**) within the **chest** to draw air into the **lungs**, artificial ventilation is accomplished by forcing air or oxygen into the **lungs** under an external positive pressure.

The positive pressure required to deliver a set volume (tidal... ... a patient is dependent on two factors: (1) the compliance, stiffness or elasticity of the lung, and (2) the resistance to gas flow within the conducting airways. For example, a llstiff' lung that is damaged by pulmonary fibrosis, disease or trauma requires a higher pressure to deliver a set tidal volume than a normal elastic lung. Similarly, gas will encounter less resistance through a normal airway that is not narrowed by bronchospasm or asthma, kinked by a poor airway opening technique, or plugged with blood, mucous, vomit or other debris.

As a result, manual and automatic ventilation **techniques** must accommodate a range of pressures. With a common tidal volume of gas that is delivered, the patient's **lung** and airway condition will determine the pressure needed to ventilate the patient.

However, there is a safe upper limit to the pressures that can be used to prevent **lung** damage. The danger of pneumothorax or **lung** rupture due to excessive pressures is considered to occur between 75 and 85 cmH20Regarding the...

...200 litres/minute at pressures of 100

4 cmH20 are commonly delivered when fully trained emergency medical personnel use the manual ventilating techniques involving Bag - Valve -Masks and mouth-to-mouth resuscitation, with patient isolating valves on pocket masks and face shields.

The problem in the emergency medical service field is...

...that they are competent in using the manual devices and that the manual devices and methods themselves are efficacious. Many technicians claim that the manual "feel" of the BVM allows them to make clinical judgements on the patient's lung condition. In reality what they are feeling is the backpressure created by the high flow...

...reality during literally life and death situations the operators are constantly

preoccupied. The bag- valve -mask requires almost continuous contact with one hand of the user and thereby imposes extreme...

...722,394 to Loescher shows an example of a BVM including a high pressure exhaust **valve** . U.S. Patent No. 5,537,998 to Bauman provides a spring loaded piston which... ...the invention below.

DISCLOSURE\_OF\_THE\_INVENTION

The invention relates to an improved bag- valve -mask (BVM) device with flow control valve to eliminate the danger of patient distension and aspiration of stomach contents during ...patient face sealing edge, flexible manually squeezed bag with a one way intake and output valves in flow communication with a gas source and the mask inlet, and exhaust port for exhausting exhaled gas from the mask when the bag output valve is closed. The flow control valve is interposed between the mask and bag to automatically and variably limit the rate of...

...with reference to the accompanying drawing wherein.

Figure I is a view of a Bag- Valve -Mask where a patient ventilated by the operator and the gas flow is controlled with a flow control valve located in a modified neck bushing disposed between the bag and the mask, the flow control valve having a frusto-conical valve plug slidably biased to the right and moved to the left to restrict the gas flow through the valve in response to gas flow impinging on the upstream surface of the valve plug.

Figure 2 is a longitudinal section view through the flow control **valve** with sliding **valve** stem, spring loaded frusto-conical piston and frusto-conical inlet chamber serving as a **valve** seat.

7
Figure 3 is a perspective view of a face shield with a flow control valve in accordance with a second embodiment of the invention disposed within the tube extending through...

...sheet.

Figure 4 is a perspective view of a face shield with a flow control valve in accordance with a third embodiment of the invention disposed within the tube extending through...

...DESCRIPTION OF PREFERRED EMBODIMENTS

Figure 1 shows the general arrangement and use of a bag- valve -mask device I also known as a BVM. The invention centres on a simple but valuable modification to the conventional BVM by insertion of a flow control valve 7 between the patient mask 2 and the bag 3. Details of one embodiment of flow control valve 7 are shown in Figure 2.

1 5 A similar flow control valve 7 can be included in any manual resuscitation device such as a pocket mask 23...

...squeezes and releases the flexible bag 3 to pump gas through a one way intake valve 4 from a breathable gas source, through a one way output valve 6 in flow communication with the mask 2. Exhaust ports 5 exhaust

exhaled gas from the mask 2 when the bag output valve 6 is closed.

The flow control valve 7 is disposed in flow communication between the mask 2 and 8 bag 3 for...

- ...the bag 3 is deflated to the same degree for each breath. The flow control **valve** 7 controls the rate or speed (for example in units of ——litres—per—minute)—of....
- ...size hands, varying strength, varying skill etc.
  As shown in Figure 2, the flow control valve 7 includes a housing 8 with control valve inlet 9, control valve outlet 10 and an orifice 12 therebetween. Gas flow sensor surface 14 senses the impingement of gas flowing from with the valve inlet 9 and the resultant sliding of the valve plug I I against the bias of spring 18 serves to automatically restrict gas flow...
- ...the plug I 1. Other means to sense the gas flow besides a spring loaded valve plug 1 1 can be provided but at higher cost than the simple device illustrated such as: a flexible diaphragm; pneumatic pressure sensing valves; rotating flow meter propellers; and electrical gas flow sensors.

As shown in Figure 2 a...

...inexpensive means to automatically variably restrict the orifice 12 can be constructed using a conical **valve** seat 12 and movable conical **valve** plug 1 1 with a gas flow impingement surface 14 and a **valve** seat mating surface 22. The plug 1 1 is normally biased away from the **valve** seat 12 by the spring 18 and is urged toward the **valve** seat 12 by gas flow against the flow impingement surface 14.

To mount the plug 1 l within the housing 8 a bulkhead 14 is included downstream of the valve seat 12. The bulkhead 14 includes perforations 16 that can be sized to ensure that at all times a minimum gas flow is permitted to pass through the valve 7 when the plug 1 l is moved to it's farthest point. The spring and motion limiter 21 serve to prevent complete closure of the gas flow control valve and always permit a 9 minimum gas flow to pass through.

The plug 1 1 is mounted to an upstream end of a **valve** stem 13 and the **valve** stem 13 is slidably mounted within a through bore 17 in the bulkhead 14 with the spring 18 disposed about the **valve** stem 13 between the plug 14 and bulkhead 14. The **valve** stem 13 preferably includes a retainer 19 downstream of the bulkhead 14 for preventing removal...

...surface 20, as does the motion limiter 21. Both surfaces 20 are disposed on the valve stem 13 a selected distance from the bulkhead 14 for limiting the range that the stem 13 can slide within the bore 17. The valve stem 13 and bulkhead bore 17 preferably have a clearance space disposed therebetween sufficient to allow lateral motion of the valve plug I 1 relative to the valve seat 12. Such clearance not only ensures that the stem 13 will not unintentionally bind...

...also allows the plug I 1 to be self-centring and prevent binding of the valve seat 12 and plug surface 22.

 $1\ 5$  With regard to the second embodiment shown in Figure 2, the same flow

control valve 7 is adapted to use with a face shield 24. The face shield 24 has...

...contamination. Since conventional face shields include a tube 26 usually with a one-way intake valve (not shown) and patient exhalation valve (not shown), the invention may be easily adopted for use with a face shield 24 by including the flow control valve 7 housed within the tube 26.

With regard to the third embodiment shown in Figure 3, the same flow control valve 7 is adapted to use with a pocket mask 23. The pocket mask 24 has...

- ...loss. Since conventional pocket masks include a tube 31 usually with a one-way intake valve (not shown) and patient exhalation valve 33, the invention may be easily adopted for use with a pocket mask 23 by including the flow control valve 7 housed within the tube 3 1. Further embodiments not illustrated include positioning the flow control valve 7 within a manually ventilated endotracheal tube that is inserted directly into the patient's...
- ...operator mouthpiece on the protruding end into which the operator breathes or attaches a bag- valve -mask device to ventilate the 1 0 patient. The use of any manually operated ventilation device can be improved by controlling the gas flow rate with a flow control valve as described herein.

Although the above description and accompanying drawings relate to a specific preferred...

# Claim

- ... from the gas inlet to the patient airway, the interface having a one way intake valve downstream of the gas inlet; and flow control means disposed in flow communication between the...
- ...claim 1 wherein the patient interface is selected from the group consisting of. a bag- valve -mask device; a pocket mask device wherein the patient interface comprises a patient mask with...
- $\dots$  patient mouthpiece. 3 . A manually operated resuscitation device according to claim 2 wherein said
  - bag- valve -mask device comprises:
  - a patient mask having a gas inlet and a patient face sealing edge;
  - a flexible bag having a one way intake **valve** in flow communication with a gas source and a one way output **valve** in flow communication with the mask inlet;
  - exhaust port means in flow communication with the patient mask for exhausting exhaled gas from the mask when the bag output valve is closed; and
  - said flow control means disposed in flow communication between the mask
- ...device according to claim 1 wherein the .12

flow control means comprise:

- a flow control  ${\bf valve}$  housing with control  ${\bf valve}$  inlet, control  ${\bf valve}$  outlet and
- an orifice therebetween;
- a gas flow sensor in flow communication with the **valve** inlet; and orifice restriction means controlled by the gas flow sensor for automatically restricting gas...

- ...gas 1 0 flow sensor is selected from the group consisting of- a spring loaded valve plug; a flexible diaphragm; pneumatic pressure sensing valves; rotating flow meter propellers; and electrical gas flow sensors.
  - 6 A manually operated resuscitation device according to claim 4 wherein the orifice restriction means comprise a **valve** seat and movable **valve** plug.
  - 7 A manually operated resuscitation device according to claim 6 wherein the plug includes a gas flow impingement surface and a valve seat mating surface, the plug being biased away from the valve seat and urged toward the valve seat by gas flow against the flow impingement surface.
  - 8 A bag- valve -mask device according to claim 6 wherein the housing includes a bulkhead downstream of the valve seat, the bulkhead including at least one perforation; and wherein the plug is mounted to an upstream end of a valve stem, the valve stem is slidably mounted within a through bore in the bulkhead with a spring disposed about the valve stem between the plug and bulkhead.
  - 9 A bag- valve -mask device according to claim 8 wherein the valve stem includes a retainer means downstream of the bulkhead for preventing removal of the stem from the bore.
  - . A bag- valve -mask device according to claim 9 wherein the retainer means comprise a shoulder with bulkhead abutting surface.
  - 11 A bag-  ${\tt valve}$  -mask device according to claim 8 wherein the  ${\tt valve}$  stein
  - includes a motion limiting means disposed on the **valve** stem a selected distance from the bulkhead for limiting the range that the stem can slide within the bore.
  - 12 A bag-  ${\bf valve}$  -mask device according to claim 1 1 wherein the motion limiting means comprise a shoulder with bulkhead abutting surface. I 0
  - 13 A bag- valve -mask device according to claim 7 wherein the valve seat and valve seat mating surface are conical surfaces.
  - 14 A bag- valve -mask device according to claim 8 wherein valve stem'and
  - 1 5 bulkhead bore have a clearance space disposed therebetween sufficient to allow lateral motion of the **valve**0 plug relative to the **valve** seat.

24/3,K/40 (Item 40 from file: 349) DIALOG(R)File 349:PCT FULLTEXT

(c) 2004 WIPO/Univentio. All rts. reserv.

00556688 \*\*Image available\*\*

CARDIOPULMONARY RESUSCITATION VENTILATOR AND METHODS VENTILATEUR ET PROCEDES DE REANIMATION CARDIO- PULMONAIRE

Patent Applicant/Assignee:

CPRX LLC,

Inventor(s):

LURIE Keith G,

ZIELINSKI Todd M,

Patent and Priority Information (Country, Number, Date):

Patent: WO 200020061 A1 20000413 (WO 0020061)

Application: WO 99US23233 19991005 (PCT/WO US9923233)

Priority Application: US 98168049 19981007

Designated States: AE AL AM AT AU AZ BA BB BG BR BY CA CH CN CR CU CZ DE DK DM EE ES FI GB GD GE GH GM HR HU ID IL IN IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT TZ UA UG UZ VN YU ZA ZW GH GM KE LS MW SD SL SZ TZ UG ZW AM AZ BY KG KZ MD RU TJ TM AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE BF BJ CF CG CI CM GA GN GW ML MR NE SN TD TG

Publication Language: English Fulltext Word Count: 11470

CARDIOPULMONARY RESUSCITATION VENTILATOR AND METHODS VENTILATEUR ET PROCEDES DE REANIMATION CARDIO- PULMONAIRE

Main International Patent Class: A61M-016/00

Fulltext Availability: Detailed Description Claims

English Abstract

The invention provides systems, and methods for ventilating a patient in association with cardiopulmonary resuscitation procedures. In one exemplary embodiment, a system (10) comprises a ventilator (12) to periodically supply respiratory gases to a patient's lungs. A sensor (14) is provided to detect chest compressions by sensing changes in intrathoracid pressure. A controller (38) is coupled to the sensor, and controls actuation of the ventilator after a predetermined number of chest compressions have been detected by the sensor.

## French Abstract

...et des procedes de ventilation d'un patient associes a des interventions de reanimation cardio- pulmonaire. Dans une forme de realisation exemplaire, un systeme (10) comprend un ventilateur (12) qui approvisionne periodiquement les poumons du patient en gaz d'inhalation. Un capteur (14) detecte les compressions thoraciques par les variations de la pression intrathoracique. Un controleur (38) est couple au capteur et commande le declenchement du ventilateur apres qu'un nombre preetabli de compressions thoraciques ait ete detecte par le capteur.

Detailed Description

CARDIOPULMONARY RESUSCITATION VENTILATOR AND

METHODS

BACKGROUND OF THE INVENTION

1. Field of the Invention

The:present invention relates generally to the field of cardiopulmonary resuscitation. In particular, the invention relates to devices and methods for ventilating a

patient in association with cardiopulmonary resuscitation procedures . WO 00/20061 PCTIUS99/23233

periodic ventilation of the patient. This is commonly accomplished by mouth-to-mouth **technique** or by using positive pressure devices, such as a self-inflating bag which relies on...

...s endotracheal tube or other artificial airway.

In order to increase cardiopulmonary circulation
induced by chest compression, a technique referred to as
active compression - decompression @(ACD) has been developed.

According to ACD techniques, the active compression phase of traditional CPR is enhanced by pressing an applicator body against the patient's chest to compress the chest. Such an applicator body is able to distribute and apply force substantially evenly over a portion of the patient's chest.

More importantly, however, the applicator body is sealed is against the patient's **chest** so that it may be lifted to actively expand the patient's **chest** during the **decompression** step. The resultant negative **intrathoracic** pressure induces venous blood to flow into the heart and **lungs** from the peripheral venous vasculature of the patient.

other techniques for increasing cardiopulmonary circulation while performing CPR include impeding airflow into the patient's lungs during decompression of the patient's chest. Such techniques are described in U.S. Patent Nos. S,551,420 and S,692,498, and...

...references are herein incorporated by reference. In one particular embodiment, airflow into the patient's chest is impeded by placing a pressure-responsive valve in the patient's airway. The valve prevents the flow of air into the patient's lungs during the decompression phase until a threshold negative intrathoracic pressure is reached. At this point, the valve opens to allow airflow to the patient's lungs. Hence, when the valve is closed, the amount of negative intrathoracic pressure is increased, thereby 3S enhancing the amount of venous blood flow to the heart and lungs.

When performing CPR, there is a need to periodically ventilate the patient. Some common techniques include mouth to-mouth ventilation, ventilatory bags, and ventilation machines. However, as of yet there has been no effective and convenient way to coordinate the timing of ventilation with the chest compressions. For example, if mouth-to-mouth resuscitation is provided, the rescuer must count each chest compression, stop chest compressions when a predetermined number of chest compressions have been performed, manually ventilate the patient with the rescuer's mouth, and then return to performing chest compressions. Similar problems are experienced when using ventilatory bags. Moreover, with many manual ventilation techniques, it is difficult, if not impossible, to precisely control the timing and volume of air delivered to the patient.

Hence, it would be desirable to provide methods and is devices for ventilating a patient in association-with cardiopulmonary resuscitation procedures. It would be particularly desirable to provide a way to easily and conveniently coordinate the timing of chest compressions with ventilation. It would be further desirable to precisely control the volume of respiratory gases...

...Patent 10os. 5,551,420 and 5,692,498, previously incorporated by reference describe. techniques for preventing airflow to the patient's lungs during the decompression phase of CPR.

ACD-CPR techniques are described in detail in Todd J. Cohen et al-., Active Compression - Decompression Resuscitation: A Novel Method of Cardiopulmonary Resuscitation, American Heart Journal, Vol. 124, No. 5, pp.

1145-1150, November 1992; and Todd J. Cohen et al., Active Compression - Decompression: A New Method of Cardiopulmonary Resuscitation, The Journal of the American Medical Association, Vol. 267, No. 21, June 3, 1992. These references are hereby incorporated by reference.

The use of a vacuum -type cup for actively compressing and decompressing a patient's chest during ACD- CPR is described in a brochure of AMBU International A/S, Copenhagen, Denmark, entitled'Directions for Use of AMBUO CardioPump', published in September...

... These references are hereby incorporated by reference.

SUMMARY OF THE INVENTION The invention provides exemplary systems and methods for ventilating a patient in association with cardiopulmonary resuscitation procedures . In-one exemplary embodiment, a ventilation system comprises a ventilator to periodically supply respiratory gases to a patient's lungs and a sensor-to compressions . A controller is coupled to the is detect chest sensor and controls actuation of the ventilator after a compressions have been detected predetermined number of chest by the sensor. Hence, such a system provides a convenient and easy way to coordinate ventilation with chest compressions by simply sensing when the patient's chest has been compressed and periodically ventilating the patient after a predetermined number of chest compressions have been detected. Preferably, the controller is configured to actuate the ventilator to supply respiratory gases to the patient once about every 2 to about 10 chest compressions, with adults typically-receiving about one ventilation for about every 5 chest compressions.

The invention includes various ways to detect when the patient's <code>chest</code> has been <code>compressed</code>. For example, in one particularly preferable aspect, the <code>system</code> includes a <code>valve</code> which is placed in the patient's air way. The sensor is disposed so as to be able to detect the flow of respiratory gases through the <code>valve</code> upon <code>compression</code> of the <code>chest</code>. In this manner, an easy way is :provided to detect <code>chest</code> <code>compressions</code> simply by sensing the flow of respiratory gases

through the <code>valve</code> . In one particular aspect, the sensor comprises a strain gauge that is strained as respiratory gases flow through the <code>valve</code>, and a resistance sensing circuit to sense a change in resistance of the strain gauge when strained. Such a sensor is particularly advantageous when the <code>valve</code> includes a diaphragm, such as the diaphragms provided in the threshold negative <code>intrathoracic</code> pressure <code>valves</code> described in U.S. Patent Nos. 5,551,420 and 5,692,498, previously incorporated...

...the diaphragm moves due to gases exiting the patient, the strain gauge is strained.

other techniques for detecting chest compressions include sensing intrathoracic pressure changes in the patient's airway, sensing when an external force has been applied to the patient's chest, such as with a load cell or strain gauge positioned on the patient's chest, by sensing an impedance change in the chest wall, and the like. Sensors that may be employed to detect such parameters include pressure...

...spirometers, thermistors, pneumotachometers, capacitative sensors, and the like.

During at least a portion of the **decompression** phase, respiratory gases are preferably prevented from entering into the patient's lungs. An occlusion mechanism is preferably employed to occlude the patient's airway during the desired portion of the **decompression** phase. The occlusion mechanism may be adjustable so that it will open at a pre-set pressure level. In this way, when a threshold negative intrathoracic pressure level is reached or exceeded during **decompression**, the occlusion mechanism is actuated to allow respiratory gases to enter into the patient's **lungs**.

Actuation of the occlusion mechanism may be directly caused by the negative intrathoracic pressure within the patient, such as with a threshold valve as described in U.S. Patent Nos. 5,551,420 and 5,692,498, may...

...s airway, or may be actuated by the controller at delayed time intervals after a **chest compression** has been sensed. In the event that a sensor detects that spontaneous breathing has occurred...

...the occlusion
mechanism so that respiratory gases are free to flow to the
patient's lungs . other exemplary occlusion mechanisms that
may be employed by the invention include airways that are
closed using a rotary cam wheel, using a linear actuator with
a compression member or a pair of caliper arms, and the like.

In one particular aspect, chest compressions are performed manually. Alternatively, chest compressions may be performed using an automated compression mechanism, such as the one described in U.S. Patent No. 4,397,306, the...

... of which is herein incorporated by reference.

In another particular aspect, the ventilator comprises a compressible member, such as a bag, and a compression mechanism to compress the member. Alternatively,, a cylinder with a piston may be employed. In this way, the...

...gases supplied to the patient may be
is precisely controlled by controlling the amount of compression
of the member or the size of the cylinder and the stroke of
the piston...

...timing

circuit that may be employed to regularly actuate the ventilator during times when regular chest compressions are not being performed. In this way, the patient may be ventilated once CPR is stopped. In still another aspect, the system further includes a power supply to supply power to the controller and the ventilator. In this way, the system may be configured to be portable so as to facilitate its use in emergency procedures.

In yet another aspect, the **system** includes at least one feedback sensor that is coupled to the controller. The feedback sensor...

...the sensor may comprise an oxygen sensor, a carbon dioxide sensor, a temperature sensor, a chest compression force sensor, a depth of chest compression sensor, a chest compression pressure sensor, a pH sensor, and the like. Optionally, actuation or timing of the ventilator...

...on the state of the various physiological parameters.

In still yet another exemplary aspect, the system includes a control panel having a mode control to change the operational mode of the ventilator. As one example, the mode control may include a compression detect mode where the ventilator is actuated after a predetermined number of chest compressions have been detected by the sensor. The mode control may also include a manual ventilation...

...as previously.

described so that the patient may be ventilated at regularly timed intervals when **chest compressions** are not being performed.

The control panel may also include a threshold compression control which is used to vary the sensitivity level of the sensor. The control panel...

..of

respiratory gases supplied to the patient. Optionally, the control panel may further include a compression counter.

display which displays the number of detected chest compressions. A compression detector display may also be p@rovided-to display when each chest compression has been detected. Still further, the control panel may include a ventilation indicator to indicate...

... The control panel may also indicate the amount of pressure or force applied to the **chest**. This may be accomplished by displaying a number or a waveform demonstrating changes in **compression**, force, or pressure over time.

In another exemplary embodiment, the invention provides a method for performing cardio- pulmonary resuscitation. According to the method, a patient's chest is repeatedly compressed. Each chest compression is detected using a sensor which is coupled to a controller. The patient is periodically ventilated after a predetermined number of chest compressions have been detected. In this way, the timing of patient ventilation may be coordinated with the number of chest compressions by sensing changes in intrathoracic pressure that are caused by chest compression.

Detection of **chest compressions** may be performed in a variety of ways. For example, **chest compressions** may be , detected by sensing changes in **intrathoracic** pressure, by sensing air flowing through the patient's airway, by sensing when an external force is applied to the patient's **chest**, by sensing impedance changes in the **chest** wall, and the like. In one particular aspect, the change in **intrathoracic** pressure is sensed by placing a **valve** in the patient's airway and sensing when respiratory gases flow through the **valve**.

In one particular aspect, respiratory gases are prevented from flowing to the <code>lungs</code> with the <code>valve</code> until a threshold negative <code>intrathoracic</code> pressure is exceeded, at which time the <code>valve</code> opens to allow the respiratory gases to flow to the <code>lungs</code>. In another alternative, respiratory gases are prevented from flowing to the <code>lungs</code> using other occlusion mechanisms which operate based on signals received from the controller. In this...

...the occlusion mechanisms when it is desired to allow respiratory gases to flow to the lungs.

In another aspect, a **compressible** bag is mechanically **compressed** to ventilate the patient. The bag may be automatically **compressed** after a predetermined number of **chest compressions** have been detected, or may be manually actuated by the rescuer. In one aspect, **compression** of the patient's **chest** is stopped after cardiac function has been restored, and the patient is ventilated at regular intervals.

In still yet another aspect, at least one physiologic parameter is sensed while performing chest compressions. Such parameters may include, for example, oxygen, carbon dioxide, temperature, pH, and the like. The... one or

more of these parameters. Conveniently, a visual signal may be produced when each **chest compression** has been detected. In another option, the number of **chest compressions** may be counted and displayed for viewing by the rescuer. Also, an indicator may be...

...ventilated.

In yet another embodiment, the invention provides an exemplary ventilation device which comprises a **compressible** bag and a mechanical **compression** mechanism which may be operated to **compress** the bag. A coupling member is attached to the bag to couple the bag to a patient-.,I.s airway.

In one particular aspect, the mechanical compression mechanism comprises a plunger having a rack, a stepping motor, and a pinion coupled to a motor to move the rack.

Alternatively, the **compression** mechanism may comprise a plunger and a **compressed** air cylinder to move the plunger. Preferably, a threshold **valve** is disposed in the coupling member and is configured to open when experiencing a threshold negative **intrathoracic** pressure.

BRIEF DESCRIPTION OF THE DRAWINGS
Fig.'l is a schematic view of an exemplary
ventilator which is coupled to a **valve** having a sensor to
detect **chest compressions** by sensing changes in **intrathoracic**pressure according to the invention.

Fig. 2 illustrates an exploded view of the  $\mbox{valve}$  of Fig. 1.

Fig. 2A illustrates a diaphragm of the valve of Fig.

2 without expiratory pressure being applied.

Fig. 2B illustrates the diaphragm of Fig...

...1 showing a rack and pinion that is employed to move a plunger against a **compressible** bag to deliver inspiratory gases through the **valve** according to the invention.

Fig. 3A illustrates the ventilator of Fig. 1 having an air cylinder and plunger to compress the compressible bag according to the invention.

Fig. 4A is a side view of the ventilator of Fig. 1 illustrating a circuit board and motor or air cylinder access compartment and a **compressible** bag detach compartment.

Fig. 4B is a front view of the ventilator of Fig. 1...

...the ventilator of Fig. 1.
10, Fig. 7 is a schematic diagram of an alternative
 system for detecting chest compressions according to the
invention.

Fig. 8A illustrates a rotary cam wheel airway occlusion mechanism according...

...to close an airway lumen.

DETAILED DESCRIPTION OF THE SPECIFIC EMBODIMENTS

The invention provides exemplary systems and methods
for ventilating a patient in association with cardiopulmonary

resuscitation procedures . In a broad sense, the invention provides for the coordination of patient ventilation with chest compressions . Such coordination is preferably accomplished by sensing each time the chest is compressed and counting the number of compressions . After a predetermined number of compressions have been performed, a ventilator is actuated to ventilate the patient. Preferably, chest compressions are sensed by detecting a change in intrathoracic pressure while performing CPR. Each time the patient's chest is compressed, the intrathoracic pressure in the patient significantly increases. Such an increase may be detected and related to a chest compression .

In one particularly preferable aspect, the change in intrathoracic pressure is sensed by detecting the flow of respiratory gases from the patient's lungs during chest compressions. one particularly preferable way to detect when respiratory gases exit the patient's lungs is by placing a valve in the patient's airway and detecting the flow of respiratory gases through the valve. As one example, the valve may comprise a threshold valve having a diaphragm which opens when respiratory gases exit the patient's lungs as described generally in U.S. Patent Nos. 5,551,420 and 5,692,498...

...a strain gauge, pressure sensor, optical sensor, or the like, may be disposed in the valve to detect when the diaphragm opens. Information from the sensor is then employed to count the number of chest compressions . Another sensor that may be employed to detect a change in intrathoracic pressure is a pressure sensor that is disposed in the patient's airway. other sensors that may be employed to detect when the chest has been compressed include sensors which directly detect when an external force is applied to the chest . For example, a compression pad which is placed on the patient's chest may include a sensor, such as a strain gauge or a load cell, which generates a signal each time the pad is compressed . These signals are sent to the controller to actuate the ventilator. As another example, the compression pad may be filled with fluid'. A pressure transducer may then be employed to detect when the pad has been compressed . As another alternative, a change in impedance of the chest wall may be sensed to indicate that the chest has been compressed .

The ventilators of the invention are preferably configured to supply a precise amount of respiratory gases to the patient's lungs during each delivery. In one particularly preferable embodiment, the proper volume of respiratory gases are produced by compressing a compressible bag by a known amount. For example, a plunger may be moved against the compressible bag by a known distance to produce a precise amount of respiratory gases.

In another...

...determined by a controlled preset rate. This mechanism is advantageous to accommodate changes in patient lung compliance and decrease the overall work of ventilation during CPR.

In another particularly preferable embodiment...

- ...be transported to any given location where medical assistance is needed. In some cases, the **compressible** bag may be configured to be removed from the ventilator so that manual ventilation may...
- ...it is
  desirable to have the ventilator actuated once about every 2
  to about 10 chest compressions to properly ventilate the
  patient. Once cardiac function has been restored, the
  ventilator may be...
- ...coupled to various other sensors to monitor various physiologic parameters of the patient during the **procedure** .

For example, such sensors may include oxygen sensors, carbon dioxide sensors, temperature sensors, chest compression force sensors, depth of chest compression sensors, chest compression pressure sensors, pH sensors and the like.

Referring now to Fig. 1, an exemplary embodiment of a ventilation system 10 will be described. System 10 includes a ventilator 12 which is coupled to a pressure responsive valve system 14 by a tube 16. Although not shown, it will be appreciated that valve system 14 will be attached to ...by the invention include facial masks, endotracheal tubes, laryngeal mask airways, and the like.

Exemplary valve systems that may be employed include those described in U.S. Patent Nos. 5,541,420 and 5,692,498, previously incorporated by reference. However, it will be appreciated that other valves may be employed with ventilator 12. As described in greater detail hereinafter, valve system 14 includes a sensor to detect changes in intrathoracic pressure, and more particularly to detect when respiratory gases exit the patient's lungs. This information is transferred to ventilator 12 which counts the number of chest compressions and automatically supplies respiratory gases to the patient after a predetermined number of chest compressions have been counted.

Referring now to Fig. 2, construction of pressure responsive valve system 14 will be described in greater detail. Valve system 14 comprises a housing 18 having an inlet end 20 and an outlet end 22. A flow control valve 24 is disposed in housing 18 to control the flow of air or respiratory gases...

- ...gases through housing 18 is as follows. When respiratory gases are forced from patient's lungs, the respiratory gases are free to flow through outlet end 22, through housing 18 and...
- ...diaphragm 28 is lifted to allow the respiratory gases to flow through outlet end 22.

Valve system 14 further includes a pressure responsive valve (not shown) within a side intake 32. To

increase the magnitude and extent of negative intrathoracic pressure within the patient during the decompression phase of CPR, the pressure responsive valve within side intake 32 is configured to open only after a threshold negative intrathoracic pressure level is exceeded. In this way, respiratory gases are prevented from flowing through housing 18 by diaphragm 28 during the decompression phase. Hence, the only way for respiratory gases to enter into the patient's lungs (if ventilations are not provided) is through the pressure responsive valve inside intake 32 similar to the embodiments described in U.S. Patent No. 5,692...

...previously incorporated by reference.

In the event that the patient begins spontaneous breathing, flow control valve 24 may be turned 90 degrees clockwise to align arrow 26 with a second side...

- ...such a change in resistance may be detected and used as an indicator that the intrathoracic pressure within the patient's chest has changed. In turn, such information may be used as an indicator that a chest compression has occurred. The construction of such strain gauges is well known within the art, and...
- ...34 in combination with a Wheatstone-bridge is particularly advantageous in that the sensitivity of system 10 may be precisely controlled to accommodate patients having a variety of thoracic morphologies. Although the sensor that is employed to detect airflow through housing 18 is a...
  ...42 is provided to facilitate transport of ventilator 12.

Disposed in housing 36 is a **compressible** bag 44 which is coupled at one end to a pair of input ports 46 and 48, which are employed to supply various respiratory gases to **compressible** bag 44. Merely by way of example, input port 46 may be coupled to an...

- ...input port 48 is coupled to an oxygen source. Coupled to the other end of compressible bag 44 is an output port So through which inspiratory gases are supplied to the...
- ...50 is coupled to tube 16. Ventilator includes a plunger 52 which is employed to compress bag 44.

Plunger 52 is moved up and down by stepping-motor 54 which is...pinion 56 in a clockwise direction to move plunger 52 downward until bag 44 is compressed. After compression, stepping motor 54 is reversed causing source pinion 56 to rotate in a counterclockwise direction...
...lifting plunger 52.. Hence, by coupling plunger 52 to stepping motor 54, the amount of compression of bag 44 may be precisely controlled. In this way, a precise volume of respiratory...

...and an outlet port 70. Ports 68 and 70 are in turn coupled to a **compressed** air tank 72. When inlet port 68 is opened and outlet port 70 is closed, **compressed** air from tank 72 moves

plunger 52 downward to compress bag 44. To lift plunger 52, inl et port 68 is closed and outlet port...

- ...that is delivered to the patient. A variety of other mechanisms may be employed to **compress** bag 44 including caliper arms, cams, and the like. Further, it will be appreciated that...
- ...12 will operate from power supplied by the NiCd battery.

One important feature of ventilation system 10 is that the rechargeable battery may be recharged when not in use simply by...

...the "off" position.

This allows the rechargeable battery to be charged and fully functional for remote emergency operations.

Housing 36 is preferably constructed of a durable non-metallic material that is...

...preferable waterproof and noncorrosive to enable to withstand various regional climates. In this way, ventilation **system** 10 will be useful in a wide variety of locations where emergency operations may be performed.

As best shown in Fig. 4A, ventilator 12 includes a compressible bag compartment 80 and a circuit board and motor drive compartment 82. Doors 84 and...

- ...to allow access into compa rtments 80 and 82, respectively. As shown in Fig. 4A, compressible bag 44 is detachable from ports 46, 48 and 50 (see Fig. 1). In this way, bag 44 may be removed from ventilator 12 and used manually in connection with valve system 14. Such an arrangement may be useful during situations where ventilation system 10 is used remotely and the rechargeable battery has been depleted. In such a case, bag 44 is simply removed from compartment 80 and attached to valve system 14 which in turn is coupled to the patient's air way. Bag 44 is...
- ...position. When in the "on" position, electrical power is supplied to the various components of system 10. Control panel 38 further includes a mode control 88 which may be moved between three positions to place ventilation system 10 in a manual mode, a compression detection mode or an automatic mode. When in the manual mode, a user may manually...
- ... supplied to the patient through inspiratory gas port 50 (see Fig. 4A).

When in the compression detect mode, ventilation system 10 is configured to automatically detect and count the number of chest compressions. Ventilator 12 then automatically ventilates the patient through inspiratory gas port 50 at a preselected compression to ventilation ratio. This ratio may be adjusted by moving a compression /ventilation control 92. By way of example, compression /ventilation

control 92 may be ...has been restored but the patient still requires ventilation.

Control panel 38 further includes a **compression** threshold control 96 which may be adjusted to adjust the sensitivity of the strain gauge...

- ...previously described. In this way, the sensitivity may be adjUsted to accommodate various levels of intrathoracic expiratory pressures during CPR chest compressions. The threshold is adjusted by operating compression threshold control 96 which allows for maximum sensitivity without signal saturation to accurately detect changes in intrathoracic pressure. Compression threshold is control 96 is a 20-turn, 10,000 Ohm potentiometer that controls the...
- ...patient. Air volume control 98 may be manually adjusted to accommodate a diverse range of lung capacities. As previously described, the precise amount of air or gases are delivered to the patient by use of plunger 52 in combination with compressible bag 44. In one alternatively, control 98 may also be employed to control the pressure...
- ...the respiratory gases inspired to the patient.

other features of control panel 38 include a compression counter display 100 which allows the rescuer to view the cumulative number of compressions. Compression counter display 100 may be configured to count the total number of chest compressions or the number of chest compressions between each ventilation. A compression detect display 102 is provided to allow the viewer to visualize the compression threshold sensitivity. Display 102 reflects the signal level from the transducer amplifying circuit, and preferably comprises a bar-graph LED display that grossly represents the force of compression, i.e., the greater the applied force, the more LEDs that are illuminated.

When power...

...For example, if

mode control 88 is set to the compre ssion detection mode, and compression /ventilation control 92 is set to 5:1 (1 breath for every 5 compressions), ventilator ready display 104 will illuminate at the fourth chest compression. After the fifth compression has been detected, ventilator ready display 104 will be turned off. A ventilation display 106...

...when actuated.

Referring now to Fig. 6, a schematic of the circuitry employed within ventilation system 10 will be described. The circuitry includes a compression sensing module 108 which is coupled to the strain gauge that in turn is disposed in pressure responsive valve system 14. As previously described, compression sensing module 108 preferably includes a Wheatstone-bridge to detect changes in

the resistivity of the strain gauge during chest compressions .

The compression sensing module 108 is coupled t-o a compression counter/display module 110. Module 110 counts the number of compressions sensed by module 108 and optionally displays them on compression counter display 100 on display panel 38 (see Fig. 5).

The circuitry further includes a...

...air\_volume\_control\_98\_and\_which\_is\_\_\_\_\_
employed to actuate the mechanical components employed to
 compress bag 44 (see Fig. 3). These components are
 illustrated schematically as block 114 in Fig...

...of a capacitor timing circuit. This circuit in essence controls the duration that plunger 52 compresses bag 44. Since the speed of plunger 52 is internally set at a constant level...

...88 of control panel 38 (see Fig. 5). When mode control 88 is in the **compression** detect mode, module 112 will send a signal to actuate ventilation after a predetermined number of **compressions** have been counted by module 110.

Ventilation control module 112 is further coupled.to compression /ventilation control 92 so that ventilation control module 112 will know the number of compressions that must be is performed before a signal is sent to actuate ventilation.

Also coupled characteristics of **chest compression** may be monitored. For

example, ventilation system 10 may measure the force at which chest compressions are being performed, the pressure being applied to the chest, and the depth of chest compression.

Optionally, such information may be displayed on control panel 38 (see Fig. 5). This display...

...display and produce audible signals at regular intervals to assist the rescuer in performing regular **chest compressions**.

The circuitry further includes a signal control module 122 which is used to control logic...

...display various physiologic characteristics of-the patient, including the pressure in the patient's airway.

compression sensing module 108 is coupled to compression detect display 102 to visually display the strength of the signal being detected by module 108.

Compression sensing module 108 includes compression threshold control 96 as previously described. By adjusting control 96, the sensitivity of the compression detect display 102 may be modified. For example, display 102 may illuminate one LED bar when no compressions are being performed and 5 to 10 LED bars which a chest compression is applied.

As one example, prior to the initiation of CPR, and

with the ventilation system connected to the patient, the rescuer adjusts compression threshold control 96 to illuminate only one LED bar on compression detect display 102. This essentially sets the compression sensing circuitry in module 108 to represent zero force applied to the chest. Once compressions begin, the rescuer may monitor display 102 to "grossly" verify that an appropriate amount of force has been applied during chest compressions by observing that 5 to 10 LED bars on compression detect display 102 are illuminated. Referring back now to Fig. 1, operation of ventilation system 10 to assist in performing a CPR procedure will be described. Initially, ventilation system 10 is coupled to a patient via a coupling device, such as a facial mask...

### ...is turned

is to the on position and mode control 88 is placed in the compression detect mode. Compression /ventilation control 92 is adjusted to the desired compression /ventilation ratio. The patient then begins performing CPR as is known in the art.

When performing chest compressions, compression detect display 102 will light and grossly display the force of compression each time a compression is detected. Further, compression counter display 100 will display the number of chest compressions. When the preset number of chest compressions have been detected, ventilator 102 supplies a volume of respiratory gases to the patient through valve system 14 and counter display 100 is reset to zero. The volume of respiratory gases supplied...

...90. In

another option, bag 44 may be removed from ventilator 12 and coupled to valve system 14 so that ventilations may be manually provided to the patient by having the rescuer manually squeeze bag 44.

If the patient begins spontaneous breathing, flow control valve 24 (see Fig. 2) may be adjusted so that air may freely flow through valve system 14 to the patient's lungs.

During times when CPR is not being performed and it is still desired to ventilate...

...and volume determined by control 98.

Since ventilator 112 has its own rechargeable battery, ventilation system 10 may be used remotely to facilitate its use in medical emergencies. Further, by providing a way to sense when chest compressions are being performed, ventilation may be easily coordinated with chest compressions without requiring the rescuer to concentrate on counting the number of compressions to ensure that regular ventilations are being supplied to the patient.

Fig..7 illustrates an alternative ventilation **system** 120 which includes a ventilator 122 which is similar to ventilator 12 as previously described...

...to a patient by an airway 124. Also coupled to a

...via

airway 124 in a manner similar to that described in the previous embodiment.

Alternatively, compression pad 126 may be configured to be inflated with a fluid, such as air. With this arrangement, a pressure transducer is employed to detect pressure increases within the air filled compression pad so that chest compressions may be directly sensed. In one embodiment, cable 128 is replaced with a flexible, hollow...

...to a pressure transducer that is housed within ventilator 122. In this way, when the compression pad is compressed, the transducer within ventilator 122 detects the increase in pressure. In turn, signals genera ted...

...conducted to

the ventilator control circuitry. Alternatively, the pressure transducer may be held within the **compression** pad (or another **compression** device), to detect an increase in pressure within the pad during **chest compressions**. A signal of the pressure transducer is then preferably transmitted via a two conductor coaxial...

...previously described, it is preferred to prevent respiratory gases from flowing to the patient's lungs during at least a portion of the decompression phase of CPR.

Alternative occlusion mechanisms for preventing air from entering into the patient's airway during the **decompression** phase are illustrated in Figs. 8A-11B. Such occlusion mechanisms may be coupled to the...

...configured to open and close based on information provided by the various sensors when sensing chest compressions. For example, the occlusion mechanisms may be configured to be closed until a specified time period after a chest compression has been detected to insure that sufficient time has passed during the decompression phase. At this point, the occlusion mechanisms are configured to open to allow respiratory gases to flow to the patient's lungs.

Various sensing mechanisms may also be provided to detect when the patient begins spontaneous breathing...

...mechanisms will be opened to allow the free flow of air into the patient's lungs . Further, the ventilators may be configured to open the various occlusion

mechanisms after a predetermined negative intrathoracic pressure level has been met or exceeded. In this way, the opening pressures of the...

- ...9B illustrate a linear actuator occlusion mechanism 142. occlusion mechanism 142 comprises a pair of compression members 144 and 146 that are disposed on opposite sides of an airway lumen 148...
- ...a linear actuator\_152.\_As\_illustrated\_in\_Fig.\_9B,\_when\_linear\_actuator 152 is actuated, compression member 144 is forced against airway lumen 148 to close airway lumen 148.

Figs. 10A...

... Figs'. 11A and 11B illustrate a caliper occlusion mechanism 158. Caliper occlusion mechanism 158 includes compression members 160 and 162 that are disposed between airway lumen 164. A pair of caliper... ...linear actuator 172 is operated, caliper arms 166

and 168 are brought together to force compression members 160

and 162 against airway lumen 164.

Figs. 12A and 12B illustrate a mesh...

### Claim

- 1 A system for ventilating a patient in association with a cardiopulmonary resuscitation procedure , the **system** comprising: a ventilator to periodically supply respiratory gases to a patient's lungs; a sensor to detect chest compressions ; and a controller coupled to the sensor, the controller controlling actuation of the ventilator after a predetermined number of chest compressions have been detected by the sensor.
- 2 A system as in claim 1, wherein the controller is configured to actuate the ventilator to supply respiratory gases to the patient once about every 2 to about 10 chest compressions .
- 3 A system as in claim 1, wherein the sensor is configured to sense changes in intrathoracic pressure to detect chest compressions .
- 4 A system as in claim 1, further comprising a valve that is adapted to be placed in the patient's airway, and wherein the sensor is disposed to detect the flow of respiratory gases through the valve upon compression of the chest .
- 5 A system as in claim 4, wherein the sensor comprises a strain gauge which is strained as respiratory gases flow through the valve and deflect a diaphragm, and a resistance sensing circuit to sense a change in resistance of the strain gauge when strained.
- 6 A system as in claim 4, wherein the sensor is configured to detect an increase in pressure in the patient's

airway with each chest compression .

- 7 A system as in claim 4, wherein the valve includes a region to prevent respiratory gases from flowing to the lungs until a threshold negative intrathoracic pressure is exceeded at which time the valve opens'to allow the flow of respiratory gases to the lungs.
- 8 A system as in claim 1, further comprising a chest compression member coupled to the controller, and wherein—the—sensor—is—disposed—to—sense—when—a—compressive—force is applied to the chest compression member.
- 9 A system as in claim 8, wherein the chest compression member comprises a chest pad.
- 10 A system as in claim 1, wherein the sensor :2 comprises an impedance sensor to sense a change in impedance in the chest wall of the patient upon compression of the chest .
- 11 A system as in claim 1, wherein the ventilator comprises a compressible member and a compression mechanism to compress the compressible member.
- 12 A system as in claim 1, further comprising an occlusion mechanism to prevent respiratory gases from entering the patient's lungs during at least a portion of a decompression phase of the cardiopulmonary resuscitation procedure.
- 13 A **system** as in claim 12, wherein the occlusion mechanism comprises an airway and a threshold **valve** disposed in the airway.
- 14 A system as in claim 12, wherein the occlusion mechanism comprises an airway and a rotary cam wheel to compress the airway.
- 15 A system as in claim 12, wherein the occlusion mechanism comprises an airway, and a linear actuator and a compression member to compress the airway.
- 16 A **system** as in claim 12, wherein the occlusion mechanism comprises an airway, and a pair of caliper arms to **compress** the airway.
- 17 A system as in claim 12, wherein the occlusion mechanism has adjustable operating pressure levels to vary a threshold negative intrathoracic pressure level that must be exceeded before the occlusion mechanism will allow respiratory gases to flow to the patient's lungs.

  18 A system as in claim 17, wherein the occlusion mechanism is coupled to the controller which is configured to operate the occlusion mechanism.
- 19 A **system** as in claim 1, further comprising a **compression** mechanism coupled to the controller to **compress** the **chest**.

- 20 A **system** as in claim 1, further comprising a power supply to supply power to the controller and the ventilator.
- 21 A **system** as in claim 1, further comprising at least one feedback sensor coupled to the controller.
- 22 A system as in claim 21, wherein the feedback sensor is selected from the group of sensors consisting of oxygen sensors, carbon dioxide sensors, temperature sensors,—chest—compression—force—sensors,—depth-of—chest—compression—sensors, chest compression pressure sensors and pH sensors.
- 23 A **system** as in claim 1, further comprising a control panel having a mode control to change the operational mode of the ventilator.
- 24 A system as in claim 23, wherein the mode control includes a compression detect mode where the ventilator is actuated after the predetermined number of chest compressions have been detected by the sensor.
- 25 A **system** as in claim 23, wherein the mode control includes a manual ventilation mode, and wherein...
- ...actuate the ventilator when the mode control is in the manual ventilation mode.
  - 26 A **system** as in claim 23, wherein the mode control includes an automatic ventilation mode, and wherein...
- ...timed intervals when the mode control is in the .5 automatic ventilation mode.
  - 27 A **system** as in claim 23, wherein the control panel further includes a threshold **compression** control to vary the sensitivity level of the sensor.
  - 28 A **system** as in claim 23, wherein the control panel further includes a respiratory gas volume control...
- $\dots$  control the volume of respiratory gases supplied by the ventilator upon each actuation.
  - 29 A **system** as@in claim 23, wherein the control panel further includes a respiratory gas control to...
- ...the pressure of the respiratory gases delivered with each actuation of the ventilator.
  - 30 A system as in claim 23, wherein the control panel further includes a compression counter display to display the number of detected chest compressions, and a compression detect display to display the detection of a chest compression.
  - 31 A **system** as in claim 23, wherein the control panel includes a **compression** display to display **compression** pressures or forces supplied to the **chest**.

- 32 A **system** as in claim 23, wherein the control panel further includes a ventilation indicator to indicate when the ventilator is actuated.
- 33 A method for performing cardiopulmonary resuscitation, the method comprising: repeatedly compressing a patient's chest; detecting each chest compression with a sensor that is coupled to a controller; and periodically ventilating the patient after a predetermined-number of chest compressions—have-been-detected.
- 34 A method as in claim 33, further comprising ventilating the patient once about every 2 to about 10 chest compressions.
- 35 A method as in claim 33, further comprising placing a valve in the patient's airway, and wherein the sensing step comprises sensing when respiratory gases flow through the valve upon compression of the chest.

  36 A method as in claim 35, further comprising preventing respiratory gases from flowing to the lungs with, 3 the valve until a threshold negative intrathoracic pressure is exceeded at which time the valve opens to allow the flow of respiratory gases to the lungs.
- 37 A method as in claim 33, further comprising sensing changes in intrathoracic pressure to detect chest compressions .
- 38 A method as in claim 33, further comprising sensing when a force has been applied to the patient's chest to detect chest compressions.
- 39 A method as in claim 33, further comprising preventing respiratory gases from entering into the patient's lungs during at least a portion of a decompression phase.
- 40 A method as in claim 39, further comprising varying an intrathoracic pressure level at which respiratory gases are allowed to enter into the patient's lungs during the decompression phase.
- 41 A method as in claim 33, further comprising manually compressing the patient's chest or providing chest compressions with a compression mechanism coupled to the controller.
- 42 A method as in claim 33, further comprising mechanically compressing an air bag to ventilate the patient.
- 43 A method as in claim 42, wherein the air bag is automatically compressed after the predetermined number of chest compressions have been detected.
- 44 A method as in claim 42, wherein compression of the air bag is manually actuated.
- 45 A method as in claim 33, further comprising stopping compression of the patient's chest and ventilating

the patient at regular intervals.

- 46 A method as in claim 33, further comprising sensing at least one physiologic parameter while performing chest compressions.
- 47 A method as in claim 44, wherein the physiologic parameter is selected from the group -consisting of oxygen, carbon dioxide, temperature and pH.
- 48 A method as in claim 46, further comprising visually displaying when each chest compression has been detected.
- 49 A method as in claim 46, further comprising counting the number of chest compression and displaying the number of counted compressions.
- 50 A **method** as in claim 33, further comprising visually displaying an indicator each time the patient is ventilated.
- 51 A method as in claim 33, further comprising controlling the volume of respiratory gases supplied to the...
- ...maintaining the supplied gases at the sensed pressure for a specified time period. 52 A method as in claim 33, further comprising sensing when the patient takes a spontaneous breath and initiating an inspiratory ventilation cycle to assist the patient's breathing.
  - I 53. A method as in claim 52, further comprising sensing when the patient begins regular spontaneous breathing and ceasing the inspiratory ventilation cycle.
  - 54 A method as in claim 53, further comprising sensing if the patient stops spontaneous breathing and periodically ventilating the patient after the predetermined number of chest compressions have been detected.
  - 55 A ventilation device comprising:
  - a compressible member;
  - a mechanical compression mechanism which is operable to compress the compressible member;
  - a coupling member attached to the **compressible** member to couple the **compressible** member to a patient's airway; and
  - a sensor to detect chest compressions .
  - 56 A device as in claim 55, wherein the mechanical compression mechanism comprises a plunger having a rack, a stepping motor., and a pinion coupled to...
- ...to move the rack.
  - 57 A device as in claim 55, wherein the mechanical
  - compression mechanism comprises a plunger and a compressed air cylinder to.move the plunger.
  - 58 A device as in claim 55, further comprising a threshold valve disposed in the coupling member, the threshold

```
valve being configured to open when experiencing a threshold
 negative intrathoracic pressure.
 1
 1
 1
 z s
 Hill I
 S@ I
 I_(J_
 I...
...00 a cl
 0 0 0 0
 No -7 (o
 -60
 b4
 ΑO
  Compression Compression Mode
 Threshold /Ventilation Comp. DeL
 Ventilator Compres!
 Manual Auto Ready Counte
 Air Volume A to 2- Manual
 Ventilation
 (ml) Rate Ventilation
 OFF 10
  Compression
 CoLinter/Display
 Module
 ompression Di%
 Sensing Timing Module Ventilation
 Module Control Module
 Force, Pressure,
 & Depth...IPQ or to both national classification and IPC
 B. FIELDS SEARCHED
 Minimum documentation searched (classification system followed by
 classification symbols) U.S.: 128/204.189 204.23t 204.249 204.289...
```

24/3,K/42 (Item 42 from file: 349)

DIALOG(R) File 349: PCT FULLTEXT

(c) 2004 WIPO/Univentio. All rts. reserv.

00487662 \*\*Image available\*\*
PULMONARY PRESSURE MODULATOR

MODULATEUR DE PRESSION PULMONAIRE

Patent Applicant/Assignee:

PIPER Samuel David,

Inventor(s):

\_PIPER\_Samuel\_David,

Patent and Priority Information (Country, Number, Date):

Patent:

WO 9919014 A1 19990422

Application:

WO 98US20181 19980924 (PCT/WO US9820181)

Priority Application: US 97949894 19971014

Designated States: AL AM AT AU AZ BA BB BG BR BY CA CH CN CU CZ DE DK EE ES FI GB GE GH GM HR HU ID IL IS JP KE KG KP KR KZ LC LK LR LS LT LU LV MD MG MK MN MW MX NO NZ PL PT RO RU SD SE SG SI SK SL TJ TM TR TT UA UG UZ VN YU ZW GH GM KE LS MW SD SZ UG ZW AM AZ BY KG KZ MD RU TJ TM AT BE CH CY DE DK ES FI FR GB GR IE IT LU MC NL PT SE BF BJ CF CG CI CM GA GN GW ML MR NE SN TD TG

Publication Language: English Fulltext Word Count: 8314

## PULMONARY PRESSURE MODULATOR

MODULATEUR DE PRESSION PULMONAIRE

Main International Patent Class: A61M-016/20

Fulltext Availability: Detailed Description Claims

### English Abstract

A dual area pressure pulmonary modulator apparatus which provides constant flow, pressure cycled ventilatory support to patients. The pressure pulmonary modulator apparatus opens at a selected pressure and shuts at a substantially lower pressure. The pressure pulmonary modulator apparatus can be incorporated into an automatic resuscitator suited for providing ventilatory support during...

...combined with a nebulizer to serve as a positive pressure aerosol therapy device. The pressure pulmonary modulator apparatus can also be incorporated into a percussive therapy device used for the mobilization of mucus in patients. The pressure pulmonary modulator apparatus may be made almost entirely of injection molded plastic and is inexpensive, portable...

## French Abstract

L'invention concerne un appareil modulateur de pression **pulmonaire** zone duelle qui fournit une assistance ventilatoire a debit constant et a cycles de pression aux patients. Le modulateur de pression **pulmonaire** s'ouvre a une pression selectionnee et se ferme a une pression sensiblement plus faible. Le modulateur de pression **pulmonaire** peut etre incorpore a un reanimateur automatique servant a apporter une aide ventilatoire pendant la...

...servir de dispositif de traitement fournissant un aerosol a pression positive. Le modulateur de pression pulmonaire peut etre egalement incorpore a un dispositif de traitement a percussion servant a mobiliser le mucus des patients. Le modulateur de pression pulmonaire qui peut etre realise presque entierement en plastique moule par injection, est

peu couteux, portable...

Detailed Description

PULMONARY PRESSURE MODULATOR

BACKGROUND OF THE INVENTION

Field of the Invention

This invention pertains generally to respiratory ventilation devices, and more particularly to a constant flow **pulmonary** modulator which can be adapted to a number of applications including (1) a respiratory device...

...provided\_by\_clinicians\_through\_the\_use\_of\_a\_manual\_resuscitator\_or\_an\_ automatic ventilatory device.

Manual resuscitators are typically equipped with a self-inflating bag, a set of check valves which control the direction of inhalation and exhalation gases, and a patient interface which is...

...the selfinflating bag thus applying pressure and causing gas to flow into the patient's lungs. Inhalation ends and exhalation begins when the operator stops squeezing the bag, allowing the pressurized gas in the patient's lungs to escape to the ambient environment. Most manual resuscitators are equipped with the means to maintain a small minimum positive pressure on the patient's lungs throughout exhalation commonly called Positive End Expiratory Pressure (PEEP). During exhalation, the self-inflating bag reinflates and the process may be repeated.

Manual resuscitators are simple and inexpensive. Unfortunately, manual resuscitators are easy to misuse. A large number of...

- ...volumes or constant flow for pre-set amounts of time, regardless of the patient's lung compliance. Lung compliance is prone to sudden changes during transport, potentially causing patient airway pressures to increase...the volume delivered; thus volumes of gas delivered to the patient vary with variances in lung compliances, preventing the patient from receiving a harmful amount of pressure and insuring appropriate ventilation...
- ...in prior technology.

BRIEF SUMMARY OF THE INVENTION

The present invention generally comprises a pressure **pulmonary** modulator

apparatus which will inflate and discharge any pneumatic capacitance for a wide range of...

- ...when provided with a constant flow of gas. In a first embodiment, the patient's **lungs** serve as the pneumatic capacitance, which is cyclically inflated and discharged (inhalation followed by exhalation...
- $\ldots$  of use and associated cost of a manual resuscitator.

In a second embodiment, the pressure **pulmonary** modulator is in fluid communication with an attached pneumatic capacitance which may be caused to...

...the patient which is in constant fluid communication with the primary cavity of the pressure pulmonary modulator. The pulmonary capacitance may be

configured to oscillate at frequencies up to approximately 25 Hz during the...

- ...a nebulizer, providing therapeutic relief, in addition to the delivered ventilatory support. In either embodiment, compressed air or oxygen is delivered directly to the pneumatic capacitor, thus charging the pneumatic capacitor. During discharge, all gas flows through the pressure pulmonary modulator. The invention cycles the pneumatic capacitor by controlling at what pressure charging ends and...
- ...exhausted into the atmosphere. When the pneumatic capacitor pressure drops to a specified level, the **valve** of the pressure **pulmonary** modulator closes, and the pneumatic capacitor begins to be charged by the continuous flow of gas; thus the cycle is repeated indefinitely.

In the first embodiment, the pressure **pulmonary** modulator apparatus essentially comprises a dual area piston having a surface area that rests against...

- ...piston is in the open position. When the dual area piston is closed, it prevents compressed gas from escaping and causing the pneumatic capacitor to become charged by the incoming compressed gas. During charging, the pressure in the pneumatic capacitor increases until the force of the...
- ...the piston. During discharge, the exhaled gases pass by the piston and out of the system through an adjustable flow restrictor used to control the rate at which discharged gases are...may spontaneously breathe by triggering inhalation prior to the beginning of exhalation. A one-way valve may optionally be provided to increase the ease of the patient's inhalation. Under such...
- ...effects of aerosol in addition to ventilatory support.

In the second embodiment where the pressure <code>pulmonary</code> modulator apparatus is in fluid communication with a mechanical pneumatic capacitance, the pressure <code>pulmonary</code> modulator apparatus can be coupled with a nebulizer to deliver both a medication aerosol and high frequency bursts of <code>compressed</code> gas.

In such a configuration, when a patient inhales through a mouthpiece, he or she...

- ...oscillations are frequently called an intrapulmonary treatment, and has been shown to help mobilize patient lung secretions and fluids. It is worth noting that the second embodiment of the invention could...
- ...volume of the pneumatic capacitor and placing a fixed or variable restrictor between the pressure **pulmonary** modulator apparatus and the pneumatic capacitor, the second embodiment of the invention could be used
- ...ventilator apparatus which can be equipped, or have a built-in high pressure pop-off valve as a safety feature to prevent the unintended build up of patient airway pressure due to malfunction or misuse. Such a high pressure pop-off valve may be equipped with the means to produce an audible tone which will notify an...causes pressure dial 18 to move longitudinally relative to piston face 26, thereby increasing the

compressive force on spring 30 as pressure dial 18 is moved closer to piston face 26. Pressure dial 18 therefore allows adjustment of the compressive force of spring 30 against piston 12. Piston face 26 moves longitudinally within a cylindrical...this purpose, examples of which may include, but are not limited to the following: a compressed air spring; a sealed diaphragm; a balloon; an expandable chamber; a rigid chamber with compressed air and bellows.

Flow restrictor port 16 is located within housing 22 and is in...


..rate\_dial\_20\_allows control of a patient's exhalation\_duration. An\_annular flow restrictor valve seat 52 is located within flow restrictor port 16. Flow restrictor valve seat 52 functions in conjunction with tapered inner end 55 of rate dial\_20\_to...

...its largest setting and poses little restriction to flow.

The restricting area between flow restrictor valve seat 52 and the tapered inner end 55 of rate dial 20 is adjustable by...

- ...rate dial 20 causes tapered inner end 55 to move longitudinally relative to flow restrictor valve seat 52. Flow restrictor valve seat 52 and tapered inner end 55 at the inner end of rate dial 20 functions similar to a needle valve to create a restrictive annular region to restrict the flow of gas therethrough. Slots 54...
- ...the adjustment range of rate dial 20. Use of tapered inner end 55 and annular valve seat 52 provides for a sensitive adjustment of gas flow resistance. Although the preferred embodiment...
- ...inner end 55 of rate dial 20 with slots 54 therein along with flow restrictor valve seat 52 to restrict gas flow therethrough, those skilled in the art would recognize that...
- ...until the force of the patient's airway pressure on piston face 26 overcomes the **compressive** force of spring 30, which causes piston 12 to open (when piston face 26 moves away from interior end 28 of primary port 14). Once piston 12 begins to open, **compressed** gas from the pneumatic capacitor enters chamber 42 and rushes toward flow restrictor port 16...
- ...the passage of gas through flow restrictor port 16 is restricted by annular flow restrictor **valve** seat 52 and tapered inner end 55 of rate dial 20. This gas restriction causes...
- ...by the pneumatic capacitor. Although such a feature duration. In the preferred embodiment, patient demand valve 72 has a very low resistance to flow, which is on the order of approximately...
- ...mask 86 or an endotracheal tube (not shown) which the patient wears during the breathing **process** associated with resuscitator 78. Because the piston 12 is closed during inhalation, all incoming gas...
- ...masks (not shown) and a 15 mm ID for connection to endotracheal tubes.

Pop-off valve 70 provides a safety feature to prevent the patient airway pressure from exceeding any set value. Pop-off valve 70 is biased by spring 88 and equipped with a sealing O-ring 90. Pop-off valve 70 opens



anytime the patient's airway pressure exceeds a preset value. Pop-off valve 70 has a stem 92 which travels within an axial tube 94 within end cap 96. Pop-off valve 70 can also be equipped with a means to create an audible tone and a visual signal when the valve 70 is opened.

When inhalation pressure reaches that which is dialed on pressure dial 18  $\dots$ 

- ...piston face 26 and the surface area circumscribed by Oring 62. Pressure dial 18 and pulmonary modulator spring 30 are designed so that the resuscitator delivers a maximum pneumatic capacitor peak...
- ...20 cm H2O, although this is not the physical limit of the apparatus.

Referring also to FIG. 5 and FIG 6A, pulmonary modulator apparatus 10 can be adapted to function as a positive pressure aerosol device 98, wherein a nebulizerassemblyl00isaftachedtoprimaryportl4of pulmonarymodulator apparatus 1 0. Such a device functions identically as previously described with a nebulizer assembly...

- ...102 having a mouthpiece 104, an air entrainment port 106, a one-way air demand valve assembly 108, a reservoir 1 1 0 with a primary orifice 1 1 2 located...
- ...baffle 114 with a secondary orifice 116. In this configuration, there is no pop-off valve and the patient breathes through mouthpiece 104.

Top cover 102 includes a nebulizer chamber 118 located beneath, one-way demand valve 108 built into the upper portion of the top cover 102, and an elbow receptacle...

- ...which allows nebulizer assembly 1 00 to be attached to primary port 14 of the **pulmonary** modulator apparatus 10 via an elbow connector 122. Oneway demand **valve** assembly 108 permits air to be entrained into positive pressure aerosol device 98 as may...
- ...use by the patient but does not allow any gas pressure to escape externally. Demand **valve** assembly 108 includes a cylindrical **valve** body 124 inserted into an air entrainment port 106 located adjacent the upper portion of...
- ...A flapper 126 is inserted into air entrainment port 106 between top cover 102 and valve body 124. Demand valve assembly ...allows for connection of nippled oxygen tubing which is commonly used in hospitals to supply compressed gas. Those skilled in the art will appreciate that many different nebulizers and pneumatic arrangements...

## ...configuration.

Percussive therapy device 130 delivers both a medication aerosol and high frequency bursts of **compressed** gas. When a patient inhales through mouthpiece 104, the patient entrains air through air entrainment...

...cm H20. The delivery of aerosol and the high frequency airway oscillations help mobilize patient lung secretions and fluids.

PTD 130 functions by receiving **compressed** gas, typically above approximately 15 psig, through **compressed** gas inlet 136. **Compressed** gas inlet 136 is built into pneumatic capacitor top 138 and supplies **compressed** gas through a channel 142 within pneumatic capacitor top 138 to pneumatic capacitor assembly 132...should be noted that any number of different springs can be used to accomplish different **pulmonary** effects.—When—pressure—modulator—piston—12—is—closed,—pneumatic—capacitor—choke 140 is delivering gas...during the time the mucus is being mobilized, the average speed of gas in the **lungs** is directed out and not into the **lung**. In the event that cycling during other phases of the respiratory cycle were beneficial, PTD...

- ...pneumatic capacitor. Although such a device would be significantly bulkier, and force required for the **valve** to overcome the pneumatic capacitor's pressure during exhalation, thus sealing interior end 160 of ...
- ...of sealed diaphragm 168, whereby rotating the dial 166 in one direction causes it to **compress** diaphragm 168 and rotating it in another direction causes it to **decompress** diaphragm 168.

  Thus, dial 166 allows adjustment of sealed diaphragm's 168 internal pressure.

## Although...

...interior end 160 of primary port 162 having a tapered seat 178 which mates with valve 164 to seal the interior end 160 of primary port 162, any similar means of sealing interior end 160 of inlet port 162 will suffice. Valve 164 is circumscribed by a groove 180 within which an O-ring 182 is fitted...

## Claim

- ... port
  - (c) a gas inlet port in fluid communication with said adapter body whereby a compressed gas source can be attached to said adapter body; and
  - (d) a patient connection port...
- ...8 An apparatus as recited in claim 7, further comprising:
   (a) a one-way flapper valve, said flapper valve in fluid
   communication
   with said adapter body, said flapper valve capable of permitting
   airflow into said
   adapter body; and
   (b) means to automatically release gas...capacitor, said pneumatic
  - (b) means to automatically release gas...capacitor, said pneumatic capacitor in fluid communication with said primary port.
  - 12 A positive pressure pulmonary apparatus, comprising:
  - (a) a chamber, said chamber including a sleeve;
  - (b) a primary port, said...
- ...inlet port, said gas inlet port in fluid communication with said adapter body whereby a **compressed** gas source can be attached to said patient adapter; and
  - (d) a patient connection port...

- ...16 An apparatus as recited in claim 15, further comprising:
  - (a) a one-way flapper valve , said flapper valve in fluid communication

with said adapter body, said flapper valve capable of permitting airflow into said adapter body; and

(b) means to automatically release gas...said secondary orifice in fluid communication

with said nebulizer chamber; and

- (d) a one-way valve, said valve located within said air entrainment port,—said—valve—capable of entraining air into-said—nebulizer—chamber.
- 26 A positive pressure pulmonary apparatus, comprising:
- (a) valve means for sealing off flow communication with a patient airway, said valve means including a surface area capable of fluidly communicating with said patient airway, said valve means capable of being opened and closed, whereby said surface area is capable of fluidly communication with said patient's airway when said valve means is closed is less than said surface area capable of fluidly communicating with said patient airway when said valve means is open; (b) a flow restrictor, said flow restrictor in fluid communication with said patient airway when said valve means is open and not in flow communication with said patient airway when said valve means is closed;
- (c) a restoring force acting on said **valve** mean, said restoring force biasing said **valve** means to close in the absence of a force sufficient to maintain

said valve means open;

- (d) wherein said **valve** means closes and inhalation begins at one pressure, thereby causing said patient to become inflated and an airway pressure to increase and causing said **valve** means to open and exhalation to begin at a second pressure; and
- (e) wherein exhaled...
- ...delivery of gas to said apparatus.
  - 30 A constant flow, percussive therapy device, comprising:
  - (a) valve means for sealing off flow communication with a pneumatic capacitor, said valve means including a surface area, said valve means capable of

being opened and closed;

(b) wherein said pneumatic capacitor providing a pressure acting to . open said valve mean, said pneumatic capacitor in fluid communication with said valve surface area, wherein said valve surface area in fluid communication with said pneumatic capacitor is less when said valve means is closed than when said

valve means is open;

(c) a restoring force acting on said valve means, said restoring force acting in opposition to said opening pressure in a manner as to cause said valve

means to close in the absence of said opening pressure;

(d) a chamber, said chamber...

- ...a flow restrictor, said flow restrictor in fluid communication with said pneumatic capacitor when said **valve** is open and not in fluid communication with
  - said pneumatic capacitor when said valve is closed; and
  - (g) a patient breathing port, said port in fluid communication with said flow restrictor, said port in fluid communication with said chamber when said valve means is open.

- 31 An apparatus as recited in claim 30, further comprising an aerosol...
  ...breathing port.
  - 32 An apparatus as recited in claim 31, further comprising an air entrainment valve, said valve in fluid communication with said patient breathing port, said valve including means to allow gas to enter said device when a third pressure within said device is less than atmospheric pressure, said valve including means to prevent gas from escaping from said device when a fourth pressure within...

```
Set
         Items
                 Description
         1082
S1
                 AU=(LURIE K? OR LURIE, K? OR MENK V? OR MENK, V? OR ZIELIN-
              SKI T? OR ZIELINSKI, T? OR BIONDI J? OR BIONDI, J?)
S2
                 CPR OR (CARDIOPULMON? OR CARDIO() PULMON?) (W) (RESUSCIT? OR -
              RESPIRAT? OR VENTILAT? OR CIRCULAT?) OR MANUAL?()RESUSC? OR E-
              MERGENCY() MEDICAL?
S3
                 PEEP OR PEP OR POSITIVE() (ASSIST? OR PRESSUR?) (2N) (BREATH?
              OR VENTILAT? OR RESPIRAT?) OR POSITIVE()END()EXPIR?()PRESSURE
              OR (MEDICAL OR EMT OR FIRE) (2N) RESCUE?
S4
       195395
                 VACUUM? OR SUCTION? OR NEGATIVE() PRESSURE? OR EXTRACT?(3N) -
              (POSITIVE OR RESPIRAT? OR EXPIRAT? OR EXHAL?)
S5
                 BAG OR BAGS OR SACK? ? OR SMARTBAG? OR SMART() BAG OR AMBUB-
              AG? OR AMBU OR POUCH?? OR BELLOW?
S6
       732041
                MANIPULAT? OR DECOMPRESS? OR COMPRESS?
S7
      2648650
                 THORAX? OR THORAC? OR CHEST??? OR LUNG? ? OR PULMON? OR IN-
              TRATHORA?
S8
        16732
                 VENOUS (2N) (RETURN OR CIRCULAT?) OR (BLOODFLOW? OR BLOOD()F-
              LOW? OR BLOOD()CIRCULAT?)(2N)(RETURN? OR BACK)(2N)(HEART? OR -
              CARDIAC?) OR LOWER?()PRESSUR?(2N)(RIGHT()ATRIUM) OR LOWER?()P-
              RESSUR?(2N)(THORAX? OR THORAC?)()VENA()CAVA
S9
       290908
                 VALVE??? OR VALVING
                 HYPOTENS? OR HYPOTENT? OR LOW()BLOOD()PRESSURE OR HEAD()(T-
S10
       663328
             RAUMA? OR INJUR?) OR CARDIAC()ARREST OR HEART()ATTACK OR MYOC-
             ARD?()INFARCT? OR (HEMORRHAG? OR HAEMORRHAG?)()SHOCK? OR BLOO-
             D()LOSS??
S11
      2583850
                 WIRELESS? OR WIRE()LESS? OR REMOTE? OR RADIO? OR TRANSPOND?
              OR TELECOMMUNICAT?
                                                                    NONPAT
LIT
BIBLIOG-
MEDICAL
FILES
SUSERD
STOPHIC
S12
     10634152
                METHOD? ?
S13
     16686002
                SYSTEM? ?
S14
      5347076
                TECHNIQUE? ?
S15
      1913553
                PROCEDURE? ?
S16
      3490557
                PROCESS??
S17
          330
                S2:S3(10N)S5
S18
            0
                S17 AND S8
S19
           10
                S17 AND S11
S20
          116
                S17 AND S9
S21
           3
                S20 AND S4
S22
           79
                S20 AND S7
S23
           68
                S22 AND S12:S16
S24
           14
                S22 AND S10
S25
           91
                S19 OR S21:S24
           51
S26
                RD (unique items)
? show files
File 155:MEDLINE(R) 1966-2004/May W2
         (c) format only 2004 The Dialog Corp.
File
       5:Biosis Previews(R) 1969-2004/May W2
         (c) 2004 BIOSIS
      73:EMBASE 1974-2004/May W2
File
         (c) 2004 Elsevier Science B.V.
File
      71:ELSEVIER BIOBASE 1994-2004/May W1
         (c) 2004 Elsevier Science B.V.
File 144: Pascal 1973-2004/May W2
         (c) 2004 INIST/CNRS
```

File

94:JICST-EPlus 1985-2004/Apr W3

(c) 2002 The Gale Group

(c) 2004 Japan Science and Tech Corp(JST)

File 583: Gale Group Globalbase (TM) 1986-2002/Dec 13

26/3,K/44 (Item 8 from file: 73)

DIALOG(R) File 73: EMBASE

(c) 2004 Elsevier Science B.V. All rts. reserv.

06135671 EMBASE No: 1995168763

Flow-dependent properties of positive expiratory pressure devices

Christensen E.F.; Jensen R.H.; Schonemann N.K.; Petersen K.D.

Dept. of Anesthesiology, Arrhus Kommunehospital, University Hospital of Arrhus, Arrhus Denmark

Monaldi Archives for Chest Disease (MONALDI ARCH. CHEST DIS.) (Italy)

1995, -50/2 - (150 - 153) -

CODEN: MACDE ISSN: 1122-0643 DOCUMENT TYPE: Journal; Article

LANGUAGE: ENGLISH SUMMARY LANGUAGE: ENGLISH

Valves for positive expiratory pressure (PEP) can be characterized as threshold resistors, ideally providing pressure independent...

...resistor type compared to threshold resistor devices. Pressures were measured on three different flow resistor valves: the PEP-mask, the Pari-PEP- System and the System 22-PEP with orifice diameters of 1.5-5.0 mm; and on three threshold resistors, the underwater seal, the Ambu Positive End - Expiratory Pressure ( PEEP ) valve and the Vital Signs PEEP valve with pressures of 0, 5, 10, 15 and 20 cmHinf 20. All devices were studied...

...120 and 150 l-minsup -sup 1. The PEP-mask, the Pari-PEP and the System 22-PEP showed the typical pattern of flow resistors, i.e. a pressure increasing with flow, dependent on the diameter of the orifice. The underwater seal and the Vitral Signs PEEP valves acted as almost ideal threshold resistors. The Ambu PEEP valves acted as threshold resistors at the lower flows, but showed flow-dependency at higher flows. The Vital Signs PEEP valves gave lower pressures and Ambu PEEP valves gave higher pressures compared with indicated values, whereas the underwater seal gave the intended pressure...
MEDICAL DESCRIPTORS:

airflow; article; artificial ventilation; calibration; comparative study; controlled study; expiratory flow; pressure; valve SECTION HEADINGS:

- 015 Chest Diseases, Thoracic Surgery and Tuberculosis
- 024 Anesthesiology
- 027 Biophysics, Bioengineering and Medical Instrumentation

26/3,K/49 (Item 13 from file: 73)

DIALOG(R) File 73: EMBASE

(c) 2004 Elsevier Science B.V. All rts. reserv.

01625786 EMBASE No: 1980183461

Effect of AMBU - PEEP - valve on respiration, blood gases and hemodynamics during spontaneous breathing of air

Saev S.K.; Jordanova-Ivanova S.T.; Hinkov O.D.

Inst. Cardiovasc. Dis., Med. Acad., 1309 Sofia Bulgaria

Anaesthesiologie und Reanimation ( ANAESTHESIOL. REANIM. ) (Germany)

1980, \_5/1\_(50<del>-</del>58)\_\_\_\_

CODEN: ANRED

DOCUMENT TYPE: Journal

LANGUAGE: ENGLISH SUMMARY LANGUAGE: GERMAN

Effect of AMBU - PEEP - valve on respiration, blood gases and hemodynamics during spontaneous breathing of air

A non-rebreathing system for respiration with positive end expiratory pressure was constructed, consisting of a non-rebreathing value ( AMBU -E- valve ) and a PEEP - valve ( AMBU - PEEP - valve ). The study was performed on 18 healthy volunteers in order to find the most suitable...

 $\dots 0.5$  kPa) applied at short time intervals between the phases is proposed as the **method** of choice in clinical and first aid conditions for improvement of blood oxygenation. Construction of... MEDICAL DESCRIPTORS:

\*artificial ventilation; \*cardiovascular system; \*positive end expiratory pressure

therapy; respiratory system

SECTION HEADINGS:

024 Anesthesiology

015 Chest Diseases, Thoracic Surgery and Tuberculosis

```
Description
Set
        Items
                AU=(LURIE K? OR LURIE, K? OR MENK V? OR MENK, V? OR ZIELIN-
S1
          725
             SKI T? OR ZIELINSKI, T? OR BIONDI J? OR BIONDI, J?)
                CPR OR (CARDIOPULMON? OR CARDIO()PULMON?)(W)(RESUSCIT? OR -
S2
        23411
             RESPIRAT? OR VENTILAT? OR CIRCULAT?) OR MANUAL?()RESUSC? OR E-
             MERGENCY () MEDICAL?
                PEEP OR PEP OR POSITIVE() (ASSIST? OR PRESSUR?) (2N) (BREATH?
        25940
S3
             OR VENTILAT? OR RESPIRAT?) OR POSITIVE()END()EXPIR?()PRESSURE
             OR (MEDICAL OR EMT OR FIRE) (2N) RESCUE?
                VACUUM? OR SUCTION? OR NEGATIVE() PRESSURE? OR EXTRACT?(3N) -
S4
       449257
             _(POSITIVE_OR_RESPIRAT?_OR_EXPIRAT?_OR_EXHAL?)_
                BAG OR BAGS OR SACK? ? OR SMARTBAG? OR SMART()BAG OR AMBUB-
       111606
$5
             AG? OR AMBU OR POUCH?? OR BELLOW?
      1027947
                MANIPULAT? OR DECOMPRESS? OR COMPRESS?
S6
S7
       840507
                THORAX? OR THORAC? OR CHEST??? OR LUNG? ? OR PULMON? OR IN-
             TRATHORA?
                VENOUS (2N) (RETURN OR CIRCULAT?) OR (BLOODFLOW? OR BLOOD()F-
S8
         4117
             LOW? OR BLOOD()CIRCULAT?)(2N)(RETURN? OR BACK)(2N)(HEART? OR -
             CARDIAC?) OR LOWER?() PRESSUR?(2N) (RIGHT() ATRIUM) OR LOWER?() P-
             RESSUR?(2N)(THORAX? OR THORAC?)()VENA()CAVA
S9
       190483
                VALVE??? OR VALVING
                HYPOTENS? OR HYPOTENT? OR LOW()BLOOD()PRESSURE OR HEAD()(T-
S10
       275879
             RAUMA? OR INJUR?) OR CARDIAC()ARREST OR HEART()ATTACK OR MYOC-
             ARD?()INFARCT? OR (HEMORRHAG? OR HAEMORRHAG?)()SHOCK? OR BLOO-
             D()LOSS??
                WIRELESS? OR WIRE() LESS? OR REMOTE? OR RADIO? OR TRANSPOND?
S11
      2982531
              OR TELECOMMUNICAT?
      7853682
                METHOD? ?
S12
     11650221
                SYSTEM? ?
S13
S14
      4338798
                TECHNIQUE? ?
      1671492
                PROCEDURE? ?
S15
      5044645
                PROCESS??
S16
            0
                IC=(A62B? OR A61G? OR A61M?)
S17
S18
          305
                S2:S3 AND S5
S19
          305
                S18 NOT S1
S20
            0
                S19 AND S8
                S19 AND S9
S21
           82
                S19 AND S11
S22
           11
S23
           92
                S21:S22
                S23 AND (S4 OR S6:S7 OR S10 OR S12:S16)
S24
           80
                RD (unique items)
S25
           80
? show files
File 94:JICST-EPlus 1985-2004/Apr W3
         (c) 2004 Japan Science and Tech Corp(JST)
      95:TEME-Technology & Management 1989-2004/May W1
File
         (c) 2004 FIZ TECHNIK
      99: Wilson Appl. Sci & Tech Abs 1983-2004/Apr
File
         (c) 2004 The HW Wilson Co.
      35:Dissertation Abs Online 1861-2004/Apr
File
         (c) 2004 ProQuest Info&Learning
File 111:TGG Natl.Newspaper Index(SM) 1979-2004/May 17
         (c) 2004 The Gale Group
File 583: Gale Group Globalbase (TM) 1986-2002/Dec 13
         (c) 2002 The Gale Group
       2:INSPEC 1969-2004/May W2
File
         (c) 2004 Institution of Electrical Engineers
File
       6:NTIS 1964-2004/May W3
         (c) 2004 NTIS, Intl Cpyrght All Rights Res
File
       8:Ei Compendex(R) 1970-2004/May W2
         (c) 2004 Elsevier Eng. Info. Inc.
      34:SciSearch(R) Cited Ref Sci 1990-2004/May W2
File
```

(c) 2004 Inst for Sci Info

File 434:SciSearch(R) Cited Ref Sci 1974-1989/Dec

(c) 1998 Inst for Sci Info

File 65:Inside Conferences 1993-2004/May W2

(c) 2004 BLDSC all rts. reserv.

File 473: FINANCIAL TIMES ABSTRACTS 1998-2001/APR 02

(c) 2001 THE NEW YORK TIMES

File 474: New York Times Abs 1969-2004/May 15

(c) 2004 The New York Times

File 475: Wall Street Journal Abs 1973-2004/May 14

\_\_\_\_\_(c)\_2004\_The\_New\_York\_Times\_\_\_\_\_\_

File 481:DELPHES Eur Bus 95-2004/May W1

(c) 2004 ACFCI & Chambre CommInd Paris

File 48:SPORTDiscus 1962-2004/May

(c) 2004 Sport Information Resource Centre

File 50:CAB Abstracts 1972-2004/Apr

(c) 2004 CAB International

?

25/3,K/14 (Item 3 from file: 34)
DIALOG(R)File 34:SciSearch(R) Cited Ref Sci
(c) 2004 Inst for Sci Info. All rts. reserv.

12259726 Genuine Article#: 747QZ No. References: 10
Title: A pilot study to evaluate the SMART BAG (R): A new
 pressure-responsive, gas-flow limiting bag - valve -mask device
Author(s): Wagner-Berger HG (REPRINT); Wenzel V; Voelckel WG; Rheinberger
 K; Stadlbauer KH; Muller T; Augenstein S; von Goedecke A; Lindner KH;
 Keller C

Title: A pilot study to evaluate the SMART BAG (R): A new pressure-responsive, gas-flow limiting bag - valve -mask device ... Abstract: be important to minimize the risk of stomach inflation when ventilating an unprotected airway with positive pressure ventilation. In this study, we assessed the effects of a standard self-inflating bag compared with a new pressure-responsive, inspiratory gas flow-limiting device (SMART BAG (R)) on respiratory mechanics in 60 adult patients undergoing routine induction of anesthesia. Respiratory variables were measured using a pulmonary monitor. The SMART BAG (R) resulted in significantly decreased inspiratory flow rate and peak airway pressure while providing adequate

- 25/3,K/16 (Item 5 from file: 34)
  DIALOG(R)File 34:SciSearch(R) Cited Ref Sci
  (c) 2004 Inst for Sci Info. All rts. reserv.
- 11710192 Genuine Article#: 684XE No. References: 18
- Title: Decreasing peak flow rate with a new bag valve -mask device: effects on respiratory mechanics, and gas distribution in a bench model of an unprotected airway
- Author(s): Wagner-Berger HG (REPRINT); Wenzel V; Stallinger A; Voelckel WG; Rheinberger K; Stadlbauer KH; Augenstein S; Dorges V; Lindner KH;

  Hormann-C
- Corporate Source: Innsbruck Univ, Dept Anaesthesiol & Crit Care Med, Anichstr 35/A-6020 Innsbruck//Austria/ (REPRINT); Innsbruck Univ, Dept Anaesthesiol & Crit Care Med, A-6020 Innsbruck//Austria/; Univ Kiel, Dept Anaesthesiol, Kiel//Germany/
- Journal: RESUSCITATION, 2003, V57, N2 (MAY), P193-199
- ISSN: 0300-9572 Publication date: 20030500
- Publisher: ELSEVIER SCI IRELAND LTD, CUSTOMER RELATIONS MANAGER, BAY 15, SHANNON INDUSTRIAL ESTATE CO, CLARE, IRELAND
- Language: English Document Type: ARTICLE (ABSTRACT AVAILABLE)
- Title: Decreasing peak flow rate with a new bag 1- valve -mask device: effects on respiratory mechanics, and gas distribution in a bench model of an...
- ...Abstract: in order to minimise the risk of stomach inflation when ventilating an unprotected airway with positive pressure ventilation. The purpose of this study was to assess the effects of a newly developed bag valve -mask device ( SMART BAG (R), O-Two Systems International, Ont., Canada) that limits peak inspiratory flow. A bench model simulating a patient with an unintubated airway was used consisting of a face mask, manikin head, training lung ( lung compliance, 100 ml/cm H2O, airway resistance 4 cm H2O/1/S, lower oesophageal sphincter...
- ...stomach). Twenty nurses were randomised to each ventilate the manikin using a standard single person technique for 1 min (respiratory rate, 12/min) with either a standard adult self-inflating bag, or the SMART BAG (R). The volunteers were blinded to the experimental design of the model until completion of the experimental protocol. The SMART BAG (R) vs. standard self-inflating bag resulted in significantly (P < 0.05) lower mean+/-S.D. peak inspiratory flow rates (32...
- ...vs. 61+/-13 1/min), peak inspiratory pressure (12+/-2 vs. 17+/-2 cm H2O), lung tidal volumes (525+/-111 vs. 680+/-154 ml) and stomach tidal volumes (0+/-0 vs...
- ...785+/-172 ml) were comparable. The mask leakage observed is not an uncommon factor in <code>bag valve -mask</code> ventilation with leakage fractions of 25-40% having been previously reported. The differences observed between the standard BVM and the <code>SMART BAG</code> (R) are due more to the anatomical design of the mask and the non-anatomical...
- ...interface and should introduce a standardized mask leakage fraction. The use of a two-person technique may have removed the problem of mask leakage. In conclusion, using the SMART BAG (R) during simulated ventilation of an unintubated patient in respiratory arrest significantly decreased inspiratory flow...
- ...and resulted in a significantly longer inspiratory time when compared to a standard self-inflating **bag** . (C) 2003 Published by Elsevier Science Ireland Ltd.

...Identifiers--BASIC LIFE-SUPPORT; CARDIOPULMONARY - RESUSCITATION; TIDAL VOLUMES; VENTILATION; PRESSURE; ARREST; RISK

25/3,K/18 (Item 7 from file: 34)
DIALOG(R)File 34:SciSearch(R) Cited Ref Sci
(c) 2004 Inst for Sci Info. All rts. reserv.

11500469 Genuine Article#: 657NQ No. References: 18

Title: Optimizing bag - valve -mask ventilation with a new mouth-to- bag resuscitator

Author(s): Wagner-Berger HG (REPRINT) ; Wenzel V; Stallinger A; Voelckel WG
 ; Rheinberger K; Augenstein S; Herff H; Idris AH; Dorges V; Lindner KH;
 Hormann C

Corporate-Source: Innsbruck-Univ,Dept-Anesthesiol-&-Grit-Care-Med,Anichstr-35/A-6020 Innsbruck//Austria/ (REPRINT); Innsbruck Univ,Dept Anesthesiol & Crit Care Med;A-6020 Innsbruck//Austria/; Univ Florida,Coll Med, Dept Emergency Med,Gainesville//FL/; Univ Kiel,Dept Anesthesiol,Kiel//Germany/

Journal: RESUSCITATION, 2003, V56, N2 (FEB), P191-198

ISSN: 0300-9572 Publication date: 20030200

Publisher: ELSEVIER SCI IRELAND LTD, CUSTOMER RELATIONS MANAGER, BAY 15, SHANNON INDUSTRIAL ESTATE CO, CLARE, IRELAND

Language: English Document Type: ARTICLE (ABSTRACT AVAILABLE)

# Title: Optimizing bag - valve -mask ventilation with a new mouth-to- bag resuscitator

- Abstract: When ventilating an unintubated patient with a self-inflating bag, high peak inspiratory flow rates may result in high peak airway pressure with subsequent stomach inflation; this may occur frequently when rescuers without daily experience in bag valve -mask ventilation need to perform advanced airway management. The purpose of this study was to assess the effects of a newly developed self-inflating bag (mouth-to-bag resuscitator; Ambu, Glostrup, Denmark) that limits peak inspiratory flow. A bench model simulating a patient with an unintubated airway was used, consisting of a face mask, manikin head, training lung (lung compliance, 100 ml/0.098 kPa (100 ml/cm H(2)OA airway resistance, 0...
- ...manikin for 1 min (respiratory rate: 12 per minute) with either a standard self-inflating bag or the mouth-to-bag resuscitator, which requires the rescuer to blow up a single-use balloon inside the self-inflating bag, which in turns displaces air towards the patient. When supplemental oxygen is added, ventilation with...
- ...be obtained, since expired air is only used as the driving gas. The mouth-to- bag resuscitator therefore allows two instead of one hand sealing the mask on the patient's...
- ...the experimental design of the model until completion of the experimental protocol. The mouth-to-bag resuscitator versus standard self-inflating bag resulted in significantly (P < 0.05) higher mean +/- S.D. mask tidal volumes (1048 +/- 161 vs. 785 +/- 174 ml) and lung tidal volumes (911 +/- 148 vs. 678 +/- 157 ml), longer inspiratory times (1.7 +/- 0.4...
- ...volumes (16 +/- 30 vs. 18 +/- 35 ml) were comparable. In conclusion, employing the mouth-to- bag resuscitator during simulated ventilation of an unintubated patient in respiratory arrest significantly decreased inspiratory flow rate and improved lung tidal volumes, while decreasing mask leakage. (C) 2002 Elsevier Science Ireland Ltd. All rights reserved.
- ...Identifiers-- CARDIOPULMONARY RESUSCITATION ; TIDAL VOLUMES; RESPIRATORY SYSTEM ; AIRWAY PRESSURE; STOMACH; ARREST; RISK

BUANT

25/3,K/54 (Item 43 from file: 34)
DIALOG(R)File 34:SciSearch(R) Cited Ref Sci
(c) 2004 Inst for Sci Info. All rts. reserv.

06586614 Genuine Article#: ZC716 No. References: 15

Title: Effectiveness of mask ventilation in a training mannikin. A comparison between the Oxylator EM100 and the bag - valve device

Author(s): Osterwalder JJ (REPRINT); Schuhwerk W

Corporate Source: KANTONSSPITAL, DEPT EMERGENCY & SURG/CH-9007 ST GALLEN//SWITZERLAND/ (REPRINT)

Journal:-RESUSCITATION, 1-998, V36, N1 (JAN), P23-27-

ISSN: 0300-9572 Publication date: 19980100

Publisher: ELSEVIER SCI IRELAND LTD, CUSTOMER RELATIONS MANAGER, BAY 15,

SHANNON INDUSTRIAL ESTATE CO, CLARE, IRELAND

Language: English Document Type: ARTICLE (ABSTRACT AVAILABLE)

- ...Title: of mask ventilation in a training mannikin. A comparison between the Oxylator EM100 and the bag valve device
- ...Abstract: study in a training mannikin to find out whether the Oxylator EM100, compared with the <code>bag</code>, obtains improved ventilation and a decrease in gastric inflation. In a randomized crossover study, 72...
- ...the operating theatre, emergency department and intensive care unit of two hospitals. We used the Ambu (R)-Bag Mark III with mask No. 4, the Oxylator EM100 with a pressure setting of 35 cm H2O run in the manual setting, the Ambu (R)-Man C mannikin as well as the Ambu (R)-CPR computer program. The resuscitation cycles of the standard two-rescuer's adult procedure lasted 3 min each, with a 3-min pause between the crossover procedure. The participants could improve their ventilatory volume with the Oxylator EM100 by 635 ml (95% confidence interval 578-692 ml) compared with the bag ventilation. The number of subjects who could attain a mean ventilatory volume of 800 ml or more increased from 15% to 98.6% (P < 0.001): Compared with the bag, the increase of adequate respirations (greater than or equal to 800 ml) obtained by the...
- ...the Oxylator EM100. The Oxylator EM100 showed significantly better results in the mannikin than the **bag**. Of most importance is a significant lowering of gastric inflation and less so a marked increase in ventilatory volume. Our trial **procedure** with a relatively high **lung** compliance and a high oesophageal sphincter opening simulated favorable conditions. Owing to a large in...
- ...Identifiers-- CARDIOPULMONARY RESUSCITATION

25/3,K/77 (Item 66 from file: 34)
DIALOG(R)File 34:SciSearch(R) Cited Ref Sci
(c) 2004 Inst for Sci Info. All rts. reserv.

Journal: CRITICAL CARE MEDICINE, 1991, V19, N11, P1425-1431 Language: ENGLISH Document Type: ARTICLE (Abstract Available)

Title: MANUAL RESUSCITATORS AND SPONTANEOUS VENTILATION - AN EVALUATION Abstract: Background and Methods: Although it is useful in certain clinical situations for manual resuscitator units to be used with spontaneously ventilating patients, there are few data regarding their performance in these settings. We measured the percent-delivered oxygen from 13 adult manual resuscitator units during simulated spontaneous ventilation in the range of respiratory frequency, tidal volume, and oxygen supply in which manual resuscitator units might be used with patients. We also measured the resistive pressure developed during simulated...

...all influenced percent-delivered oxygen, but the most important determinant of percent-delivered oxygen was valve design. Valves incorporating a "disc" element to prevent air entrainment from the expiratory port gave the most efficient oxygen delivery, while "duck-bill" valves did not reliably prevent air entrainment. Only two of the manual resuscitator units tested developed high resistive pressure.

Conclusion: Reliable administration of high percent-delivered oxygen to...

...ventilating patients, while retaining the capability to manually ventilate them, is best achieved by a manual resuscitator unit with a valve of low resistance, incorporating a disc to prevent air entrainment. We recommend that manufacturers indicate on the product information sheet the degree (and confidence limits) to which their manual resuscitator unit presents resistance and delivers oxygen to a spontaneously ventilating subject.

25/3,K/79 (Item 68 from file: 34)
DIALOG(R)File 34:SciSearch(R) Cited Ref Sci
(c) 2004 Inst for Sci Info. All rts. reserv.

00815466 Genuine Article#: EZ155 No. References: 0

Title: PRELIMINARY EVALUATION OF A PROTOTYPE TUBE- VALVE -MASK VENTILATOR FOR EMERGENCY ARTIFICIAL-VENTILATION

Author(s): GIFFEN PR; HOPE CE

Journal: ANNALS OF EMERGENCY MEDICINE, 1991, V20, N3, P262-266

Language: ENGLISH Document Type: ARTICLE (Abstract Available) (NO REFS KEYED)

## Title: PRELIMINARY EVALUATION OF A PROTOTYPE TUBE- VALVE -MASK VENTILATOR FOR EMERGENCY ARTIFICIAL-VENTILATION

... Abstract: adequate ventilatory volumes and a high oxygen and low carbon dioxide delivery.

Design: The tube- valve -mask ventilator is powered by the exhaled air of the operator and uses a tube...

...is filled between breaths. Mouth-to-mouth breathing was the standard against which the tube- valve -mask ventilator and the other accepted methods of mouth-to-mask and bag - valve -mask were assessed.

Setting: Comparison studies were conducted during simulated two-person CPR using a training mannikin equipped to measure ventilation volume and delivered oxygen and carbon dioxide...

...as operators.

Interventions: The order in which the pairs of operators performed each of the **techniques** was randomized.

Measurements and main results: The ventilation volume and the percentage of oxygen and carbon dioxide delivered by each **technique** were as follows (mean +/- SD): Mouth-to mouth (760 +/- 290 mL, 17 +/-1% O2, 3...

...CO2), mouth-to-mask (910 +/- 350 mL, 41 +/- 8% O2, 2.5 +/- 0.4% CO2), bag - valve -(soft) mask (550 +/- 230 mL, 94 +/- 3% O2, 0.03 +/- 0.02% CO2), bag - valve -(rigid) mask (560 +/- 300 mL, 96 +/- 3% O2, 0.03 +/- 0.02% CO2), and tube- valve -mask (860 +/- 290 mL, 91 +/- 7% O2, 0.2 +/- 0.2% CO2).

Conclusion: In the hands of relatively inexperienced operators, mouth-to-mouth, mouth-to-mask, and tube- valve -mask techniques provide adequate ventilation volumes to a mannikin. This was not the case with the bag - valve -mask systems (800 mL; P = 0.5 by t test). Of the systems that provide adequate ventilation volume, the tube-valve -mask appears superior in that higher oxygen and lower carbon dioxide concentrations can also be...

25/3,K/80 (Item 1 from file: 434)
DIALOG(R)File 434:SciSearch(R) Cited Ref Sci
(c) 1998 Inst for Sci Info. All rts. reserv.

08637892 Genuine Article#: M3085 No. References: 0

Title: OXYGEN ENRICHMENT OF BAG - VALVE -MASK UNITS DURING POSITIVE PRESSURE VENTILATION - A COMPARISON OF VARIOUS TECHNIQUES

Author(s): CAMPBELL TP; STEWART RD; KAPLAN RM; DEMICHIEI RV; MORTON R

Corporate Source: UNIV PITTSBURGH, SCH MED, DIV EMERGENCY
MED/PITTSBURGH//PA/15261

Journal: -ANNALS-OF-EMERGENCY-MEDICINE, 1988, -V17, -N3, -P232-235-Language: ENGLISH Document Type: ARTICLE (NO REFS KEYED)

Title: OXYGEN ENRICHMENT OF BAG - VALVE -MASK UNITS DURING POSITIVE - PRESSURE VENTILATION - A COMPARISON OF VARIOUS TECHNIQUES

```
Set
        Items
                Description
                AU=(LURIE K? OR LURIE, K? OR MENK V? OR MENK, V? OR ZIELIN-
S1
             SKI T? OR ZIELINSKI, T? OR BIONDI J? OR BIONDI, J?)
                CPR OR (CARDIOPULMON? OR CARDIO()PULMON?)(W)(RESUSCIT? OR -
S2
             RESPIRAT? OR VENTILAT? OR CIRCULAT?) OR MANUAL?() RESUSC? OR E-
             MERGENCY() MEDICAL?
                PEEP OR PEP OR POSITIVE() (ASSIST? OR PRESSUR?) (2N) (BREATH?
S3
             OR VENTILAT? OR RESPIRAT?) OR POSITIVE()END()EXPIR?()PRESSURE
             OR (MEDICAL OR EMT OR FIRE) (2N) RESCUE?
                VACUUM? OR SUCTION? OR NEGATIVE()PRESSURE? OR EXTRACT?(3N)-
       157768
S4
          ____(POSITIVE_OR_RESPIRAT?_OR_EXPIRAT?_OR_EXHAL?)_
                BAG OR BAGS OR SACK? ? OR SMARTBAG? OR SMART()BAG OR AMBUB-
             AG? OR AMBU OR POUCH?? OR BELLOW?
                MANIPULAT? OR DECOMPRESS? OR COMPRESS?
       525160
S6
                THORAX? OR THORAC? OR CHEST??? OR LUNG? ? OR PULMON? OR IN-
S7
             TRATHORA?
                VENOUS (2N) (RETURN OR CIRCULAT?) OR (BLOODFLOW? OR BLOOD()F-
S8
         1620
             LOW? OR BLOOD()CIRCULAT?)(2N)(RETURN? OR BACK)(2N)(HEART? OR -
             CARDIAC?) OR LOWER?() PRESSUR?(2N) (RIGHT() ATRIUM) OR LOWER?() P-
             RESSUR?(2N)(THORAX? OR THORAC?)()VENA()CAVA
                VALVE??? OR VALVING
S9
       156467
                HYPOTENS? OR HYPOTENT? OR LOW() BLOOD() PRESSURE OR HEAD() (T-
S10
       106229
             RAUMA? OR INJUR?) OR CARDIAC()ARREST OR HEART()ATTACK OR MYOC-
             ARD?()INFARCT? OR (HEMORRHAG? OR HAEMORRHAG?)()SHOCK? OR BLOO-
             D()LOSS??
               WIRELESS? OR WIRE() LESS? OR REMOTE? OR RADIO? OR TRANSPOND?
S11.
      3941213
              OR TELECOMMUNICAT?
               METHOD? ?
S12
      1374233
      8305671
                SYSTEM? ?
S13
      1012783
                TECHNIQUE? ?
S14
      1611763
                PROCEDURE? ?
S15
      4032021
                PROCESS??
S16
          388
                S2:S3(10N)S5
S17
                S17 NOT S1
          384
S18
          19
                S18 AND S8
S19
S20
          127
                S18 AND S11
           75
                S18 AND S9
S21
           26
                S21 AND S11
S22
                S21 AND (S4 OR S6:S7 OR S10)
S23
           68
           75
                S21 OR S23
S24
S25
           66
                S24 AND S12:S16
           75
S26
                S22:S25
              RD (unique items)
           59
S27
? show files
File 16:Gale Group PROMT(R) 1990-2004/May 17
          (c) 2004 The Gale Group
File 160:Gale Group PROMT(R) 1972-1989
         (c) 1999 The Gale Group
File 148:Gale Group Trade & Industry DB 1976-2004/May 17
         (c) 2004 The Gale Group
File 149:TGG Health&Wellness DB(SM) 1976-2004/May W2
          (c) 2004 The Gale Group
File 621: Gale Group New Prod. Annou. (R) 1985-2004/May 14
          (c) 2004 The Gale Group
```

File 444: New England Journal of Med. 1985-2004/May W3

(c) 2004 Reed Business Information Ltd.

File 441:ESPICOM Pharm&Med DEVICE NEWS 2004/May W2 (c) 2004 ESPICOM Bus.Intell.

(c) 2004 Mass. Med. Soc.

File 369: New Scientist 1994-2004/May W2

File 370:Science 1996-1999/Jul W3

(c) 1999 AAAS

File 129:PHIND(Archival) 1980-2004/May W2

(c) 2004 PJB Publications, Ltd.

File 130:PHIND(Daily & Current) 2004/May 17
(c) 2004 PJB Publications, Ltd.
File 135:NewsRx Weekly Reports 1995-2004/May W1
(c) 2004 NewsRx

File 98:General Sci Abs/Full-Text 1984-2004/May

(c) 2004 The HW Wilson Co.

File 15:ABI/Inform(R) 1971-2004/May 15

\_\_\_(c)\_2004\_ProQuest\_Info&Learning\_\_

27/3,K/7 (Item 2 from file: 148) DIALOG(R) File 148: Gale Group Trade & Industry DB (c) 2004 The Gale Group. All rts. reserv.

08929197 SUPPLIER NUMBER: 18610992 (USE FORMAT 7 OR 9 FOR FULL TEXT) Airway management during active compression - decompression CPR. (includes reply) (Letter to the Editor)

Rottenberg, Eric M.; Stiell, Ian G.; Hebert, Paul C.; Wells, George A.; Laupacis, Andreas

JAMA, The Journal of the American Medical Association, v276, n6, p448(2) August-14, 1996 ---

DOCUMENT TYPE: Letter to the Editor

ISSN: 0098-7484

LANGUAGE:

RECORD TYPE: Fulltext WORD COUNT: 958 LINE COUNT: 00080

Airway management during active compression - decompression CPR. (includes reply) (Letter to the Editor)

...the Editor. -- Dr Stiell and colleagues (1) published a study comparing the effect of active compression - decompression (ACD) cardiopulmonary resuscitation (CPR) and standard CPR on outcomes of in-hospital and out-of-hospital victims of cardiac arrest . They concluded that ACD CPR did not improve survival or neurologic outcomes in any group of patients with cardiac arrest . However, testing ACD CPR in a system in which the ambulance services did not have the capability for endotracheal intubation is biased against successful application of ACD CPR. Since previous animal studies tested the **method** under conditions that included endotracheal intubation, it is a significant methodological error not to control...

ensures a patent airway and allows air to move freely in and out of the lungs . The ACD CPR technique involves the use of a suction -cup device applied to the sternum to allow the rescuer to lift up and expand ( decompress ) the patient's chest between downward compressions .(1) Among other advantages, this action allows more air to be drawn into the lungs during chest compression and ventilation (ventilation allowed by the bellows action of multiple consecutive chest compressions ) than does standard CPR, (2) provided the airway is patent(3) As a result, air trapping in the lungs can be increased, which can augment the generated intrathoracic pressure(2) According to Halperin et al,(2) "Current evidence suggests that the intrathoracic pressure pump is probably responsible for most of the driving force for blood movement during standard external chest compression, although the cardiac compression pump probably contributes to some extent."

During standard CPR in humans, it is possible for...

...research is necessary to clarify whether upper-airway patency can be maintained reliably with these techniques during chest compression ventilation or spontaneous gasping, or whether such techniques are necessary at all." One of many reasons standard CPR is often ineffective and ACD...

 $\dots$ 1) may be because the head tilt or jaw thrust maneuver was not maintained during chest compression ventilation or spontaneous gasping. A single bystander cannot simultaneously compress the chest and maintain a patent airway with the head tilt or jaw thrust maneuver and it is unclear whether or not airway patency was adequately maintained during compression ventilation in the study of Sriell et al. Therefore, because there is no experimental evidence...

- 1. Stiell IG, Hebert PC, Wells GA, et al. The Ontario trial of active compression decompression cardiopulmonary resuscitation for in-hospital and prehospital cardiac arrest. JAMA. 1996;275:1417-1423.
- 2. Halperin HR, Chandra NC, Levin HR, et al. Newer methods of improving blood flow during CPR. Ann Emerg Med. 1996;27:553-562.
- 3. Tucker K J, Khan JH, Savitt MA. Active compression decompression resuscitation: effects on pulmonary ventilation. Resuscitation. 1993;26:125-131.
  - 4. Idris AH. Reassessing the need for ventilation during...
- ...the standard CPR group, had exactly the same airway and ventilation management. This consisted of CPR by 2 professional rescuers who used standard oropharyngeal airways and bag valve -mask ventilation prior to arrival at the hospital. All out-of-hospital rescuers were also...
- ...Rottenberg may have overlooked the fact that in many US and most Canadian jurisdictions, prehospital cardiac arrest patients are not intubated until they arrive at the hospital. Consequently, the out-of-hospital...
- ...wanted to determine if ACD CPR improved survival in out-of-hospital emergency medical services **systems** that do not provide advanced cardiac life support measures. Unfortunately, we were unable to demonstrate...

## ...Investigators

Ottawa, Ontario

- 1. Lurie KG, Shultz JJ, Callaham ML, et al. Evaluation of active compression decompression CPR in victims of out-of-hospital cardiac arrest . JAMA. 1994;271: 1405-1411.
- 2. Schwab TM, Callaham ML, Madsen CD, Utecht TA. A randomized clinical trial of active compression decompression CPR vs standard CPR in out-of-hospital cardiac arrest in two cities, JAMA. 1995;273:1261-1268.

...DESCRIPTORS: Cardiac arrest --

27/3,K/21 (Item 16 from file: 148) DIALOG(R)File 148:Gale Group Trade & Industry DB (c) 2004 The Gale Group. All rts. reserv.

02331113 SUPPLIER NUMBER: 03667860 (USE FORMAT 7 OR 9 FOR FULL TEXT) What to do after CPR; how to help the patient get the air he needs. Jones, Sande RN, v48, p28(6)

March, 1985

ISSN: 0033-7021 LANGUAGE: ENGLISH WORD\_COUNT: \_ 2694 LINE\_COUNT: \_ 00202 ISSN: 0033-7021 RECORD TYPE: FULLTEXT

he needs

All the sophisticated equipment in the world won't save a patient in cardiac arrest unless you can maintain an open airway. While clearing the airway initially may not be...

...and endotracheal tubes.

When and how to use oral and nasal airways Unconscious patients in cardiac arrest often need an oropharyngeal, or oral, airway adjunct to prevent the tongue from falling back...

...near the back of the tongue, rotate it back to its proper position. An alternative method is to move the tongue out of the way with a tongue depressor, then insert the airway by holding it in its normal position. Practice these techniques on a mannequin until you can use them confidently.

Once the airway's in place...

...skin ulceration.

How to ventilate the patient correctly

After an airway has been inserted, a manual resuscitator --also known as a bag - valve -mask device or Ambu bag --is used to deliver positive pressure breaths . The equipment you'll need for this procedure0 includes a self-inflating bag with mask, an oxygen connecting tube, an oxygen reservoir, and...

...spread your thumb and index finger on the mask, one on either side of the valve connection. Use a squeezing motion of your hand to seal the rim of the mask to the patient's face.

With your other hand, compress the bag. Watch the patient's chest to make sure it rises and falls with each squeeze. You should feel resistance during....

...you should hear air escape during exhalation. If the resistance increases as you continue to compress the bag, assess the patient for obstruction of the airway or a change in lung compliance. You may need to re-establish correct head position or readjust the mask for ...

...placed upside down. You should practice on a mannequin until you feel comfortable with this procedure .

Each time you squeeze all the air out of the bag, you deliver 500 to 700 cc of air into your patient's lungs . Since cardiac arrest patients usually need a higher oxygen concentration than the 21% in room air, have someone attach oxygen tubing from the flow meter of the oxygen outlet to the inlet valve of the bag and turn on the flow meter while you continue ventilating with room...use a bag with a reservoir, what flow rate you use, and how fast you compress the bag . Most manual resuscitators with an attached reservoir deliver an inspired oxygen

concentration of 75% to 90% at a...

- ...and aspirate gastric contents. If gastric distention occurs, you should insert a nasogastric tube to **decompress** the stomach. It's also a good idea to use a transparent resuscitator mask so...
- ...patent airway but still have problems ventilating the patient—as evidenced by increased resistance, poor **chest** movement, and rapidly increasing gastric distention. In that event, the patient probably needs to be...
- ...the airway with your mouth or a manual resuscitator and watch for the patient's **chest** to rise. Have someone check for bilateral breath sounds as you do this. If the **chest** rises and breath sounds are present, the device is properly positioned. You can then inflate the cuff by injecting 30 cc of air with a Luer-Lok syringe through the **valve** located at the top of the tube. Recheck placement after the cuff has been inflated...
- ...a small hole at the distal end of the tube and a one-way, nonrefluxing valve at the upper end to prevent air from entering the stomach. The opening in the...
- ...end allows a nasogastric tube to be inserted through the esophageal tube and connected to suction to decompress the stomach.

The most common complication associated with EOA and EGTA tubes is accidental endotracheal...

...patient usually vomits when either tube is removed and esophageal occlusion is relieved, so keep suction equipment connected at the bedside. Before an EOA or EGTA is removed, the patient should...
...at both ends. Thus it acts as a vent for the stomach and permits gastric suctioning.

Unlike the EOA and EGTA, the tracheoesophageal airway can stay in the trachea if it...

...in the esophagus.

When the patient needs an endotracheal tube

Endotracheal intubation is the preferred **technique** for airway management because it provides more direct control over the airway than other **methods**. An ET tube is usually inserted when the patient requires long-term mechanical ventilation. The...inflated with 5 to 10 cc of air. This feature guards against aspiration and allows **suctioning** and intermittent positive pressure ventilation with 100% oxygen.

Unless you have the special training required...

- ...Many physicians place a malleable stylet in the tube to stiffen it during insertion. A suction set-up should be at the bedside.
- \* For a detailed description all illustrations of the insertion **procedure** , see Garrity, E.M. Emergency! When intubation is up to you. RN 46:49, October...
- ...water-soluble lubricant to the end of the ET tube.

You may be asked to **suction** the patient before intubation so that the physician can get a clearer view of the...

... To perform this maneuver, apply firm, backward pressure over the cricoid cartilage until the insertion **procedure** is completed and the cuff inflated.

You may also be asked to confirm bilateral breath...

- ...bagged into the tube. If you hear breath sounds on only one side of the **chest** , it may mean that the tube has passed into a mainstem bronchus and must be...
- ...the tube has entered the esophagus instead of the trachea and must be removed. A  $\,$  chest  $\,$  X-ray should always be done post-intubation to verify placement.

To secure the ET...

- ...hold the tube in place without adhesive tape.
- ————Maintaining-a-patient's-airway-during-a—cardiac—arrest—is-a—demanding task that requires not only knowledge of, but also practice in, using...
- ...DESCRIPTORS: Technique;

27/3,K/52 (Item 1 from file: 129)
DIALOG(R)File 129:PHIND(Archival)
(c) 2004 PJB Publications, Ltd. All rts. reserv.

00759800

Alert over US single-use resuscitator entering UK Clinica 1012 p5, June 21, 2002 (20020621) STORY TYPE: F WORD COUNT: 154

...for the US market have been mistakenly distributed\_to\_UK\_customers\_with\_a\_pressure-limiting\_valve\_\_\_\_\_override feature that is not described in the user instructions. A device alert issued this week by the Medical Devices Agency (MDA) warns that a number of Ambu Spur infant/child single-use manual resuscitators, made by Ambu of the US, pose a risk of overpressure.

Both the UK and US versions of the device have a 40cm H2O pressure-limiting valve. The US version, however, has an additional override clip covering the valve, preventing this from opening. Pre-use testing of the resuscitator cannot be performed as specified...

27/3,K/54 (Item 3 from file: 129)
DIALOG(R)File 129:PHIND(Archival)
(c) 2004 PJB Publications, Ltd. All rts. reserv.

00071970

Comparing ventilation methods Clinica 230 p19, January 09, 1987 (19870109) WORD COUNT: 219

### Comparing ventilation methods

...to-mask ventilation is called for by researchers who performed a study to compare six methods of emergency ventilation, and report their findings in a letter to The Lancet (November 29th, p 1274). Medical students were asked to use six methods of ventilation on a manikin modified to include a Wright spirometer in the trachea. The methods studied were mouth-to-mouth, bag- valve -mask with one operator, mouth-to-mask, bag- valve -mask with two operators, Brook Airway, and mouth to Ambu mask.

In cardiopulmonary resuscitation, say the researchers, the delivery of an adequate tidal volume is vital, and the American...

...ml. The students were unable to deliver adequate volumes via the Brook airway or bag- valve -mask with one operator. Adequate ventilation was achieved with the bag- valve - mask and two operators, while use of the remaining methods resulted in inflation of more than three times the recommended minimum.

The researchers do point...

...delivery of excessive tidal volumes carries the risk of gastric distension and regurgitation and diminished lung volume (by elevation of the diaphragm)"....

27/3,K/56 (Item 1 from file: 135) DIALOG(R) File 135: NewsRx Weekly Reports (c) 2004 NewsRx. All rts. reserv.

0000044914 (USE FORMAT 7 OR 9 FOR FULLTEXT) Technique and Valve Improve CPR Heart Disease Weekly, March 22, 2000, p.9-10

DOCUMENT TYPE:

Expanded Reporting LANGUAGE: English

RECORD TYPE:

FULLTEXT

WORD COUNT: -- -- 592--

## Technique and Valve Improve CPR

A cardiopulmonary resuscitation (CPR) technique using devices developed at the University of Minnesota Medical School has been shown in a clinical trial to maintain near-normal blood pressure in heart

The study was published in the March 7, 2000, issue of the American

The **method** improves upon active **compression** - **decompression** (ACD) CPR, which is performed with a hand-held plunger-like device called the CardioPump. With this technique, blood is pushed out of the chest to the brain and other organs during compression , just as in standard CPR. Unlike standard CPR, the pump actively pulls the chest back to its original position during decompression . It improves the flow of oxygenated blood to the heart, increases the volume of blood pumped with each compression, and allows more air to flow into the lungs.

A previous study by a group that included the authors of the Circulation article showed that ACD CPR significantly improved long-term survival rates among patients who had cardiac arrest outside the hospital. That study was published in the August 19, 1999, New England Journal of Medicine .

The latest study introduced a valve to ACD CPR . During CPR the chest works like a bellows , and the valve improves the function of the bellows. The valve has a silicone diaphragm that decreases pressure in the chest during decompression . This results in a greater vacuum effect, which pulls more blood back into the heart and thus improves overall CPR efficacy.

The study involved 21 patients, 10 who had ACD CPR without the valve , 11 with it. More patients returned to spontaneous circulation with (n=4)than without (n=2) the **valve**; those with the **valve** also returned faster (average 19.8 minutes with vs. 26.5 minutes without). With the combination of the valve and the pump, patients in cardiac arrest had near-normal blood pressures for up to 30 minutes or until they were resuscitated...

...the division of cardiology at the university and co-developer of the pump and the valve . "This is the first time we have used this combination of devices in patients. With...

...give their consent.

More than 400,000 patients die every year from out-of-hospital arrest in the United States, where it remains the number one cardiac cause of death.

"Fewer than five percent of patients with out-of-hospital cardiac arrest in the United States ever survive to hospital discharge, due in part to the inherent...

...and brain get less than 30% of normal blood flow. With ACD CPR plus the valve , those organs get more than 60% of normal flow. The group will

conduct further studies...